

CodeWarrior®

MSL C++ Reference



Because of last-minute changes to CodeWarrior, some of the information in this manual may be inaccurate. Please read the Release Notes on the CodeWarrior CD for the latest up-to-date information.

Revised: 980818 rdl

Metrowerks CodeWarrior copyright ©1993–1998 by Metrowerks Inc. and its licensors.
All rights reserved.

Documentation stored on the compact disk(s) may be printed by licensee for personal use. Except for the foregoing, no part of this documentation may be reproduced or transmitted in any form by any means, electronic or mechanical, including photocopying, recording, or any information storage and retrieval system, without permission in writing from Metrowerks Inc.

Metrowerks, the Metrowerks logo, CodeWarrior, and Software at Work are registered trademarks of Metrowerks Inc. PowerPlant and PowerPlant Constructor are trademarks of Metrowerks Inc.

All other trademarks and registered trademarks are the property of their respective owners.

ALL SOFTWARE AND DOCUMENTATION ON THE COMPACT DISK(S) ARE SUBJECT TO THE LICENSE AGREEMENT IN THE CD BOOKLET.

How to Contact Metrowerks:

U.S.A. and international	Metrowerks Corporation 9801 Metric, Suite 100 Austin, TX 78758 U.S.A.
---------------------------------	--

Canada	Metrowerks Inc. 1500 du College, Suite 300 Ville St-Laurent, QC Canada H4L 5G6
---------------	---

Ordering	Voice: (800) 377-5416 Fax: (512) 873-4901
-----------------	--

World Wide Web	http://www.metrowerks.com
-----------------------	---

Registration information	register@metrowerks.com
---------------------------------	--

Technical support	support@metrowerks.com
--------------------------	--

Sales, marketing, & licensing	sales@metrowerks.com
--	--

CompuServe	goto Metrowerks
-------------------	-----------------

Table of Contents

1 Introduction	39
Metrowerks Year 2000 Compliance	39
About the MSL C++ Library Reference Manual	39
2 MSL C++ Reference	43
Overview of the MSL C++ Reference	43
Definitions.	43
Character Sequences	43
Byte Strings	44
Multibyte Strings.	44
Wide-Character Sequences	44
Multi-Thread Safety	45
Features not implemented in MSL C++	45
Template Functionality	46
ANSI/ISO Library Functionality	46
3 Language Support Library	47
Overview of Language Support Libraries	47
Types and Macros	47
Macros	48
NULL	48
offsetof.	48
sizeof.	48
Type Implementations	48
Character types	49
Enumeration.	49
Integral types	49
Wide character types	50
Bool type	50
Floating point types	50
Void type	50
Numeric Limits.	50
Template Class numeric_limits.	51
numeric_limits::is_specialized	51

Table of Contents

numeric_limits::min	52
numeric_limits::max	52
numeric_limits::digits	52
numeric_limits::digits10	52
numeric_limits::is_signed	53
numeric_limits::is_integer	53
numeric_limits::is_exact	53
numeric_limits::radix	53
numeric_limits::epsilon	54
numeric_limits::round_error	54
numeric_limits::min_exponent	54
numeric_limits::min_exponent10	54
numeric_limits::max_exponent	54
numeric_limits::max_exponent10	55
numeric_limits::has_infinity	55
numeric_limits::has_quiet_NaN	55
numeric_limits::has_signaling_NaN	55
numeric_limits::has_denorm	56
numeric_limits::infinity	56
numeric_limits::quiet_NaN	56
numeric_limits::signaling_NaN	56
numeric_limits::denorm_min	56
numeric_limits::is_bounded	57
numeric_limits::is_modulo	57
numeric_limits::traps	57
numeric_limits::tinyness_before	57
numeric_limits::round_style	58
Dynamic Memory Storage Allocation Errors	58
Class bad_alloc	58
Constructor–bad_alloc	58
Copy Constructor–bad_alloc	58
Assignment Operator–bad_alloc	59
bad_alloc::what	59
Class bad_cast	59
Constructor–bad_cast	59

Copy Constructor–bad_cast	59
Assignment Operator–bad_cast	60
bad_cast::what	60
Class bad_typeid	60
Constructor–bad_typeid	60
Copy Constructor–bad_typeid	60
Assignment Operator–bad_typeid	61
bad_typeid::what	61
4 Diagnostics Library	63
Overview of Diagnostics Library	63
Exception Classes	63
Class exception	64
Constructor–exception	64
Copy Constructor–exception	64
Assignment Operator–exception	65
Destructor–exception	65
exception::what	65
Class logic_error	65
Constructor–logic_error	65
Class domain_error	66
Constructor–domain_error	66
Class invalid_argument	66
Constructor–invalid_argument	66
Class length_error	66
Constructor–length_error	67
Class out_of_range	67
Constructor–out_of_range	67
Class runtime_error	67
Constructor–runtime_error	68
Class range_error	68
Constructor–range_error	68
Class overflow_error	68
Constructor–overflow_error	68

Table of Contents

5 General Utilities Libraries	71
Overview of General Utilities Libraries	71
Allocator Classes	71
Passing Allocators to STL Containers	72
Extracting Information from an Allocator Object	72
The Default Allocator Interface	73
Typedef Declarations	75
allocator::pointer	75
allocator::const_pointer	75
allocator::reference	75
allocator::const_reference	76
allocator::value_type	76
Allocator Member Functions.	76
Constructor-allocator	76
Destructor-allocator	76
allocator::size_type	77
allocator::difference_type	77
allocator::address.	77
allocator::const_address.	77
allocator::allocate.	78
allocator::deallocate	78
allocator::max_size	78
Custom Allocators	79
allocator::vec_default	79
allocator::vec_large	79
allocator::vec_huge	79
Allocator Requirements	79
Function Objects	80
Function Adaptors	80
Arithmetic Operations.	81
plus	82
minus.	82
times	82
divides	82
modulus	82

negate	83
Comparison Operations	83
equal_to	83
not_equal_to.	83
greater	84
less	84
greater_equal	84
less_equal	84
Logical Operations	85
logical_and	85
logical_or	85
logical_not	85
Negator Adaptors	86
not1	86
not2	86
Binder Adaptors	86
bind1st	87
bind2nd.	87
Adaptors for Pointers to Functions	87
ptr_fun-unary	88
ptr_fun-binary.	88
Specialized Algorithms	89
uninitialized_copy	89
uninitialized_fill	89
uninitialized_fill_n	90
Template class auto_ptr	90
Constructor-auto_ptr.	91
auto_ptr Destructor.	91
auto_ptr::get.	92
auto_ptr::release	92
Assignment Operator=auto_ptr	92
Dereferencing Operator*auto_ptr.	92
Association Operator->auto_ptr	92

Table of Contents

6 21 Strings Library	95
Overview of Strings Classes	95
21.1 Character traits	95
21.1.1 Character Trait Definitions	96
21.1.2 Character Trait Requirements.	96
21.1.3 Character Trait Type Definitions	97
21.1.4 struct char_traits<T>	98
21.2 String Classes	99
21.3 Class basic_string.	105
21.3.1 Constructors and Assignments	111
21.3.2 Iterator Support	114
21.3.3 Capacity.	115
21.3.4 Element Access.	116
21.3.5 Modifiers	117
21.3.6 String Operations.	121
23.3.7 Non-Member Functions and Operators	126
21.3.7.9 Inserters and extractors	132
23.4 Null Terminated Sequence Utilities	133
 7 Localization Library	 137
Overview of the Localization Library	137
Class locale	138
Typedef Declarations	138
Public Data Members	140
Constructors.	140
Default Constructor	140
Overloaded and Copy Constructors	140
Public member operators	142
Assignment Operator= locale	142
Equality Operator== locale	142
Not Equal Operator!= locale	143
Grouping Operator locale	143
Public Member Functions	143
locale::name	143
locale::has	144

locale::use	144
Static Member Functions	145
locale::global.	145
locale::classic	145
locale::transparent	145
Global Operators.	146
Extractor Operator >> locale	146
Insertter Operator << locale	146
Class facet	146
Class id	148
The Numerics Category	148
Class numpunct	149
Typedef Declarations numpunct	149
numpunct::char_type	149
numpunct::string.	149
Public Member Functions numpunct	150
numpunct::decimal_point	150
numpunct::thousands_sep.	150
numpunct::grouping	150
numpunct::truename	151
numpunct::falsename.	151
Class num_get	151
Typedef Declarations num_get.	151
char_type	151
iter_type	151
ios	152
Public Member Functions num_get.	152
num_get::get.	152
Class num_put	153
Typedef Declarations num_put.	153
char_type	153
iter_type	153
ios	153
Public Member Functions num_put.	154
num_put::put	154

Table of Contents

The Collate Category	155
Class Collate	155
Typedef Declarations collate	155
char_type	155
string	155
Public Member Functions collate	156
collate::compare	156
collate::transform.	156
collate::hash	156
Ctype Category.	157
Class ctype<charT>	157
Typedef Declarations ctype<charT>.	158
char_type	158
Public Member Functions ctype<charT>.	158
ctype::is	158
ctype::do_is	158
ctype::scan_is	159
ctype::scan_not	159
ctype::toupper	160
ctype::tolower	160
ctype::widen.	160
ctype::narrow	161
Class ctype<char> Specialization	161
Data Members ctype<char>	162
ctype::ctype_mask	162
ctype::table_	162
ctype::classic_table_	162
ctype::delete_it_	162
Public Member Functions ctype<char>	163
constructor ctype<char>	163
ctype::is for ctype<char>	163
ctype::scan_is for ctype<char>	164
ctype::scan_not for ctype<char>	164
ctype::tolower for ctype<char>.	164
ctype::toupper for ctype<char>.	165

ctype::widen for ctype<char>	165
ctype::narrow for ctype<char>	165
Class codecvt	166
Typedef Declarations codecvt	166
from_type	166
to_type	166
state_type	166
Member Functions codecvt	167
The Monetary Category	168
Class money_punct	169
Typedef Declarations money_punct	169
char_type	169
string_type	169
Public Member Functions money_punct	169
money_punct::decimal_point	169
money_punct::thousands_sep.	170
money_punct::groupint	170
money_punct::curr_symbol.	170
money_punct::positive_sign	170
money_punct::negative_sign	171
money_punct::frac_digits.	171
money_punct::pos_format	171
money_punct::neg_format	171
Class money_put	172
Typedef Declarations money_put.	172
char_type	172
iter_type	172
string	172
ios	172
Public Member Functions money_put.	172
money_put::put	173
Class money_get	173
Typedef Declarations money_get	173
char_type	173
iter_type	174

Table of Contents

string	174
ios	174
Public Member Functions money_get	174
money_get::get.	174

8 Containers Library 177

Overview of the Containers Library	177
What Are Containers	177
Basic Design and Organization of Containers	178
Common Members of All Containers	179
Common Type Definitions in All Containers	180
Common Member Functions in all Containers	182
Sequence Container Requirements	185
Associative Container Requirements	187
Basic Design and Organization.	187
Equality of Keys	187
Additional Definitions	187
Associative Container Types and Member Functions	188
Organization of the Container Class Descriptions	192
Template class vector<T>	193
Type Definitions vector	194
Constructors, Destructors and Related Functions vector	196
Comparison Operations vector.	198
Element Access Member Functions vector	198
Insert Member Functions vector	200
Erase Member Functions vector	201
Notes on Insert and Erase Member Functions vector	202
Specialization Class vector<bool>	202
Public Member Functions	203
Template class deque<T>	203
Typedef Declarations deque	204
Constructors, Destructors and Related Functions deque	205
Comparison Operations deque.	207
Element Access Member Functions deque	207
Insert Member Functions deque	209

Table of Contents

Erase Member Functions deque	210
Deque Class Notes	211
Storage Management	211
Complexity of Insertion	211
Notes on Erase Member Functions	212
Template class list<T>	212
Typedef Declarations list	213
Constructors, Destructors and Related Functions list	215
Comparison Operations list	216
Element Access Member Functions list	217
Insert Member Functions list.	218
Erase Member Functions list.	219
Special Operations list	220
List Class Notes	222
Notes on Insert Member Functions	222
Notes on Erase Member Functions	222
Template class set<T>	223
Typedef Declarations set	223
Constructors, Destructors and Related Functions set	226
Comparison Operations set	227
Element Access Member Functions set	228
Insert Member Functions set.	229
Erase Member Functions set	230
Special Operations set.	231
Template class multiset<Key>	232
Typedef Declarations multiset	233
Constructors, Destructors and Related Functions multiset . .	236
Comparison Operations multiset	237
Element Access Member Functions multiset	238
Insert Member Functions multiset	239
Erase Member Functions multiset	240
Special Operations multiset	241
Template class map<Key, T>	242
Typedef Declarations map.	243
Constructors, Destructors and Related Functions map. . . .	246

Table of Contents

Comparison Operations map	247
Element Access Member Functions map.	248
Insert Member Functions map	250
Erase Member Functions map	251
Special Operations map	251
Template class multimap<Key, T>	253
Typedef Declarations multimap	254
Constructors, Destructors and Related Functions multimap .	257
Comparison Operations multimap	258
Element Access Member Functions multimap	259
Insert Member Functions multimap.	260
Erase Member Functions multimap.	261
Special Operations multimap	262
Template class stack.	264
Public Member Functions stack	264
Comparison Operations stack	265
Template class queue	266
Public Member Functions queue	267
Comparison Operations queue.	268
Template class priority_queue	268
Constructors priority_queue.	269
Public Member Functions priority_queue	270
Comparison Operations priority_queue	271

9 Iterators Library **273**

Overview of Iterators	273
Value type.	274
Distance type	274
Past-the-end values.	274
Dereferenceable values.	274
Singular values.	274
Reachability	275
Ranges	275
Mutable versus constant	275
Iterator Requirements	275

Input Iterator Requirements	276
Output Iterator Requirements	277
Forward Iterator Requirements.	278
Bidirectional Iterator Requirements.	279
Random Access Iterator Requirements	279
Stream Iterators	280
Template class istream_iterator	281
Constructor istream_iterator	282
Default Constructor	282
Overloaded and Copy Constructors	282
Destructor.	282
Public Member Functions istream_iterator.	283
Dereferencing Operator *	283
Incrementation Operator ++	283
Comparison Operations istream_iterator	283
Equality Operator ==	283
Template class ostream_iterator.	284
Constructor ostream_iterator	284
Default Constructor	284
Overloaded and Copy Constructors	285
Destructor.	285
Public Member Functions ostream_iterator	285
Dereferencing Operator *	285
Assignment Operator =	285
Incrementation Operator ++	285
Template class istreambuf_iterator	286
Typedef Declarations istreambuf_iterator	287
char_type	287
traits_type.	287
streambuf	287
istream	287
Placeholder proxy istreambuf_iterator	287
Constructor istreambuf_iterator	288
Default Constructor	288
Overloaded and Copy Constructor	288

Table of Contents

Operators istreambuf_iterator	288
Dereferencing Operator *	288
Incrementation Operator ++	288
istream_iterator::equal	289
istream_iterator::iterator_category	289
Equality Operator ==	289
Not Equal Operator !=	290
Template class ostreambuf_iterator	290
Typedef Declarations ostreambuf_iterator	290
char_type	291
traits_type.	291
streambuf	291
ostream	291
Constructor ostreambuf_iterator	291
Default Constructor	291
Overloaded and Copy Constructors	291
Operators ostreambuf_iterator	292
Dereferencing Operator *	292
ostreambuf_iterator::equal.	292
ostreambuf_iterator::iterator_category	292
Equality Operator ==	292
Not Equal Operator !=	292
Template class reverse_bidirectional_iterator	293
Constructor reverse_bidirectional_iterator	294
Default Constructor	294
Overloaded Constructors	294
Public Member Functions reverse_bidirectional_iterator.	294
reverse_bidirectional_iterator::base	294
Dereferencing Operator *	294
Incrementation Operator ++	294
Decrementation Operator --	295
Equality Operator ==	295
Template class reverse_iterator	296
Constructor reverse_iterator	296
Default Constructor	296

Overloaded and Copy Constructors	296
Public Member Functions reverse_iterator	297
reverse_iterator::base	297
Dereferencing Operator *	297
Incrementation Operator ++	297
Decrementation Operator --	297
Add Operator +	298
Add & Assign Operator +=	298
Minus Operator -.	298
Minus & Assign Operator -=	298
Subset Operator []	299
Equality Operator ==	299
Less Than Operator <.	299
Minus Operator -.	300
Add Operator +	300
Template class back_insert_iterator	300
Constructor back_insert_iterator	301
Copy Constructor	301
Public Member Functions back_insert_iterator	301
Assignment Operator =	301
Dereferencing Operator *	301
Incrementation Operator ++	301
back_insert_iterator::back_inserter	302
Template class front_insert_iterator	302
Constructor front_insert_iterator	302
Copy Constructor	302
Public Member Functions front_insert_iterator	302
Assignment Operator =	302
Dereferencing Operator *	302
Incrementation Operator ++	303
front_insert_iterator::front_inserter	303
Template class insert_iterator.	303
Constructor insert_iterator.	303
Copy Constructor	303
Public Member Function insert_iterator	304

Table of Contents

Assignment Operator =	304
Dereferencing Operator *	304
Incrementation Operator ++	304
insert_iterator::inserter	304

10 Algorithms Library 305

Overview of the Algorithms Library.	305
In-place and Copying Versions.	305
Algorithms with Predicate Parameters	306
Binary Predicates.	306
Non Mutating Sequence Algorithms	307
for_each.	307
find.	308
find_if	308
adjacent_find	309
count	310
count_if.	310
mismatch	311
equal	312
search	313
Mutating Sequence Algorithms.	314
copy	315
copy_backward	315
swap	316
iter_swap	316
swap_ranges.	317
transform	317
replace	318
replace_if	319
replace_copy	319
replace_copy_if	320
fill	320
fill_n	321
generate.	321
generate_n	322

remove 322
remove_if 323
remove_copy 324
remove_copy_if 324
unique 325
unique_copy. 326
reverse 327
reverse_copy 327
rotate 327
rotate_copy 328
random_shuffle 329
partition 329
stable_partition 330
Sorting and Related Algorithms 331
Sorting 332
sort. 332
stable_sort. 333
partial_sort 333
partial_sort_copy. 334
nth_element 335
Binary Searching 336
binary_search 336
lower_bound 337
upper_bound 338
equal_range 339
Merging. 340
merge. 340
inplace_merge 341
Set Operations on Sorted Structures. 342
includes. 343
set_union 343
set_intersection 344
set_difference 345
set_symmetric_difference 346
Heap Operations. 347

Table of Contents

push_heap 348
pop_heap 349
make_heap 349
sort_heap 350
Finding Min and Max. 351
min. 351
max 352
min_element. 352
max_element 353
Lexicographical Comparison. 354
lexicographical_compare 354
Permutation Generators. 355
next_permutation 355
prev_permutation 356
Generalized Numeric Algorithms. 356
accumulate 357
inner_product 357
partial_sum 359
adjacent_difference. 360

11 Numerics Library **363**

Overview of the Numerics Library 363
Numeric Type Requirements 363
Numeric Arrays 364
Template Class valarray 365
Constructors valarray. 365
Default Constructor 365
Overloaded Constructors 366
Copy Constructor 366
Conversion Constructors 366
Destructor. 367
Assignment Operators valarray 367
Assignment Operator = 367
Overloaded Assignment Operators 367
Element Access valarray 368

Subscript Operator [] 368
Subset Operations valarray 368
Subscript Operator [] 368
Unary Operators valarray 368
Add Operator + 369
Minus Operator -. 369
Complement Operator ~ 369
Not Operator !. 369
Computed Assignment Type valarray<T> 369
Multiply & Assign Operator *=. 369
Divide and Assign Operator /= 370
Remainder & Assign Operator %= 370
Add & Assign Operator += 370
Minus and Assign Operator -= 370
XOR and Assign Operator ^= 370
And & Assign Operator &= 370
Or & Assign Operator = 370
Not Equal Operator != 370
Right Shift & Assign Operator >>= 370
Computed Assignment Type<T> 371
Multiply & Assign Operator *=. 371
Divide & Assign Operator /= 371
Remainder & Assign Operator %= 371
Add & Assign Operator += 371
Minus & Assign Operator -= 371
XOR & Assign Operator ^= 371
And & Assign Operator &= 372
Not Equal Operator != 372
Right Shift & Assign Operator >>= 372
Non-Member Binary Operators valarray 372
Multiply Operator * 372
Divide Operator / 372
Remainder Operator % 373
Add Operator + 373
Minus Operator -. 373

Table of Contents

Bitwise XOR Operator ^	373
Bitwise And Operator &.	374
Bitwise Or Operator	374
Left Shift Operator <<.	374
Right Shift Operator >>.	374
Logical And Operator &&.	374
Logical Or Operator 	375
Overloaded Binary Operators valarray	375
Multiply Operator *	375
Divide Operator /	375
Remainder Operator %	376
Add Operator +	376
Minus Operator -.	376
Bitwise XOR Operator ^.	377
Bitwise And Operator &.	377
Bitwise Or Operator 	377
Left Shift Operator <<.	378
Right Shift Operator >>.	378
Logical And Operator &&.	378
Logical Or Operator 	379
Comparison Operators valarray	379
Equality Operator ==	379
Less Than Operator <.	380
Greater Than Operator >	380
Not Equal Operator !=	380
Greater Than or Equal Operator >=	380
Overloaded Comparison Operators valarray.	381
Equality Operator ==	381
Not Equal Operator !=	381
Less Than Operator <.	382
Greater Than Operator >	382
Less Than or Equal Operator <=	382
Greater Than or Equal Operator >=	383
Member Functions valarray	383
valarray::length	383

Pointer Conversion	383
valarray::sum	384
valarray::fill	384
valarray::shift	384
valarray::cshift	384
valarray::apply	385
valarray::free	385
Min And Max Functions valarray	385
valarray::min	385
valarray::max	386
Transcendentals valarray	386
valarray::abs	386
valarray::acos	386
valarray::asin	387
valarray::atan	387
valarray::atan2	387
valarray::cos	387
valarray::cosh	388
valarray::exp	388
valarray::log	388
valarray::log10	388
valarray::pow	388
valarray::sin	389
valarray::sinh	389
valarray::sqrt	389
valarray::tan	389
valarray::tanh	389
Class slice	390
Constructors slice	390
Overloaded and Copy Constructors	390
Access Functions slice	391
slice::start	391
slice::length	391
slice::stride	391
Template class slice_array	391

Table of Contents

Constructors slice_array	392
Default and Copy Constructor	392
Assignment Operators slice_array	392
Assignment Operator =	392
Computed Assignment slice_array	392
Multiply & Assign Operator *=	392
Divide & Assign Operator /=	393
Remainder & Assign Operator %=	393
Add & Assign Operator +=	393
Minus & Assign Operator -=	393
XOR & Assign Operator ^=	393
And & Assign Operator &=	393
Or & Assign Operator =	393
Left Shift & Assign Operator <<=	393
Right shift & Assign Operator >>=	393
Public Member Function slice_array	394
slice_array::fill	394
Class gslice	394
Constructors gslice	394
Default Constructor	394
Overloaded Constructors	395
Access Functions gslice	395
gslice::start	395
gslice::length.	395
gslice::stride	395
Template Class gslice_array	395
Constructors gslice_array	396
Default and Copy Constructors	396
Assignment gslice_array	396
Assignment Operator =	396
Computed Assignment gslice_array	396
Multiply & Assign Operator *=	397
Divide & Assign Operator /=	397
Remainder & Assign Operator %=	397
Add & Assign Operator +=	397

Minus & Assign Operator -=	397
XOR & Assign Operator ^=	397
And & Assign Operator &=	397
Or & Assign Operator =	397
Left Shift & Assign Operator <<=	397
Right Shift & Assign Operator >>=	398
Public Member Function gslice_array	398
gslice_array::fill	398
Template Class mask_array	398
Constructors mask_array	399
Constructors.	399
Assignment mask_array.	399
Assignment Operator =	399
Computed Assignment mask_array.	399
Multiply & Assign Operator *=	399
Divide & Assign Operator /=	399
Remainder & Assign Operator %=	400
Add & Assign Operator +=	400
Minus & Assign Operator -=	400
XOR & Assign Operator ^=	400
And & Assign Operator &=	400
Or & Assign Operator =	400
Left Shift & Assign Operator <<=	400
Right Shift & Assign Operator >>=	400
Public Member Function mask_array	401
mask_array::fill	401
Template Class indirect_array	401
Constructors indirect_array	401
Default and Copy Constructors	401
Assignment indirect_array	402
Assignment Operator =	402
Computed Assignment indirect_array.	402
Multiply & Assign Operator *=	402
Divide & Assign Operator /=	402
Remainder & Assign Operator %=	402

Table of Contents

Add & Assign Operator +=	403
Minus & Assign Operator -=	403
XOR & Assign Operator ^=	403
And & Assign Operator &=	403
Or & Assign Operator =	403
Left Shift & Assign Operator <<=	403
Right Shift & Assign Operator >>=	403
Public Member Function indirect_array	403
indirect_array::fill	403
Generalized Numeric Operations	404
Template Class accumulate.	404
Template Class inner_product	405
Template Class partial_sum	405
Template Class adjacent_difference	406
12 26.2 Complex Class	409
Overview of the Complex Class Library	409
_MSL_CX_LIMITED_RANGE	409
Header <complex>	410
26.2.3 Complex Specializations	414
Complex Template Class.	416
Constructors and Assignments.	416
Complex Member Functions.	417
Operators	417
Overloaded Operators and Functions	419
Complex Operators.	420
Complex Value Operations	423
Complex Transcendentals	425
13 27.1 Input and Output Library	429
Overview of Input and Output Library	429
Input and Output Library Summary	429
27.1 Iostreams requirements	430
27.1.1 Definitions.	430
27.1.2 Type requirements	431
27.1.2.5 Type SZ_T	431

14	27.2 Forward Declarations	433
	Overview of Input and Output Streams Forward Declarations. . .	433
	Header <iosfwd>.	433
15	27.3 Standard Iostream Objects	435
	Overview of Standard Input and Output Stream Objects. . . .	435
	Header <iostream>.	435
	27.3.1 Narrow stream objects.	436
	istream cin	436
	ostream cout.	436
	ostream cerr	436
	ostream clog.	437
	27.3.2 Wide stream objects.	437
	istream win	437
	ostream wout	437
	wostream werr.	438
	wostream wlog	438
16	27.4 Iostreams Base Classes	439
	Overview of Input and Output Stream Base Classes.	439
	Header <ios>.	439
	27.4.1 Typedef Declarations	440
	27.4.3 Class ios_base	441
	27.4.3.1 Typedef Declarations	443
	27.4.3.1.1 failure	443
	27.4.3.1.1.1 failure	444
	failure::what.	444
	27.4.3.1.2 Type fmtflags	444
	27.4.3.1.3 Type iostate	446
	27.4.3.1.4 Type openmode	446
	27.4.3.1.5 Type seekdir	447
	27.4.3.1.6 Class Init	447
	Class Init Constructor.	447
	27.4.3.2 ios_base fmtflags state functions.	448
	flags	448
	setf.	451

Table of Contents

unsetf.	452
precision	453
width.	454
27.4.3.3 ios_base locale functions	455
imbue	455
getloc.	456
27.4.3.4 ios_base storage function.	456
xalloc.	456
iword.	456
pword	457
register_callback	457
sync_with_stdio	458
27.4.3.5 ios_base Constructor.	458
27.4.4 Template class basic_ios	458
27.4.4.1 basic_ios Constructor	460
27.4.4.2 Member Functions	461
tie	461
rdbuf	463
imbue	464
fill	464
copyfmt.	465
27.4.4.3 basic_ios iostate flags functions	466
operator bool	466
operator !	466
rdstate	466
clear	468
setstate	470
good	471
eof	471
fail	473
bad.	474
exceptions.	476
27.4.5 ios_base manipulators	476
27.4.5.1 fmtflags manipulators	476
27.4.5.2 adjustfield manipulators	478

27.4.5.3 basefield manipulators	478
27.4.5.4 floatfield manipulators	479
Overloading Manipulators	480
17 27.5 Stream Buffers	483
Overview of Stream Buffers	483
Header <streambuf>	483
27.5.1 Stream buffer requirements	483
27.5.2 Template class basic_streambuf<charT, traits>	484
27.5.2.1 basic_streambuf Constructor	487
27.5.2.2 basic_streambuf Public Member Functions	488
27.5.2.2.1 Locales	488
basic_streambuf::pubimbue	488
basic_streambuf::getloc	488
27.5.2.2.2 Buffer Management and Positioning	488
basic_streambuf::pubsetbuf	489
basic_streambuf::pubseekoff	490
basic_streambuf::pubseekpos	491
basic_streambuf::pubsync	493
27.5.2.2.3 Get Area	494
basic_streambuf::in_avail	494
basic_streambuf::snextc	494
basic_streambuf::sbumpc	495
basic_streambuf::sgetc	496
basic_streambuf::sgetn	497
27.5.2.2.4 Putback	497
basic_streambuf::sputback	497
basic_streambuf::sungetc	499
27.5.2.2.5 Put Area	499
basic_streambuf::sputc	499
basic_streambuf::sputn	500
27.5.2.3 basic_streambuf Protected Member Functions	501
27.5.2.3.1 Get Area Access	501
basic_streambuf::eback	501
basic_streambuf::gptr	501

Table of Contents

basic_streambuf::egptr	501
basic_streambuf::gbump	502
basic_streambuf::setg	502
27.5.2.3.2 Put Area Access	502
basic_streambuf::pbase	502
basic_streambuf::pptr	503
basic_streambuf::epptr	503
basic_streambuf::pbump	503
basic_streambuf::setp	503
27.5.2.4 basic_streambuf Virtual Functions	504
27.5.2.4.1 Locales	504
basic_streambuf::imbue	504
27.5.2.4.2 Buffer Management and Positioning	504
basic_streambuf::setbuf	504
basic_streambuf::seekoff	505
basic_streambuf::seekpos	505
basic_streambuf::sync	505
27.5.2.4.3 Get Area	506
basic_streambuf::showmanc	506
basic_streambuf::xsgetn	506
basic_streambuf::underflow	506
basic_streambuf::uflow	507
27.5.2.4.4 Putback	508
basic_streambuf::pbackfail	508
27.5.2.4.5 Put Area	508
basic_streambuf::xspn	508
basic_streambuf::overflow	509

18 27.6 Formatting And Manipulators 511

Overview of Formatting and Manipulators	511
Headers	511
Header <istream>	511
Header <ostream>	512
Header <iomanip>	513
27.6.1 Input Streams	513

27.6.1.1 Template class <code>basic_istream</code>	513
27.6.1.1.1 <code>basic_istream</code> Constructors	516
27.6.1.1.2 Class <code>basic_istream::sentry</code>	517
Class <code>basic_istream::sentry</code> Constructor	518
<code>sentry::Operator bool</code>	518
27.6.1.2 Formatted input functions	519
27.6.1.2.1 Common requirements	519
27.6.1.2.2 Arithmetic Extractors <code>Operator >></code>	519
27.6.1.2.3 <code>basic_istream</code> extractor operator <code>>></code>	520
Overloading Extractors:	523
27.6.1.3 Unformatted input functions	525
<code>basic_istream::gcount</code>	525
<code>basic_istream::get</code>	527
<code>basic_istream::getline</code>	530
<code>basic_istream::ignore</code>	532
<code>basic_istream::peek</code>	534
<code>basic_istream::read</code>	534
<code>basic_istream::readsome</code>	536
<code>basic_istream::putback</code>	537
<code>basic_istream::unget</code>	539
<code>basic_istream::sync</code>	541
<code>basic_istream::tellg</code>	542
<code>basic_istream::seekg</code>	542
27.6.1.4 Standard <code>basic_istream</code> manipulators	544
<code>basic_ifstream::ws</code>	544
27.6.1.4.1 <code>basic_iostream</code> Constructor	546
27.6.2 Output streams	547
27.6.2.1 Template class <code>basic_ostream</code>	547
27.6.2.2 <code>basic_ostream</code> Constructor	549
27.6.2.3 Class <code>basic_ostream::sentry</code>	550
Class <code>basic_ostream::sentry</code> Constructor	551
<code>sentry::Operator bool</code>	551
27.6.2.4 Formatted output functions	552
27.6.2.4.1 Common requirements	552
27.6.2.4.2 Arithmetic Inserter <code>Operator <<</code>	552

Table of Contents

27.6.2.4.3 basic_ostream::operator<<	554
Overloading Inserters.	556
27.6.2.5 Unformatted output functions	558
basic_ostream::tellp.	558
basic_ostream::seekp	559
basic_ostream::put	560
basic_ostream::write	561
basic_ostream::flush	563
27.6.2.6 Standard basic_ostream manipulators	565
basic_ostream::endl	566
basic_ostream::ends	566
basic_ostream::flush	567
27.6.3 Standard manipulators.	570
Standard Manipulator Instantiations	570
resetiosflags	570
setiosflags	571
:setbase	572
setfill	573
setprecision	574
setw	575
Overloaded Manipulator	576

19 27.7 String Based Streams 579

Overview of String Based Stream Classes	579
Header <sstream>	579
27.7.1 Template class basic_stringbuf.	580
27.7.1.1 basic_stringbuf constructors	581
27.7.1.2 Member functions.	583
basic_stringbuf::str	583
27.7.1.3 Overridden virtual functions	584
basic_stringbuf::underflow	584
basic_stringbuf::pbackfail	585
basic_stringbuf::overflow	585
basic_stringbuf::seekoff	586
basic_stringbuf::seekpos.	586

27.7.2 Template class basic_istream.	587
27.7.2.1 basic_istream constructors.	588
27.7.2.2 Member functions.	589
basic_istream::rdbuf.	589
basic_istream::str.	590
27.7.2.3 Class basic_ostringstream.	591
27.7.2.4 basic_ostringstream constructors.	592
27.7.2.5 Member functions.	594
basic_ostringstream::rdbuf.	594
basic_ostringstream::str.	596
27.7.3 Class basic_stringstream.	597
27.7.3.4 basic_stringstream constructors.	598
27.7.3.5 Member functions.	600
basic_stringstream::rdbuf.	600
basic_stringstream::str.	601

20 27.8 File Based Streams 603

Overview of File Based Streams	603
Header <fstream>	603
27.8.1 File streams	603
27.8.1.1 Template class basic_filebuf.	604
27.8.1.2 basic_filebuf Constructors	606
27.8.1.3 Member functions.	606
basic_filebuf::is_open.	606
basic_filebuf::open.	607
basic_filebuf::close.	609
27.8.1.4 Overridden virtual functions	609
basic_filebuf::showmanyc.	609
basic_filebuf::underflow.	610
basic_filebuf::pbackfail.	610
basic_filebuf::overflow.	610
basic_filebuf::seekoff.	611
basic_filebuf::seekpos.	611
basic_filebuf::setbuf.	611
basic_filebuf::sync.	612

Table of Contents

basic_filebuf::imbue	612
27.8.1.5 Template class basic_ifstream	612
27.8.1.6 basic_ifstream Constructor	613
27.8.1.7 Member functions	615
basic_ifstream::rdbuf	615
basic_ifstream::is_open	616
basic_ifstream::open	616
basic_ifstream::close	618
27.8.1.8 Template class basic_ofstream	619
27.8.1.9 basic_ofstream constructor	620
27.8.1.10 Member functions	621
basic_ofstream::rdbuf	621
basic_ofstream::is_open	623
basic_ofstream::open	623
basic_ofstream::close	625
27.8.1.11 Template class basic_fstream	626
27.8.1.12 basic_fstream Constructor	627
27.8.1.13 Member Functions	628
basic_fstream::rdbuf	628
basic_fstream::is_open	630
basic_fstream::open	630
basic_fstream::close	631
21 C Library files	633
27.8.2 C Library files	633
<stdio> Macros	633
<stdio> Types	633
<stdio> Functions	634
22 Annex D Strstream	635
Overview of Strstream Classes	635
Header <strstream>	635
Strstreambuf Class	638
Strstreambuf constructors and Destructors	640
Strstreambuf Public Member Functions	641
freeze	641

Table of Contents

pcount 642
str 643
Protected Virtual Member Functions 644
setbuf. 644
seekoff 645
seekpos 645
underflow. 645
pbackfail 646
overflow 646
Istrstream Class 647
Constructors and Destructor 648
Constructors. 648
Destructor. 649
Public Member Functions 649
rdbuf 649
str 650
Ostrstream Class 650
Constructors and Destructor 651
Constructors. 651
Destructor. 652
Public Member Functions 653
freeze. 653
pcount 654
rdbuf 655
str 655
Strstream Class. 656
Strstream Types 657
Constructors and Destructor. 657
Constructors. 657
Destructor. 657
Public Member Functions 657
freeze. 657
pcount 658
rdbuf 658
str 658

Table of Contents

23 Mutex.h	659
Overview of Mutex Support Library 659
Header <mutex.h> 659
null_mutex 662
Constructor and Destructor 662
Constructor 662
Destructor. 662
Public Member Functions 663
remove 663
acquire 663
release 663
mutex 663
Constructor and Destructor 664
Constructor 664
Destructor. 664
Public Member Functions 664
remove 664
acquire 664
release 664
try_lock. 665
mutex_block 665
Constructor and Destructors. 665
Constructor 665
Destructor. 665
Public Member Functions 666
remove 666
release 666
acquire 666
mutex_arith 666
Constructors. 667
Public Member Operators 667
Prefix operator++ 667
Postfix operator++ 668
operator+= 668
Prefix operator-- 668

Postfix operator-- 668
operator-= 668
operator== 668
operator!= 669
operator>= 669
operator> 669
operator<= 669
operator< 670
operator= 670
operator TYPE 670
rw_mutex 670
Constructor and Destructor 671
Constructor 671
Destructor 671
Public Member Functions 671
remove 671
acquire 671
release 671
try_rdlock 672
try_wrlock 672
mutex_rec 672
Constructor 673
Public Members Functions. 673
acquire 673
release 673
remove 673

Table of Contents



Introduction

This reference manual describes the contents of the C++ standard library and what Metrowerks' library provides for its users. The C++ Standard library provides an extensible framework, and contains components for: language support, diagnostics, general utilities, strings, locales, containers, iterators, algorithms, numerics, and input/output.

Metrowerks Year 2000 Compliance

The Products provided by Metrowerks under the License agreement process dates only to the extent that the Products use date data provided by the host or target operating system for date representations used in internal processes, such as file modifications. Any Year 2000 Compliance issues resulting from the operation of the Products are therefore necessarily subject to the Year 2000 Compliance of the relevant host or target operating system. Metrowerks directs you to the relevant statements of Microsoft Corporation, Sun Microsystems, Inc., Apple Computer, Inc., and other host or target operating systems relating to the Year 2000 Compliance of their operating systems. Except as expressly described above, the Products, in themselves, do not process date data and therefore do not implicate Year 2000 Compliance issues.

For additional information, visit: <http://www.metrowerks.com/about/y2k.html>.

About the MSL C++ Library Reference Manual

This section describes each chapter in this manual.

[“Overview of the MSL C++ Reference” on page 43](#), of this manual describes the language support library that provides components

Introduction

About the MSL C++ Library Reference Manual

that are required by certain parts of the C++ language, such as memory allocation and exception processing.

[“Overview of Language Support Libraries” on page 47](#), discusses the ANSI/ISO language support library.

[“Overview of Diagnostics Library” on page 63](#), elaborates on the diagnostics library that provides a consistent framework for reporting errors in a C++ program, including predefined exception classes.

[“Overview of General Utilities Libraries” on page 71](#), discusses the general utilities library, which includes components used by other library elements, such as predefined storage allocator for dynamic storage management.

[“Overview of Strings Classes” on page 95](#), discusses the strings components provided for manipulating text represented as sequences of type `char`, sequences of type `wchar_t`, or sequences of any other “character-like” type.

[“Overview of the Localization Library” on page 137](#), covers the localization components extend internationalization support for character classification, numeric, monetary, and date/time formatting and parsing among other things.

[“Overview of the Containers Library” on page 177](#), discusses container classes: lists, vectors, stacks, and so forth. These classes provide a C++ program with access to a subset of the most widely used algorithms and data structures.

[“Overview of Iterators” on page 273](#), discusses iterator classes.

[“Overview of the Algorithms Library” on page 305](#), discusses the algorithms library. This library provides sequence, sorting, and general numerics algorithms.

[“Overview of the Numerics Library” on page 363](#), discusses the numerics library. It describes the components for complex number types, numeric arrays, generalized numeric algorithms and facilities included from the ISO C library.

[“Overview of the Complex Class Library” on page 409](#) discusses the template class complex, for complex number storage and manipulation.

[“Overview of Input and Output Library” on page 429](#), overviews the input and output class libraries.

[“Overview of Input and Output Streams Forward Declarations.” on page 433](#), discusses the input and output streams forward declarations.

[“Overview of Standard Input and Output Stream Objects.” on page 435](#), discusses the initialized input and output objects.

[“Overview of Input and Output Stream Base Classes” on page 439](#), discusses the `iostream_base` class.

[“Overview of Stream Buffers” on page 483](#), discusses the stream buffer classes.

[“Overview of Formatting and Manipulators” on page 511](#), discusses the formatting and manipulator classes.

[“Overview of String Based Stream Classes” on page 579](#), discusses the string based stream classes.

[“Overview of File Based Streams” on page 603](#), discusses the file based stream classes.

[“27.8.2 C Library files” on page 633](#), discusses the namespace C library functions.

[“Overview of Mutex Support Library” on page 659](#), discusses the mutex classes.

[“Overview of Strstream Classes” on page 635](#), a non-templated array based stream class.

Introduction

About the MSL C++ Library Reference Manual



MSL C++ Reference

This chapter is an introduction to the Metrowerks Standard C++ library.

Overview of the MSL C++ Reference

This section introduces you to the definitions, conventions, terminology, and other aspects of the MSL C++ library. The topics discussed are:

- [“Definitions” on page 43](#)
- [“Features not implemented in MSL C++” on page 45](#)

Definitions

This section discusses the meaning of certain terms in the MSL C++ library. The topics discussed are:

- [“Character Sequences” on page 43](#)
- [“Byte Strings” on page 44](#)
- [“Multibyte Strings” on page 44](#)
- [“Wide-Character Sequences” on page 44](#)
- [“Multi-Thread Safety” on page 45](#)

Character Sequences

The Standard C/C++ library makes widespread use of characters and character sequences that follow a few uniform conventions:

A letter is any of the 26 lowercase or 26 uppercase letters in the basic execution character set.

The decimal-point character is the (single-byte) character used by functions that convert between a (single-byte) character sequence and a value of one of the floating-point types. It is used in the character sequence to denote the beginning of a fractional part. It is represented by a period, '.', which is also its value in the "C" locale, but may change during program execution by a call to `setlocale(int, const char*)`, or by a change to a locale object.

A character sequence is an array object `A` that can be declared as `T A[N]`, where `T` is any of the types `char`, `unsigned char`, or `signed char`, optionally qualified by any combination of `const` or `volatile`. The initial elements of the array have defined contents up to and including an element determined by some predicate. A character sequence can be designated by a pointer value `S` that points to its first element.

Byte Strings

A null-terminated byte string, or `NTBS`, is a character sequence which has a value zero appended to its contents. The length of an `NTBS` is the number of elements that precede the terminating `null` character. An empty `NTBS` has a length of zero. The value of an `NTBS` is the sequence of values of the elements up to and including the terminating null character.

Multibyte Strings

A null-terminated multibyte string, or `NTMBS`, is an `NTBS` that constitutes a sequence of valid multibyte characters, beginning and ending in the initial shift state. An `NTBS` that contains characters only from the basic character set is also an `NTMBS`. Each multibyte character then consists of a single byte.

Wide-Character Sequences

A wide-character sequence is an array object `'A'` that can be declared as `T A[N]`, where `T` is type `wchar_t`, optionally qualified by any combination of `const` or `volatile`. The initial elements of

the array have defined contents up to and including an element determined by some predicate. A character sequence can be designated by a pointer value *S* that designates its first element.

A null-terminated wide-character string, or *NTWCS*, is a wide-character sequence which has a value zero appended to its contents.

The length of an *NTWCS* is the number of elements that precede the terminating null wide character. An empty *NTWCS* has a length of zero.

The value of an *NTWCS* is the sequence of values of the elements up to and including the terminating null character.

Multi-Thread Safety

MSL C++ Library is multi-thread safe provided that the operating system supports thread-safe system calls. Library has locks at appropriate places in the code for thread safety. The locks are implemented as a mutex class -- the implementation of which may differ from platform to platform.

This ensures that the library is MT-Safe internally. For example, if a buffer is shared between two ios class objects, then only one ios object will be able to modify the shared buffer at a given time.

Thus the library will work in the presence of multiple threads in the same way as in single thread provided the user does not share objects between threads or locks between accesses to objects that are shared.

Features not implemented in MSL C++

The following sections of November 1997 Working Draft C++ will not be implemented in the MSL C++ product.

- [“Template Functionality” on page 46](#)
- [“ANSI/ISO Library Functionality” on page 46](#)

Template Functionality

There are several areas of the Standard library that depend on C++ features like member templates that have so far not been implemented.

ANSI/ISO Library Functionality

The following standard library features are not part of the current release, but are being implemented:

- Messages in Locale



Language Support Library

This chapter is a reference guide to the ANSI/ISO language support library.

Overview of Language Support Libraries

This clause in the April 1995 WPD describes the function signatures that are called implicitly, and the types of objects generated implicitly, during the execution of some C++ programs. This chapter describes the headers that declare these function signatures and define any related types. It also describes common type definitions used throughout the library, characteristics of the predefined types, functions supporting start and termination of a C++ program, support for dynamic memory management, support for dynamic type identification, support for exception processing, and other runtime support.

The topics discussed are:

- [“Types and Macros” on page 47](#)
- [“Numeric Limits” on page 50](#)
- [“Dynamic Memory Storage Allocation Errors” on page 58](#)

Types and Macros

This section discusses types and macros. The topics are:

- [“Macros” on page 48](#)
- [“Type Implementations” on page 48](#)

Macros

The macros defined are:

- [“NULL” on page 48](#)
- [“offsetof” on page 48](#)
- [“sizeof” on page 48](#)

NULL

Description The macro **NULL** is an implementation-defined C++ null-pointer constant in this International Standard. In MSL this evaluates to zero.

Source file <stddef.h>

offsetof

Description The macro **offsetof** accepts a restricted set of `type` arguments in this International Standard. `type` shall be a POD¹ structure or a POD union.

Source file <stddef.h>

sizeof

Description The **sizeof** operator yields the number of bytes in the object representation of its operand. The operand can be either an expression, which is not evaluated, or a parenthesized `type-id`.

Source file <stddef.h>

Type Implementations

There are several fundamental types. They are:

- [“Character types” on page 49](#)

¹A POD structure or union is a union that has no members that are of type pointer to members. The acronym for POD stands for “Plain Old Data”.

- [“Enumeration” on page 49](#)
- [“Integral types” on page 49](#)
- [“Wide character types” on page 50](#)
- [“Bool type” on page 50](#)
- [“Floating point types” on page 50](#)
- [“Void type” on page 50](#)

Character types

Objects declared as characters(**char**) shall be large enough to store any member of the implementation’s basic character set. If a character from this set is stored in a character object, its value shall be equivalent to the integer code of that character. It is implementation-defined whether a char object can take on negative values. Characters can be explicitly declared **unsigned** or **signed**. Plain **char**, **signed char**, and **unsigned char** are three distinct types. A **char**, a **signed char**, and an **unsigned char** occupy the same amount of storage and have the same alignment requirements; that is, they have the same object representation. For character types, all bits of the object representation participate in the value representation. For unsigned character types, all possible bit patterns of the value representation represent numbers.

Enumeration

An **enumeration** comprises a set of named integer constant values, which form the basis for an integral subrange that includes those values. Each distinct **enumeration** constitutes a different enumerated type. Each constant has the type of its **enumeration**.

Integral types

There are four signed integer types: **signed char**, **short int**, **int** and **long int**. In this list, each type provides at least as much storage as those preceding it in the list, but the implementation can otherwise make any of them equal in storage size. Plain **ints** have the natural size suggested by the machine architecture; the other signed integer types are provided to meet special needs.

For each of the signed integer types, there exists a corresponding unsigned integer type: `unsigned char`, `unsigned short int`, `unsigned int` and `unsigned long int`, each of which occupies the same amount of storage and has the same alignment requirements as the corresponding signed integer type.

Wide character types

Type `wchar_t` is a distinct type whose values can represent distinct codes for all members of the largest extended character set specified among the supported locales.

Bool type

Values of type `bool` are either `true(1)` or `false(0)`. There are no signed, unsigned, short, or long `bool` types or values.

Floating point types

There are three floating point types: `float`, `double`, and `long double`. The type `double` provides at least as much precision as `float`, and the type `long double` provides at least as much as precision as `double`.

Void type

The `void` type has an empty set of values. It is used as the return type for functions that do not return a value.

Numeric Limits

The `numeric_limits` component provides a C++ program with information about various properties of the implementation's representation of the fundamental types. Specializations will be provided for each fundamental type, both floating point and integer, including `bool`. The member `is_specialized` shall be `true` for all such specializations of `numeric_limits`.

The only class discussed is:

- [“Template Class numeric_limits” on page 51](#)

Template Class numeric_limits

This section discusses the numeric_limits template class. The functions discussed are:

Table 3.1 **numeric_limits functions**

numeric_limits::is_specialized	numeric_limits::max_exponent10
numeric_limits::min	numeric_limits::has_infinity
numeric_limits::max	numeric_limits::has_quiet_NaN
numeric_limits::digits	numeric_limits::has_signaling_NaN
numeric_limits::digits10	numeric_limits::has_denorm
numeric_limits::is_signed	numeric_limits::infinity
numeric_limits::is_integer	numeric_limits::quiet_NaN
numeric_limits::is_exact	numeric_limits::signaling_NaN
numeric_limits::radix	numeric_limits::denorm_min
numeric_limits::epsilon	numeric_limits::is_bounded
numeric_limits::round_error	numeric_limits::is_modulo
numeric_limits::min_exponent	numeric_limits::traps
numeric_limits::min_exponent10	numeric_limits::tinyness_before
numeric_limits::max_exponent	numeric_limits::round_style

numeric_limits::is_specialized

Description The member `is_specialized` makes it possible to distinguish between scalar types, which have specializations, and non-scalar types, which do not.

Definition `static const bool is_specialized;`

numeric_limits::min

Description This function returns the minimum finite value that can be `CHAR_MIN`, `SHRT_MIN`, `FLT_MIN`, `DBL_MIN`, etc. For this function, floating types with denormalization, return the minimum positive normalized value, `denorm_min`. The value returned by this function is meaningful for all specializations in which `is_bounded==true`, or `is_bounded==false` and `is_signed==false`.

Prototype `static T min();`

numeric_limits::max

Description This function returns the maximum finite value that can be `CHAR_MAX`, `SHRT_MAX`, `FLT_MAX`, `DBL_MAX`, etc. The value returned by this function is meaningful for all specializations in which `is_bounded==true`.

Prototype `static T max();`

numeric_limits::digits

Description It stores the number of radix digits that can be represented without change. For built-in integer types, it denotes the number of non-sign bits in the representation. For floating point types, it denotes the number of radix digits in the mantissa which can be `FLT_MANT_DIG`, `DBL_MANT_DIG` or `LDBL_MANT_DIG`.

Definition `static const int digits;`

numeric_limits::digits10

Description It stores the number of base 10 digits that can be represented without change. The value can be one among `FLT_DIG`, `DBL_DIG` or

LDBL_DIG. It is meaningful for all specializations in which `is_bounded==true`.

Definition `static const int digits10;`

numeric_limits::is_signed

Description It stores a value `true` if the type is signed. It is meaningful for all specializations.

Definition `static const bool is_signed;`

numeric_limits::is_integer

Description It stores a value that is `true`, if the type is integer. It is meaningful for all specializations.

Definition `static const bool is_integer;`

numeric_limits::is_exact

Description It stores a value `true` if the type uses an exact representation. All integer types are exact, but not vice versa. For example, rational and fixed-exponent representations are exact but not integer. It is meaningful for all specializations.

Definition `static const bool is_exact;`

numeric_limits::radix

Description It stores a value that specifies the base of radix of the exponent representation for floating types. Its value is usually 2 or can be `FLT_RADIX`. For integer types it specifies the base of the representation. It is meaningful for all specializations.

Definition `static const int radix;`

numeric_limits::epsilon

Description It returns the difference between 1 and the least value greater than 1 that is representable. The value can be either `FLT_EPSILON`, `DBL_EPSILON` or `LDBL_EPSILON`. The value returned is meaningful only for floating point types.

Prototype `static T epsilon();`

numeric_limits::round_error

Description It returns a value that denotes the maximum rounding error that is permitted. It is meaningful only for floating point types.

Prototype `static T round_error();`

numeric_limits::min_exponent

Description It stores the minimum negative integer such that `radix` raised to that power is in range. It is meaningful only for floating point types and the values can be `FLT_MIN_EXP`, `DBL_MIN_EXP`, `LDBL_MIN_EXP`.

Definition `static const int min_exponent;`

numeric_limits::min_exponent10

Description It stores the minimum negative integer such that 10 raised to that power is in range. It is meaningful only for floating point types and the values can be `FLT_MIN_10_EXP`, `DBL_MIN_10_EXP`, `LDBL_MIN_10_EXP`.

Definition `static const int min_exponent10;`

numeric_limits::max_exponent

Description It stores the maximum positive integer such that `radix` raised to that power is in range. It is meaningful only for floating point types and

the values can be `FLT_MAX_EXP`, `DBL_MAX_EXP`,
`LDBL_MAX_EXP`.

Definition `static const int max_exponent;`

numeric_limits::max_exponent10

Description It stores the maximum positive integer such that 10 raised to that power is in range. It is meaningful only for floating point types and the values can be `FLT_MAX_10_EXP`, `DBL_MAX_10_EXP`, `LDBL_MAX_10_EXP`.

Definition `static const int max_exponent10;`

numeric_limits::has_infinity

Description It stores a value `true` if the type has a representation for positive infinity. It is meaningful only for floating point types. It will be `true` for all specialization in which `is_iec559==true`.

Definition `static const bool has_infinity;`

numeric_limits::has_quiet_NaN

Description It stores a value `true` if the type has a representation for a quiet(non-signaling) Not a Number. It is meaningful only for floating point types. The value will be `true` for all specializations in which `is_iec559==true`.

Definition `static const bool has_quiet_NaN;`

numeric_limits::has_signaling_NaN

Description It stores a value `true` if the type has a representation for a signaling Not a Number. It is meaningful only for floating point types. The value will be `true` for all specializations in which `is_iec559==true`.

Definition `static const bool has_signaling_NaN;`

numeric_limits::has_denorm

Description It stores `true` if the type allows denormalized values (i.e. variable number of exponent bits). The value is meaningful only for floating point types.

Definition `static const bool has_denorm;`

numeric_limits::infinity

Description It returns the representation of positive infinity, if available. It is meaningful only for specializations for which `has_infinity==true`. Required in specializations for which `is_iec559==true`.

Prototype `static T infinity();`

numeric_limits::quiet_NaN

Description This function returns the representation of a quiet Not a Number if `has_quiet_NaN==true`.

Prototype `static T quiet_NaN();`

numeric_limits::signaling_NaN

Description This function returns the representation of a signaling Not a Number if `has_signaling_NaN==true`.

Prototype `static T signaling_NaN();`

numeric_limits::denorm_min

Description It returns the minimum positive denormalized value. It is meaningful for all floating point types. In this function specialization for

which has `_denorm==false`, returns the minimum positive normalized value.

Prototype `static T denorm_min();`

numeric_limits::is_bounded

Description It stores a value `true` if the set of values representable by the type is finite. All built-in types are bounded, this member would be false for arbitrary precision types. It is meaningful for all specializations.

Definition `static const bool is_bounded;`

numeric_limits::is_modulo

Description It stores a value `true` if the type is modulo. A type is modulo if it is possible to add two positive numbers and have a result that wraps around to a third number that is less than either of the two numbers. This has a value `false` for all floating types, `true` for unsigned integers, and `true` for signed integers on most machines and is meaningful for all specializations.

Definition `static const bool is_modulo;`

numeric_limits::traps

Description It stores a value `true` if trapping is implemented for the type. It is meaningful for all specializations.

Definition `static const bool traps;`

numeric_limits::tinyness_before

Description It stores a value `true` if tinyness is detected before rounding. It is meaningful only for floating point types.

Definition `static const bool tinyness_before;`

numeric_limits::round_style

Description It stores the rounding style for the type. The value stored is meaningful for all floating point types. Specializations for integer types shall return `round_toward_zero`.

Definition `static const float_round_style round_style;`

Dynamic Memory Storage Allocation Errors

This section discusses classes related to memory allocation errors. The classes discussed are:

- [“Class `bad_alloc`” on page 58](#)
- [“Class `bad_cast`” on page 59](#)
- [“Class `bad_typeid`” on page 60](#)

Class `bad_alloc`

The class `bad_alloc`, derived from the class `exception`, defines the type of objects thrown as exceptions by the implementation to report a failure to allocate storage.

Table 3.2 The member functions discussed are:

Constructor-<code>bad_cast</code>	Copy Constructor-<code>bad_alloc</code>
Assignment Operator-<code>bad_alloc</code>	bad_alloc::what

Constructor-`bad_alloc`

Description This function constructs an object of class `bad_alloc`.

Prototype `bad_alloc() throw();`

Copy Constructor-`bad_alloc`

Description This function copies an object of class `bad_alloc`.

Prototype `bad_alloc(const bad_alloc&) throw();`

Assignment Operator–bad_alloc

Description This function copies an object of class `bad_alloc`.

Prototype `bad_alloc& operator=(const bad_alloc&) throw();`

bad_alloc::what

Description Our implementation returns a `string` object instead of `const char*`. This function returns the string associated with the exception if some allocation is done, else it returns `string()`.

Prototype `virtual const char* what() const throw();`

Class bad_cast

The class `bad_cast`, derived from the `class exception`, defines the type of objects thrown as exceptions by the implementation to report the execution of an invalid dynamic-cast expression.

Table 3.3 **The member functions discussed are:**

<u>Constructor–bad_cast</u>	<u>Copy Constructor–bad_cast</u>
<u>Assignment Operator–bad_cast</u>	<u>bad_cast::what</u>

Constructor–bad_cast

Description This function constructs an object of class `bad_cast`.

Prototype `bad_cast() throw();`

Copy Constructor–bad_cast

Description This function copies or constructs an object of class `bad_cast`.

Prototype `bad_cast(const bad_cast&) throw();`

Assignment Operator–bad_cast

Description This function copies an object of class `bad_cast`.

Prototype `bad_cast& operator=(const bad_cast&) throw();`

bad_cast::what

Description Our implementation returns a `string` object instead of `const char*`. This function returns the string associated with the exception if some allocation is done, else it returns `string()`.

Prototype `virtual const char* what() const throw();`

Class bad_typeid

The class `bad_typeid`, derived from the class `exception`, defines the type of objects thrown as exceptions by the implementation to report a null pointer in a `typeid` expression.

Table 3.4 **The member functions discussed are:**

[Constructor–bad_typeid](#)

[Copy Constructor–bad_typeid](#)

[Assignment Operator–
bad_typeid](#)

[bad_typeid::what](#)

Constructor–bad_typeid

Description This function constructs an object of class `bad_typeid`.

Prototype `bad_typeid() throw();`

Copy Constructor–bad_typeid

Description These functions copy an object of class `bad_typeid`.

Prototype `bad_typeid(const bad_typeid&) throw();`

Assignment Operator–bad_typeid

Description This function copies an object of class `bad_typeid`.

Prototype `bad_typeid& operator=(const bad_typeid&) throw();`

bad_typeid::what

Description Our implementation returns a `string` object instead of `const char*`. This function returns the string associated with the exception if some allocation is done, else it returns `string()`.

Prototype `virtual const char* what() const throw();`



Diagnostics Library

This chapter is a reference guide to the ANSI/ISO exception classes, which are used for reporting several kinds of exceptional conditions, documenting program assertions, and a global variable for error number codes.

Overview of Diagnostics Library

The standard C++ library provides classes to be used to report errors in a C++ program. In the error model reflected in these classes, errors are divided into two broad categories: logic errors and runtime errors. The distinguishing characteristic of logic errors is that they are due to errors in the internal logic of the program, and are preventable. In contrast, runtime errors are due to events beyond the scope of the program. They cannot be easily predicted in advance. The header `<stdexcept.h>` defines several types of predefined exceptions for reporting errors in C++ program. These exceptions are related via inheritance.

The only group of classes in the diagnostics library are:

- [“Exception Classes” on page 63](#)

Exception Classes

There are several exception-related classes in the diagnostics library. The base class is `Class exception`. Other exception classes derive from `exception`.

The classes are:

- [“Class exception” on page 64](#)
- [“Class domain_error” on page 66](#)
- [“Class invalid_argument” on page 66](#)

- [“Class logic_error” on page 65](#)
- [“Class out_of_range” on page 67](#)
- [“Class runtime_error” on page 67](#)
- [“Class length_error” on page 66](#)
- [“Class overflow_error” on page 68](#)
- [“Class range_error” on page 68](#)

Class exception

Description The class exception defines the base class for the types of objects thrown as exceptions by C++ standard library components, and certain expressions, to report errors detected during program execution.

Table 4.1 The member functions discussed are:

[Constructor-exception](#)

[Copy Constructor-exception](#)

[Assignment Operator-exception](#)

[Destructor-exception](#)

[exception::what](#)

Constructor-exception

Description This function constructs an object of class exception. It does not throw any exceptions.

Prototype `exception() throw();`

Copy Constructor-exception

Description This function copies an exception object.

Prototype `exception& exception(const exception&) throw();`

Assignment Operator–exception

Description This function copies an exception object.

Prototype `exception& operator=(const exception&) throw();`

Destructor–exception

Description This function destroys an object of `class exception`.

Prototype `virtual ~exception() throw();`

exception::what

Description Our implementation returns a `string` object instead of `const char*`. This function returns the string associated with the exception if some allocation is done, else it returns `string()`.

Prototype `virtual const char* what() const throw();`

Class logic_error

Description The class `logic_error`, derived from [“Class exception” on page 64](#), defines the type of objects thrown as exceptions to report errors presumably detectable before the program executes, such as violations of logical preconditions or class invariants.

Table 4.2 The member functions discussed are:

[Constructor–logic_error](#)

Constructor–logic_error

Description This function constructs an object of class `logic_error`.

Prototype `logic_error(const string& what_arg);`

Class `domain_error`

Description The class `domain_error`, derived from [“Class `logic_error`” on page 65](#), defines the type of objects thrown as exceptions to report domain errors.

Table 4.3 The member functions discussed are:

[Constructor–`domain_error`](#)

Constructor–`domain_error`

Description This function constructs an object of class `domain_error`.

Prototype `domain_error(const string& what_arg);`

Class `invalid_argument`

Description The class `invalid_argument` defines the type of objects thrown as exceptions to report an invalid argument.

Table 4.4 The member functions discussed are:

[Constructor–`invalid_argument`](#)

Constructor–`invalid_argument`

Description This function constructs an object of class `invalid_argument`.

Prototype `invalid_argument(const string& what_arg);`

Class `length_error`

Description The class `length_error`, derived from [“Class `logic_error`” on page 65](#), defines the type of objects thrown as exceptions to report an attempt to produce an object whose length equals or exceeds its maximum allowable size.

Table 4.5 **The member functions discussed are:**

[Constructor-length_error](#)

Constructor-length_error

Description This function constructs an object of class `length_error`.

Prototype `length_error(const string& what_arg);`

Class out_of_range

Description The class `out_of_range`, derived from [“Class logic_error” on page 65](#), defines the type of objects thrown as exceptions to report an argument value not in its expected range.

Table 4.6 **The member functions discussed are:**

[Constructor-out_of_range](#)

Constructor-out_of_range

Description This function constructs an object of class `out_of_range`.

Prototype `out_of_range(const string& what_arg);`

Class runtime_error

Description The class `runtime_error`, derived from [“Class exception” on page 64](#), defines the type of objects thrown as exceptions to report errors presumably detectable only when the program executes.

Table 4.7 **The member functions discussed are:**

[Constructor-runtime_error](#)

Constructor–runtime_error

Description This function constructs an object of class `runtime_error`.

Prototype `runtime_error(const string& what_arg);`

Class range_error

Description The class `range_error`, derived from [“Class runtime_error” on page 67](#), defines the type of objects thrown as exceptions to report range errors.

Table 4.8 The member functions discussed are:

[Constructor–range_error](#)

Constructor–range_error

Description This function constructs an object of class `range_error`.

Prototype `range_error(const string& what_arg);`

Class overflow_error

Description The class `overflow_error`, derived from [“Class runtime_error” on page 67](#), defines the type of objects thrown as exceptions to report an arithmetic overflow error.

Table 4.9 The member functions discussed are:

[Constructor–overflow_error](#)

Constructor–overflow_error

Description This function constructs an object of class `overflow_error`.

Prototype `overflow_error(const string& what_arg);`

Diagnostics Library

Exception Classes



General Utilities Libraries

This chapter discusses the `Allocator` class.

Overview of General Utilities Libraries

Every STL container class uses an `Allocator` class to encapsulate information about the memory model being used by the program. The topics in this chapter are:

- [“Allocator Classes” on page 71](#)
- [“The Default Allocator Interface” on page 73](#)
- [“Arithmetic Operations” on page 81](#)
- [“Comparison Operations” on page 83](#)
- [“Logical Operations” on page 85](#)
- [“Negator Adaptors” on page 86](#)
- [“Binder Adaptors” on page 86](#)
- [“Adaptors for Pointers to Functions” on page 87](#)
- [“Specialized Algorithms” on page 89](#)
- [“Template class `auto_ptr`” on page 90](#)

Allocator Classes

Different memory models have different requirements for pointers, references, integer sizes, etc. The `Allocator` class encapsulates information about pointers, constant pointers, references, constant references, sizes of objects, difference types between pointers, allocation and deallocation functions, and some other functions. The

exact set of types and functions defined within the allocator are explained in the Default Allocator Interface, later in this chapter.

Since memory model information can be encapsulated in an allocator, STL containers can work with different memory models by simply providing different allocators. All operations on allocators are expected to be amortized constant time.

Additional topics are:

- [“Passing Allocators to STL Containers” on page 72](#)
- [“Extracting Information from an Allocator Object” on page 72](#)

Passing Allocators to STL Containers

Once an allocator class for a particular memory model has been written, it must be passed on to the STL container for that container to work properly in the concerned memory model. This is done by passing the allocator to the STL container as a template parameter.

For example, the vector container has the following interface:

```
template<class T, class Allocator = allocator>
class vector;
```

Here the Allocator parameter defaults to allocator. All the STL containers are not yet parameterized on Allocator. In all places where Allocator parameter is specified in the draft, default allocator is used.

Extracting Information from an Allocator Object

Allocator is obtained by a container by a macro of the same name. Once the allocator is known, the container must somehow extract the memory model information from the Allocator class. This information is extracted by simply accessing the typedefs and member functions of the Allocator class.

For example, the public interface of the vector class mentioned above contains the following typedefs to extract information about references and pointers from the Allocator class:

```
typedef Allocator<T>::reference reference;
typedef Allocator<T>::const_reference
    const_reference;
typedef Allocator<T>::pointer iterator;
typedef Allocator<T>::const_pointer
    const_iterator;
```

NOTE: If for different memory models, the types `Allocator<T>::pointer`, `Allocator<T>::size_type`, etc., will in general be different. However, the point is that these differences do not affect the vector container (or any other STL container), since the changes are completely encapsulated in the Allocator class.

The information passed on from the Allocator class to the STL container includes the types of pointers, constant pointers, references, constant references, etc., together with some member functions. Complete details of the types and functions encapsulated by the default allocator are provided in the next section.

The Default Allocator Interface

[“Class allocator declaration” on page 73](#) contains the Class allocator declaration.

Listing 5.1 Class allocator declaration

```
class allocator {
public:
    typedef size_t size_type;
    typedef ptrdiff_t difference_type;

    template<class T>
    class types {
```

General Utilities Libraries

The Default Allocator Interface

```
typedef T* pointer;
typedef const T* const_pointer;
typedef T& reference;
typedef const T& const_reference;
typedef T value_type;
};

allocator();
~allocator();

template<class T> typename
    types<T>::pointer
    address(types<T>::reference x) const;

template<class T> typename
    types<T>::const_pointer
    address(types<T>::const_reference x) const;

template<class T, class U> typename
    types<T>::pointer allocate(size_type,
    types<U>::const_pointer hint);

template<class T>
    void deallocate(types<T>::pointer p);

size_type max_size() const;
};

class allocator::types<void> { // specialization
public:
    typedef void* pointer;
    typedef const void* const_pointer;
    typedef void value_type;
};

void* operator new(size_t N, allocator& a);
```

Description In the allocator interface it can be seen that the type information is encapsulated in the nested template class `types`. Since nested class templates are not yet supported by any compilers, our implementa-

tion provides the following workaround by templating the class `allocator`.

The topics in this section discuss:

- [“Typedef Declarations” on page 75](#)
- [“Allocator Member Functions” on page 76](#)
- [“Custom Allocators” on page 79](#)
- [“Allocator Requirements” on page 79](#)

Typedef Declarations

Table 5.1 The following typedef’s are defined in the class `allocator<T>`

<code>allocator::pointer</code>	<code>allocator::const_pointer</code>
<code>allocator::reference</code>	<code>allocator::const_reference</code>
<code>allocator::value_type</code>	<code>allocator::const_address</code>

`allocator::pointer`

Description The type of a pointer in the memory model.

Definition `typedef T* pointer;`

`allocator::const_pointer`

Description The type of a constant pointer in the memory model.

Definition `typedef const T* const_pointer;`

`allocator::reference`

Description The type of a reference in the memory model.

Definition `typedef T& reference;`

allocator::const_reference

Description The type of a constant reference in the memory model.

Definition `typedef const T& const_reference`

allocator::value_type

Description `value_type` refers to the type of the objects in the container. By default, containers contain objects of the type with which they are instantiated. For example, `vector<int*>` is a declaration of a vector of pointers to integers.

Definition `typedef T value_type;`

Allocator Member Functions

Table 5.2 The Class `allocator` has the following member functions

<u>Constructor-allocator</u>	<u>Destructor-allocator</u>
<u>allocator::size_type</u>	<u>allocator::difference_type</u>
<u>allocator::address</u>	<u>allocator::const_address</u>
<u>allocator::allocate</u>	<u>allocator::deallocate</u>
<u>allocator::max_size</u>	

Constructor-allocator

Description Constructs an allocator object.

Prototype `allocator();`

Destructor-allocator

Description Destroys an allocator object.

Prototype `~allocator();`

The class `allocator` has the following other members:

`allocator::size_type`

Description `size_type` is the type that can represent the size of the largest object in the memory model.

Definition `typedef size_t size_type;`

`allocator::difference_type`

Description This is the type that can represent the difference between any two pointers in the memory model.

Definition `typedef ptrdiff_t difference_type;`

`allocator::address`

Description Returns a pointer to the referenced object `x`.

Prototype

```
template
    < class T >
allocator<T>::pointer address
    (allocator<T>::reference x);
```

`allocator::const_address`

Description Returns a constant pointer to the referenced object `x`.

Prototype

```
template
    < class T >
allocator<T>::const_pointer const_address
    (allocator<T>::const_reference x);
```

allocator::allocate

Description This member function allocates memory for `n` objects of type `size_type` but the objects are not constructed. It uses the global operator `new`.

NOTE: If that different memory models require different allocate functions (which is why the function has been encapsulated in the memory allocator class). `allocate` may raise an appropriate exception.

Prototype

```
template
    < class T >
allocator<T>::pointer allocate
    (size_type n);
```

allocator::deallocate

Description Deallocates all of the storage pointed to by the pointer `p` using the global operator `delete`. All objects in the area pointed to by `p` should be destroyed prior to the call of `deallocate`. The function is templated to allow it to be specialized for particular types in custom allocators.

Prototype

```
template
    < class T >
void deallocate
    (allocator<T>::pointer p);
```

allocator::max_size

Description Returns the largest positive value of `difference_type`. This is the same as the largest number of elements that the container can hold in the given memory model.

Prototype

```
size_type max_size();
```

Custom Allocators

The data types representing pointers (`size_type`) as well as the difference between two pointers (`difference_type`) differ across memory models.

Table 5.3 The data types representing pointers

[`allocator::vec_default`](#) [`allocator::vec_large`](#)
[`allocator::vec_huge`](#)

`allocator::vec_default`

Description A vector of 100 integers using the default allocator.

Prototype `vector<int> vec_default(100);`

`allocator::vec_large`

Description A vector of 1000 integers using the far allocator.

Prototype `vector<int, far_allocator> vec_large(1000);`

Remarks In case of the far allocator, the addressable range is 64 K. The `size_type` is a 32 bit value and `difference_type` is a 16-bit value.

`allocator::vec_huge`

Description A vector of 100,000 integers using the huge allocator.

Prototype `vector<int, huge_allocator> vec_huge(100000);`

Allocator Requirements

This section discusses

- [“Function Objects” on page 80](#)

- [“Function Adaptors” on page 80](#)

Function Objects

Description A function object encapsulates a function in an object for use by other components. This is done by overloading the function call operator, `operator()`, of the corresponding class.

Passing a function object to an algorithm is similar to passing a pointer to a function, with one important difference. Function objects are classes that have `operator()` overloaded, which makes it possible to

- pass function objects to algorithms at compile time, and
- increase efficiency, by inlining the corresponding call.

These costs make a difference when the functions involved are very simple ones, such as integer additions or comparisons.

For example, if we want to have a by-element addition of two integer vectors `a` and `b`, with the result being placed in `a`, we can do:

```
transform(a.begin(), a.end(), b.begin(),
          a.begin(), plus<int>());
```

If we want to negate every element of `a`, we do:

```
transform(a.begin(), a.end(),
          a.begin(), negate<int>());
```

In both of the above examples, the addition and negation will be inlined.

Function Adaptors

Description Function adaptors are STL classes that allow users to construct a wider variety of function objects. Using function adaptors is often easier than direct construction of a new function object type with a struct or class definition.

For example, a binder is a kind of function adapter that converts binary function objects into unary function objects by binding an argument to some particular value. The code fragment:

```
int x[1000];
int* where = find_if(x, x+1000,
    bind2nd(greater<int>(), 200));
```

finds the first integer in array `x` that is greater than 200. The base function object `greater<int>()` takes two arguments `x` and `y` and returns the greater value. By applying the binder `bind2nd` to this function object and the number 200, we produce a function object that defines a unary function that takes a single argument `x` and returns true if `x > 200`. This function object is then used as a parameter to `find_if`, to find the first element in the array that is greater than 200.

Besides binders, the library defines two other kinds of function adaptors:

- Negators are function objects that reverse the sense of predicate function objects.
- Adaptors for pointers to functions allow pointers to (unary and binary) functions to work with function adaptors that the library provides.

Arithmetic Operations

Files `#include <function.h>`

Description STL provides basic function object classes for all of the arithmetic operators in the language. The functionality of the operators is described below. The function object classes are:

Table 5.4 The functionality of the operators

<u>plus</u>	<u>times</u>
<u>divides</u>	<u>minus</u>
<u>modulus</u>	<u>negate</u>

plus

Description The plus function object accepts two operands x and y of type T , and returns the result of the computation of $x + y$.

Prototype `template< class T >
struct plus<T>`

minus

Description The minus function object accepts two operands x and y of type T , and returns the result of the computation of $x - y$.

Prototype `template< class T >
struct minus<T>`

times

Description The times function object accepts two operands x and y of type T , and returns the result of the computation of $x * y$.

Prototype `template< class T >
struct times<T>`

divides

Description The divides function object accepts two operands x and y of type T , and returns the result of the computation of x / y .

Prototype `template< class T >
struct divides<T>`

modulus

Description The modulus function object accepts two operands, x and y , of type T , and returns their result of the computation $x \% y$.

Prototype `template< class T >`

```
struct modulus<T>
```

negate

Description negate is a unary function that accepts a single operand x of type T, and returns the result of the computation of -x.

Prototype `template< class T >`
`struct negate<T>`

Comparison Operations

Files `#include <function.h>`

Description STL provides basic function object classes for all of the comparison operators in the language. The basic functionality of the comparison objects is described below.

Table 5.5 The operation classes are:

<u>equal_to</u>	<u>not_equal_to</u>
<u>greater</u>	<u>less</u>
<u>greater_equal</u>	<u>less_equal</u>

equal_to

Description An object of this type accepts two parameters, x and y, of type T, and returns true if x == y.

Prototype `template< class T >`
`struct equal_to<T>`

not_equal_to

Description An object of this type accepts two parameters, x and y, of type T, and returns true if x != y.

General Utilities Libraries

Comparison Operations

Prototype `template< class T >`
 `struct not_equal_to<T>`

greater

Description An object of this type accepts two parameters, x and y, of type T, and returns true if x > y.

Prototype `template< class T >`
 `struct greater<T>`

less

Description An object of this type accepts two parameters, x and y, of type T, and returns true if x < y.

Prototype `template< class T >`
 `struct less<T>`

greater_equal

Description An object of this type accepts two parameters, x and y, of type T, and returns true if x >= y.

Prototype `template< class T >`
 `struct greater_equal<T>`

less_equal

Description An object of this type accepts two parameters, x and y, of type T, and returns true if x <= y.

Prototype `template< class T >`
 `struct less_equal<T>`

Logical Operations

Files `#include <function.h>`

Description STL provides basic function object classes for the following logical operators in the language: and, or, not. The basic functionality of the logical operators is described below.

Table 5.6 **The logical operation classes are:**

[logical_and](#) [logical_or](#)
[logical_not](#)

logical_and

Description An object of this type accepts two parameters, *x* and *y*, of type *T*, and returns the boolean result of the logical and operation: *x* && *y*.

Prototype `template< class T >`
 `struct logical_and<T>`

logical_or

Description An object of this type accepts two parameters, *x* and *y*, of type *T*, and returns the boolean result of the logical or operation: *x* || *y*.

Prototype `template< class T >`
 `struct logical_or<T>`

logical_not

Description An object of this type accepts a single parameter, *x*, of type *T*, and returns the boolean result of the logical not operation: !*x*.

Prototype `template< class T >`
 `struct logical_not<T>`

Negator Adaptors

Files `#include <function.h>`

Description Negators are function adaptors that take a predicate and return its complement. STL provides the negators `not1` and `not2` that take a unary and binary predicate respectively and return their complements.

Table 5.7 **The negator function adaptors are:**

[not1](#)

[not2](#)

not1

Description This function accepts a unary predicate `x` as input and returns its complement `!x`.

Prototype `template
 < class Predicate >
unary_negate<Predicate> not1
 (const predicate& x);`

not2

Description This function accepts a binary predicate `x` as input and returns its complement, `!x`.

Prototype `template
 < class Predicate >
binary_negate<Predicate> not2
 (const predicate& x);`

Binder Adaptors

Files `#include <function.h>`

Description Binders are function adaptors that convert binary function objects into unary function objects by binding an argument to some particular value. STL provides two binders `bind1st` and `bind2nd`, which are described below.

Table 5.8 The binder function adaptors are:

[`bind1st`](#)

[`bind2nd`](#)

`bind1st`

Description This adapter accepts a function object `op` of two arguments and a value `x`, of type `T`. It returns a function object of one argument, constructed out of `op` with the *first* argument bound to `x`.

Prototype

```
template
    < class Operation,
      class T >
binder1st<Operation> bind1st
    (const Operation& op,
     const T& x);
```

`bind2nd`

Description This adapter accepts a function object `op` of two arguments and a value `x`, of type `T`. It returns a function object of one argument, constructed out of `op` with the second argument bound to `x`.

Prototype

```
template
    < class Operation,
      class T >
binder2nd<Operation> bind2nd
    (const Operation& op,
     const T& x);
```

Adaptors for Pointers to Functions

Files `#include <function>`

General Utilities Libraries

Adaptors for Pointers to Functions

Description Adaptors for pointers to functions are provided to allow pointers to unary and binary functions to work with the function adaptors provided in the library. They also can help avoid the “code bloat” problem arising from multiple template instances in the same program.

Table 5.9 The function pointer adaptors are:

[ptr_fun-unary](#)

[ptr_fun-binary](#)

Description STL provides two adaptors for pointers to functions: one for unary and the other for binary functions. Both the functions have the same name (which is overloaded).

ptr_fun-unary

Description This function adapter accepts a pointer to a unary function that takes an argument of type `Arg` and returns a result of type `Result`. A function object of type `pointer_to_unary_function<Arg, Result>` is constructed out of this argument, and returned.

Prototype

```
template
    < class Arg,
      class Result >
ptr_fun(Result (*x) (Arg));
```

ptr_fun-binary

Description This function adapter accepts a pointer to a binary function that accepts arguments of type `Arg1` and `Arg2` and returns a result of type `Result`. A function object of type `pointer_to_binary_function<Arg, Result>` is constructed out of this argument, and returned.

Prototype

```
template
    < class Arg,
      class Result >
ptr_fun(Result (*x) (Arg1, Arg2));
```


Specialized Algorithms

All the iterators that are used as formal template parameters in these algorithms are required to have their `operator*` return an object for which `operator&` is defined and returns a pointer to `T`. See [“Overview of Iterators” on page 273](#) where algorithms are discussed in detail.

Table 5.10 **The uninitialized copy and fill functions are:**

[uninitialized_copy](#) [uninitialized_fill](#)
[uninitialized_fill_n](#)

uninitialized_copy

Description This function behaves as follows: `while (first != last) construct (&*result++, *first++);` This function returns `result`.

Prototype `template
 < class InputIterator,
 class ForwardIterator >
ForwardIterator uninitialized_copy
 (InputIterator first,
 InputIterator last,
 ForwardIterator result);`

uninitialized_fill

Description This function behaves as follows:
 `while (first != last)
 construct (&*first++, x);`

Prototype `template
 < class ForwardIterator,
 class T >
void uninitialized_fill
 (ForwardIterator first,`

General Utilities Libraries

Template class *auto_ptr*

```
ForwardIterator last,  
const T& x);
```

uninitialized_fill_n

Description This function behaves as follows:

```
while (n--)  
    construct (&*first++, x);
```

Prototype

```
template  
    < class ForwardIterator,  
      class Size,  
      class T>  
void uninitialized_fill_n  
    (ForwardIterator first, Size n, const T& x);
```

Template class **auto_ptr**

Description Template class `auto_ptr` holds onto a pointer obtained via `new` and deletes that object when it itself is destroyed when it goes out of scope. The `auto_ptr` provides semantics of strict ownership. An object may be safely pointed to by only one `auto_ptr`, so copying an `auto_ptr` copies the pointer and transfers ownership to the destination. The declaration of `auto_ptr` is given below.

```
namespace std {  
    template<class X> class auto_ptr {  
    public:  
        typedef X element_type;  
  
        explicit auto_ptr(X* p =0) throw();  
        auto_ptr(const auto_ptr&) throw();  
        template<class Y> auto_ptr(const auto_ptr<Y>&) throw();  
  
        auto_ptr& operator=(const auto_ptr&) throw();  
        template<class Y> auto_ptr& operator=  
            (const auto_ptr<Y>&) throw();  
  
        ~auto_ptr();  
    }  
};
```

```

X& operator*() const throw();
X* operator->() const throw();
X* get() const throw();
X* release() const throw();
};
}

```

Constructor—*auto_ptr*

Description This function requires *p* to point to an object of class *X* or a class derived from *X* for which `delete` *p* is defined and accessible. or else *p* is a null pointer.

Prototype `explicit auto_ptr(X* p =0) throw();`

Postconditions: *this holds the pointer to *p*. *this owns *get() if and only if *p* is not a null pointer.

Prototype `auto_ptr(const auto_ptr&) throw();`

Postconditions: *this holds the pointer returned from *a*.release(). *this owns *get() if and only if *a* owns **a*.

Remarks Calls *a*.release().

Prototype `template<class Y> auto_ptr
(const auto_ptr<Y>& a) throw();`

Postconditions: *this holds the pointer returned from *a*.release(). *this owns *get() if and only if *a* owns **a*.

Remarks

- *Y** can be implicitly converted to *X**.
- Calls *a*.release().

auto_ptr Destructor

Description Destroys the *auto_ptr*.

General Utilities Libraries

Template class *auto_ptr*

Prototype `~auto_ptr();`

Remarks If **this* owns **get()* then delete *get()*.

auto_ptr::get

Description This function returns the pointer *p* specified as the argument to the constructor `auto_ptr (X* p)` or as the argument to the most recent call to `reset (X* p)`.

Prototype `X* get () const;`

auto_ptr::release

Description This function releases the pointer and after a call to this function `get ()` will return 0.

Prototype `X* release ();`

Assignment Operator=auto_ptr

Description Copies the argument *a* to **this*.

Prototype `auto_ptr& operator=
 (const auto_ptr& a) throw();
template<class Y> auto_ptr& operator=
 (const auto_ptr<Y>& a) throw();`

Dereferencing Operator*auto_ptr

Description This returns `*get ()` provided `get ()` does not return 0.

Prototype `X& operator* () const;`

Association Operator->auto_ptr

Description Returns the pointer associated.

Prototype `x* operator-> () const;`

General Utilities Libraries

Template class auto_ptr



21 Strings Library

This chapter is a reference guide to the ANSI/ISO String class that describes components for manipulating sequences of characters, where characters may be of type `char`, `wchar_t`, or of a type defined in a C++ program.

Overview of Strings Classes

The strings library is based on the ANSI/ISO string class description and includes

- [“21.1 Character traits” on page 95](#) defines types and facilities for character manipulations
- [“21.2 String Classes” on page 99](#) lists string and character structures and classes
- [“21.3 Class `basic_string`” on page 105](#) defines facilities for character sequence manipulations.
- [“23.4 Null Terminated Sequence Utilities” on page 133](#) lists facilities for Null terminated character sequence strings.

21.1 Character traits

This section defines a class template `char_traits<charT>` and two specializations for `char` and `wchar_t` types. These types are required by string and stream classes and are passed to these classes as formal parameters `charT` and `traits`.

The topics in this section are:

- [“21.1.1 Character Trait Definitions” on page 96](#)
- [“21.1.2 Character Trait Requirements” on page 96](#)
- [“21.1.3 Character Trait Type Definitions” on page 97](#)
- [“21.1.4 struct `char_traits<T>`” on page 98](#)

21 Strings Library

21.1 Character traits

21.1.1 Character Trait Definitions

character Any object when treated sequentially can represent text. This term is not restricted to just `char` and `wchar_t` types

character container type A class or type used to represent a character. This object must be POD (Plain Old Data).

traits A class that defines types and functions necessary for handling characteristics.

NTCTS A null character termination string is a character sequence that proceeds the null character value `charT(0)`.

21.1.2 Character Trait Requirements

These types are required by string and stream classes and are passed to these classes as formal parameters `charT` and `traits`.

assign Used for character type assignment.

```
static void assign  
    (char_type, const char_type);
```

eq Used for `bool` equality checking.

```
static bool eq  
    (const char_type&, const char_tye&);
```

lt Used for `bool` less than checking.

```
static bool lt(const char_type&, const char_type&);
```

compare Used for NTCTS comparison.

```
static int compare  
    (const char_type*, const char_type*, size_t n);
```

length Used when determining the length of a NTCTS.

```
static size_t length  
    (const char_type*);
```

find Used to find a character type in an array

```
static const char_type* find  
    (const char_type*, int n, const char_type&);
```

move Used to move one NTCTS to another even if the receiver contains the sting already.

```
static char_type* move  
    (char_type*, const char_type*, size_t);
```


copy Used for copying a NTCTS that does not contain the NTCTS already.

```
static char_type* copy
(char_type*, const char_type*, size_t);
```

not_eof Used for bool inequality checking.

```
static int_type not_eof
(const int_type&);
```

to_char_type Used to convert to a char type from an int_type

```
static char_type to_char_type
(const int_type&);
```

to_int_type Used to convert from a char type to an int_type.

```
static int_type to_int_type
(const char_type&);
```

eq_int_type Used to test for deletion.

```
static bool eq_int_type
(const int_type&, const int_type& );
```

get_state Used to store the state of the file buffer.

```
static state_type get_state
(pos_type pos);
```

eof Used to test for the end of a file.

```
static int_type eof();
```

21.1.3 Character Trait Type Definitions

There are several types defined in the char_traits structure for both wide and conventional char types.

Table 6.1 The functions are:

Type	Defined	Use
char	char_type	char values
int	int_type	integral values of char types including eof
streamoff	off_type	stream offset values

21 Strings Library

21.1 Character traits

streampos	pos_type	stream position values
mbstate_t	state_type	file state values

21.1.4 struct char_traits<T>

Description The template structure is overloaded for both the `wchar_t` type `struct char_traits<wchar_t>`. This specialization is used for string and stream usage.

NOTE: The `assign`, `eq` and `lt` are the same as the `=`, `==` and `<` operators.

Prototype

```
namespace std {
template<>
// struct char_traits<wchar_t> or
struct char_traits<char> {
    typedef char char_type;
    typedef int int_type;
    typedef streamoff off_type;
    typedef streampos pos_type;
    typedef mbstate_t state_type;

    static void assign(char_type, const char_type);
    static bool eg(const char_type&, const
char_tye&);
    static bool lt(const char_type&, const
char_type&);

    static int compar(const char_type*, const
char_type*, size_t n);
    static size_t length(const char_type*);
    static const char_type* find(const char_type*,
int n, const char_type&);

    static char_type* move(char_type*, const
char_type*, size_t);
```

```

static char_type* copy(char_type*, const
char_type*, size_t);
static char_type* assign(char_type*, size_t,
char_type);

static int_type not_eof(const int_type&);
static char_type to_char_type(const int_type&);
static int_type to_int_type(const char_type&);
static bool eq_int_type(const int_type&, const
int_type& );
static state_type get_state(pos_type pos);
static int_type eof();
};
}

```

21.2 String Classes

The header <string> define string and trait classes used to manipulate character and wide character like template arguments.

```

namespace std {

template<class charT> struct char_traits;
template <> struct char_traits<char>;
template <> struct char_traits<wchar_t>;

template
<class charT,
class traits =char_traits<charT>,
class Allocator = allocator<charT> >
class basic_string;

template
<class charT, class traits, class Allocator>
basic_string <charT,traits, Allocator>
operator+
    (const basic_string
      <charT,traits,Allocator>& lhs,
    const basic_string

```

21 Strings Library

21.2 String Classes

```
<charT, traits, Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
basic_string<charT,traits,Allocator>
operator+
    const charT* lhs,
    const basic_string
        <charT, traits, Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
basic_string<charT,traits,Allocator>
operator+
    (charT lhs, const basic_string
        <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
basic_string<charT,traits,Allocator>
operator+
    (const basic_string
        <charT,traits,Allocator>& lhs,
    const charT* rhs);
```

```
template
<class charT, class traits, class Allocator>
basic_string<charT,traits,Allocator>
operator+
    (const basic_string
        <charT,traits,Allocator>& lhs, charT rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator==
    (const basic_string
        <charT,traits,Allocator>& lhs,
    const basic_string
        <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator==
    (const charT* lhs,
     const basic_string
         <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator==
    (const basic_string<charT,
     traits,Allocator>& lhs,
     const charT* rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator!=
    (const basic_string
         <charT,traits,Allocator>& lhs,
     const basic_string
         <charT,traits, Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator!=
    (const charT* lhs,
     const basic_string
         <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator!=
    (const basic_string
         <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator<
    (const basic_string
```

21 Strings Library

21.2 String Classes

```
        <charT,traits,Allocator>& lhs,  
        const basic_string  
        <charT,traits,Allocator>& rhs);
```

```
template  
<class charT, class traits, class Allocator>  
bool operator<  
    (const basic_string  
        <charT,traits,Allocator>& lhs,  
    const charT* rhs);
```

```
template  
<class charT, class traits, class Allocator>  
bool operator<  
    (const charT* lhs,  
    const basic_string  
        <charT,traits,Allocator>& rhs);
```

```
template  
<class charT, class traits, class Allocator>  
bool operator>  
    (const basic_string  
        <charT,traits,Allocator>& lhs,  
    const basic_string  
        <charT,traits,Allocator>& rhs);
```

```
template  
<class charT, class traits, class Allocator>  
bool operator>  
    (const basic_string  
        <charT,traits,Allocator>& lhs,  
    const charT* rhs);
```

```
template  
<class charT, class traits, class Allocator>  
bool operator>  
    (const charT* lhs,  
    const basic_string  
        <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator<=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator<=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator<=
    (const charT* lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator>=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator>=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

```
template
<class charT, class traits, class Allocator>
bool operator>=
```

21 Strings Library

21.2 String Classes

```
(const charT* lhs,
const basic_string
    <charT,traits,Allocator>& rhs);

template
<class charT, class traits, class Allocator>
void swap
    (basic_string<charT,traits,Allocator>& lhs,
    basic_string<charT,traits,Allocator>& rhs);

template
<class charT, class traits, class Allocator>
basic_istream<charT,traits>&
operator>>
    (basic_istream<charT,traits>& is,
    basic_string<charT,traits,Allocator>& str);

template
<class charT, class traits, class Allocator>
basic_ostream<charT, traits>&
operator<<
    (basic_ostream<charT, traits>& os,
    const basic_string
        <charT,traits,Allocator>& str);

template
<class charT, class traits, class Allocator>
basic_istream<charT,traits>&
getline
    (basic_istream<charT,traits>& is,
    basic_string<charT,traits,Allocator>& str,
    charT delim);

template
<class charT, class traits, class Allocator>
basic_istream<charT,traits>&
getline
    (basic_istream<charT,traits>& is,
    basic_string<charT,traits,Allocator>& str);
```



```
typedef basic_string<char> string;
typedef basic_string<wchar_t> wstring;
};
}
```

21.3 Class `basic_string`

The `class basic_string` is used to store and manipulate a sequence of character like types of varying length known as strings.

Remarks Memory for a string is allocated and deallocated as necessary by member functions.

The first element of the sequence is at position zero.

The iterators used by `basic_string` are random iterators and as such qualifies as a reversible container

The topics in this section include:

- [“21.3.1 Constructors and Assignments” on page 111](#)
- [“21.3.2 Iterator Support” on page 114](#)
- [“21.3.3 Capacity” on page 115](#)
- [“21.3.4 Element Access” on page 116](#)
- [“21.3.5 Modifiers” on page 117](#)
- [“21.3.6 String Operations” on page 121](#)
- [“23.3.7 Non-Member Functions and Operators” on page 126](#)

NOTE: In general, the string size can be constrained by memory restrictions.

Prototype

```
namespace std {
template
    <class charT, class traits = char_traits<charT>,
    class Allocator = allocator<charT> >
class basic_string {
```

21 Strings Library

21.3 Class *basic_string*

```
    public:
typedef traits traits_type;
typedef typename traits::char_type value_type;
typedef Allocator allocator_type;
typedef typename Allocator::size_type size_type;
typedef typename Allocator::difference_type
    difference_type;
typedef typename Allocator::reference reference;
typedef typename Allocator::const_reference
    const_reference;
typedef typename Allocator::pointer pointer;
typedef typename Allocator::const_pointer
    const_pointer;
// typedef implementation defined iterator;
// typedef implementation defined const_iterator;
typedef std::reverse_iterator<iterator>
    reverse_iterator;
typedef std::reverse_iterator<const_iterator>
    const_reverse_iterator;

static const size_type npos = -1;

explicit basic_string
    (const Allocator& a = Allocator());
basic_string
    (const basic_string& str,
     size_type pos = 0,
     size_type n = npos,
     const Allocator& a = Allocator());
basic_string
    (const charT* s,
     size_type n,
     const Allocator& a = Allocator());
basic_string
    (const charT* s,
     const Allocator& a = Allocator());
basic_string
    (size_type n,
     charT c,
```

```
    const Allocator& a = Allocator();
template<class InputIterator>
basic_string
    (InputIterator begin,
     InputIterator end,
     const Allocator& a = Allocator());

~basic_string();

basic_string& operator= (const basic_string& str);
basic_string& operator=(const charT* s);
basic_string& operator=(charT c);

iterator begin();
const_iterator begin() const;
iterator end();
const_iterator end() const;
reverse_iterator rbegin();
const_reverse_iterator rbegin() const;
reverse_iterator rend();
const_reverse_iterator rend() const;

size_type size() const;
size_type length() const;
size_type max_size() const;
void resize(size_type n, charT c);
void resize(size_type n);
size_type capacity() const;
void reserve(size_type res_arg = 0);
void clear();
bool empty() const;

const_reference operator[](size_type pos) const;
reference operator[](size_type pos);
const_reference at(size_type n) const;
reference at(size_type n);

basic_string& operator+=(const basic_string& str);
basic_string& operator+=(const charT* s);
basic_string& operator+=(charT c);
```

21 Strings Library

21.3 Class *basic_string*

```
basic_string& append(const basic_string& str);
basic_string& append(
    const basic_string& str,
    size_type pos, size_type n);
basic_string& append(const charT* s, size_type n);
basic_string& append(const charT* s);
basic_string& append(size_type n, charT c);
template<class InputIterator>
basic_string& append
    (InputIterator first, InputIterator last);
void push_back(const charT);
basic_string& assign(const basic_string&);
basic_string& assign
    (const basic_string& str,
    size_type pos, size_type n);
basic_string& assign(const charT* s, size_type n);
basic_string& assign(const charT* s);
basic_string& assign(size_type n, charT c);
template<class InputIterator>
basic_string& assign
    (InputIterator first, InputIterator last);
basic_string& insert
    (size_type pos1, const basic_string& str);
basic_string& insert
    (size_type pos1, const basic_string& str,
    size_type pos2, size_type n);
basic_string& insert
    (size_type pos, const charT* s, size_type n);
basic_string& insert
    (size_type pos, const charT* s);
basic_string& insert
    (size_type pos, size_type n, charT c);
iterator insert(iterator p, charT c = charT());
void insert(iterator p, size_type n, charT c);
template<class InputIterator>
void insert
    (iterator p, InputIterator first,
    InputIterator last);
basic_string& erase
    (size_type pos = 0, size_type n = npos);
```

```
iterator erase(iterator position);
iterator erase(iterator first, iterator last);
basic_string& replace
    (size_type pos1, size_type n1,
     const basic_string& str);
basic_string& replace
    (size_type pos1, size_type n1,
     const basic_string& str,
     size_type pos2, size_type n2);
basic_string& replace
    (size_type pos, size_type n1,
     const charT* s, size_type n2);
basic_string& replace
    (size_type pos, size_type n1, const charT* s);
basic_string& replace
    (size_type pos, size_type n1,
     size_type n2, charT c);
basic_string& replace
    (iterator i1, iterator i2,
     const basic_string& str);
basic_string& replace
    (iterator i1, iterator i2,
     const charT* s, size_type n);
basic_string& replace(
    iterator i1, iterator i2, const charT* s);
basic_string& replace
    (iterator i1, iterator i2,
     size_type n, charT c);
template<class InputIterator>
basic_string& replace
    (iterator i1, iterator i2,
     InputIterator j1, InputIterator j2);

size_type copy
    (charT* s, size_type n,
     size_type pos = 0) const;
void swap(basic_string<charT, traits, Allocator>&);

const charT* c_str() const;
const charT* data() const;
```

21 Strings Library

21.3 Class *basic_string*

```
allocator_type get_allocator() const;
size_type find
    (const basic_string& str,
     size_type pos = 0) const;
size_type find
    (const charT* s, size_type pos,
     size_type n) const;
size_type find
    (const charT* s, size_type pos = 0) const;
size_type find (charT c, size_type pos = 0) const;
size_type rfind
    (const basic_string& str,
     size_type pos = npos) const;
size_type rfind
    (const charT* s, size_type pos,
     size_type n) const;
size_type rfind
    (const charT* s, size_type pos = npos) const;
size_type rfind
    (charT c, size_type pos = npos) const;
size_type find_first_of
    (const basic_string& str,
     size_type pos = 0) const;
size_type find_first_of
    (const charT* s, size_type pos,
     size_type n) const;
size_type find_first_of
    (const charT* s, size_type pos = 0) const;
size_type find_first_of
    (charT c, size_type pos = 0) const;
size_type find_last_of
    (const basic_string& str,
     size_type pos = npos) const;
size_type find_last_of
    (const charT* s,
     size_type pos, size_type n) const;
size_type find_last_of
    (const charT* s, size_type pos = npos) const;
size_type find_last_of
    (charT c, size_type pos = npos) const;
```

```

size_type find_first_not_of
    (const basic_string& str,
     size_type pos = 0) const;
size_type find_first_not_of
    (const charT* s, size_type pos,
     size_type n) const;
size_type find_first_not_of
    (const charT* s, size_type pos = 0) const;
size_type find_first_not_of
    (charT c, size_type pos = 0) const;
size_type find_last_not_of
    (const basic_string& str,
     size_type pos = npos) const;
size_type find_last_not_of
    (const charT* s,
     size_type pos, size_type n) const;
size_type find_last_not_of
    (const charT* s, size_type pos = npos) const;
size_type find_last_not_of
    (charT c, size_type pos = npos) const;
basic_string substr
    (size_type pos = 0, size_type n = npos) const;
int compare(const basic_string& str) const;
int compare(
    size_type pos1, size_type n1,
    const basic_string& str) const;
int compare
    (size_type pos1, size_type n1,
     const basic_string& str,
     size_type pos2, size_type n2) const;
int compare(const charT* s) const;
int compare
    (size_type pos1, size_type n1, const charT* s,
     size_type n2 = npos) const;
};
}

```

21.3.1 Constructors and Assignments

Constructor, destructor and assignment operators and functions.

21 Strings Library

21.3 Class *basic_string*

Constructors

Description The various `basic_string` constructors construct a string object for character sequence manipulations. All constructors include an `Allocator` argument that is used for memory allocation.

Prototype `explicit basic_string
(const Allocator& a = Allocator());`

Remarks This default constructor, constructs an empty string. A zero sized string that may be copied to is created.

```
basic_string  
(const basic_string& str,  
 size_type pos = 0,  
 size_type n = npos,  
 const Allocator& a = Allocator());
```

Remarks This constructor takes a string class argument and creates a copy of that string, with size of the length of that string and a capacity at least as large as that string.

- An exception is thrown upon failure

```
basic_string  
(const charT* s,  
 size_type n,  
 const Allocator& a = Allocator());
```

Remarks This constructor takes a `const char` array argument and creates a copy of that array with the size limited to the `size_type` argument.

- The `charT*` argument shall not be a null pointer
- An exception is thrown upon failure

```
basic_string  
(const charT* s,  
 const Allocator& a = Allocator());
```

Remarks This constructor takes an `const char` array argument. The size is determined by the size of the `char` array.

- The `charT*` argument shall not be a null pointer


```
basic_string
    (size_type n,
     charT c,
     const Allocator& a = Allocator());
```

Remarks This constructor creates a string of size_type n size repeating charT c as the filler.

- A `length_error` is thrown if n is less than `npos`.

```
template<class InputIterator>
basic_string
    (InputIterator begin,
     InputIterator end,
     const Allocator& a = Allocator());
```

Remarks This iterator string takes InputIterator arguments and creates a string with its first position starts with begin and its ending position is end. Size is the distance between beginning and end.

Destructor

Description Deallocates the memory referenced by the `basic_string` object.

Prototype `~basic_string ();`

Assignment Operator

Description Assigns the input string, char array or char type to the current string.

Prototype `basic_string& operator= (const basic_string& str);`

Remarks If *this and str are the same object has it has no effect.

```
basic_string& operator=(const charT* s);
```

Remarks Used to assign a NCTCS to a string.

```
basic_string& operator=(charT c);
```

Remarks Used to assign a single char type to a string.

21 Strings Library

21.3 Class *basic_string*

Assignment & Addition Operator *basic_string*

Description	Appends the string rhs to the current string.
Prototype	<pre>string& operator+= (const string& rhs); string& operator+= (const charT* s); string& operator+= (charT s);</pre>
Remarks	Both of the overloaded functions construct a string object from the input s, and append it to the current string.
Return	The assignment operator returns the <code>this</code> pointer.

21.3.2 Iterator Support

Member functions for string iterator support.

begin

Description	Returns an iterator to the first character in the string
Prototype	<pre>iterator begin(); const_iterator begin() const;</pre>
end	

Description	Returns an iterator that is past the end value.
--------------------	---

Prototype	<pre>iterator end(); const_iterator end() const;</pre>
------------------	--

rbegin

Description	Returns an iterator that is equivalent to <code>reverse_iterator(end())</code> .
--------------------	--

Prototype	<pre>reverse_iterator rbegin();</pre>
------------------	---------------------------------------

```
const_reverse_iterator rbegin() const;
```

rend

Description Returns an iterator that is equivalent to `reverse_iterator(begin())`.

Prototype `reverse_iterator rend();`
`const_reverse_iterator rend() const;`

21.3.3 Capacity

Member functions for determining a strings capacity.

size

Description Returns the size of the string.

Prototype `size_type size() const;`

length

Description Returns the length of the string

Prototype `size_type length() const;`

max_size

Description Returns the maximum size of the string.

Prototype `size_type max_size() const;`

resize

Description Resizes the string to size `n`.

Prototype `void resize(size_type n);`
`void resize(size_type n, charT c);`

21 Strings Library

21.3 Class *basic_string*

Remarks If the size of the string is longer than `size_type n`, it shortens the string to `n`, if the size of the string is shorter than `n` it appends the string to size `n` with `charT c` or `charT()` if no filler is specified.

capacity

Description Returns the memory storage capacity.

Prototype `size_type capacity() const;`

reserve

Description A directive that indicates a planned change in memory size to allow for better memory management.

Prototype `void reserve(size_type res_arg = 0);`

clear

Description Erases from `begin()` to `end()`.

Prototype `void clear();`

empty

Description Empties the string stored.

Prototype `bool empty() const;`

Returns Returns `true` if the size is equal to zero, otherwise `false`.

21.3.4 Element Access

Member functions and operators for accessing individual string elements.

operator[]

Description An operator used to access an indexed element of the string.

Prototype `const_reference operator[](size_type pos) const;`
`reference operator[](size_type pos);`

at

Description A function used to access an indexed element of the string.

Prototype `const_reference at(size_type n) const;`
`reference at(size_type n);`

21.3.5 Modifiers

Operators for appending a string.

21.3.5.1 operator+=

Description An Operator used to append to the end of a string.

Prototype `basic_string& operator+=(const basic_string& str);`
`basic_string& operator+=(const charT* s);`
`basic_string& operator+=(charT c);`

21.3.5.2 append

Member functions for appending to the end of a string.

Description A function used to append to the end of a string.

Prototype `basic_string& append(const basic_string& str);`
`basic_string& append(`
`const basic_string& str,`
`size_type pos, size_type n);`
`basic_string& append(const charT* s, size_type n);`
`basic_string& append(const charT* s);`

21 Strings Library

21.3 Class *basic_string*

```
basic_string& append(size_type n, charT c);

template<class InputIterator>
basic_string& append
    (InputIterator first, InputIterator last);
```

21.5.3.3 assign

Description Assigns a string, Null Terminated Character Type Sequence or char type to the string.

Prototype

```
basic_string& assign(const basic_string&);

basic_string& assign
    (const basic_string& str,
     size_type pos, size_type n);

basic_string& assign(const charT* s, size_type n);

basic_string& assign(const charT* s);

basic_string& assign(size_type n, charT c);

template<class InputIterator>
basic_string& assign
    (InputIterator first, InputIterator last);
```

Remarks If there is a size argument whichever is smaller the string size or argument value will be assigned.

21.3.5.4 insert

Description Inserts a string, Null Terminated Character Type Sequence or char type into the string.

Prototype

```
basic_string& insert
    (size_type pos1, const basic_string& str);

basic_string& insert
    (size_type pos1, const basic_string& str,
```

```

        size_type pos2, size_type n);

basic_string& insert
    (size_type pos, const charT* s, size_type n);

basic_string& insert
    (size_type pos, const charT* s);

basic_string& insert
    (size_type pos, size_type n, charT c);
iterator insert(iterator p, charT c = charT());

void insert(iterator p, size_type n, charT c);

template<class InputIterator>
void insert
    (iterator p, InputIterator first,
     InputIterator last);

```

Remarks May throw an exception,

21.3.5.5 erase

Description Erases the string

Prototype `basic_string& erase`
`(size_type pos = 0, size_type n = npos);`
`iterator erase(iterator position);`
`iterator erase(iterator first, iterator last);`

Remarks May throw an exception,

21.3.5.6 replace

Description Replaces the string with a `string`, Null Terminated Character Type Sequence or `char` type.

Prototype `basic_string& replace`
`(size_type pos1, size_type n1,`
`const basic_string& str);`

21 Strings Library

21.3 Class *basic_string*

```
basic_string& replace
    (size_type pos1, size_type n1,
     const basic_string& str,
     size_type pos2, size_type n2);

basic_string& replace
    (size_type pos, size_type n1,
     const charT* s, size_type n2);

basic_string& replace
    (size_type pos, size_type n1, const charT* s);

basic_string& replace
    (size_type pos, size_type n1,
     size_type n2, charT c);

basic_string& replace
    (iterator i1, iterator i2,
     const basic_string& str);

basic_string& replace
    (iterator i1, iterator i2,
     const charT* s, size_type n);

basic_string& replace(
    iterator i1, iterator i2, const charT* s);

basic_string& replace
    (iterator i1, iterator i2,
     size_type n, charT c);

template<class InputIterator>
basic_string& replace
    (iterator i1, iterator i2,
     InputIterator j1, InputIterator j2);
```

Remarks May throw an exception,

21.3.5.7 copy

Description Copies a Null Terminated Character Type Sequence to a string up to the size designated.

Prototype `size_type copy
(charT* s, size_type n,
size_type pos = 0) const;`

Remarks The function `copy` does not pad the string with Null characters.

21.3.5.8 swap

Description Swaps one string for another.

Prototype `void swap(basic_string<charT,traits,Allocator>&);`

21.3.6 String Operations

Member functions for sequences of character operations.

c_str

Description Returns the string as a Null terminated character type sequence.

Prototype `const charT* c_str() const;`

data

Description Returns the string as an array without a Null terminator.

Prototype `const charT* data() const;`

get_allocator

Description Returns a copy of the `allocator` object used to create the string.

21 Strings Library

21.3 Class *basic_string*

Prototype `allocator_type get_allocator() const;`

21.3.6.1 find

Description Finds a string, Null Terminated Character Type Sequence or char type in a string starting from the beginning.

Prototype `size_type find
 (const basic_string& str,
 size_type pos = 0) const;`

`size_type find
 (const charT* s, size_type pos,
 size_type n) const;`

`size_type find
 (const charT* s, size_type pos = 0) const;`

`size_type find (charT c, size_type pos = 0) const;`

Returns The found position or `npos` if not found.

21.3.6.2 rfind

Description Finds a string, Null Terminated Character Type Sequence or char type in a string testing backwards from the end.

Prototype `size_type rfind
 (const basic_string& str,
 size_type pos = npos) const;`

`size_type rfind
 (const charT* s, size_type pos,
 size_type n) const;`

`size_type rfind
 (const charT* s, size_type pos = npos) const;`

`size_type rfind`

`(charT c, size_type pos = npos) const;`

Returns The found position or `npos` if not found.

21.6.3.3 `find_first_of`

Description Finds the first position of one of the elements in the function's argument starting from the beginning.

Prototype

```
size_type find_first_of  
(const basic_string& str,  
 size_type pos = 0) const;  
  
size_type find_first_of  
(const charT* s, size_type pos,  
 size_type n) const;  
  
size_type find_first_of  
(const charT* s, size_type pos = 0) const;  
  
size_type find_first_of  
(charT c, size_type pos = 0) const;
```

Returns The found position or `npos` if not found.

21.3.6.4 `find_last_of`

Description Finds the last position of one of the elements in the function's argument starting from the beginning.

Prototype

```
size_type find_last_of  
(const basic_string& str,  
 size_type pos = npos) const;  
  
size_type find_last_of  
(const charT* s,  
 size_type pos, size_type n) const;  
  
size_type find_last_of  
(const charT* s, size_type pos = npos) const;
```

21 Strings Library

21.3 Class *basic_string*

```
size_type find_last_of  
(charT c, size_type pos = npos) const;
```

Returns The found position or `npos` if not found.

21.3.6.5 `find_first_not_of`

Description Finds the first position that is not one of the elements in the function's argument starting from the beginning.

Prototype

```
size_type find_first_not_of  
(const basic_string& str,  
size_type pos = 0) const;
```

```
size_type find_first_not_of  
(const charT* s, size_type pos,  
size_type n) const;
```

```
size_type find_first_not_of  
(const charT* s, size_type pos = 0) const;
```

```
size_type find_first_not_of  
(charT c, size_type pos = 0) const;
```

Returns The found position or `npos` if not found.

21.3.6.6 `find_last_not_of`

Description Finds the last position that is not one of the elements in the function's argument starting from the beginning.

Prototype

```
size_type find_last_not_of  
(const basic_string& str,  
size_type pos = npos) const;
```

```
size_type find_last_not_of  
(const charT* s,  
size_type pos, size_type n) const;
```

```
size_type find_last_not_of
```

```
(const charT* s, size_type pos = npos) const;
```

```
size_type find_last_not_of  
(charT c, size_type pos = npos) const;
```

Returns The found position or `npos` if not found.

21.3.6.7 substr

Description Returns a string if possible from beginning at the first arguments position to the last position.

Prototype `basic_string substr
(size_type pos = 0, size_type n = npos) const;`

Remarks May throw an exception,

21.3.6.8 compare

Description Compares a `string`, `substring` or Null Terminated Character Type Sequence with a lexicographical comparison.

Prototype `int compare(const basic_string& str) const;`

```
int compare(  
    size_type pos1, size_type n1,  
    const basic_string& str) const;
```

```
int compare  
    (size_type pos1, size_type n1,  
    const basic_string& str,  
    size_type pos2, size_type n2) const;
```

```
int compare(const charT* s) const;
```

```
int compare  
    (size_type pos1, size_type n1, const charT* s,  
    size_type n2 = npos) const;
```

21 Strings Library

21.3 Class *basic_string*

Returns Less than zero if the `string` is smaller than the argument lexicographically, zero if the `string` is the same size as the argument lexicographically and greater than zero if the `string` is larger than the argument lexicographically.

23.3.7 Non-Member Functions and Operators

21.3.7.1 `operator+`

Description Appends one string to another.

Prototype

```
template
    <class charT, class traits, class Allocator>
    basic_string<charT,traits,Allocator>
operator+
    (const basic_string
     <charT,traits, Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
    basic_string<charT,traits,Allocator>

operator+
    (const charT* lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
    basic_string<charT,traits,Allocator>
operator+
    (charT lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
```

```

        basic_string<charT,traits,Allocator>
operator+
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);

template
    <class charT, class traits, class Allocator>
    basic_string<charT,traits,Allocator>
operator+
    (const basic_string
     <charT,traits,Allocator>& lhs, charT rhs);

```

Returns The combined strings.

21.3.7.2 operator==

Description Test for lexicographical equality.

Prototype

```

template
    <class charT, class traits, class Allocator>
bool operator==
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
bool operator==
    (const charT* lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
bool operator==
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);

```

21 Strings Library

21.3 Class *basic_string*

Returns True if the strings match otherwise false.

21.3.7.3 operator!=

Description Test for lexicographical inequality.

Prototype

```
template
    <class charT, class traits, class Allocator>
bool operator!=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
bool operator!=
    (const charT* lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
bool operator!=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

Returns True if the strings do not match otherwise false.

21.3.7.4 operator<

Description Tests for a lexicographically less than condition.

Prototype

```
template
    <class charT, class traits, class Allocator>
bool operator<
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
```



```
<charT,traits,Allocator>& rhs);
```

```
template
    <class charT, class traits, class Allocator>
bool operator<
    (const charT* lhs,
     const basic_string
       <charT,traits,Allocator>& rhs);
```

```
template
    <class charT, class traits, class Allocator>
bool operator<
    (const basic_string
       <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

Returns True if the first argument is lexicographically less than the second argument otherwise false.

21.3.7.5 operator>

Description Tests for a lexicographically greater than condition.

Prototype

```
template
    <class charT, class traits, class Allocator>
bool operator>
    (const basic_string
       <charT,traits,Allocator>& lhs,
     const basic_string
       <charT,traits,Allocator>& rhs);
```

```
template
    <class charT, class traits, class Allocator>
bool operator>
    (const charT* lhs,
     const basic_string
       <charT,traits,Allocator>& rhs);
```

```
template
    <class charT, class traits, class Allocator>
```

21 Strings Library

21.3 Class *basic_string*

```
bool operator>
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

Returns True if the first argument is lexicographically greater than the second argument otherwise false.

21.3.7.6 operator<=

Description Tests for a lexicographically less than or equal to condition.

Prototype

```
template
    <class charT, class traits, class Allocator>
bool operator<=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);
```

```
template
    <class charT, class traits, class Allocator>
bool operator<=
    (const charT* lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);
```

```
template
    <class charT, class traits, class Allocator>
bool operator<=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

Returns True if the first argument is lexicographically less than or equal to the second argument otherwise false.

21.3.7.7 operator>=

Description Tests for a lexicographically greater than or equal to condition.

Prototype

```
template
    <class charT, class traits, class Allocator>
bool operator>=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
bool operator>=
    (const charT* lhs,
     const basic_string
     <charT,traits,Allocator>& rhs);

template
    <class charT, class traits, class Allocator>
bool operator>=
    (const basic_string
     <charT,traits,Allocator>& lhs,
     const charT* rhs);
```

Returns True if the first argument is lexicographically greater than or equal to the second argument otherwise false.

21.3.7.8 swap

Description This non member `swap` exchanges the first and second arguments.

Prototype

```
template
    <class charT, class traits, class Allocator>
void swap
    (basic_string<charT,traits,Allocator>& lhs,
     basic_string
     <charT,traits,Allocator>& rhs);
```

21.3.7.9 Inserters and extractors

Overloaded inserters and extractors for `basic_string` types.

operator>>

Description Overloaded `extractor` for stream input operations.

Prototype

```
template
    <class charT, class traits, class Allocator>
    basic_istream<charT,traits>&
operator>>
    (basic_istream<charT,traits>& is,
     basic_string<charT,traits,Allocator>& str);
```

Remarks Characters are extracted and appended until `n` characters are stored or `end-of-file` occurs on the input sequence;

operator<<

Description Inserts characters from a string object from into a output stream.

Prototype

```
template
    <class charT, class traits, class Allocator>
    basic_ostream<charT, traits>&
operator<<
    (basic_ostream<charT, traits>& os,
     const basic_string
       <charT,traits,Allocator>& str);
```

getline

Description Extracts characters from a `stream` and appends them to a `string`.

Prototype

```
template
    <class charT, class traits, class Allocator>
    basic_istream<charT,traits>&
getline
    (basic_istream<charT,traits>& is,
```

```

        basic_string
        <charT,traits,Allocator>& str,
        charT delim);
template
    <class charT, class traits, class Allocator>
    basic_istream<charT,traits>&
getline
    (basic_istream<charT,traits>& is,
     basic_string<charT,traits,Allocator>& str)

```

Remarks Extracts characters from a `stream` and appends them to the `string` until the end-of-file occurs on the input sequence (in which case, the `getline` function calls `setstate eofbit`) or the delimiter is encountered in which case, the delimiter is extracted but not appended.

If the function extracts no characters, it calls `setstate(failbit)` in which case it may throw an exception.

23.4 Null Terminated Sequence Utilities

The standard requires C++ versions of the standard libraries for use with characters and Null Terminated Character Type Sequences.

Character Support

The standard provides for namespace and character type support.

Table 6.2 Headers `<cctype.h>` and `<cwctype.h>`

<code><cctype.h></code>	<code><cwctype.h></code>	<code><cctype.h></code>	<code><cwctype.h></code>
<code>isalnum</code>	<code>iswalnum</code>	<code>isprint</code>	<code>iswprint</code>
<code>isalpha</code>	<code>iswalpha</code>	<code>ispunct</code>	<code>iswpunct</code>
<code>isctrl</code>	<code>iswctrl</code>	<code>isspace</code>	<code>iswspace</code>
<code>isdigit</code>	<code>iswdigit</code>	<code>isupper</code>	<code>iswupper</code>
<code>isgraph</code>	<code>iswgraph</code>	<code>isxdigit</code>	<code>iswxdigit</code>

<cctype.h>	<cwctype.h>	<cctype.h>	<cwctype.h>
isalnum	iswalnum	isprint	iswprint
islower	iswlower		
tolower	towlower	toupper	towupper
	wctype		iswctype
	wctrans		towctrans
Macros		EOF	WEOF

String Support

The standard provides for namespace and wide character type for Null Terminated Character Type Sequence functionality.

Table 6.3 Headers <cstring.h> and <wchar.h>

<cstring.h>	<wchar.h>	<cstring.h>	<wchar.h>
memchr	wmemchr	strerror	
memcmp	wmemcmp	strlen	wcslen
memcpy	wmemcpy	strncat	wcsncat
memmove	wmemmove	strncmp	wcsncmp
memset	wmemset	strncpy	wcsncpy
strcat	wcscat	strpbrk	wcspbrk
strchr	wcschr	strrchr	wcsrchr
strcmp	wcscmp	strspn	wcsspn
strcoll	wscoll	strstr	wcsstr
strcpy	wscpy	strtok	wcstok
strcspn	wcscspn	strxfrm	wcsxfrm
Type	mbstate_t	size_t	wint_t

<cstring.h>	<wchar.h>	<cstring.h>	<wchar.h>
memchr	wmemchr	strerror	
memcmp	wmemcmp	strlen	wcslen
memcpy	wmemcpy	strncat	wcsncat
memmove	wmemmove	strncmp	wcsncmp
memset	wmemset	strncpy	wcsncpy
Macro	NULL	NULL	WCHAR_MAX
Macro			WCHAR_MIN

Input and Output Manipulations

The standard provides for namespace and wide character support for manipulation and conversions of input and output and character and character sequences.

Table 6.4 Additional <wchar.h> and <stdlib.h> support

wchar.h	wchar.h	wchar.h	<stdlib.h>
btowc	mbrtowc	wcrtomb	atol
fgetwc	mbsinit	wcscoll	atof
fgetws	mbsrtowcs	wcsftime	atoi
fputwc	putwc	wcstod	mblen
fputws	putwchar	wcstol	mbstowcs
fwide	swscanf	wcsrtombs	mbtowc
fwprintf	swprintf	wcstoul	strtod
fwscanf	ungetwc	wctob	strtol
getwc	vfwprintf	wprintf	strtoul
getwchar	vwprintf	wscanf	wctomb
mbrlen	vswprintf		wcstombs

21 Strings Library

23.4 Null Terminated Sequence Utilities



Localization Library

This chapter is a reference guide to the ANSI/ISO standard C++ Localization library and is based on the April 1995 Draft Working Paper of the ANSI/ISO committee.

Overview of the Localization Library

C++ localization library extends the internationalization facilities provided by the C library in such a way that will help programmers to encapsulate the cultural differences.

Files `#include <mlocale.h>`
 `#include <locale.h>`

Description The localization library is a set of classes that help C++ programmers to encapsulate the cultural differences that come up especially while porting an application across different user communities. Hence, this library provides a set of classes that include internationalization support for character classification, string collation, formatting and parsing of date, time, numeric and monetary quantities, message retrieval etc.

In different countries people use different formats for formatting date, time, currency etc., For example in India, the date is written using the DD/MM/YY (D-Day, M-Month and Y-Year) format while in the USA, it is the MM/DD/YY format. This difference (though, “minor”) may cause problems when any software system is being used by people belonging to different communities. So, as soon as the ISO C standard was published, the work on improvising the internationalization support began and this work was published as the ISO C Amendment I.

The C++ support for internationalization is summarized in two header files. The header `<mlocale>` declares the set of classes like

Localization Library

Class locale

locale, facet etc., which are part of the C++ standard library and the header `<locale>` declares the elements of localization library from the standard C library.

This section summarizes the classes and convenience interfaces provided by the C++ library for internationalization. The topics in this chapter are:

- [“Class locale” on page 138](#)
- [“Class facet” on page 146](#)
- [“Class id” on page 148](#)
- [“The Numerics Category” on page 148](#)
- [“The Collate Category” on page 155](#)
- [“Ctype Category” on page 157](#)
- [“The Monetary Category” on page 168](#)

Class locale

Class `locale` is used for implementing a type-safe polymorphic collection of facets (feature-sets) indexed by facet types. The following sections illustrate the components of the class `locale`.

The topics are:

- [“Typedef Declarations” on page 138](#)
- [“Public Data Members” on page 140](#)
- [“Constructors” on page 140](#)
- [“Public member operators” on page 142](#)
- [“Public Member Functions” on page 143](#)
- [“Static Member Functions” on page 145](#)
- [“Global Operators” on page 146](#)

Typedef Declarations

Description	Category, when given a legal value, represents a collection of facets. Valid category values include 0 and the <code>locale</code> member bit-
--------------------	--

mask elements `collate`, `ctype`, `monetary`, `numeric`, `time` and `messages`. In addition, `locale` member `all` is defined such that the expression

```
(collate | ctype | monetary | numeric | time | messages) == all
```

The categories and their corresponding facets are given below.

Definition `typedef unsigned category;`

Table 7.1 Categories and corresponding facets

Category	Include Facets
<code>collate</code>	<code>collate<char></code> , <code>collate<wchar_t></code>
<code>ctype</code>	<code>ctype<char></code> , <code>ctype<wchar_t></code> , <code>codecvt<char,</code> <code> wchar_t, mbstate_t></code> , <code>codecvt<wchar_t,</code> <code> char, mbstate_t></code>
<code>monetary</code>	<code>moneypunct <char, bool></code> , <code>moneypunct <wchar_t, bool></code> , <code>money_get<char, bool, II></code> , <code>money_get<wchar_t, bool, II></code> , <code>money_put<char, bool, II></code> , <code>money_put<wchar_t, bool, II></code>
<code>numeric</code>	<code>numpunct<char></code> , <code>numpunct<wchar_t></code> , <code>num_get<char, II></code> , <code>num_get<wchar_t, II></code> , <code>num_put<char, OI></code> , <code>num_put<wchar_t, OI></code>

Localization Library

Class locale

Category	Include Facets
time	time_get<char, bool, II>, time_get<wchar_t, bool, II> time_put<char, bool, II>, time_put<wchar_t, bool, II>
messages	messages<char>, messages<wchar_t>

Public Data Members

The class `locale` has two nested classes in it, [“Class facet” on page 146](#) and [“Class id” on page 148](#). The [“Class facet” on page 146](#) acts as a base class for all locale facets.

Constructors

Default Constructor

Description Default constructor constructs a locale which is a snapshot of the current global locale. The current global locale can be set by calling either the standard “C” function `setlocale()` or `locale::global(const locale&)`.

Prototype `locale () throw();`

Overloaded and Copy Constructors

Prototype `locale (const locale& other) throw();`

Description Copy constructor constructs an instance of the class `locale` which is a copy of the locale `other`.

Prototype `explicit locale (const char* std_name);`

Remarks Constructs a locale using the standard C locale names (for example, “POSIX”). If the argument `std_name` passed to it is not a valid

name, then a `runtime_error` exception is thrown. The valid set of `std_name` include "C", null string and any other implementation-defined value.

Prototype `locale`
 `(const locale& other,`
 `const char* std_name,`
 `category cat);`

Remarks Creates a locale as a copy of `other` except for the facets identified by the category argument `cat`, for which the semantics will be the same as that of the second argument `std_name`. The resulting locale will have a name if and only if `other` has a name.

Prototype `template`
 `< class Facet >`
 `locale`
 `(const locale& other,`
 `Facet* f);`

Remarks A locale is constructed which does not have a name. The constructed locale has all the features set from the first locale argument `other`, except that of the type `Facet`, for which the second argument is used.

Prototype `template`
 `< class Facet >`
 `locale`
 `(const locale& other,`
 `const locale& one);`

Remarks A locale which does not have a name is constructed such that all the facets are incorporated from the first argument `other` and that facet which is identified by the template parameter `Facet`, is incorporated from the second argument `one`. If the second argument does not have a facet of that particular type, `runtime_error` exception is thrown.

Prototype `locale`
 `(const locale& other,`

Localization Library

Class locale

```
const locale& one,  
category cat);
```

Remarks A locale is constructed which has all the facets from the first argument `other`, except those facet(s) that are specified by the category argument `cat`. These facets that are specified by the categories are installed from the second argument. The constructed locale will have a name if and only if the first two locales are named.

Public member operators

The locale class has four public member operators.

- [Assignment Operator= locale](#)
- [Equality Operator== locale](#)
- [Not Equal Operator!= locale](#)
- [Grouping Operator locale](#)

Assignment Operator= locale

Description Creates a copy of `other`, replacing the current value.

Prototype

```
const locale& operator =  
    (const locale& other) const;
```

Equality Operator== locale

Description The function returns true if and only if any of the following conditions are satisfied.

- Both arguments are the same locale
- If one is a copy of the other
- Both locales have a name and they are identical

Prototype

```
bool operator == (const locale& other) const;
```

Not Equal Operator!= locale

Description Evaluates the following expression and returns the result: `!(*this == other)`.

Prototype `bool operator != (const locale& other) const;`

Grouping Operator locale

Description Compares two strings according to the `collate<charT>` facet of `locale`. This member operator satisfied requirements for a comparator predicate template argument as applied to strings.

Prototype `template <class charT, class IS_Traits>
 bool operator()
 (const basic_string<charT,
 IS_Traits>& s1, const basic_string<charT,
 IS_Traits>& s2) const;`

Remarks Since member templates are not supported, our library does not provide this function yet.

Public Member Functions

Table 7.2 The public member functions are

locale::name

[locale::name](#)

[locale::has](#)

[locale::use](#)

Description The name of `*this`, if it has one; otherwise, the string `""`.

Prototype `const basic_string<char>& name() const;`

locale::has

Description An indication whether the facet requested is present in `*this`. Also, see `use`.

Prototype

```
template <class Facet> bool has() const;  
template <class Facet> bool has (  
    const locale& loc, Facet* f);
```

Remarks The semantics of this function is the same as explained above, except that locale argument is also passed as an argument, instead of being implicit.

See Also [“locale::use” on page 144](#).

locale::use

Description The function returns a reference to the Facet of the locale. If the facet requested is not present in the locale on which the function was applied but present in the current global locale, returns the global locale's instance of Facet.

Prototype

```
template <class Facet> const Facet& use() const;  
template <class Facet> const Facet& use (  
    const locale& loc, Facet* f);
```

Remarks The semantics of this function is the same as explained above, except that locale argument is also passed as an argument, instead of being implicit.

See Also [“locale::has” on page 144](#).

Static Member Functions

Table 7.3 The static member functions are:

locale::global

[locale::global](#)

[locale::classic](#)

[locale::transparent](#)

Description The function sets the global locale to its argument. Subsequent calls to the default constructor and of other library functions affected by the function `setlocale()`, use the locale `loc` until the next call to this function or `setlocale()`.

Prototype `static locale global (const locale& loc);`

locale::classic

Description A call to this member returns the standard “C” locale. This is equivalent to constructing a locale using a call to the constructor `locale(“C”)`.

Prototype `static const locale& classic();`

locale::transparent

Description This function returns the continuously updated global locale. A locale which implements semantics that vary dynamically as the global locale is changed.

Prototype `static locale transparent();`

Global Operators

Table 7.4 The global operators are:

Extractor Operator >> locale

[Extractor Operator >> locale](#)

[Inserter Operator << locale](#)

Description This function tries to read a line into a string and construct a locale from it. If either operation fails, sets failbit of streams. This operator is not yet implemented in our library.

Prototype

```
template
    < class charT,
      class Traits>
basic_istream<charT, Traits>& operator >>
    (basic_istream<charT,
      Traits>& s,
     locale& loc);
```

Inserter Operator << locale

Description The usual stream output operator for locales.

Prototype

```
template
    < class charT,
      class Traits >
basic_ostream<charT, Traits>& operator <<
    (basic_ostream<charT,
      Traits>& s,
     locale& loc);
```

Class facet

Description Class facet is the base class for locale feature sets. Declaration of the class facet is given below.

Prototype `class locale::facet {`

```

protected :
    facet (size_t refs = 0);
    virtual ~facet ();
private :
    facet (const facet&); // not defined
    void operator= (const facet&); // not
defined
};

```

Remarks A class is a *facet* if it is publicly derived from another *facet*, or if it is a class derived from `locale::facet` and containing a declaration as follows:

```
static locale::id id;
```

See also [“Class id” on page 148](#)

A program that passes a type that is not a *facet* (explicit or deduced) as a parameter to a *locale* function expecting a *facet*, is ill-formed.

The `refs` argument to the constructor is used for lifetime management. If (`refs == 0`) the *facet*’s lifetime is managed by the *locale* or *locales* it is incorporated into. If (`refs == 1`) its lifetime is until explicitly deleted.

For some standard facets (say *FACET*), a standard “*FACET_byname*” class, derived from it, implements the semantics equivalent to that *facet* of the *locale* constructed by *locale* (`const char*`). Each *FACET_byname* *facet* provides a constructor,

```
FACET_byname(const char* name, size_t refs = 0);
```

where *name* names the *locale*, and the `refs` argument is passed to the base class constructor. If there is no “*..._byname*” version of a particular *facet*, the base class implements such semantics itself.

Prototype

```

class Facet : public locale::facet {
protected :
    virtual <return_type> do_F (...) const;
    //....
public :
    <return_type> F(...) const
        { return do_F (...);}
}

```

Localization Library

Class id

```
//...

Facet(size_t refs = 1) : locale::facet(refs){}

protected :
~Facet () {}
};
```

Remarks There are 6 different categories in which the facets provided by C++ localization library are divided. They are `collate`, `ctype`, `monetary`, `numeric`, `time`, `messages`. Each of the standard categories includes a family of facets. See also:

- [“The Numerics Category” on page 148](#)
- [“The Collate Category” on page 155](#)
- [“Ctype Category” on page 157](#)
- [“The Monetary Category” on page 168](#)

Class id

Description This class is used for identification of a locale facet. A mandatory object of this class used as an index in every derived facet facilitates lookup and initialization of facets. This type-id mechanism ensures that every facet type installed in a locale is assigned a unique id. Id is for every facet type and not for every facet object.

See also [“Class facet” on page 146](#)

The Numerics Category

The numerics category consists of three templated classes. These classes handle all the numeric formatting and parsing. These classes are publicly derived from `locale::facet`.

The classes are:

- [“Class numpunct” on page 149](#)
- [“Class num_get” on page 151](#)

- [“Class num_put” on page 153](#)

Classes `num_get` and `num_put` use `num_punct` for numeric formatting and parsing.

Class `num_punct`

Description This class specifies numeric punctuation. The base class provides classic “C” numeric formats, while `num_punct_byname` version supports named locale (e.g. POSIX, X/OPEN) numeric formatting semantics. Other two numeric facets, `num_get` and `num_put` use `num_punct` facet installed in a particular locale to parse/format numeric quantities.

The topics discussed for this class are:

- [“Typedef Declarations `num_punct`” on page 149](#)
- [“Public Member Functions `num_punct`” on page 150](#)

Typedef Declarations `num_punct`

Description The following typedef’s are defined in the class `num_punct`.

`num_punct::char_type`

Definition `typedef charT char_type;`

`num_punct::string`

Definition `typedef basic_string<charT> string;`

Public Member Functions *numpunct*

Table 7.5 The public member functions are:

numpunct::decimal_point

[*numpunct::decimal_point*](#)

[*numpunct::thousands_sep*](#)

[*numpunct::grouping*](#)

[*numpunct::truename*](#)

[*numpunct::falsename*](#)

Description The function returns a string for use as the decimal radix separator. The base class implementation of this member returns a ".". The `num_get<charT, InputIterator>` class is not required to recognize numbers formatted using a decimal radix separator if it is not a one-character string.

Prototype `string decimal_point() const;`

numpunct::thousands_sep

Description The function returns a string which is the thousand separator. The base class implementation of this member returns the empty string. The `num_get<charT, InputIterator>` class is not required to recognize the numbers formatted using a thousand separator if it is not a one-character string.

Prototype `string thousands_sep() const;`

numpunct::grouping

Description This function returns a vector `vec` in which `vec[i]` represents the number of digits in the group at position `i` starting with 0 as the rightmost group. If `vec.size() <= i`, the number is the same as group `(i-1)`; if `(i < 0 || vec[i] <= 0)`, the size of the digit group is unlimited. The base-class implementation this returns the empty vector.

Prototype `vector<char> grouping() const;`

num_punct::truename

Description Returns a string representing the name of the boolean value `true`. The base class implementation return the strings “true”.

Prototype `string truename() const;`

num_punct::falsename

Description Returns a string representing the name of the boolean value `false`. The base class implementation return the strings “false”.

Prototype `string falsename() const;`

Class num_get

Description Template class `num_get` has the following set of typedef’s and public member functions.

- [“Typedef Declarations num_get” on page 151](#)
- [“Public Member Functions num_get” on page 152](#)

Typedef Declarations num_get

Description The following typedef’s are defined in the class `num_get`.

char_type

Definition `typedef charT char_type;`

iter_type

Definition `typedef InputIterator iter_type;`

ios

Definition `typedef basic_ios<charT> ios;`

Public Member Functions num_get

There is one function.

num_get::get

Description All the above functions read characters from `in`, interpreting them according to flags set in `str` and the `ctype<charT>` facet and `num_punct<charT>` facet installed in the locale `loc`. These functions ignore the state of `str` initially. But they indicate failure by calling `str.setstate (ios_base::failbit)`. If an error occurs, `v` is not changed; otherwise it is set to the resulting value. Digit grouping separators are optional; if present, digit grouping is checked after the entire number is read. When reading a non-numeric boolean value, the names are compared exactly.

Prototype `iter_type get
 (iter_type in,
 iter_type end,
 ios& str,
 const locale&
 bool& v) const;
iter_type get
 (iter_type in,
 iter_type end,
 ios& str,
 const locale&
 long& v) const;
iter_type get
 (iter_type in,
 iter_type end,
 ios& str,
 const locale&
 unsigned long& v) const;
iter_type get`


```
        (iter_type in,  
         iter_type end,  
         ios& str,  
         const locale&,  
         double& v) const;  
iter_type get  
        (iter_type in,  
         iter_type end,  
         ios& str,  
         const locale&,  
         long double& v) const;
```

Class `num_put`

Description Template class `num_put` has the following set of typedef's and public member functions.

- [“Typedef Declarations `num_put`” on page 153](#)
- [“Public Member Functions `num_put`” on page 154](#)

Typedef Declarations `num_put`

Description The following typedef's are defined in the class `num_put`.

`char_type`

Definition `typedef charT char_type;`

`iter_type`

Definition `typedef OutputIterator iter_type;`

`ios`

Definition `typedef basic_ios<charT> ios;`

Public Member Functions num_put

There is one function.

num_put::put

Description All the above functions write characters to the sequence out, formatting val according to the flags set in str, ctype<charT> and numpunct<charT> facets installed inside locale loc. These functions insert digit group separators as specified by numpunct<charT>::grouping().

Prototype

```
iter_type put
    (iter_type out,
     ios& str,
     const locale& loc,
     bool val) const;
iter_type put
    (iter_type out,
     ios& str,
     const locale& loc,
     long val) const;
iter_type put
    (iter_type out,
     ios& str,
     const locale& loc,
     unsigned long val) const;
iter_type put
    (iter_type out,
     ios& str,
     const locale& loc,
     double val) const;
iter_type put
    (iter_type out,
     ios& str,
     const locale& loc,
     long double val) const;
```

Remarks All the above functions ignore and do not change the stream state. They return an iterator pointing immediately after the last character produced.

The Collate Category

Collate category consists of one template class `collate` which provides features for use in the collation (comparison) and hashing of strings.

See Also [“Class Collate” on page 155](#)

Class Collate

Description This class provides features for use in the collation (comparison) and hashing of strings. A locale member function template, `operator()`, uses the `collate` facet to allow a locale to act directly as the predicate argument for standard algorithms (see Chapter 9) and containers operating on strings. The base class implementation applied lexicographic ordering (see 9.30).

- [“Typedef Declarations `collate`” on page 155](#)
- [“Public Member Functions `collate`” on page 156](#)

Typedef Declarations `collate`

Description The following typedef’s are defined in the class `collate`.

`char_type`

Definition `typedef charT char_type;`

`string`

Definition `typedef basic_string<charT> string;`

Public Member Functions collate

Table 7.6 The public member functions are:

collate::compare

[collate::compare](#)

[collate::transform](#)

[collate::hash](#)

Description Compares the two strings and returns 1 if the first string is greater than the second, -1 if less; zero otherwise.

Prototype

```
int compare
    (const char_type* low1,
     const char_type* high1,
     const char_type* low2,
     const char_type* high2) const;
```

collate::transform

Description This function returns a string that, when compared lexicographically with the result of calling `transform()` on another string, yields the same result as calling `compare()` on the same two strings.

Prototype

```
string transform
    (const char* low,
     const char* high) const;
```

collate::hash

Description Returns an integer value equal to the result of calling `hash()` on any other string for which `compare()` returns 0 (i.e. equal) when passed the two strings.

Prototype

```
long hash
    (const char* low,
     const char* high) const;
```

Ctype Category

In this category, there are two templated classes, `ctype<charT>` and `codecvt<fromtT, toT, statetT>`. There is also a specialization of `ctype<charT>` for the `char` data type.

Class `locale::ctype` encapsulates the C library `ctype` features. This class is typically used by rest of the library classes for character classing. A specialization `locale::ctype<char>` is provided, so that the member functions on type `char` may be implemented inline.

The two templated classes in this category are:

- [“Class `ctype<charT>`” on page 157](#)
- [“Class `ctype<char>` Specialization” on page 161](#)
- [“Class `codecvt`” on page 166](#)

Class `ctype<charT>`

Description The definition of class `ctype_base` which is the base class for `ctype` is given below.

Prototype

```
class ctype_base {
public :
    enum ctype_mask
    {
        space, print, cntrl, upper, lower,
        alpha, digit, punct, xdigit,
        alnum = alpha | digit, graph = alnum | punct
    };
};
```

NOTE: The type `ctype_mask` is a bitmask type. As noted before, `locale's ctype` facet encapsulates the C library `ctype` features. This facet is derived from `locale::facet` and `ctype_base`.

- [“Typedef Declarations `ctype<charT>`” on page 158](#)

- [“Public Member Functions `ctype<charT>`” on page 158](#)

Typedef Declarations `ctype<charT>`

Description The following typedef’s are defined in the class `Ctype`.

`char_type`

Definition `typedef charT char_type;`

Public Member Functions `ctype<charT>`

Table 7.7 The public member functions are

`ctype::is`

[`ctype::is`](#)

[`ctype::do_is`](#)

[`ctype::scan_is`](#)

[`ctype::scan_not`](#)

[`ctype::toupper`](#)

[`ctype::tolower`](#)

[`ctype::widen`](#)

[`ctype::narrow`](#)

Description This function classify a character or sequence of characters. For each argument character, this function identifies a value `M` of type `ctype_mask`. The function `is()` returns the result `(M & mask) != 0`.

Prototype `bool is
 (ctype_mask mask,
 char_type c) const;`

See Also `do_is()`

`ctype::do_is`

Description This function classify a character or sequence of characters. For each argument character, this function identifies a value `M` of type

`ctype_mask`. The `do_is()` function simply places `M` for all `*p` where `(low <= p && p < high)`, into `vec[p-low]` and returns `high`.

Prototype `const char_type* do_is`
 `(const char_type* low,`
 `const char_type* high,`
 `ctype_mask* vec) const;`

See Also `is()`

ctype::scan_is

Description This function locates a character in the buffer `[low, high)` that conforms to the classification mask, `mask`. It returns the smallest pointer `p` in the range `[low, high)` such that `(*p)` would return `true`; otherwise, returns `high`.

Prototype `const char* scan_is`
 `(ctype_mask mask,`
 `const char_type* low,`
 `const char_type* high) const;`

ctype::scan_not

Description This function locates a character in the buffer `[low, high)` that fails to the classification mask, `mask`. It returns the smallest pointer `p` in the range `[low, high)` such that `(*p)` would return `false`; otherwise, returns `high`.

Prototype `const char* scan_not`
 `(ctype_mask mask,`
 `const char_type* low,`
 `const char_type* high) const;`

ctype::toupper

Description These functions convert a character or sequence of characters to upper-case. The first function returns the corresponding upper-case character if it is known to exist, or its argument if not. The second form replaces each character *p in the range [low, high) for which a corresponding upper-case character exists, with that character and returns high.

Prototype

```
charT toupper (char_type c) const;  
const char_type* toupper  
    (char_type* low,  
    const char_type* high) const;
```

ctype::tolower

Description These functions convert a character or sequence of characters to lower-case. The first function returns the corresponding lower-case character if it is known to exist, or its argument if not. The second form replaces each character *p in the range [low, high) for which a corresponding lower-case character exists, with that character and returns high.

Prototype

```
charT tolower (char_type c) const;  
const char_type* tolower  
    (char_type* low,  
    const char_type* high) const;
```

ctype::widen

Description These function apply the simplest reasonable transformation from a char value or sequence of char values to the corresponding char_type value or values. The only characters for which unique transformations are required are the digits, alphabetic characters, '-', '+', newline and space. For any character c, the transformed character of c is not a member of any character classification that c is not also a member of. The first function returns the transformed value and the second form transforms each character *p in the range

[low, high) placing the result in dest[p-low] and returns high.

Prototype `char_type widen (char c) const;
const char* widen
 (const char* low,
 const char* high,
 char_type* dest) const;`

ctype::narrow

Description These function apply the simplest reasonable transformation from a char_type value or sequence of char_type values to the corresponding char value or values. The only characters for which unique transformations are required are the digits, alphabetic characters, '-', '+', newline and space. For any character c, the transformed character of c is not a member of any character classification that c is not also a member of. In addition, the expression (narrow(c) - '0') evaluates to the digit value of the character. The first function returns the transformed value or default if no mapping is readily available and the second form transforms each character *p in the range [low, high) placing the result(or default if no simplest transformation is readily available) in dest[p-low] and returns high.

Prototype `char narrow
 (char_type c,
 char default) const;
const char_type* narrow
 (const char_type* low,
 const char_type* high,
 char default,
 char* dest) const;`

Class ctype<char> Specialization

ctype<char> specialization is provided so that the member functions on type char can be implemented inline. This specializa-

tion is provided because it affects the derivation interface for ctype<char>.

- [“Data Members ctype<char>” on page 162](#)
- [“Public Member Functions ctype<char>” on page 163](#)

Data Members ctype<char>

The following are the protected or private data members of ctype<char>.

ctype::ctype_mask

Definition `static const ctype_mask;`

ctype::table_

Definition `const ctype_mask* const table_;`

ctype::classic_table_

Definition `static const mask classic_table_[UCHAR_MAX+1];`

ctype::delete_it_

Definition `bool delete_it_;`

Remarks The type `delete_it_` is a private flag,

Public Member Functions `ctype<char>`

Table 7.8 The public member functions are:

constructor `ctype<char>`

<code>constructor ctype<char></code>	<code>ctype::is for ctype<char></code>
<code>ctype::scan_is for ctype<char></code>	<code>ctype::scan_not for ctype<char></code>
<code>ctype::tolower for ctype<char></code>	<code>ctype::toupper for ctype<char></code>
<code>ctype::widen for ctype<char></code>	<code>ctype::narrow for ctype<char></code>

Description This constructor initializes the protected member `table_` with the `tab` argument if nonzero, or the static value `classic_table_` otherwise, and initializes the private member `delete_it_` to `(tab && del)`. The `refs` argument is passed to the base class constructor.

Prototype `ctype`
`(const ctype_mask* tab = 0,`
`bool del = false,`
`size_t refs = 0);`

`ctype::is for ctype<char>`

Description The first function returns `table_[(unsigned char)c] & mask`. The second function, for all `*p` in the range `[low, high)` assigns `vec[p-low]` to `table_[(unsigned char)*p]` and it returns `high`.

Prototype `bool is`
`(ctype_mask mask,`
`char c) const;`
`const char* is`
`(const char* low,`

```
const char* high,  
ctype_mask* vec) const;
```

ctype::scan_is for ctype<char>

Description This function returns the smallest *p* in the range [*low*, *high*) such that `table_[(unsigned char)*p] & mask) == true`.

Prototype

```
const char* scan_is  
    (ctype_mask mask,  
    const char* low,  
    const char* high) const;
```

ctype::scan_not for ctype<char>

Description This function returns the smallest *p* in the range [*low*, *high*) such that `table_[(unsigned char)*p] & mask) == false`.

Prototype

```
const char* scan_not  
    (ctype_mask mask,  
    const char* low,  
    const char* high) const;
```

ctype::tolower for ctype<char>

Description These functions convert a character or sequence of characters to lower-case. The first function returns the corresponding lower-case character if it is known to exist, or its argument if not. The second form replaces each character **p* in the range [*low*, *high*) for which a corresponding lower-case character exists, with that character and returns *high*.

Prototype

```
char tolower (char c) const;  
const char* tolower  
    (char* low,  
    const char* high) const;
```

ctype::toupper for ctype<char>

Description These functions convert a character or sequence of characters to upper-case. The first function returns the corresponding upper-case character if it is known to exist, or its argument if not. The second form replaces each character *p in the range [low, high) for which a corresponding upper-case character exists, with that character and returns high.

Prototype

```
char toupper (char c) const;
const char* toupper
    (char* low,
     const char* high) const;
```

ctype::widen for ctype<char>

Description The second function copies contents of the range [low, high) to dest and returns high. The first function returns c.

Prototype

```
char widen (char c) const;
const char* widen
    (const char* low,
     const char* high,
     char* dest) const;
```

ctype::narrow for ctype<char>

Description The second function copies contents of the range [low, high) to dest and returns high. The first function returns c.

Prototype

```
char narrow
    (char c,
     char /* dfault */) const;
const char* narrow (
    const char* low,
    const char* high,
    char /* dfault */,
    char* dest) const;
```

Class codecvt

Description Definition of class `codecvt_base`, used as a base class for `codecvt` facet is given below.

Prototype

```
class codecvt_base {
    public :
        enum result {ok, partial, error, noconv};
};
```

The class `codecvt<fromT, toT, stateT>` is for use when converting from one codeset to another, such as from wide characters to multibyte characters, or vice versa. Instances of this facet are typically used in pairs instantiated oppositely. The `stateT` argument selects the pair of codesets being mapped between. This implementation provides the following two specializations for `codecvt` facet `codecvt<char, wchar_t, mbstate_t>` and `codecvt<wchar_t, char, mbstate_t>`.

- [“Typedef Declarations codecvt” on page 166](#)
- [“Member Functions codecvt” on page 167](#)

Typedef Declarations codecvt

Description The following typedef’s are defined in the class `codecvt`.

from_type

Definition `typedef fromT from_type;`

to_type

Definition `typedef toT to_type;`

state_type

Definition `typedef stateT state_type;`

Member Functions codecvt

There is one function.

Prototype `codecvt::result convert`
 (
 state_type& state,
 const from_type* from,
 const from_type* from_end,
 const from_type*& from_next,
 to_type* to,
 to_type* to_limit,
 to_type*& to_next
) const;

NOTE: This function requires the following conditions to hold true. (`from <= from_end` && `to <= to_end`) and state initialized if at the beginning of a sequence, or else equal to the result of converting the preceding characters in the sequence.

This function translates characters in the range (`from`, `from_end`), placing the results starting at `to`. It stops when it runs out of character to translate or space to put the results, or if it encounters a character it cannot convert. It always leaves the `from_next` and `to_next` pointers pointing one beyond the last character successfully converted. If no translation is needed (returns `codecvt_base::noconv`), sets `to_next` equal to `to`. In any case, this function does not write into `*to_limit`. This function returns an enumeration value of type `codecvt_base::result` as summarized below:

Table 7.9 convert result values

The Monetary Category

Value	Meaning
ok	completed the conversion
partial	ran out of space in the destination
error	encountered a from_type character it could not convert
noconv	no conversion was needed

The monetary category consists of three template classes `money_punct`, `money_put` and `money_get` to handle monetary formatting and parsing. In all the three classes, a template parameter indicates whether local or international monetary formats are to be used. The `money_get<>` and `money_put<>` facets use `money_punct<>` members to determine all formatting details. `money_punct<>` provides basic format information for money processing.

The declaration of the class `money_base`, which is a base class for `money_punct` is given below.

Prototype

```
class money_base {
    public :
        enum part
            {none, space, symbol, sign, value};
        struct pattern
            { char field[4];};
};
```

The classes in the monetary category are:

- [“Class money_punct” on page 169](#)
- [“Class money_put” on page 172](#)
- [“Class money_get” on page 173](#)

Class **money_punct**

Description This class provides money punctuation, similar to `num_punct<>` of the numerics category.

- [“Typedef Declarations money_punct” on page 169](#)
- [“Public Member Functions money_punct” on page 169](#)

Typedef Declarations money_punct

Description The following typedef’s are defined in the class `money_punct`.

char_type

Definition `typedef charT char_type;`

string_type

Definition `typedef basic_string<charT> string_type;`

Public Member Functions money_punct

Table 7.10 The public member functions are:

money_punct::decimal_point

money_punct::decimal_point	money_punct::thousands_sep
money_punct::grouping	money_punct::curr_symbol
money_punct::positive_sign	money_punct::negative_sign
money_punct::frac_digits	money_punct::neg_format
money_punct::frac_digits	

Description This function returns the radix separator to use in case `frac_digits()` is greater than zero.

Localization Library

Class moneypunct

Prototype `basic_string<charT,traits>
 decimal_point() const;`

moneypunct::thousands_sep

Description This function returns the digit group separator to use in case `grouping()` specifies a digit grouping pattern.

Prototype `basic_string<charT,traits>
 thousands_sep() const;`

Remarks The two functions above have been changed to return `charT`, in the April 1995 draft. But this implementation still returns a `string`.

moneypunct::groupint

Description This function returns a vector `vec` in which `vec[i]` represents the number of digits in the group at position `i` starting with 0 as the rightmost group. If `vec.size() <= i`, the number is the same as `group(i-1)`; if `(i < 0 || vec[i] <= 0)`, the size of the digit group is unlimited. The base-class implementation this returns the empty vector.

Prototype `vector<char> grouping () const;`

moneypunct::curr_symbol

Description This function returns the string to use as the currency identifier symbol.

Prototype `string_type curr_symbol () const;`

moneypunct::positive_sign

Description This function returns the string to use to indicate a positive monetary value.

Prototype `string_type positive_sign () const;`

moneypunct::negative_sign

Description This function returns the string to use to indicate a negative monetary value. If this is a one-char-string containing '(', it is paired with a matching ')'.
Prototype `string_type negative_sign () const;`

moneypunct::frac_digits

Description This function returns the number of digits after the decimal radix separator, if any.
Prototype `int frac_digits () const;`

moneypunct::pos_format

Description This function returns a four-element array specifying the order in which the syntactic elements appear in the monetary format. In this array, each element is an enumeration value of type `money_base::part`. Each enumeration value appears exactly once. `none`, if present, is not first; `space`, if present, is neither first nor last. Otherwise, the elements may appear in any order. In international instantiations, the result is always { `symbol`, `sign`, `none`, `value`}.

Prototype `money_base::pattern pos_format () const;`

moneypunct::neg_format

Description This function returns a four-element array specifying the order in which the syntactic elements appear in the monetary format. In this array, each element is an enumeration value of type `money_base::part`. Each enumeration value appears exactly once. `none`, if present, is not first; `space`, if present, is neither first nor last. Otherwise, the elements may appear in any order. In international instantiations, the result is always { `symbol`, `sign`, `none`, `value`}.

Prototype `money_base::pattern neg_format () const;`

Class money_put

Description Class money_put contains the following set of typedefs and public member functions.

- [“Typedef Declarations money_put” on page 172](#)
- [“Public Member Functions money_put” on page 172](#)

Typedef Declarations money_put

Description The following typedef’s are defined in the class money_put.

char_type

Definition `typedef charT char_type;`

iter_type

Definition `typedef OutputIterator iter_type;`

string

Definition `typedef basic_string<charT> string;`

ios

Definition `typedef basic_ios<charT> ios;`

Public Member Functions money_put

There is one function.

money_put::put

Description Writes characters to *s*, according to the format specified by the `money_punct<charT>` facet of `loc`, and `f.flags()`. Ignores any fractional part of units, or any characters in digits beyond the (optional) leading '-' and immediately subsequent digits. If format flags specify filling with internal space, the fill characters are placed where none or space appears in the formatting pattern. Returns an iterator pointing immediately after the last character produced.

Prototype

```
iter_type put
    (iter_type s,
     ios& f,
     const locale& loc,
     double units&) const;
iter_type put
    (iter_type s, ios& f,
     const locale& loc,
     const string& SixDgts) const
```

Class money_get

Description Class `money_get` contains the following set of typedefs and public member functions.

- [“Typedef Declarations money_get” on page 173](#)
- [“Public Member Functions money_get” on page 174](#)

Typedef Declarations money_get

Description The following typedef's are defined in the class `money_get`.

char_type

Definition `typedef charT char_type;`

iter_type

Definition `typedef InputIterator iter_type;`

string

Definition `typedef basic_string<charT> string;`

ios

Definition `typedef basic_ios<charT> ios;`

Public Member Functions money_get

There is one function.

money_get::get

Description These functions read characters from `s` until they have constructed a monetary value, as specified in `str.flags()` and the `money_punct<charT>` facet of `loc`, or until it encounters an error or runs out of characters. The result is a pure sequence of digits, representing a count of the smallest unit of currency representable. Digit group separators are optional; if present, digit grouping is checked after all syntactic elements have been read. Where `space` or `none` appear in the format pattern, except at the end optional whitespace is consumed. These functions set `units` or `digits` from the sequence of digits found. `units` is negated, or `digits` is preceded by `'-'` for a negative value. These functions indicate a failure by calling `str.setstate (failbit)`. On error, `units` or `digits` argument is unchanged. These function return an iterator pointing immediately beyond the last character recognized as part of a valid monetary quantity.

Prototype `iter_type get
 (iter_type s,
 iter_type end,
 ios& str,`

```
        const locale& loc,  
        double& units) const  
iter_type get  
    (iter_type s,  
     iter_type end,  
     ios& str,  
     const locale& loc,  
     string& digits) const
```

Localization Library

Class money_get



Containers Library

This chapter discusses the containers library. These classes support lists, sets, maps, stacks, queues, and more.

Overview of the Containers Library

Standard C++ containers are divided into two broad categories: **sequence containers** and **associative containers**.

The topics in this chapter are:

- [“What Are Containers” on page 177](#)
- [“Organization of the Container Class Descriptions” on page 192](#)
- [“Template class vector<T>” on page 193](#)
- [“Template class deque<T>” on page 203](#)
- [“Template class list<T>” on page 212](#)
- [“Template class set<T>” on page 223](#)
- [“Template class multiset<Key>” on page 232](#)
- [“Template class map<Key, T>” on page 242](#)
- [“Template class multimap<Key, T>” on page 253](#)
- [“Template class stack” on page 264](#)
- [“Template class queue” on page 266](#)
- [“Template class priority_queue” on page 268](#)

What Are Containers

This section discusses the concept of a container, and how they work in the containers library. There are several common features of

all the container classes. These features are discussed in this section as well.

The topics in this section are:

- [“Basic Design and Organization of Containers” on page 178](#)
- [“Common Type Definitions in All Containers” on page 180](#)
- [“Common Members of All Containers” on page 179](#)
- [“Common Member Functions in all Containers” on page 182](#)
- [“Sequence Container Requirements” on page 185](#)
- [“Associative Container Requirements” on page 187](#)
- [“Associative Container Types and Member Functions” on page 188](#)

Basic Design and Organization of Containers

Sequence containers include vectors, lists and deques. These contain elements of a single type, organized in a strictly linear arrangement. Although only the three most basic sequence containers are provided in this version of STL, it is possible to construct other sequence containers efficiently using these basic containers through the use of `container` adaptors, which are STL classes that provide interface mappings. STL provides adaptors for stacks, queues and priority queues.

The second STL container category consists of associative containers, which include sets, multisets, maps and multimaps. Associative containers allow for the fast retrieval of data based on keys. For example, a map (also known as an `associative array`) allows a user to retrieve an object of type `T` based on a key of some other type, while sets allow for the fast retrieval of the keys themselves.

All of the STL containers have three important characteristics:

- Every container allocates and manages its own storage.
- Every container provides a minimal set of operations (as member functions) to access and maintain its storage. The provided set of member functions includes:

- **Constructors and destructors:** these functions allow users to construct and destroy instances of the container. Most containers have several kinds of constructors.
- **Element access member functions:** these allow users to access the container elements. In most instances, the element access member functions do not change the container.
- **Insertion member functions:** these are used to insert elements into the container.
- **Erase member functions:** used to delete elements from the container.
- Each container has an allocator object associated with it. This allocator object encapsulates information about the memory model currently being used, and allows the classes to be portable across various platforms.

The same naming convention is used for the member functions of all containers, resulting in a very uniform interface to all the classes.

There is a great deal of similarity in the interfaces of all STL containers. Some differences exist between sequence and associative container interfaces, which we examine after taking a look at the common components.

Common Members of All Containers

The public members of STL containers fall into a two level hierarchy. The first level defines members that are common to *all* containers, while the second level contains two categories:

- members common to sequence containers (vectors, lists, deques).
- members common to associative containers (sets, maps, multisets, multimaps).

The common members of all STL containers fall into two distinct categories: **type definitions** and **member functions**. We take a look at each in turn.

Common Type Definitions in All Containers

The common type definitions found in each STL container are presented below. It is assumed that `X` is a container class containing objects of type `T`, `a` and `b` are values of `X`, `u` is an identifier and `r` is a value of `X&`.

value_type

Description Type of values the container holds.

Definition `X::value_type`

reference

Description Type that can be used for storing into `X::value_type` objects. This type is usually `X::value_type&`.

Definition `X::reference`

const_reference

Description A constant reference type identical to `X::reference`.

Definition `X::const_reference`

pointer

Description A pointer type pointing to `X::reference`.

Definition `X::pointer`

iterator

Description An iterator type that points to `X` instances. It is either a random access iterator type (for vector or deque) or a bidirectional iterator type (for other containers).

Definition `X::iterator`

const_iterator

Description A iterator type that can be used with constant instances of type X. It is either a constant random access iterator type (for vector or deque) or a constant bidirectional iterator type (for other containers).

Definition `X::const_iterator`

reverse_iterator

Description An iterator type identical to `X::iterator` except that traversal direction is reversed (`X::reverse_iterator::operator++` is `X::iterator::operator--`, etc.).

Definition `X::reverse_iterator`

const_reverse_iterator

Description A constant iterator type identical to `X::const_iterator` except that traversal direction is reversed.

Definition `X::const_reverse_iterator`

difference_type

Description The type that can represent the difference between any two X iterator objects (varies with the memory model).

Definition `X::difference_type`

size_type

Description The type that can represent the size of any X instance (varies with the memory model).

Definition `X::size_type`

Common Member Functions in all Containers

The common member functions required to be in each STL container are outlined below. In the descriptions, it is assumed that *X* is a container class containing objects of type *T*, *a* and *b* are values of *X*, *u* is an identifier and *r* is a value of *X*&.

Default Constructor

Description The default constructor. Takes constant time.

Prototype `X ()`

Overloaded and Copy Constructors

Prototype `X (a) ;`

Remarks Constructor. Takes linear time.

Prototype `X u (a) ;`

Remarks Copy Constructor. Takes linear time.

Destructor

Description Destructor. The destructor is applied to every element of *a*, and all the memory is returned. Takes linear time.

Prototype `(&a) -> ~X () ;`

begin

Description Returns an iterator (`const_iterator` for constant *a*), that can be used to begin traversing all locations in the container.

Prototype `a.begin () ;`

end

Description Returns an iterator (const_iterator for constant a), that can be used in a comparison for ending traversal through the container.

Prototype `a.end();`

rbegin

Description Returns a reverse_iterator (const_reverse_iterator for constant a) that can be used to begin traversing through all locations of the container in the reverse of the normal order.

Prototype `a.rbegin();`

rend

Description Returns a reverse_iterator (const_reverse_iterator for constant a) that can be used in a comparison for ending a reverse-direction traversal through all locations in the container.

Prototype `a.rend();`

Equality Operator ==

Description Equality operation on containers of the same type. Returns true when the sequences of elements in a and b are element wise equal (using `X::value_type::operator==`). Takes linear time.

Prototype `a == b`

Not Equal Operator !=

Description The opposite of the equality operation. Takes linear time.

Prototype `a != b`

Assignment Operator =

Description The assignment operator for containers. Takes linear time.

Containers Library

What Are Containers

Prototype `r = a`

size

Description Returns the number of elements in the container.

Prototype `a.size();`

max_size

Description `size()` of the largest possible container.

Prototype `a.max_size();`

empty

Description Returns true if the container is empty (i.e., if `a.size() == 0`).

Prototype `a.empty();`

Less Than Operator <

Description Compares two containers lexicographically. Takes linear time.

NOTE: lexicographical comparisons are described in chapter 10
Set Operations on Sorted Structures

Prototype `a < b`

Greater Than Operator >

Description Returns true if `b < a`, as defined above. Takes linear time.

Prototype `a > b`

Less Than or Equal Operator <=

Description Returns true if `!(a > b)`. Takes linear time.

Prototype `a <= b`

Greater Than or Equal`>=`

Description Returns true if `!(a < b)`. Takes linear time.

Prototype `a >= b`

swap

Description Swaps two containers of the same type in constant time.

Prototype `a.swap(b);`

Remarks From the above definitions, we note that several comparison functions, constructors, type definitions and other member functions are shared between all STL containers, allowing their interfaces to be very uniform.

NOTE: Shallow Copies: It must be noted that the assignment operators of all STL containers make shallow copies. This means that the assignment operator will simply copy the assigned container exactly as is, and will not traverse pointers downwards to make copies recursively of elements that the container elements might possibly point to.

Sequence Container Requirements

All STL Sequence containers define two constructors, three insert member functions and two erase member functions in addition to the common types and member functions mentioned in the previous section.

The additional members are defined below. In the definitions, `x` is assumed to be a sequence class (e.g., a vector, list or deque), `i` and `j` satisfy input iterator requirements, `[i, j)` is a valid range, `n` is a value of `x::size_type`, `p` is a valid iterator to `a`, `q`, `q1` and `q2`

Containers Library

What Are Containers

are valid dereferenceable iterators to `a`, `[q1, q2)` is a valid range, `t` is a value of `X::value_type`.

Prototype `X(n, t);`
 `X a(n, t);`

Remarks Constructs a sequence with `n` copies of `t`.

`X(i, j);`
 `X a(i, j);`

Remarks Constructs a sequence equal to the range `[i,j)`.

insert

Description Inserts a copy or copies of an element.

Prototype `a.insert(p, t);`

Remarks Inserts a copy of `t` before `p`. Returns an iterator pointing to the inserted copy.

Prototype `a.insert(p, n, t);`

Remarks Inserts `n` copies of `t` before `p`.

Prototype `a.insert(p, i, j);`

Remarks Inserts copies of elements in `[i,j)` before `p`.

erase

Description Erases the element or elements.

Prototype `a.erase(q);`

Erases the element pointed to by `q`.
`a.erase(q1, q2);`

Erases the elements in the range `[q1,q2)`.

NOTE: These additional member functions only define some basic insert, erase and construction operations. All other operations on the containers (such as sorting, searching, transformations, etc.) are carried out by generic algorithms provided by the library.

Associative Container Requirements

STL provides four basic kinds of associative containers: set, multiset, map and multimap.

Before taking a detailed look at the type definitions and member functions provided by the associative containers, we need to define a few terms and explain some of the ideas behind the design.

Basic Design and Organization

All associative containers are parameterized on a type `Key` and an ordering relation `Compare` that induces a total ordering on elements of `Key`. In addition, map and multimap associate an arbitrary type `T` with the `Key`. An object of type `Compare` is called the *comparison object* of the container.

Equality of Keys

For associative containers, it is important to note that equality of keys depends on the equivalence relation imposed by the comparison, and not on the operator `==` on keys. Thus, two keys `k1` and `k2` are considered equal if, for a comparison object `comp`,

```
comp(k1,k2)==false && comp(k2,k1)==false.
```

Additional Definitions

The set and map containers support unique keys; they can store at most one element of each key. multiset and multimap containers support equal keys; i.e., they can store multiple elements that have the same key.

Containers Library

What Are Containers

For set and multiset, the value type is the same as the key type; i.e., the values stored in sets and multisets are basically the keys themselves. For map and multimap, the value type is `pair<const Key, T>`; i.e., the elements stored in maps and multimaps are pairs whose first elements are `const Key` values and whose second elements are `T` values.

Finally, an iterator of an associative container is of the bidirectional iterator category. insert operations do not affect the validity of iterators and references to the container, and erase operations only invalidate iterators and references to the erased elements.

Listed below are the type definitions and member functions defined by associative containers in addition to the common container members outlined previously.

In all the definitions, we assume that `X` is an associative container class, `a` is a value of `X`, `a_uniq` is a value of `X` when `X` supports unique keys and `a_eq` is a value of `X` when `X` supports equal keys. `i` and `j` satisfy input iterator requirements and refer to elements of `value_type`. `[i, j)` is a valid range, `p` is a valid iterator to `a`, `q`, `q1`, and `q2` are valid dereferenceable iterators to `a`, `[q1, q2)` is a valid range, `t` is a value of `X::value_type` and `k` is a value of `X::key_type`.

Associative Container Types and Member Functions

key_type

Description The type of keys, `Key`, with which the container is instantiated.

Definition `X::key_type`

key_compare

Description The comparison object type, `Compare`, with which the container is instantiated.

Definition `X::key_compare`

value_compare

Description A type for comparing objects of `X::value_type`. This is the same as `key_compare` for set and multiset, while for map and multimap it is a type that compares pairs of Key and T values by comparing their keys using `X::key_compare`.

Definition `X::value_compare`

Constructors

Description Constructs a container object.

Prototype `X();`
`X a;`

Remarks Constructs an empty container, using `Compare()` as a comparison object. Takes constant time.

Prototype `X(c);`
`X a(c);`

Remarks Constructs an empty container, using `c` as a comparison object. Takes constant time.

`X(i,j,c);`
`X a(i,j,c);`

Remarks Constructs an empty container, using `c` as a comparison object, and inserts elements from the range `[i,j)` in it. Takes $N \log N$ time in general, where N is the distance from `i` to `j`; linear if `[i,j)` is sorted with `value_comp()`.

`X(i,j);`
`X a(i,j);`

Remarks Same as above, but uses `Compare()` as a comparison object.

key_comp

Description Returns the comparison object, of type `X::key_compare`, out of which `a` was constructed.

Containers Library

What Are Containers

Prototype `a.key_comp();`

value_comp

Description Returns an object of type `X::value_compare` constructed out of the comparison object.

Prototype `a.value_comp();`

insert

Description Inserts elements under various and specific conditions.

Prototype `a_uniq.insert(t);`

Remarks Inserts `t` if and only if there is no element in the container with key equal to the key of `t`. Returns a `pair<iterator, bool>` whose `bool` component indicates whether the insertion was made and whose `iterator` component points to the element with key equal to the key of `t`. Takes time logarithmic in the size of the container.
`a_eq.insert(p, t);`

Remarks Inserts `t` into the container and returns the iterator pointing to the newly inserted element.
`a.insert(p, t);`

Remarks Inserts `t` if and only if there is no element with key equal to the key of `t` in containers that support unique keys (i.e., sets and maps). Always inserts `t` in containers that support equal keys (i.e., multisets and multimaps). Iterator `p` is a hint pointing to where the insert should start to search. Takes time logarithmic in the size of the container in general, but amortized constant if `t` is inserted right after `p`.
`a.insert(i, j);`

Remarks Inserts the elements from the range `[i,j)` into the container. Takes $N\log N$ time in general, where N is the distance from `i` to `j`. Linear if `[i,j)` is sorted according to `value_comp()`.

erase

- Description** Erases and element under various specific conditions.
- Prototype** `a.erase(k);`
- Remarks** Erases all elements in the container with key equal to k. Returns the number of erased elements.
`a.erase(q);`
- Remarks** Erases the element pointed to by q.
`a.erase(q1,q2);`
- Remarks** Erases all the elements in the range [q1,q2). Takes $\log(\text{size}() + N)$ time, where N is the distance from q1 to q2.

find

- Description** Returns an iterator pointing to an element with key equal to k, or `a.end()` if such an element is not found.
- Prototype** `a.find(k);`

count

- Description** Returns the number of elements with key equal to k.
- Prototype** `a.count(k);`

lower_bound

- Description** Returns an iterator pointing to the first element with key not less than k.
- Prototype** `a.lower_bound(k);`

upper_bound

- Description** Returns an iterator pointing to the first element with key greater than k.

Containers Library

Organization of the Container Class Descriptions

Prototype `a.upper_bound(k);`

equal_range

Description Returns a pair of iterators (const iterators if `a` is constant), the first equal to `lower_bound(k)` and the second equal to `upper_bound(k)`.

Prototype `a.equal_range(k);`

NOTE: It must be noted that associative containers provide two constructors to copy ranges: `X(i,j,c)` and `X(i,j)`. The first version, `X(i,j,c)`, uses `c` as a comparison object, while the second constructor, `X(i,j)`, uses the comparison object `Compare()` constructed from the `Compare` type with which `X` is instantiated.

Organization of the Container Class Descriptions

Description The remaining sections of this chapter describe the specific requirements for the three sequence containers (vector, list, deque) and associative containers (set, multiset, map, multimap). Each of these container class descriptions contains the following subsections:

- **Files**—shows the header file to be included in programs that use the class.
- **Class Declaration**—the class name and template parameters are shown.
- **Description**—describes the basic functionality of the class. It serves as a short introduction to the particular container being described.
- **Type Definitions**—explains the type definitions in the public interface of the class.
- **Constructors, Destructors and Related Functions**—contains descriptions of constructors and destructors in the class. Some classes also have other related functions that deal with allocation and deallocation issues, and these are explained wherever required.

- **Element Access Member Functions**—explains the functionality of all member functions that are used to access elements in the container.
- **Insert Member Functions**—explains all member functions that are used to insert elements into the container.
- **Erase Member Functions**—details all member functions that are used to erase elements from the container.
- **Additional Notes Section(s)**—this section or sections contain details such as implementation dependencies, time complexity discussions for insert and erase member functions, memory model dependencies, etc. Any important information that is not included in the other sections is included in the notes sections.

Template class vector<T>

Files `#include <vector.h>`

Declaration `template
 < class T >
class vector;`

Description Vectors are containers that arrange elements of a given type in a strictly linear arrangement, and allow fast random access to any element (i.e., any element can be accessed in constant time).

Vectors allow constant time insertions and deletions at the end of the sequence. Inserting and/or deleting elements in the middle of a vector requires linear time. Further details of the time complexity of vector insertion can be found in the notes section.

The topics in this section are:

- [“Type Definitions vector” on page 194](#)
- [“Constructors, Destructors and Related Functions vector” on page 196](#)
- [“Comparison Operations vector” on page 198](#)
- [“Element Access Member Functions vector” on page 198](#)

- [“Erase Member Functions vector” on page 201](#)
- [“Insert Member Functions vector” on page 200](#)
- [“Notes on Insert and Erase Member Functions vector” on page 202](#)
- [“Specialization Class vector<bool>” on page 202](#)

Type Definitions `vector`

Iterator

Description iterator is a random access iterator type referring to T.

Definition `typedef iterator;`

`const_iterator`

Description `const_iterator` is a constant random access iterator type referring to `const T`.

Definition `typedef const_iterator;`

Remarks It is guaranteed that there is a constructor for `const_iterator` out of it-erator.

`T*`

Description The type `T*` (pointer to T).

Definition `typedef Allocator<T>::pointer pointer;`

`reference`

Description The type `T&` that can be used for storing into T objects.

Definition `typedef Allocator<T>::reference reference;`

`const_reference`

Description `typedef Allocator<T>::const_reference`

`const_reference;`

Definition The type `const T&` that can be used for storing into T objects.

`size_type`

Description `size_type` is an unsigned integral type that can represent the size of any vector instance.

Definition `typedef size_type;`

`difference_type`

Description A signed integral type that can represent the difference between any two pointers to `vector::iterator` objects.

Definition `typedef difference_type;`

`value_type`

Description The type of values the vector holds. This is simply T.

Definition `typedef T value_type;`

`reverse_iterator`

Description Non-constant reverse random access iterator.

Definition `typedef reverse_iterator;`

`const_reverse_iterator`

Description Constant reverse random access iterator.

Definition `typedef const_reverse_iterator;`

Constructors, Destructors and Related Functions `vector`

Default Constructor

Description The default constructor. Constructs a vector of size zero.

Prototype `vector();`

Overloaded and Copy Constructors

Prototype `explicit vector
 (size_type n,
 const T& value = T());`

Remarks Constructs a vector of size `n` and initializes all its elements with `value`. If the second argument is not supplied, `value` is obtained with the default constructor, `T()`, for the element value type `T`.

Prototype `vector(const vector<T>& x);`

Remarks The vector copy constructor. Constructs a vector and initializes it with copies of the elements of vector `x`.

`vector
 (const_iterator first,
 const_iterator last);`

Remarks Constructs a vector of size `last-first` and initializes it with copies of elements in the range `[first,last)`.

Assignment Operator `=`

Description The vector assignment operator. Replaces the contents of the current vector with a copy of the parameter vector `x`.

Prototype `vector<T>& operator=
 (const vector<T>& x);`

Reserve

Description This member function is a directive that informs the vector of a planned change in size, so storage can be managed accordingly. It does not change the size of the vector, and it takes time at most linear in the size of the vector. Reallocation happens at this point if and only if the current capacity is less than the argument of reserve (capacity is a vector member function that returns the size of the allocated storage in the vector). After a call to reserve, the capacity is greater than or equal to the argument of reserve if reallocation happens, and equal to the previous capacity otherwise.

Prototype `void reserve(size_type n);`

Remarks Reallocation invalidates all the references, pointers, and iterators referring to the elements in the vector. It is guaranteed that no reallocation takes place during the insertions that happen after reserve takes place till the time when the size of the vector reaches the size specified by reserve.

Destructor

Description The vector destructor. Returns all allocated storage back to the free store.

Prototype `~vector();`

vector::swap

Description Swaps the contents of the current vector with those of the input vector `x`. The current vector replaces `x` and vice versa.

Prototype `void swap(vector<T>& x);`

Comparison Operations vector

Equality Operator ==

Description Equality operation on vectors. Returns true if the sequences of elements in x and y are element-wise equal (using T::operator==). Takes linear time.

Prototype

```
bool operator==(
    (const vector<T>& x,
    const vector<T>& y);
```

Less Than Operator <

Description Returns true if x is lexicographically less than y, false otherwise. Takes linear time.

Prototype

```
bool operator<
    (const vector<T>& x,
    const vector<T>& y);
```

Element Access Member Functions vector

vector::begin

Description Returns an iterator (const_iterator for constant vector) that can be used to begin traversing through the vector.

Prototype

```
iterator begin();
const_iterator begin() const;
```

vector::end

Description Returns an iterator (const_iterator for constant vector) that can be used in a comparison for ending traversal through the vector.

Prototype

```
iterator end();
const_iterator end() const;
```

`vector::rbegin`

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant vectors) that can be used to begin traversing the vector in the reverse of the normal order.

Prototype `reverse_iterator rbegin();`
`const_reverse_iterator rbegin();`

`vector::rend`

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant vectors) that can be used in a comparison for ending reverse-direction traversal through the vector.

Prototype `reverse_iterator rend();`
`const_reverse_iterator rend();`

`vector::size`

Description Returns the number of elements currently stored in the vector.

Prototype `size_type size() const;`

`vector::max_size`

Description Returns the maximum possible size of the vector.

Prototype `size_type max_size() const;`

`vector::capacity`

Description Returns the largest number of elements that the vector can store without reallocation. See also the `reserve` member function.

Prototype `size_type capacity() const;`

Containers Library

Template class `vector<T>`

`vector::empty`

Description Returns true if the vector contains no elements (i.e., if `begin() == end()`), false otherwise.

Prototype `bool empty() const;`

Subset Operator []

Description Returns the *n*th element from the beginning of the vector in constant time.

Prototype `reference operator[](size_type n);`
`const reference operator[](size_type n) const;`

`vector::front`

Description Returns the first element of the vector; i.e., the element referred to by the iterator `begin()`. Undefined if the vector is empty.

Prototype `reference front();`
`const_reference front() const;`

`vector::back`

Description Returns the last element of the vector; i.e., the element pointed to by the iterator `end()-1`. Undefined if the vector is empty.

Prototype `reference back();`
`const_reference back() const;`

Insert Member Functions `vector`

The time complexities of all insert member functions are described in the notes subsections at the end of this section.

`vector::push_back`

Description Adds the element *x* at the end of the vector.

Prototype `void push_back(const T& x);`

`vector::insert`

Description Inserts an element or elements into position or positions referred to in the vector object.

Prototype `iterator insert(iterator position, const T& x);`

Remarks Inserts the element `x` at the position in the vector referred to by the iterator `position`. Elements already in the vector are moved as required. The iterator returned refers to the position at which the element was inserted.

Prototype `void insert
 (iterator position,
 size_type n,
 const T& x = T());`

Remarks Inserts `n` copies of the element `x` starting at the position referred to by the iterator `position`.

Prototype `void insert
 (iterator position,
 const T* first,
 const T* last);`

Remarks Copies of elements in the range `[first,last)` are inserted into the vector at the position referred to by the iterator `position`.

Erase Member Functions `vector`

`vector::pop_back`

Description Erases the last element of the vector.

Prototype
`void pop_back();`

Containers Library

Template class `vector<T>`

`vector::erase`

- Description** Erases one or more elements from a vector.
- Prototype** `void erase(iterator position);`
- Remarks** Erases the element of the vector pointed to by the iterator position.
- Prototype** `void erase(iterator first, iterator last);`
- Remarks** The iterators `first` and `last` are assumed to point into the vector, and all elements in the range `[first,last)` are erased from the vector.

Notes on Insert and Erase Member Functions

vector

Inserting a single element into a vector is linear in the distance from the insertion point to the end of the vector. The amortized complexity of inserting a single element at the end of a vector is constant (see Section 1.4.2 for discussion of amortized complexity).

Insertion of multiple elements into a vector with a single call of the `insert` member function is linear in the sum of the number of elements plus the distance to the end of the vector. This means that it is much faster to insert many elements into the middle of a vector at once than to do the insertions one at a time.

All `insert` member functions cause reallocation if the new size is greater than the old capacity. If no reallocation happens, all the iterators and references before the insertion point remain valid.

`erase` invalidates all iterators and references after the point of the `erase`. The destructor of `T` is called for each erased element and the assignment operator of `T` is called the number of times equal to the number of elements in the vector after the erased elements.

Specialization Class `vector<bool>`

Files `#include <vector.h>`

Description This class is a specialization of the template class `vector<T>` so as to optimize space allocation. All the member functions of template class `vector<T>` are defined for this class also and it has an extra member function `swap()`.

In this implementation `vector<bool>` has been replaced by a class `bit_vector` since `bool` has not been implemented.

Public Member Functions

`vector::swap`

Description In this implementation, this function is a global function which swaps the contents of `x` and `y`.

Prototype `void swap(reference x, reference y);`

Template class deque<T>

Files `#include <deque.h>`

Declaration `template <class T> class deque;`

Description This class implements a deque of objects of type `T`. Deques are very much like vectors, except that they can be expanded in both directions: they allow constant time insertion and deletion of objects at either end.

Like vectors, deques allow fast random access to any element in constant time.

The topics in this section are:

- [“Typedef Declarations deque” on page 204](#)
- [“Constructors, Destructors and Related Functions deque” on page 205](#)
- [“Comparison Operations deque” on page 207](#)
- [“Element Access Member Functions deque” on page 207](#)

- [“Insert Member Functions deque” on page 209](#)
- [“Erase Member Functions deque” on page 210](#)
- [“Deque Class Notes” on page 211](#)

Typedef Declarations deque

Description The following typedef’s are defined in the class `deque<T>`.

iterator

Definition `typedef iterator;`

const_iterator

Definition `typedef const_iterator;`

`iterator` is a random access iterator referring to `T`. `const_iterator` is a constant random access iterator referring to `const T`.

pointer

Description The type `T*` (pointer to `T`).

Definition `typedef Allocator<T>::pointer pointer;`

reference

Description The type `T&` that can be used for storing into `T` objects.

Definition `typedef Allocator<T>::reference reference;`

const_reference

Description The type `const T&` for const references that can be used for storing into `T` objects.

Definition `typedef Allocator<T>::const_reference
const_reference;`

size_type

Description size_type is an unsigned integral type that can represent the size of any deque instance.

Definition `typedef size_type;`

difference_type

Description A signed integral type that can represent the difference between any two deque::iterator objects.

Definition `typedef difference_type;`

value_type

Description The type of values the deque holds. This is simply T.

Definition `typedef T value_type;`

reverse_iterator

Description Non-constant reverse random access iterators

Definition `typedef reverse_iterator;`

const_reverse_iterator

Description Constant reverse random access iterators

Definition `typedef const_reverse_iterator;`

Constructors, Destructors and Related Functions deque

Default Constructor

Description The default constructor. Constructs a deque with size zero.

Containers Library

Template class *deque*<T>

Prototype `deque();`

Overloaded and Copy Constructors

Prototype `explicit deque
 (size_type n,
 const T& value = T());`

Remarks Constructs a deque of size *n*, and initializes all its elements with *value*. The default for *value* is set to *T()*, where *T()* is the default constructor of the type passed to the deque class template.

Prototype `deque(const deque<T>& x);`

Remarks The deque copy constructor. Constructs a deque and initializes it with copies of the elements of deque *x*.

Prototype `deque
 (const_iterator first,
 const_iterator last);`

Remarks Constructs a deque of size *last-first* and initializes it with copies of elements in the range *[first,last)*.

Assignment Operator =

Prototype `deque<T>& operator=
 (const deque<T>& x);`

Remarks The deque assignment operator. Replaces the contents of the current deque with a copy of the parameter deque *x*.

Destructor

Description The set destructor. Returns all allocated storage back to the free store.

Prototype `~deque();`

deque::swap

Description Swaps the contents of the current deque with those of the input deque x. The current deque replaces x and vice versa.

Prototype `void swap(deque<T>& x);`

Comparison Operations deque

Equality Operator ==

Description Equality operation on deques. Returns true if the sequences of elements in x and y are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==(const deque<T>& x,
const deque<T>& y);`

Less Than Operator <

Description Returns true if x is *lexicographically* less than y, false otherwise. Takes linear time.

Prototype `bool operator<(const deque<T>& x,
const deque<T>& y);`

Element Access Member Functions deque

deque::begin

Description Returns an iterator (`const_iterator` for constant deque) that can be used to begin traversing through all locations in the deque.

Prototype `iterator begin()
const_iterator begin() const;`

Containers Library

Template class *deque*<T>

deque::end

Description Returns an iterator (`const_iterator` for constant deque) that can be used in a comparison for ending traversal through the deque.

Prototype `iterator end();`
`const_iterator end() const;`

deque::rbegin

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant deques), that can be used to begin traversing all locations in the deque in the reverse of the normal order.

Prototype `reverse_iterator rbegin();`
`const_reverse_iterator rbegin() const;`

deque::rend

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant deques), that can be used in a comparison for ending reverse-direction traversal through all locations in the deque.

Prototype `reverse_iterator rend();`
`const_reverse_iterator rend();`

deque::size

Description Returns the number of elements in the deque.

Prototype `size_type size() const;`

deque::max_size

Description Returns the maximum possible size of the deque.

Prototype `size_type max_size() const;`

deque::empty

Description Returns true if the deque contains no elements (i.e., if `begin() == end()`), false otherwise

Prototype `bool empty() const;`

Subset Operator []

Description Allows constant time access to the *n*th element of the deque.

Prototype `reference operator[](size_type n);`
`const_reference operator[](size_type n) const;`

deque::front

Description Returns the first element of the deque; i.e., the element pointed to by the iterator `begin()`.

Prototype `reference front();`
`const_reference front() const;`

deque::back

Description Returns the last element of the deque; i.e., the element pointed to by the iterator `end()-1`.

Prototype `reference back();`
`const_reference back() const;`

Insert Member Functions deque

deque::push_front

Description Adds the element *x* at the beginning of the deque.

Prototype `void push_front(const T& x);`

Containers Library

Template class *deque*<T>

deque::push_back

Description Adds the element *x* at the end of the deque.

Prototype `void push_back(const T& x);`

deque::insert

Description Inserts one or more elements into a position in the deque.

Prototype `iterator insert(iterator position, const T& x);`

Remarks Inserts the element *x* at the position in the deque pointed to by the iterator *position*. The iterator returned points to the position that contains the inserted element.

Prototype `void insert
(iterator position,
size_type n,
const T& x = T());`

Description Inserts *n* copies of the element *x* starting at the position pointed to by the iterator *position*.

Prototype `void insert
(iterator position,
const T* first,
const T* last;`

Description Inserts elements into the deque before the position pointed to by the iterator *position*. Copies of elements in the range *[first,last)* are inserted into the deque.

Erase Member Functions deque

deque::pop_front

Description

Prototype
`void pop_front();`

deque::pop_back

Description Erases the last element of the deque.

Prototype `void pop_back();`

deque::erase

Description Erases one or more elements of the deque.

Prototype `void erase(iterator position);`

Remarks Erases the element of the deque pointed to by the iterator position.
`void erase(iterator first, iterator last);`

Remarks The iterators first and last are assumed to point into the deque, and all elements in the range [first,last) are erased from the deque.

Deque Class Notes

Storage Management

As with all STL containers, all storage management in deques is handled automatically. Deques are implemented using segmented storage (unlike vectors). This means that all deque elements are not necessarily kept in contiguous locations in memory.

Complexity of Insertion

Deques are specially optimized for insertion of single elements at either the beginning or the end of the data structure. Such insertions always take constant time and cause a single call to the copy constructor of T, where T is the type of the inserted object.

If an element is inserted into the middle of the deque, then in the worst case the time taken is linear in the minimum of the distance

from the insertion point to the beginning of the deque and the distance from the insertion point to the end of the deque.

The insert and push member functions invalidate all the iterators and references to the deque.

Notes on Erase Member Functions

The erase and pop invalidate all the iterators and references to the deque. The number of calls to the destructor (of the erased type T) is the same as the number of elements erased, but the number of calls to the assignment operator of T is equal to the minimum of the number of elements before the erased elements and the number of elements after the erased elements.

Template class `list<T>`

Files `#include <list.h>`

Declaration `template
 < class T >
class list;`

Description This class implements the sequence abstraction as a linked list. All lists are “doubly-linked” and may be traversed in either direction.

Lists should be used in preference to other sequence abstractions when there are frequent insertions and deletions in the middle of sequences. As with all STL containers, storage management is handled automatically.

Unlike vectors or deques, lists are not random-access data structures. For this reason, some STL generic algorithms such as `sort`, `random_shuffle`, etc., cannot operate on lists. The list class provides its own sort member function.

Besides `sort`, lists also include some other special member functions for splicing two lists, reversing lists, making all list elements unique

and for merging two lists. All of these special member functions are discussed on [“Special Operations list” on page 220](#).

The topics in this section are:

- [“Typedef Declarations list” on page 213](#)
- [“Constructors, Destructors and Related Functions list” on page 215](#)
- [“Comparison Operations list” on page 216](#)
- [“Element Access Member Functions list” on page 217](#)
- [“Insert Member Functions list” on page 218](#)
- [“Erase Member Functions list” on page 219](#)
- [“Special Operations list” on page 220](#)
- [“List Class Notes” on page 222](#)

Typedef Declarations list

Description The following typedef’s are defined in the class `list<T>`.
iterator

Description The type `iterator` is a bidirectional iterator referring to `T`.

Definition `typedef iterator;`
const_iterator

Description The type `const_iterator` is a constant bidirectional iterator referring to `const T`. It is guaranteed that there is a constructor for `const_iterator` out of `iterator`.

Definition `typedef const_iterator;`
pointer

Description The type `T*` (pointer to `T`).

Definition `typedef Allocator<T>::pointer pointer;`

Containers Library

Template class `list<T>`

reference

Description The type `T&` that can be used for storing into `T` objects.

Definition `typedef Allocator<T>::reference reference;`

const_reference

Description The type `const T&` for const references that can be used for storing into `T` objects.

Definition `typedef Allocator<T>::const_reference
const_reference;`

size_type

Description `size_type` is an unsigned integral type that can represent the size of any `list` instance.

Definition `typedef size_type;`

difference_type

Description A signed integral type that can represent the difference between any two `list::iterator` objects.

Definition `typedef difference_type;`

value_type

Description The type `T` of values the list holds.

Definition `typedef T value_type;`

reverse_iterator

Description Non-constant reverse bidirectional iterator type.

Definition `typedef reverse_iterator;`

const_reverse_iterator

Description Constant reverse bidirectional iterator type.

Definition `typedef const_reverse_iterator;`

Constructors, Destructors and Related Functions list

Default Constructor

Description The default constructor. Constructs an empty list.

Prototype `list();`

Overloaded and Copy Constructors

Description Constructs a list of size `n`, and initializes all its elements with value.

Prototype `explicit list
 (size_type n,
 const T& value = T());`

Prototype `list(const list<T>& x);`

Remarks The list copy constructor. Constructs a list and initializes it with copies of the elements of list `x`.

Prototype `list(const T* first, const T* last);`

Remarks Constructs a list of size `last-first` and initializes it with copies of elements in the range `[first,last)`.

Assignment Operator =

Description The list assignment operator. Replaces the contents of the current list with a copy of the parameter list `x`.

Prototype `list<T>& operator=(const list<T>& x);`

Containers Library

Template class `list<T>`

Destructor

Description The list destructor. Returns all allocated storage back to the free store.

Prototype `~list();`

`list::swap`

Description Swaps the contents of the current list with those of the input list `x`. The current list replaces `x` and vice versa.

Prototype `void swap(list<T>& x);`

Comparison Operations list

Equality Operator `==`

Description Equality operation on lists. Returns true if the sequences of elements in `x` and `y` are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==
 (const list<T>& x,
 const list<T>& y);`

Less Than Operator `<`

Description Returns true if `x` is lexicographically less than `y`, false otherwise. Takes linear time

Prototype `bool operator<
 (const list<T>& x,
 const list<T>& y);`

Element Access Member Functions list

list::begin

Description Returns an iterator (`const_iterator` for constant list) that can be used to begin traversing through the list.

Prototype `iterator begin();`
`const_iterator begin() const;`

list::end

Description Returns an iterator (`const_iterator` for constant list) that can be used in a comparison for ending traversal through the list.

Prototype `iterator end();`
`const_iterator end() const;`

list::rbegin

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant lists), that can be used to begin traversing the list in the reverse of the normal order.

Prototype `reverse_iterator rbegin();`
`const_reverse_iterator rbegin() const;`

list::rend

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant lists), that can be used in a comparison for ending reverse-direction traversal through the list.

Prototype `reverse_iterator rend();`
`const_reverse_iterator rend() const;`

list::size

Description Returns the number of elements currently stored in the list.

Containers Library

Template class `list<T>`

Prototype `size_type size() const;`

`list::max_size`

Description Returns the maximum possible size of the list.

Prototype `size_type max_size() const;`

`list::empty`

Description Returns true if the list contains no elements (i.e., if `begin() == end()`), false otherwise

Prototype `bool empty() const;`

`list::front`

Description Returns the first element of the list; i.e., the element pointed to by the iterator `begin()` .

Prototype `reference front();`
`const_reference front() const;`

`list::back`

Description Returns the last element of the list; i.e., the element pointed to by the iterator `end()-1` .

Prototype `reference back();`
`const_reference back() const;`

Insert Member Functions list

`list::push`

Description Inserts the element `x` at the beginning of the list .

Prototype `void push_front(const T& x);`

list::push_back

Description Inserts the element x at the end of the list.

Prototype `void push_back(const T& x);`

list::insert

Description Inserts one or more elements into the list.

Prototype `iterator insert(iterator position, const T& x);`

Remarks Inserts the element x at the position in the list pointed to by the iterator position. The iterator returned points to the position that contains the inserted element.

Prototype `void insert
 (iterator position,
 size_type n,
 const T& x = T());`

Remarks Inserts n copies of the element x starting at the position pointed to by the iterator position

`void insert
 (iterator position,
 const T* first,
 const T* last);`

Remarks Inserts elements into the list before the position pointed to by the iterator position. Copies of elements in the range [first,last) are inserted into the list.

Erase Member Functions list

list::pop_front

Description Erases the first element of the list.

Prototype `void pop_front();`

Containers Library

Template class `list<T>`

`list::pop_back`

Description Erases the last element of the list.

Prototype `void pop_back();`

`list::erase`

Description Erases one or more elements of the list pointed to by the iterator position.

Prototype `void erase(iterator position);`

Remarks Erases the element of the list pointed to by the iterator position.

Prototype `void erase(iterator first, iterator last);`

Remarks The iterators `first` and `last` are assumed to point into the list, and all elements in the range `[first, last)` are erased from the list.

Special Operations list

`list::splice`

Description These member functions inserts the contents of list `x` before the iterator position, and `x` becomes empty.

Prototype `void splice(iterator position, list<T>& x);`

Remarks This member function inserts the contents of list `x` before the iterator position, and `x` becomes empty. The operation takes constant time. Essentially, the contents of `x` are transferred into the current list.

Prototype `void splice
 (iterator position,
 list<T>& x,
 iterator x_elem);`

Remarks Inserts the element pointed to by iterator `x_elem` from list `x` before position, and removes the element from `x`. It takes constant time. `x_elem` is assumed to be a valid iterator of the list `x`. The function basically transfers a single element from the list `x` into the current list.

Prototype

```
void splice
    (iterator position,
     list<T>& x,
     iterator first,
     iterator last);
```

Remarks Inserts the elements in the range `[first, last)` before the iterator position, and removes the elements from list `x`. The operation takes linear time. The range `[first,last)` is assumed to be a valid range in `x`.

`list::remove`

Description This function removes all elements in the list that are equal to `value`, using `T::operator==`. The relative order of other elements is not affected. The entire list is traversed exactly once.

Prototype

```
void remove(const T& value);
```

`list::unique`

Description This function erases all but the first element from every consecutive group of equal elements in the list. Exactly `size()-1` applications of `T::operator==` are done. This function is most useful when the list is sorted, so that all elements that are equal appear in consecutive positions. In that case, each element in the resulting list is unique.

Prototype

```
void unique();
```

`list::merge`

Description This function merges the argument list `x` into the current list. It is assumed that both lists are sorted according to the `operator<` of type `T`. The merge is stable; i.e., for equal elements in the two lists, the elements from the current list always precede the elements from the

Containers Library

Template class `list<T>`

argument list `x`. `x` becomes empty after the merge. At most `size() + x.size() - 1` comparisons are done.

Prototype `void merge(list<T>& x);`

`list::reverse`

Description Reverses the order of the elements in the list. It takes linear time.

Prototype `void reverse();`

`list::sort`

Description Sorts the list according to the operator< of type `T`. The sort is stable; i.e., the relative order of equal elements is preserved. Approximately $N \log N$ comparisons are done, where N is equal to `size()`.

Prototype `void sort();`

List Class Notes

Notes on Insert Member Functions

List insert operations do not affect the validity of iterators and references to other elements of the list. Insertion of a single element of type `T` into a list takes constant time and makes only one call to the copy constructor of `T`. Insertion of multiple elements into a list is linear in the number of elements inserted, and the number of calls to the copy constructor of `T` is exactly equal to the number of elements inserted.

Notes on Erase Member Functions

`erase` invalidates only the iterators and references to the erased elements. Erasing a single element of type `T` is a constant time operation, with a single call to the destructor of `T`. Erasing a range in a list takes time linear in the size of the range, and the number of calls to the destructor of type `T` is exactly equal to the size of the range.

Template class `set<T>`

Files `#include <set.h>`

Declaration

```
template
    < class Key,
      class Compare = less<Key> >
class set;
```

Description A `set<Key, Compare>` stores unique elements of type `Key`, and allows for the retrieval of the elements themselves. All elements in the set are ordered by the ordering relation `Compare`, which induces a total ordering on the elements.

As with all STL containers, the set container only allocates storage and provides a minimal set of operations (such as insert, erase, find, count, etc.). The set does not itself provide operations for union, intersection, difference etc. These operations are handled by generic algorithms in STL.

The topics in this section are:

- [“Typedef Declarations set” on page 223](#)
- [“Constructors, Destructors and Related Functions set” on page 226](#)
- [“Comparison Operations set” on page 227](#)
- [“Element Access Member Functions set” on page 228](#)
- [“Insert Member Functions set” on page 229](#)
- [“Erase Member Functions set” on page 230](#)
- [“Special Operations set” on page 231](#)

Typedef Declarations set

Description The following typedef’s are defined in the class `set`.

key_type

Description The type of the keys with which the set is instantiated.

Containers Library

Template class *set*<T>

Definition `typedef Key key_type;`

value_type

Description `value_type` represents the type of the values stored in the set. This is the same as `key_type`.

Definition `typedef Key value_type;`

`value_type` represents the type of the values stored in the set. This is the same as `key_type`.

pointer

Description The type `Key*` (pointer to `Key`).

Definition `typedef Allocator<Key>::pointer pointer;`

The type `Key*` (pointer to `Key`).

reference

Description The type `Key&` that can be used for storing into `Key` objects.

Definition `typedef Allocator<Key>::reference reference;`

const_reference

Description The type `Const Key&` for const references that can be used for storing into `Key` objects.

Definition `typedef Allocator<Key>::const_reference
const_reference;`

The type `Key&` (`const Key&` for const references) that can be used for storing into `Key` objects.

compare_key

Description The comparison object type, `Compare`, with which the set is instantiated. This type is used to order the keys in the set.

Definition `typedef Compare key_compare;`

value_compare

Description This is the ordering relation that is used to order the values stored in the set. Its type is the same as `key_compare`, since the type of a value stored in a set is the same as the type of the key.

Definition `typedef Compare value_compare;`

iterator

Description The type `iterator` is a constant bidirectional iterator referring to `const value_type`.

Definition `typedef iterator;`

const_iterator

Description The type `const_iterator` is the same type as `iterator`.

Definition `typedef const_iterator;`

size_type

Description `size_type` is an unsigned integral type that can represent the size of any set instance.

Definition `typedef size_type;`

difference_type

Description A signed integral type that can represent the difference between any two `set::iterator` objects.

Definition `typedef difference_type;`

reverse_iterator

Description Non-constant reverse bidirectional iterator type.

Containers Library

Template class `set<T>`

Definition `typedef reverse_iterator;`

`const_reverse_iterator`

Description Constant reverse bidirectional iterator type.

Definition `typedef const_reverse_iterator;`

Constructors, Destructors and Related Functions `set`

Default Constructor

Description The default constructor. Constructs an empty set using the relation `comp` to order the elements.

Prototype `set(const Compare& comp = Compare());`

Overloaded and Copy Constructors

Prototype `set(const set<Key, Compare>& x);`

Remarks The set copy constructor. Constructs a set and initializes it with copies of the elements of set `x`.

Prototype `set
 (const value_type* first,
 const value_type* last,
 const Compare& comp = Compare());`

Remarks Constructs an empty set and initializes it with copies of elements in the range `[first,last)`. The ordering relation `comp` is used to order the elements of the set.

Assignment Operator `=`

Description The set assignment operator. Replaces the contents of the current set with a copy of the parameter set `x`.

Prototype `set<Key, Compare>& operator=
 (const set<Key,
 Compare>& x);`

set::swap

Description Swaps the contents of the current set with those of the input set x. The current set replaces x and vice versa.

Prototype `void swap(set<Key, Compare>& x);`

Destructor

Description The set destructor. Returns all allocated storage back to the free store.

Prototype `~set();`

Comparison Operations set

Equality Operator ==

Description Equality operation on sets. Returns true if the sequences of elements in x and y are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==
 (const set<Key,
 Compare>& x,
 const set<Key,
 Compare>& y);`

Less Than Operator <

Description Returns true if x is lexicographically less than y, false otherwise. Takes linear time.

Prototype `bool operator<
 (const set<Key,
 Compare>& x,`

```
const set<Key,  
Compare>& y);
```

Element Access Member Functions *set*

set::key_compare

Description This function returns the comparison object of the set. The comparison object is an object of class *Compare*, which represents the ordering relation used to construct the set.

Prototype `key_compare key_comp() const;`

set::value_comp

Description Returns an object of type *value_compare* constructed out of the comparison object. For sets, this is simply an object of type *Compare*.

Prototype `value_compare value_comp() const;`

set::begin

Description Returns the iterator that can be used to begin traversing through all locations in the set.

Prototype `iterator begin() const;`

set::end

Description Returns an iterator that can be used in a comparison for ending traversal through the set.

Prototype `iterator end() const;`

set::rbegin

Description Returns a *reverse_iterator*, that can be used to begin traversing all locations in the set in the reverse of the normal order.

Prototype `reverse_iterator rbegin();`

set::rend

Description Returns a `reverse_iterator`, that can be used in a comparison for ending reverse-direction traversal through all locations in the set.

Prototype `reverse_iterator rend();`

set::empty

Description Returns true if the set is empty, false otherwise.

Prototype `bool empty() const;`

set::size

Description Returns the number of elements in the set.

Prototype `size_type size() const;`

set::max_size

Description Returns the maximum possible size of the set. The maximum size is simply the total number of elements of type `Key` that can be represented in the memory model used.

Prototype `size_type max_size() const;`

Insert Member Functions set

set::insert

Description Inserts one or more elements into the set.

Prototype `iterator insert
 (iterator position,
 const value_type& x);`

Containers Library

Template class `set<T>`

Remarks Inserts the element `x` into the set if `x` is not already present in the set. The iterator position is a hint, indicating where the insert function should start to search to do the insert. The search is necessary since sets are ordered containers.

The insertion takes $O(\log N)$ time, where N is the number of elements in the set, but is amortized constant if `x` is inserted right after the iterator position.

Prototype `pair<iterator, bool> insert
(const value_type& x);`

Remarks Inserts the element `x` into the set if `x` is not already present in the set. The returned value is a pair, whose `bool` component indicates whether the insertion has taken place, and whose iterator component points to the just inserted element in the set, if the insertion takes place, otherwise to the element `x` already present.

The insertion takes $O(\log N)$ time, where N is the number of elements in the set.

Prototype `void insert
(const value_type* first,
const value_type* last);`

Remarks Copies of elements in the range `[first,last)` are inserted into the set. This insert member function allows elements from other containers to be inserted into the set.

In general, the time taken for this insertion is $N \log(\text{size}() + N)$, where N is the distance from `first` to `last`, and linear if the range `[first,last)` is sorted according to the set ordering relation `value_comp()`.

Erase Member Functions `set`

`set::erase`

Description Erases one or more set elements.

Prototype `void erase(iterator position);`

Remarks Erases the set element pointed to by the iterator position. The time taken is amortized constant.

Prototype `size_type erase(const key_type& x);`

Remarks Erases all the set elements with key equal to *x* (i.e., removes all *x*'s from the set). Returns the number of erased elements, which is 1 if *x* is present in the set, and 0 otherwise (since sets do not store duplicate elements). In general, this function takes time proportional to $\log(\text{size}()) + \text{count}(x)$, where $\text{count}(k)$ is a set member function that returns the number of elements with key equal to *k*.

Prototype `void erase(iterator first, iterator last);`

Remarks The iterators *first* and *last* are assumed to point into the set, and all elements in the range $[\text{first}, \text{last})$ are erased from the set. The time taken is $\log(\text{size}()) + N$, where *N* is the distance from *first* to *last*.

Special Operations set

set::find

Description Searches for the element *x* in the set. If *x* is found, the function returns the iterator pointing to it. Otherwise, `end()` is returned. The function takes $O(\log N)$ time, where *N* is the number of elements in the set.

Prototype `iterator find(const key_type& x) const;`

set::count

Description Returns the number of elements in the set that are equal to *x*. If *x* is present in the set, this number is always 1; otherwise, it is 0. The function takes $O(\log(\text{size}()))$ time.

Prototype `size_type count(const key_type& x) const;`

Containers Library

Template class *multiset*<Key>

set::lower_bound

Description Returns an iterator pointing to the first set element whose key is not less than x. Since set elements are not repeated, the returned iterator points to x itself if x is present in the set. If x is not present in the set, end() is returned. The function takes O(log N) time, where N is the number of elements in the set.

Prototype `iterator lower_bound(const key_type& x) const;`

set::upper_bound

Description The upper_bound function returns an iterator to the first set element whose key is greater than x. If no such element is found, end() is returned. The function takes O(log N) time, where N is the number of elements in the set.

Prototype `iterator upper_bound(const key_type& x) const;`

set::equal_range

Description This function returns the pair(lower_bound(x), upper_bound(x)). The function takes O(log N) time, where N is the number of elements in the set.

Prototype `pair<iterator,iterator> equal_range
(const key_type& x) const;`

Template class **multiset**<Key>

Files `#include <multiset.h>`

Declaration `template
 < class Key,
 class Compare = less<Key> >
class multiset;`

Description A multiset is an associative container that can store multiple copies of the same key. As with regular sets, all elements in the multiset are

ordered by the ordering relation Compare, which induces a total ordering on the elements.

Multisets are necessary because we sometimes need to store elements, all of which are alike in most ways but which differ only in certain known characteristics. For example, a set of cars sorted by the make of the car would be a multiset, since there could be several cars in the set with the same manufacturer, but different in other aspects, such as engine capacity, price, etc.

The interface of the multiset class is exactly the same as that of the regular set class. The only difference is that multisets possibly contain multiple values of the same key value. As a result, some of the member functions also have slightly different semantics.

The topics in this section are:

- [“Typedef Declarations multiset” on page 233](#)
- [“Constructors, Destructors and Related Functions multiset” on page 236](#)
- [“Comparison Operations multiset” on page 237](#)
- [“Element Access Member Functions multiset” on page 238](#)
- [“Insert Member Functions multiset” on page 239](#)
- [“Erase Member Functions multiset” on page 240](#)
- [“Special Operations multiset” on page 241](#)

Typedef Declarations multiset

Description The following typedef's are defined in the class `multiset`.

key_type

Description The type of the keys with which the multiset is instantiated.

Definition `typedef Key key_type;`

Containers Library

Template class *multiset*<Key>

value_type

Description value_type represents the type of the values stored in the multiset. This is the same as key_type.

Definition `typedef Key value_type;`

pointer

Description The type Key* (pointer to Key).

Definition `typedef Allocator<Key>::pointer pointer`

reference

Description The type Key& that can be used for storing into Key objects.

Definition `typedef Allocator<Key>::reference reference;`

const_reference

Description The type const Key& for const references that can be used for storing into Key objects.

Definition `typedef Allocator<Key>::const_reference
const_reference;`

key_compare

Description The comparison object type, Compare, with which the multiset is instantiated. This type is used to order the keys in the multiset.

Definition `typedef Compare key_compare;`

value_compare

Description This is the ordering relation that is used to order the values stored in the multiset. Its type is the same as key_compare, since the type of a value stored in a multiset is the same as the type of the key.

Definition `typedef Compare value_compare;`

iterator

Description The type `iterator` is a constant bidirectional iterator referring to `const value_type`.

Definition `typedef iterator;`

const_iterator

Description The type `const_iterator` is the same type as `iterator`.

Definition `typedef const_iterator;`

size_type

Description `size_type` is an unsigned integral type that can represent the size of any multiset instance.

Definition `typedef size_type;`

difference_type

Description A signed integral type that can represent the difference between any two `multiset::iterator` objects.

Definition `typedef difference_type;`

reverse_iterator

Description Non-constant reverse bidirectional iterator types.

Definition `typedef reverse_iterator;`

const_reverse_iterator

Description Constant reverse bidirectional iterator types.

Definition `typedef const_reverse_iterator;`

Constructors, Destructors and Related Functions multiset

Default Constructor

Description The default constructor. Constructs an empty multiset using the relation comp to order the elements.

Prototype `multiset(const Compare& comp = Compare());`

Overloaded and Copy Constructors

Prototype `multiset(const multiset<Key, Compare>& x);`

Remarks The multiset copy constructor. Constructs a multiset and initializes it with copies of the elements of multiset x.

Prototype `multiset
 (const value_type* first,
 const value_type* last,
 const Compare& comp = Compare());`

Remarks Constructs an empty multiset and initializes it with copies of elements in the range [first,last). The ordering relation comp is used to order the elements of the multiset.

Assignment Operator =

Description The multiset assignment operator. Replaces the contents of the current multiset with a copy of the parameter multiset x.

Prototype `multiset<Key, Compare>& operator=
 (const multiset<Key,
 Compare>& x);`

multiset::swap

Description Swaps the contents of the current multiset with those of the input multiset x. The current multiset replaces x and vice versa.

Prototype `void swap(multiset<Key, Compare>& x);`

Destructor

Description The multiset destructor. Returns all allocated storage back to the free store.

Prototype `~multiset();`

Comparison Operations multiset

Equality Operator ==

Description Equality operation on multisets. Returns true if the sequences of elements in x and y are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==
 (const multiset<Key,
 Compare>& x,
 const multiset<Key,
 Compare>& y);`

Less Than Operator <

Description Returns true if x is lexicographically less than y, false otherwise. Takes linear time.

Prototype `bool operator<
 (const multiset<Key,
 Compare>& x,
 const multiset<Key,
 Compare>& y);`

Element Access Member Functions multiset

multiset::key_comp

Description This function returns the comparison object of the multiset. The comparison object is an object of class Compare, which represents the ordering relation used to construct the multiset.

Prototype `key_compare key_comp() const;`

multiset::value_comp

Description Returns an object of type value_compare constructed out of the comparison object. For multisets, this is simply an object of type Compare.

Prototype `value_compare value_comp() const;`

multiset::begin

Description Returns the iterator that can be used to begin traversing through all locations in the multiset.

Prototype `iterator begin() const;`

multiset::end

Description Returns an iterator that can be used in a comparison for ending traversal through the multiset.

Prototype `iterator end() const;`

multiset::rbegin

Description Returns a reverse_iterator, that can be used to begin traversing all locations in the multiset in the reverse of the normal order.

Prototype `reverse_iterator rbegin();`

multiset::rend

Description Returns a reverse_iterator, that can be used in a comparison for ending reverse-direction traversal through all locations in the multiset.

Prototype reverse_iterator rend();

multiset::empty

Description Returns true if the multiset is empty, false otherwise.

Prototype bool empty() const;

multiset::size

Description Returns the number of elements in the multiset.

Prototype size_type size() const;

multiset::max_size

Description Returns the maximum possible size of the multiset. The maximum size is simply the total number of elements of type Key that can be represented in the memory model used.

Prototype size_type max_size() const;

Insert Member Functions multiset

multiset::insert

Description Inserts one more elements into the multiset.

Prototype iterator insert
(iterator position,
const value_type& x);

Remarks Inserts the element x into the multiset if x is not already present in the multiset. The iterator position is a hint, indicating where the insert function should start to search to do the insert. This insertion

Containers Library

Template class *multiset*<Key>

takes $O(\log N)$ time in general, where N is the number of elements in the multiset, but is amortized constant if x is inserted right after the iterator position.

Prototype `iterator insert(const value_type& x);`

Remarks Inserts the element x into the multiset and returns the iterator pointing to the newly inserted element. The function takes $O(\log N)$ time, where N is the number of elements in the multiset.

Prototype `void insert
(const value_type* first,
const value_type* last);`

Remarks Copies of elements in the range $[first, last)$ are inserted into the multiset. This insert member function allows elements from other containers to be inserted into the multiset.

In general, the function takes $O(N \log(\text{size()} + N))$ time, where N is the distance from $first$ to $last$, and $O(N)$ time if the range $[first, last)$ is sorted according to the multiset ordering relation `value_comp()`.

Erase Member Functions *multiset*

multiset::erase

Description Erases one or more multiset elements.

Prototype `void erase(iterator position);`

Remarks Erases the multiset element pointed to by the iterator position. The time taken is amortized constant.

Prototype `size_type erase(const key_type& x);`

Remarks Erases the multiset element with key equal to x (i.e., removes all x 's from the multiset). Returns the number of erased elements. In general, this function takes time proportional to $\log(\text{size}()) + \text{count}(x)$,

where `count(k)` is a multiset member function that returns the number of elements with key equal to `k`.

Prototype `void erase(iterator first, iterator last);`

Remarks The iterators `first` and `last` are assumed to point into the multiset, and all elements in the range `[first,last)` are erased from the multiset. The time taken is $\log(\text{size}()) + N$, where N is the distance from `first` to `last`.

Special Operations multiset

multiset::find

Description Searches for the element `x` in the multiset. If `x` is found, the function returns the iterator pointing to it. Otherwise, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the multiset.

Prototype `iterator find(const key_type& x) const;`

multiset::count

Description Returns the number of elements in the multiset that are equal to `x`. The function takes $O(\log N)$ time, where N is the number of elements in the multiset.

Prototype `size_type count(const key_type& x) const;`

multiset::lower_bound

Description Returns an iterator pointing to the first multiset element whose key is not less than `x`. If no such element is found, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the multiset.

Prototype `iterator lower_bound(const key_type& x) const;`

Containers Library

Template class `map<Key, T>`

`multiset::upper_bound`

Description The `upper_bound` function returns an iterator to the first multiset element whose key is greater than `x`. If no such element is found, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the multiset.

Prototype `iterator upper_bound(const key_type& x) const;`

`multiset::equal_range`

Description This function returns the `pair(lower_bound(x), upper_bound(x))`. The function takes $O(\log N)$ time, where N is the number of elements in the multiset.

Prototype `pair<iterator, iterator> equal_range
(const key_type& x) const;`

Template class `map<Key, T>`

Files `#include <map.h>`

Declaration

```
template
    < class Key,
      class T,
      class Compare = less<Key> >
class map;
```

Description A map is an associative container that supports unique keys of a given type `Key`, and provides for fast retrieval of values of another type `T` based on the stored keys. As in all other STL associative containers, the ordering relation `Compare` is used to order the elements of the map.

Maps are necessary because we often need to associate elements of one type with values of another. For example, consider a telephone directory, which contains associations of names (string types) and phone numbers (integers). A `map<string, long>` can be used to pro-

vide for fast retrieval of a phone-number that corresponds to a given name.

Elements are stored in maps as pairs in which each Key has an associated value of type T. Since maps store only unique keys, each map contains at most one <Key, T> pair for each Key value. It is not possible to associate a single Key with more than one value.

The topics in this section are:

- [“Typedef Declarations map” on page 243](#)
- [“Constructors, Destructors and Related Functions map” on page 246](#)
- [“Comparison Operations map” on page 247](#)
- [“Element Access Member Functions map” on page 248](#)
- [“Insert Member Functions map” on page 250](#)
- [“Erase Member Functions map” on page 251](#)
- [“Special Operations map” on page 251](#)

Typedef Declarations map

Description The following typedef’s are defined in the class `map`.

key_type

Description `key_type` represents the type of the keys in the map.

Definition `typedef Key key_type;`

value_type

Description `value_type` represents the type of the values stored in the map. Since maps store pairs of values, `value_type` is a pair which associates every key (of type Key) with a value of type T.

Definition `typedef pair<const Key, T> value_type;`

Containers Library

Template class `map<Key, T>`

key_compare

Description This is the comparison object type, `Compare`, with which the map is instantiated. It is used to order keys in the map.

Definition `typedef Compare key_compare;`

value_compare

Description A class for comparing objects of `map::value_type` (i.e., objects of type `pair<const Key, T>`), by comparing their keys using `map::key_compare`.

Definition `class value_compare;`

iterator

Description `iterator` is a bidirectional iterator referring to `value_type`. It is guaranteed that there is a constructor for `const_iterator` out of `iterator`.

Definition `typedef iterator;`

const_iterator

Description `Const_iterator` is a constant bidirectional iterator referring to `const value_type`. It is guaranteed that there is a constructor for `const_iterator` out of `iterator`.

Definition `typedef const_iterator;`

pointer

Description The type `value_type*`. (i.e., `pair<const Key, T>*`).

Definition `typedef Allocator<value_type>::pointer pointer;`

reference

Description The type `pair<const Key, T>&` that can be used for storing into `map::value_type` objects.

Definition `typedef Allocator<value_type>::reference
 reference;`

const_reference

Description The type `const Key, T>&` (`const pair<const Key, T>&` for `const` references that can be used for storing into `map::value_type` objects.

Definition `typedef Allocator<value_type>::const_reference
 const_reference;`

size_type

Description `size_type` is an unsigned integral type that can represent the size of any `map` instance.

Definition `typedef size_type;`

difference_type

Description A signed integral type that can represent the difference between any two `map::iterator` objects.

Definition `typedef difference_type;`

reverse_iterator

Description Non-constant reverse bidirectional iterator types.

Definition `typedef reverse_iterator;`

const_reverse_iterator

Description Constant reverse bidirectional iterator types.

Definition `typedef const_reverse_iterator;`

Constructors, Destructors and Related Functions map

Default Constructor

Description The default constructor. Constructs an empty map using the relation `comp` to order the elements.

Prototype `map(const Compare& comp = Compare());`

Overloaded and Copy Constructors

Prototype `map(const map<Key, T, Compare>& x);`

Remarks The map copy constructor. Constructs a map and initializes it with copies of the elements of map `x`.

Prototype `map
 (const value_type* first,
 const value_type* last,
 const Compare& comp = Compare());`

Remarks Constructs an empty map and initializes it with copies of elements in the range `[first,last)`. The ordering relation `comp` is used to order the elements of the map.

Assignment Operator =

Description The map assignment operator. Replaces the contents of the current map with a copy of the parameter map `x`.

Prototype `map<Key, T, Compare>& operator=
 (const map<Key,
 Compare>& x);`

map::swap

Description Swaps the contents of the current map with those of the input map `x`. The current map replaces `x` and vice versa.

Prototype `void swap(map<Key, T, Compare>& x);`

Destructor

Description The map destructor. Returns all allocated storage back to the free store.

Prototype `~map();`

Comparison Operations map

Equality Operator ==

Description Equality operation on maps. Returns true if the sequences of elements in x and y are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==
 (const map<Key,
 Compare>& x,
 const map<Key,
 Compare>& y);`

Less Than Operator <

Description Returns true if x is lexicographically less than y, false otherwise. Takes linear time.

Prototype `bool operator<
 (const map<Key,
 Compare>& x,
 const map<Key,
 Compare>& y);`

Element Access Member Functions map

map::key_comp

Description This function returns the comparison object of the map. The comparison object is an object of class Compare, which represents the ordering relation used to construct the map.

Prototype `key_compare key_comp() const;`

map::value_comp

Description Returns an object of type value_compare constructed out of the comparison object. For maps, value_compare is a class that can be used to compare values stored as pairs in the map.

Prototype `value_compare value_comp() const;`

map::begin

Description Returns an iterator (const_iterator for constant map) that can be used to begin traversing through all locations in the map.

Prototype `iterator begin()
const_iterator begin() const;`

map::end

Description Returns an iterator (const_iterator for constant map) that can be used in a comparison for ending traversal through the map.

Prototype `iterator end()
const_iterator end() const;`

map::rbegin

Description Returns a reverse_iterator (const_reverse_iterator for constant maps), that can be used to begin traversing all locations in the map in the reverse of the normal order.

Prototype `reverse_iterator rbegin();`
 `const_reverse_iterator rbegin() const;`

map::rend

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant maps), that can be used in a comparison for ending reverse-direction traversal through all locations in the map.

Prototype `reverse_iterator rend();`
 `const_reverse_iterator rend() const;`

map::empty

Description Returns true if the map is empty, false otherwise.

Prototype `bool empty() const;`

map::size

Description Returns the number of elements in the map.

Prototype `size_type size() const;`

map::max_size

Description Returns the maximum possible size of the map. The maximum size is simply the total number of elements of type `Key` that can be represented in the memory model used.

Prototype `size_type max_size() const;`

Sub Operator []

Description For a `map<Key, T, Compare>`, this operator returns the element of type `T` that is associated with the key `Key`.

Prototype `reference operator[] (const key_type& x);`

Containers Library

Template class `map<Key, T>`

Remarks The map subscripting operator is different from the subscripting operator of vectors and deques in that if the map contains no element of type `T` associated with Key `x`, then the pair `(x, T())` is inserted into the map.

Insert Member Functions `map`

`map::insert`

Description Inserts one or more elements or values into the map.

Prototype

```
iterator insert
(iterator position,
const value_type& x);
```

Remarks Inserts the value `x` into the map if `x` is not already present in the map. The iterator position is a hint, indicating where the `insert` function should start to search to do the insert. This insertion takes $O(\log N)$ time in general, where N is the number of elements in the set, but is amortized constant if `x` is inserted right after the iterator position.

Prototype

```
pair<iterator, bool> insert
(const value_type& x);
```

Remarks Inserts the value `x` into the map if `x` is not already present in the map. The returned value is a `pair`, whose `bool` component indicates whether the insertion has taken place, and whose iterator component points to the just inserted value in the map, if the insertion takes place, otherwise to the value `x` already present.

NOTE: If Notice, that `x` is a pair of type `pair< Key, T>`. The function takes $O(\log N)$ time, where N is the number of elements in the set.

Prototype

```
void insert
(const value_type* first,
const value_type* last);
```

Remarks Copies of elements in the range [first,last) are inserted into the map. This insert member function allows elements from other containers to be inserted into the map. In general, this insertion takes $O(N\log(\text{size}()+N))$ time, where N is the distance from first to last, and $O(N)$ time if the range [first,last) is sorted according to the map ordering relation `value_comp()`.

Erase Member Functions map

`map::erase`

Description Erases one or more map elements.

Prototype `void erase(iterator position);`

Remarks Erases the map element pointed to by the iterator position. The time taken is amortized constant.

Prototype `size_type erase(const key_type& x);`

Remarks Erases the map element with key equal to x (i.e., removes all pairs whose first element is x from the map). Returns the number of erased elements, which is 1 if x is present in the map, and 0 otherwise. In general, this function takes time proportional to $\log(\text{size}()) + \text{count}(x)$, where `count(k)` is a map member function that returns the number of elements with key equal to k .

Prototype `void erase(iterator first, iterator last);`

Remarks The iterators `first` and `last` are assumed to point into the map, and all elements in the range [first,last) are erased from the map. The time taken is $\log(\text{size}())+N$, where N is the distance from first to last.

Special Operations map

`map::find`

Description Searches the map for an element with Key equal to x . If such an element is found, the function returns the iterator (`const_iterator` for

Containers Library

Template class *map*<Key, T>

constant maps) pointing to it. Otherwise, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the map.

Prototype `iterator find(const key_type& x);`
 `const_iterator find(const key_type& x) const;`

map::count

Description Returns the number of elements in the map with Key equal to x . If an element with Key equal to x has been inserted into the map then this number is always 1; otherwise, it is 0.

Prototype `size_type count(const key_type& x) const;`

map::lower_bound

Description Returns an iterator (`const_iterator` for constant maps) pointing to the first map element whose key is not less than x . If the map contains an element with key not less than x , then the returned iterator points to this element. If such an element is not present in the map, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the map.

Prototype `iterator lower_bound`
 `(const key_type& x);`
 `const_iterator lower_bound`
 `(const key_type& x) const;`

map::upper_bound

Description The `upper_bound` function returns an iterator (`const_iterator` for constant maps) to the first map element whose key is greater than x . If no such element is found, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the map.

Prototype `iterator upper_bound`
 `(const key_type& x)`
 `const_iterator upper_bound`
 `(const key_type& x) const;`

map::equal_range

Description This function returns the pair(lower_bound(x), upper_bound(x)) . The function takes O(log N) time, where N is the number of elements in the map.

Prototype `pair<iterator, iterator> equal_range
 (const key_type& x);
pair<const_iterator, const_iterator> equal_range
 (const key_type& x) const;`

Template class multimap<Key, T>

Files `#include <multimap.h>`

Declaration `template
 < class Key,
 class T,
 class Compare = less<Key> >
class multimap;`

It is assumed that the operators operator== and an operator< are defined on the type Key.

Description A multimap is an associative container that stores allows users to store multiple keys of a given type Key, and to efficiently retrieve values of another type T based on the stored Key. As in all other STL associative containers, the ordering relation Compare is used to order the elements of the map.

Multimaps are necessary because we often need to associate more than one object of type T with each Key.

For example, consider a telephone directory organized by last names. Here we might need to associate different telephone numbers (of type integer) with all names ending in Smith. A multimap<name, integer> can be used to hold this information (where name is an appropriately defined type). Corresponding to each name, there might be several telephone numbers, allowing us to

Containers Library

Template class `multimap<Key, T>`

easily determine the telephone numbers of different people all of whose last names are Smith.

Elements are stored in multimaps as pairs in which each Key has an associated value of type T. Since multimaps allow multiple keys, it is possible to associate a single Key with more than one value (as was done in the example above).

The topics in this section are:

- [“Typedef Declarations multimap” on page 254](#)
- [“Constructors, Destructors and Related Functions multimap” on page 257](#)
- [“Comparison Operations multimap” on page 258](#)
- [“Element Access Member Functions multimap” on page 259](#)
- [“Insert Member Functions multimap” on page 260](#)
- [“Erase Member Functions multimap” on page 261](#)
- [“Special Operations multimap” on page 262](#)

Typedef Declarations multimap

Description The following typedef’s are defined in the class `multimap`.

key_type

Description `key_type` represents the type of the keys in the multimap.

Definition `typedef Key key_type;`

value_type

Description `value_type` represents the type of the values stored in the multimap. Since multimaps store pairs of values, `value_type` is a pair which associates every key (of type `Key`) with a value of type `T`.

Definition `typedef pair<const Key, T> value_type;`

key_compare

Description This is the comparison object type, `Compare`, with which the map is instantiated. It is used to order keys in the map.

Definition `typedef Compare key_compare;`

value_compare

Description A class for comparing objects of `multimap::value_type` (i.e., objects of type `pair<const Key, T>`), by comparing their keys using `multimap::key_compare`.

Definition `class value_compare;`

iterator

Description Iterator is a bidirectional iterator referring to `value_type`. It is guaranteed that there is a constructor for `const_iterator` out of `iterator`.

Definition `typedef iterator,;`

const_iterator

Description `Const_iterator` is a constant bidirectional iterator referring to `const value_type`. It is guaranteed that there is a constructor for `const_iterator` out of `iterator`.

Definition `typedef const_iterator;`

value_type*

Description The type `value_type*` (i.e., `pair<const Key, T>*`).

Definition `typedef Allocator<value_type>::pointer pointer;`

reference

Description The type `pair<const Key, T>&` that can be used for storing into `map::value_type` objects.

Template class `multimap<Key, T>`

const_reference

```
Definition   typedef Allocator<value_type>::const_reference
               const reference;
```

size_type

Definition `typedef size type;`

difference_type

Definition `typedef difference type;`

reverse_iterator

Definition `typedef reverse iterator;`

const reverse_iterator

Definition `typedef const reverse iterator;`

Constructors, Destructors and Related Functions `multimap`

Default Constructor

Description The default constructor. Constructs an empty `multimap` using the `relationcomp` to order the elements.

Prototype `multimap(const Compare& comp = Compare());`

Overloaded and Copy Constructors

Prototype `multimap
(const multimap<Key,
T,
Compare>& x);`

Remarks The `multimap` copy constructor. Constructs a `multimap` and initializes it with copies of the elements of `multimap x`.

```
multimap  
(const value_type* first,  
const value_type* last,  
const Compare& comp = Compare());
```

Remarks Constructs an empty `multimap` and initializes it with copies of elements in the range `[first,last)`. The ordering relation `comp` is used to order the elements of the `multimap`.

Assignment Operator `=`

Description The `multimap` assignment operator. Replaces the contents of the current `multimap` with a copy of the parameter `multimap x`.

Prototype `multimap<Key, T, Compare>& operator=
(const multimap<Key,
Compare>& x);`

Containers Library

Template class *multimap*<Key, T>

multimap::swap

Description Swaps the contents of the current multimap with those of the input multimap x. The current multimap replaces x and vice versa.

Prototype `void swap(multimap<Key, T, Compare>& x);`

Destructor

Description The multimap destructor. Returns all allocated storage back to the free store.

Prototype `~multimap();`

Comparison Operations multimap

Equality Operator ==

Description Equality operation on multimaps. Returns true if the sequences of elements in x and y are element-wise equal (using T::operator==). Takes linear time.

Prototype `bool operator==(const multimap<Key, Compare>& x, const multimap<Key, Compare>& y);`

Less Than Operator <

Description Returns true if x is lexicographically less than y, false otherwise. Takes linear time.

Prototype `bool operator<(const multimap<Key, Compare>& x, const multimap<Key, Compare>& y);`

Element Access Member Functions `multimap`

`multimap::key_comp`

Description This function returns the comparison object of the `multimap`. The comparison object is an object of class `Compare`, which represents the ordering relation used to construct the `multimap`.

Prototype `key_compare key_comp() const;`

`multimap::value_comp`

Description Returns an object of type `value_compare` constructed out of the comparison object. For `multimaps`, `value_compare` is a class that can be used to compare values stored as pairs in the `multimap`.

Prototype `value_compare value_comp() const;`

`multimap::begin`

Description Returns an iterator (`const_iterator` for constant `multimap`) that can be used to begin traversing through all locations in the `multimap`.

Prototype `iterator begin();`
`const_iterator begin() const;`

`multimap::end`

Description Returns an iterator (`const_iterator` for constant `multimap`) that can be used in a comparison for ending traversal through the `multimap`.

Prototype `iterator end();`
`const_iterator end() const;`

`multimap::rbegin`

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant `multimaps`), that can be used to begin traversing all locations in the vector in the reverse of the normal order.

Containers Library

Template class *multimap*<Key, T>

Prototype `reverse_iterator rbegin();`
 `const_reverse_iterator rbegin() const;`

multimap::rend

Description Returns a `reverse_iterator` (`const_reverse_iterator` for constant `multimaps`), that can be used in a comparison for ending reverse-direction traversal through all locations in the `multimap`.

Prototype `reverse_iterator rend();`
 `const_reverse_iterator rend() const;`

multimap::empty

Description Returns true if the `multimap` is empty, false otherwise.

Prototype `bool empty() const;`

multimap::size

Description Returns the number of elements in the `multimap`.

Prototype `size_type size() const;`

multimap::max_size

Description Returns the maximum possible size of the `multimap`. The maximum size is simply the total number of elements of type `Key` that can be represented in the memory model used.

Prototype `size_type max_size() const;`

Insert Member Functions multimap

multimap::Insert

Description Inserts a value or elements into a `multimap` object.

Prototype `iterator insert`
 `(iterator position,`

```
const value_type& x);
```

Remarks Inserts the value `x` into the `multimap` if `x` is not already present in the `multimap`. The iterator position is a hint, indicating where the `insert` function should start to search to do the insert. The insertion takes $O(\log N)$ time in general, where N is the number of elements in the map, but is amortized constant if `x` is inserted right after the iterator position.

Prototype `iterator insert(const value_type& x);`

Remarks Inserts the value `x` into the `multimap` and returns the iterator pointing to the newly inserted value.

NOTE: The value `x` is a pair of the form `pair<const Key, T>`. The insertion takes $O(\log N)$ time, where N is the number of elements in the map.

```
void insert
    (const value_type* first,
     const value_type* last);
```

Remarks Copies of elements in the range `[first,last)` are inserted into the `multimap`. This `insert` member function allows elements from other containers to be inserted into the `multimap`. In general, the time taken for this insertion is $O(N \log(\text{size}() + N))$, where N is the distance from `first` to `last`, and $O(N)$ if the range `[first,last)` is sorted according to the `multimap` ordering relation `value_comp()`.

Erase Member Functions `multimap`

`multimap::erase`

Description Erases one or more elements or values from the `multimap` object.

Prototype `void erase(iterator position);`

Remarks Erases the `multimap` element pointed to by the iterator position. The time taken is amortized constant.

Containers Library

Template class *multimap*<Key, T>

Prototype `size_type erase(const key_type& x);`

Remarks Erases the multimap element with key equal to x (i.e., removes all pairs whose first element is x from the multimap). Returns the number of erased elements.

NOTE: There could be more than one multimap element with key equal to x, since multimaps allow multiple keys.

In general, this function takes time proportional to $\log(\text{size}()) + \text{count}(x)$, where $\text{count}(k)$ is a multimap member function that returns the number of elements with key equal to k.

Prototype `void erase(iterator first, iterator last);`

Remarks The iterators first and last are assumed to point into the multimap, and all elements in the range [first,last) are erased from the multimap. The time taken is $O(\log(\text{size}()) + N)$, where N is the distance from first to last.

Special Operations multimap

multimap::find

Description Searches the multimap for an element with Key equal to x. If such an element is found, the function returns the iterator (const_iterator for constant multimaps) pointing to it. Otherwise, end() is returned. The function takes $O(\log N)$ time, where N is the number of elements in the multimap.

Prototype `iterator find(const key_type& x);`
 `const_iterator find(const key_type& x) const;`

multimap::count

Description Returns the number of elements in the multimap with key equal to x.

Prototype `size_type count(const key_type& x) const;`

`multimap::lower_bound`

Description Returns an iterator (`const_iterator` for constant `multimaps`) pointing to the first `multimap` element whose key is not less than `x`. If the `multimap` contains an element with Key not less than `x`, then the returned iterator points to this single element. If such an element is not present in the `multimap`, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the `multimap`.

Prototype `iterator lower_bound`
 `(const key_type& x) const;`
`const_iterator lower_bound`
 `(const key_type& x) const;`

`multimap::upper_bound`

Description The `upper_bound` function returns an iterator (`const_iterator` for constant `multimaps`) to the first `multimap` element whose key is greater than `x`. If no such element is found, `end()` is returned. The function takes $O(\log N)$ time, where N is the number of elements in the `multimap`.

Prototype `iterator upper_bound`
 `(const key_type& x) const;`
`const_iterator upper_bound`
 `(const key_type& x) const;`

`multimap::equal_range`

Description This function returns the `pair(lower_bound(x), upper_bound(x))`. The function takes $O(\log N)$ time, where N is the number of elements in the `multimap`.

Prototype `pair<iterator,iterator> equal_range`
 `(const key_type& x) const;`
`pair<const_iterator,const_iterator> equal_range`
 `(const key_type& x) const;`

Template class stack

Files `#include <stack.h>`

Declaration `template <class Container> class stack;`

NOTE: It is assumed that the operators `operator==` and `operator<` are defined for objects of type `Container`.

Description A stack is a data structure that allows the following operations: insertion at one end, deletion from the same end, retrieving the value at the end, and testing for emptiness. Thus, stacks provide a “last-in/first-out” service. The element deleted or retrieved is always the last one inserted.

STL provides a stack container adapter, which can be used to instantiate a stack with any container that supports the following operations: `back`, `push_back`, and `pop_back`. In particular, vectors, lists and deques can be used to instantiate stacks.

The topics in this section are:

- [“Public Member Functions stack” on page 264](#)
- [“Comparison Operations stack” on page 265](#)

Public Member Functions stack

stack::empty

Description Returns true if the stack is empty, false otherwise.

Prototype `bool empty() const;`

stack::size

Description Returns the current size of the stack (i.e the number of elements the stack currently holds).

Prototype `size_type size() const;`

stack::top

Description Returns the element at the top of the stack. The stack remains unchanged.

Prototype `value_type& top() const;,
const value_type& top() const;`

stack::push

Description Inserts the value `x` at the top of the stack.

Prototype `void push(const value_type& x);`

stack::pop

Description Removes the element at the top of the stack.

Prototype `void pop();`

Comparison Operations **stack**

Equality Operator ==

Description Equality operation on stacks. Returns true if the sequences of elements in `x` and `y` are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==
 (const stack<container>& x,
 const stack<container>& y);`

Less Than Operator <

Description Returns true if `x` is lexicographically less than `y`, false otherwise. Takes linear time.

Prototype `bool operator<`

```
(const stack<container>& x,  
const stack<container>& y);
```

Template class queue

Files `#include <queue.h>`

Declaration `template <class Container> class queue;`

It is assumed that the operators `operator==` and an `operator<` are defined for objects of type `Container`.

Description A queue is a data structure in which elements are inserted at one end and removed from the opposite end. The order of removal is the same as the order of insertion.

STL provides a queue container adapter, which can be used to instantiate a queue with any container that supports the following operations: `empty`, `size`, `front`, `back`, `push_back`, and `pop_front`. In particular, lists and deques can be used to instantiate queues:

`queue< list<int> >`, declares a queue of integers with an underlying list implementation

`queue< deque<float> >`, declares a queue of floats with an underlying deque implementation.

NOTE: The vectors cannot be used to instantiate queues, since they do not provide a `pop_front` function. This function is not provided for vectors, since it would be highly inefficient for long vectors.

The topics in this section are:

- [“Public Member Functions queue” on page 267](#)
- [“Comparison Operations queue” on page 268](#)

Public Member Functions queue

queue::empty

Description Returns true if the queue is empty, false otherwise.

Prototype `bool empty() const;`

queue::size

Description Returns the current size of the queue (i.e the number of elements the queue currently holds).

Prototype `size_type size() const;`

queue::front

Description Returns the element at the front of the queue. The queue remains unchanged.

Prototype `value_type& front() const;`
`const value_type& front() const;`

queue::back

Description Returns the element at the end of the queue. This is the element that was last inserted into the queue. The queue remains unchanged.

Prototype `value_type& back() const;`
`const value_type& back() const;`

queue::push

Description Adds the element x at the end of the queue.

Prototype `void push(const value_type& x);`

queue::pop

Description Removes the element at the front of the queue.

Containers Library

Template class *priority_queue*

Prototype `void pop()`

Comparison Operations `queue`

Equality Operator `==`

Description Equality operation on queues. Returns true if the sequences of elements in `x` and `y` are element-wise equal (using `T::operator==`). Takes linear time.

Prototype `bool operator==
 (const queue<container>& x,
 const queue<container>& y);`

Less Than Operator `<`

Description Returns true if `x` is lexicographically less than `y`, false otherwise. Takes linear time.

Prototype `bool operator<
 (const queue<container>& x,
 const queue<container>& y);`

Template class `priority_queue`

Files `#include <queue.h>`

Declaration `template <class Container> class priority_queue;`

It is assumed that the operators `operator==` and `operator<` are defined for objects of type `Container`.

Description A priority queue is a container in which the element immediately available for retrieval is the largest of those in the container, for some particular way of ordering the elements. The order of removal is the same as the order of insertion.

STL provides a `priority_queue` container adapter, which can be used to instantiate a `priority_queue` with any container that sup-

ports the following operations: `empty`, `size`, `front`, `push_back`, and `pop_back`. In particular, vectors and deques can be used to instantiate `priority_queues`.

NOTE: Since `priority_queues` involve an ordering on their elements, a comparison function object `comp` needs to be supplied to instantiate a `priority_queue`. For example:

`priority_queue< vector<int>, less<int> >`, declares a `priority_queue` of integers with a vector implementation and using the built-in `<` operation for integers to compare the objects.

`priority_queue< deque<float>, greater<float> >`, declares a `priority_queue` of floats with a deque implementation, using the `>` operation on floats for comparisons.

NOTE: Since `>` is used instead of `<`, the element available for retrieval at any time is actually the smallest element rather than the largest.

The topics in this section are:

- [“Constructors `priority_queue`” on page 269](#)
- [“Public Member Functions `priority_queue`” on page 270](#)
- [“Comparison Operations `priority_queue`” on page 271](#)

Constructors `priority_queue`

Default Constructor

Description	The default constructor. Constructs a <code>priority_queue</code> using a comparison function object of type <code>Compare</code> .
Prototype	<code>priority_queue (const Compare& x = Compare());</code>

Overloaded and Copy Constructors

Prototype `priority_queue
 (const value_type* first,
 const value_type* last,
 const Compare& x = Compare());`

Remarks Constructs a priority queue whose elements are copies of elements in the range [first,last). The default comparison function used is Compare.

Public Member Functions *priority_queue*

priority_queue::empty

Description Returns true if the *priority_queue* is empty, false otherwise.

Prototype `bool empty() const;`

priority_queue::size

Description Returns the current size of the *priority_queue* (i.e the number of elements the *priority_queue* currently holds).

Prototype `size_type size() const;`

priority_queue::top

Description Returns the element at the top of the *priority_queue*. The *priority_queue* remains unchanged.

Prototype `value_type& top() const;
const value_type& top() const;`

priority_queue::push

Description Adds the element *x* to the *priority_queue*.

Prototype `void push(const value_type& x);`

`priority_queue::pop`

Description Removes the element at the top of the `priority_queue`.

Prototype `void pop();`

Comparison Operations `priority_queue`

Equality and comparison operations are not provided for `priority_queue`s.

Containers Library

Template class priority_queue



Iterators Library

This chapter presents the concept of iterators in detail, defining and illustrating the five iterator categories of input iterators, output iterators, forward iterators, bidirectional iterators and random access iterators.

Overview of Iterators

This chapter is a reference guide to the requirements that must be satisfied by a class or a built-in type to be used as an iterator. The – iterators of a particular category include: stream iterator classes, iterator adaptors (reverse iterators and insert iterators).

The principle sections in this chapter are:

- [“Iterator Requirements” on page 275](#)
- [“Stream Iterators” on page 280](#)
- [“Template class istream_iterator” on page 281](#)
- [“Template class ostream_iterator” on page 284](#)
- [“Template class istreambuf_iterator” on page 286](#)
- [“Template class ostreambuf_iterator” on page 290](#)
- [“Template class reverse_bidirectional_iterator” on page 293](#)
- [“Template class reverse_iterator” on page 296](#)
- [“Template class back_insert_iterator” on page 300](#)
- [“Template class front_insert_iterator” on page 302](#)
- [“Template class insert_iterator” on page 303](#)

The following terminology is used in the statement of iterator requirements.

Value type

Iterators are objects that have `operator*` returning a value of some class or built-in type `T` called the `value type` of the iterator.

Distance type

For every iterator type for which equality is defined, there is a corresponding signed integral type called the `distance type` of the iterator.

Past-the-end values

Just as a regular pointer to an array guarantees that there is a valid pointer value pointing past the last element of the array, so for any iterator type there is an iterator value that points past the last element of a corresponding container. These values are called `past-the-end` values.

Dereferenceable values.

Values of the iterator for which `operator*` is defined are called dereferenceable. STL components never assume that past-the-end values are dereferenceable.

Singular values.

Iterators might also have singular values that are not associated with any container. For example, after the declaration of an uninitialized pointer `x` (as with `int* x;`), `x` should always be assumed to have a singular value of a pointer. Results of most expressions are undefined for singular values. The only exception is an assignment of a non-singular value to an iterator that holds a singular value. In this case the singular value is overwritten the same way as any other value. Dereferenceable and past-the-end values are always non-singular.

Reachability

An iterator `j` is called reachable from an iterator `i` if and only if there is a finite sequence of applications of `operator++` to `i` that makes `i == j`. If `i` is reachable from `j`, they refer to the same container.

Ranges

Most of the library's algorithmic templates that operate on containers have interfaces that use ranges. A range is a pair of iterators that serve as beginning and end markers for a computation. A range `[i, i)` is an empty range; in general, a range `[i, j)` refers to the positions in a container starting with the one referred to by `i` up to but not including the one pointed to by `j`. Range `[i, j)` is valid if and only if `j` is reachable from `i`. The result of the application of the algorithms in the library to invalid ranges is undefined.

Mutable versus constant

Iterators can be mutable or constant depending on whether the result of `operator*` behaves as a reference or as a reference to a constant. Constant iterators do not satisfy the requirements for output iterators.

NOTE: For all iterator operations that are required in each category, the computing time requirement is `constant time` (amortized). For this reason, we will not mention computing times separately in any of the following sections on requirements.

Iterator Requirements

This section discusses the requirements for all five types of iterators. The topics in this section are:

- [“Input Iterator Requirements” on page 276](#)
- [“Output Iterator Requirements” on page 277](#)

- [“Forward Iterator Requirements” on page 278](#)
- [“Random Access Iterator Requirements” on page 279](#)
- [“Bidirectional Iterator Requirements” on page 279](#)

In this and the following four requirements sections, for each iterator type X we will assume

- a and b denote values of type X ,
- n denotes a value of the distance type for X ,
- r denotes a value of $X\&$,
- t denotes a value of value type T , and
- u , tmp , and m denote identifiers.

Input Iterator Requirements

A class or a built-in type X satisfies the requirements of an input iterator for the value type T if and only if the expressions described below are valid.

$X(a)$ The copy constructor, which makes $X(a) == a$. A destructor is assumed.

$X\ u(a);$ $X\ u = a;$ Either of these results in $u == a$.

$a == b$ The return type must be convertible to `bool`, and `==` must be an equivalence relation.

$a != b$ The return type must be convertible to `bool`, and the result must be the same as `!(a == b)`.

$*a$ The return type must be convertible to T . It is assumed that a is dereferenceable. If $a == b$, then it must be the case that $*a == *b$.

$++r$ The return type must be convertible to `const X&`. It is assumed that r is dereferenceable. The result is that r is either dereferenceable or r is the past-the-end value of the container, and `&r == &++r`.

$r++$ The return type must be convertible to `const X&`. The result must be the same as that of `{ X tmp = r; ++r; return tmp; }`

$*++r$ $*r++$ The return type must be convertible to T .

NOTE: For input iterators, `a == b` does not imply `++a == ++b`. The main consequence is that algorithms on input iterators should be single pass algorithms; i.e., they should never attempt to copy the value of an iterator and use it to pass through the same position twice. Furthermore, value type `T` is not required to be an lvalue type, so algorithms on input iterators should not attempt to assign through them. (Forward iterators remove these restrictions.)

Output Iterator Requirements

A class or a built-in type `X` satisfies the requirements of an output iterator for the value type `T` if and only if the expressions described below are valid.

`X(a); *a = t` is equivalent to `*X(a) = t`. Further, a destructor is assumed in this case.

`X u(a); X u = a;` The result is that `u` is a copy of `a`.

NOTE: However that equality and inequality are not necessarily defined, and algorithms should not attempt to use output iterators to pass through a position twice (i.e., should be single-pass).

`*a = t` `t` is assigned through the iterator to the position to which `a` refers. The result of this operation is not used.

`++r` The return type must be convertible to `const X&`. It is assumed that `r` is dereferenceable on the left hand side of an assignment. The result is that `r` is either dereferenceable on the left hand side of an assignment or `r` is the past-the-end value of the container, and `&r == &++r`.

`r++` The return type must be convertible to `const X&`. The result must be the same as that of `{ X tmp = r; ++r; return tmp; }`

`*++r` `*r++` The return type must be convertible to `T`.

NOTE: The only valid use of operator* on output iterators is on the left hand side of an assignment statement. As with input it-

erators, algorithms that use output iterators should be single-pass. Equality and inequality operators might not be defined. Algorithms that use output iterators can be used with ostream as the destination for placing data via the `ostream_iterator` class as well as with insert iterators and insert pointers.

Forward Iterator Requirements

A class or a built-in type `X` satisfies the requirements of a forward iterator for the value type `T` if and only if the expressions described below are valid.

`X u;` The resulting value of `u` might be singular. A destructor is assumed.

`X(); X()` `X()` might be singular.

`X(a);` The result is required to satisfy `a == X(a)`.

`X u(a); X u = a;` The result is required to satisfy `u == a`.

`a == b` The return type must be convertible to `bool`, and `==` must be an equivalence relation.

`a != b` The return type must be convertible to `bool`, and the result must be the same as `!(a == b)`.

`r = a` The return type is `X&` and the result must satisfy `r == a`.

`*a` The return type must be convertible to `T`. It is assumed that `a` is dereferenceable. If `a == b`, then it must be the case also that `*a == *b`. If `X` is mutable, `*a = t` is valid.

`++r` The return type must be convertible to `X&`. It is assumed that `r` is dereferenceable, and the result is that `r` is either dereferenceable or is the past-the-end value, and `&r == &++r`. Moreover, `r == s` and `r` is dereferenceable implies `++r == ++s`.

`r++` The return type must be convertible to `const X&`. The result must be the same as that of `{ X tmp = r; ++r; return tmp; }`

`*++r` `*r++` The return type must be convertible to `T`.

NOTE: The condition that `a == b` implies `++a == ++b` (which is not true for input or output iterators) and the removal of the restrictions on the number of the assignments through the iterator (which applies to output iterators) allows the use of multi-pass one-directional algorithms with forward iterators.

Bidirectional Iterator Requirements

A class or a built-in type `X` satisfies the requirements of a bidirectional iterator for the value type `T` if and only if the expressions described below are valid, in addition to the requirements that are described in the previous section, forward iterators.

--r The return type is `X&`. It is assumed that there exists `s` such that `r == ++s`, and the result is `r` refers to the same position as `s`, is dereferenceable and `&r == &--r`. Both of the following properties must hold: `--(++r) == r`, and if `--r == --s` implies that `r == s`.

r-- The return type must be convertible to `const X&`.

***r--** The return type must be convertible to `T`.

Random Access Iterator Requirements

A class or a built-in type `X` satisfies the requirements of a random access iterator for the value type `T` if and only if the expressions described below are valid, in addition to the requirements of a bidirectional iterator type.

r += n The return type must be `X&`. The result must be the same as would be computed by

```
{ Distance m = n;
  if (m >= 0)
    while (m-->) ++r;
  else
    while (m++>) --r;
  return r;}
```

but is computed in constant time.

a + n n + a The return type must be *X*. The result must be the same as would be computed by

`{ X tmp = a; return tmp += n; }.`

r -= n The return type must be *X&*. The result must be the same as would be computed by `r += -n`.

a - n The return type must be *X*. The result must be the same as would be computed by `{ X tmp = a; return tmp -= n; }.`

b - a The return type must be *Distance*. It is assumed that there exists a value *n* of the type *Distance* such that `a + n == b`; the result returned is *n*.

a[n] The return type must be convertible to *T*.

a < b The return type must be convertible to *bool*, and `<` must be a total ordering relation.

a > b The return type must be convertible to *bool*, and `>` must be a total ordering relation opposite to `<`.

a >= b The return type is convertible to *bool*, and the result must be the same as that of `!(a < b)`.

a <= b The return type is convertible to *bool*, and the result must be the same as that of `!(b < a)`.

Stream Iterators

The library provides *stream iterators*, defined by template classes, to allow algorithms to work directly with input/output streams. The *istream_iterator* class defines input iterator types and the *ostream_iterator* class defines output iterator types. For example, the following code fragment:

```
istream_iterator<int> end_of_stream;  
partial_sum_copy(istream_iterator<int>(cin),  
end_of_stream, ostream_iterator<int>(cout, "\n"));
```

reads a file containing integers from the input stream *cin*, and prints the partial sums to *cout*, separated by newline characters.

The two stream iterators are:

- [“Template class *istream_iterator*” on page 281](#)

- [“Template class `ostream_iterator`” on page 284](#)

The `istream_iterators` are used to read values from the input stream for which they are constructed. The `ostream_iterators`, are used to write values into the output stream for which they are constructed.

Template class `istream_iterator`

Files `#include <iterator.h>`

Description An `istream_iterator<T>` reads (using `operator>>`) successive elements of type `T` from the input stream for which it was constructed. Each time `++` is used on a constructed `istream_iterator<T>` object, the iterator reads and stores a value of `T`. The end of stream value is reached when `operator void*()` on the stream returns `false`. In this case, the iterator becomes equal to the `end-of-stream` iterator value. This end-of-stream value can only be constructed using the constructor with no arguments: `istream_iterator<T>()`. Two end-of-stream iterators are always equal. An end-of-stream iterator is not equal to a non-end-of-stream iterator. Two non-end-of-stream iterators are equal when they are constructed from the same stream.

One can only use `istream_iterators` to read values; it is impossible to store anything into a position referred to by an `istream_iterator` value.

The main peculiarity of `istream` iterators is that fact that `++` operators are not equality-preserving; that is, `i == j` does not guarantee that `++i == ++j`. Every time `++` is used a new value is read from the associated `istream`. The practical consequence of this fact is that `istream` iterators can only be used with single-pass algorithms.

Prototype `template`
 `template`
 `< class T,`
 `class charT,`
 `class traits = char_traits<charT>`

Iterators Library

Template class istream_iterator

```
class Distance = ptrdiff_t >
class istream_iterator: input_iterator<T,Distance>;
```

The topics in this section are:

- [“Constructor istream_iterator” on page 282](#)
- [“Public Member Functions istream_iterator” on page 283](#)
- [“Comparison Operations istream_iterator” on page 283](#)

Constructor istream_iterator

Default Constructor

Description Constructs the end-of-stream iterator value.

NOTE: The two end-of-stream iterators are always equal.

Prototype `istream_iterator();`

Overloaded and Copy Constructors

Prototype `istream_iterator
(istream& s);`

Remarks Constructs an `istream_iterator<T>` object that reads values from the input stream `s`.

```
istream_iterator  
(const istream_iterator<T,  
    Distance>& x);
```

Remarks Copy constructor.

Destructor

Prototype `~istream_iterator();`

Public Member Functions istream_iterator

Dereferencing Operator *

Description Dereferencing operator. By returning a reference to `const T`, it ensures that it cannot be used to write values to the input stream for which the iterator is constructed.

Prototype `const T& operator*() const;`

Incrementation Operator ++

Description Incrementation operators.

Prototype `istream_iterator<T, Distance>& operator++();`

Remarks This operator reads and stores a value of `T` each time it is called.

Prototype `istream_iterator <T, Distance> operator++(int);`

Remarks This operator reads and stores `x` values of `T` each time it is called.

Comparison Operations istream_iterator

Equality Operator ==

Description Equality operator. Two end-of-stream iterators are always equal. An end-of-stream iterator is not equal to a non-end-of-stream iterator. Two non-end-of-stream iterators are equal when they are constructed from the same stream.

Prototype

```
template
    < class T,
      class Distance>
bool operator==
    (const istream_iterator<T,Distance>& x,
     const istream_iterator<T,Distance>& y);
```

Template class ostream_iterator

Files `#include <iterator.h>`

Description An `ostream_iterator<T>` object writes (using `operator<<`) successive elements onto the output stream for which it was constructed. If it is constructed with `char*` as a constructor argument, then this `delimiter` string is written to the stream after each `T` value is written.

Prototype

```
template
    < class T,
      class charT,
      class traits = char_traits<charT> >
class ostream_iterator : public output_iterator;
```

Remarks It is not possible to read a value of the output iterator. It can only be used to write values out to an output stream for which it is constructed.

The topics in this section are:

- [“Constructor ostream_iterator” on page 284](#)
- [“Public Member Functions ostream_iterator” on page 285](#)

Constructor ostream_iterator

Default Constructor

Description Constructs an iterator that can be used to write to the output stream `s`.

Prototype `ostream_iterator(ostream& s);`

Overloaded and Copy Constructors

Description Constructs an iterator that can be used to write to the output stream `s`. The character string `delimiter` is written out after every value (of type `T`) written to `s`.

Prototype `ostream_iterator(ostream& s, const char* delim);`
`ostream_iterator(const ostream_iterator<T>& x);`

Remarks Copy constructor.

Destructor

Prototype `~ostream_iterator ();`

Public Member Functions ostream_iterator

Dereferencing Operator *

Description Dereferencing operator. An assignment `*o = t` through an output iterator `o` causes `t` to be written to the output stream and the stream pointer advanced in preparation for the next write.

Prototype `ostream_iterator<T>& operator*();`

Assignment Operator =

Description Assignment operator. Replaces the current iterator with a copy of the iterator `x`.

Prototype `ostream_iterator<T>& operator=`
`(const ostream_iterator<T>& x);`

Incrementation Operator ++

Description These operators are present to allow ostream iterators to be used with algorithms that both assign through an output iterator and ad-

Iterators Library

Template class *istreambuf_iterator*

vance the iterator; they actually do nothing, since assignments through the iterator advance the stream pointer also.

Prototype `ostream_iterator <T>& operator++();`
 `ostream_iterator <T> operator++(int x);`

Template class *istreambuf_iterator*

Declaration `template`
 `<class charT,`
 `class traits = char_traits<charT> >`
 `class istreambuf_iterator;`

Description The template class *istreambuf_iterator* reads successive characters from the *streambuf* for which it was constructed. *operator** provides access to the current input character, if any. Each time *operator++* is evaluated, the iterator advanced to the next input character. If the end of stream is reached (*streambuf::sgetc ()* returns *traits::eof()*), the iterator becomes equal to the end of stream iterator value. The default constructor *istreambuf_iterator ()* and the constructor *istreambuf_iterator(0)* both construct an end of stream iterator object suitable for use as an end-of-range.

The result of *operator* ()* on an end of stream is undefined. For any other iterator value a *char_type* is returned. It is impossible to assign a character via an input iterator. In input iterators, *++* operators are not equality preserving, that is, *i == j* does not guarantee at all that *++i == ++j*. Every time *++* is evaluated a new value is used. A practical consequence of this fact is that an *istreambuf_iterator* object can be used only for one-pass algorithms. Two end of stream iterators are always equal. An end of stream iterator is not equal to a non-end of stream iterator.

The topics in this section are:

- [“Typedef Declarations *istreambuf_iterator*” on page 287](#)
- [“Placeholder proxy *istreambuf_iterator*” on page 287](#)
- [“Constructor *istreambuf_iterator*” on page 288](#)

- [“Operators istreambuf_iterator” on page 288](#)

Typedef Declarations `istreambuf_iterator`

Description The following typedef’s are defined in the class `istreambuf_iterator`.

`char_type`

Prototype `typedef charT char_type;`

`traits_type`

Prototype `typedef traits traits_type;`

`streambuf`

Prototype `typedef basic_streambuf<charT, traits>
streambuf;`

`istream`

Prototype `typedef basic_istream<charT,
traits istream;`

Placeholder proxy `istreambuf_iterator`

Class `istreambuf_iterator<charT, traits>::proxy` provides a temporary placeholder as the return value of the post-increment operator (`operator++`). It keeps the character pointed to by the previous value of the iterator for some possible future access to get the character.

Constructor *istreambuf_iterator*

Default Constructor

Description Constructs an end-of-stream iterator.

Prototype `istreambuf_iterator ();`

Overloaded and Copy Constructor

Description

Prototype `istreambuf_iterator
(basic_istream<charT, traits>& s);`

Remarks This constructs the *istream_iterator* pointing to the *basic_streambuf* object `*(s.rdbuf())`.
`istreambuf_iterator (const proxy& p);`

Remarks This constructs the *istreambuf_iterator* pointing to the *basic_streambuf* object related to the proxy object *p*.

Operators *istreambuf_iterator*

Dereferencing Operator *

Description This operator extracts one character pointed to by the *streambuf* *sbuf_*.

Prototype `charT operator* ();`

Incrementation Operator ++

Description These operators advances the iterator.

Prototype `istreambuf_iterator<charT, traits>&
istreambuf_iterator<charT, traits>::operator++`

());

Remarks This operator advances the iterator and returns the result.

Prototype

```
proxy istreambuf_iterator
    <charT,
    traits>::operator++
    (int);
```

Remarks This operator advances the iterator and returns the proxy object keeping the character pointed to by the previous iterator.

istream_iterator::equal

Description This function returns true if and only if both iterators are either at end-of-stream, or are the end-of-stream value, regardless of what streambuf they iterator over.

Prototype

```
bool equal
    (istreambuf_iterator<charT, traits>& b);
```

istream_iterator::iterator_category

Description Returns the category of the iterator s.

Prototype

```
input_iterator_tag iterator_category
    (const istreambuf_iterator& s);
```

Equality Operator ==

Description `operator==` returns `a.equal (b)`.

Prototype

```
template
    < class charT,
    class traits >
bool operator==
    (istreambuf_iterator<charT, traits>& a,
    istreambuf_iterator<charT, traits>& b);
```

Not Equal Operator !=

Description This returns `!a.equal(b)`.

Prototype

```
template
    < class charT,
      class traits >
bool operator!=
    (ostreambuf_iterator<charT,
      traits>& a,
     ostreambuf_iterator<charT, traits>& b);
```

Template class ostreambuf_iterator

Declaration

```
template
    <class charT,
      class traits = char_traits<charT> >
class ostreambuf_iterator;
```

Description The template class `ostreambuf_iterator` writes successive characters onto the output stream from which it was constructed. It is not possible to get a value out of the output iterator. Two output iterators are equal if they are constructed with the same output streambuf.

The topics in this section are:

- [“Typedef Declarations ostreambuf_iterator” on page 290](#)
- [“Constructor ostreambuf_iterator” on page 291](#)
- [“Operators ostreambuf_iterator” on page 292](#)

Typedef Declarations ostreambuf_iterator

Description The following typedef's are defined in the class `ostreambuf_iterator`.

char_type

Prototype `typedef charT char_type;`

traits_type

Prototype `typedef traits traits_type;`

streambuf

Prototype `typedef basic_streambuf<charT, traits>
 streambuf;`

ostream

Prototype `typedef basic_ostream<charT, traits> ostream;`

Constructor ostreambuf_iterator

Default Constructor

Description Constructs an iterator with `sbuf_` set to 0.

Prototype `ostreambuf_iterator ();`

Overloaded and Copy Constructors

Prototype `ostreambuf_iterator (ostream& s);`

Remarks This constructs the `ostream_iterator` pointing to the `basic_streambuf` object `*(s.rdbuf())`.

Prototype `ostreambuf_iterator (streambuf* s);`

Remarks This constructs the `ostreambuf_iterator` pointing to the `basic_streambuf` object `s`.

Operators *ostreambuf_iterator*

Dereferencing Operator *

Description This operator returns `*this`.

Prototype `ostreambuf_iterator<charT, traits>& operator*
();`

ostreambuf_iterator::equal

Description This function returns true if `sbuf_ == b.sbuf_`.

Prototype `bool equal
(ostreambuf_iterator<charT, traits>& b);`

ostreambuf_iterator::iterator_category

Description Returns `output_iterator_tag()`.

Prototype `output_iterator_tag iterator_category
(const ostreambuf_iterator& s);`

Equality Operator ==

Description `operator==` returns `a.equal (b)`.

Prototype `template <class charT, class traits>
bool operator==
(ostreambuf_iterator<charT,
traits>& a,
ostreambuf_iterator<charT,
traits> & b);`

Not Equal Operator !=

Description This returns `!a.equal (b)`.

Prototype `template`
 `< class charT,`
 `class traits >`
 `bool operator!=`
 `(ostreambuf_iterator<charT,`
 `traits>& a,`
 `ostreambuf_iterator<charT,`
 `traits>& b);`

Template class `reverse_bidirectional_iterator`

Bidirectional iterators and random access iterators have a corresponding reverse iterator adaptor. These adaptors produce iterators that can be used for traversing through a data structure in the opposite of the normal direction. This section describes `reverse_bidirectional_iterator` and the following section describes `reverse_iterator` (for reversing a random access iterator).

The `reverse_bidirectional_iterator` adaptor takes a bidirectional iterator and produces a new bidirectional iterator for traversal in the opposite direction.

Declaration A template class for reverse bidirectional iterators.

Prototype `template`
 `< class BidirectionalIterator,`
 `class T,`
 `class Reference = T&,`
 `class Distance = ptrdiff_t >`
 `class reverse_bidirectional_iterator : public`
 `bidirectional_iterator<T, Distance>`

The topics in this section are:

- [“Constructor `reverse_bidirectional_iterator`” on page 294](#)
- [“Public Member Functions `reverse_bidirectional_iterator`” on page 294](#)

Constructor `reverse_bidirectional_iterator`

Default Constructor

Prototype `reverse_bidirectional_iterator();`

Overloaded Constructors

Prototype `explicit reverse_bidirectional_iterator
 (BidirectionalIterator x);`

Remarks This constructor initializes the value of `current` with `x`.

Public Member Functions `reverse_bidirectional_iterator`

`reverse_bidirectional_iterator::base`

Prototype `BidirectionalIterator base();`

Dereferencing Operator `*`

Prototype `Dereference operator *();`

Incrementation Operator `++`

Prototype `reverse_bidirectional_iterator
 < BidirectionalIterator,
 T,
 Reference,
 Distance >&
operator ++();`

Prototype `reverse_bidirectional_iterator
 < BidirectionalIterator,
 T,
 Reference,`

```
Distance >
operator ++(int);
```

Decrementation Operator --

Prototype `reverse_bidirectional_iterator`
 `< BidirectionalIterator,`
 `T,`
 `Reference,`
 `Distance>&`
 `operator --();`

Prototype `reverse_bidirectional_iterator`
 `<BidirectionalIterator,`
 `T,`
 `Reference,`
 `Distance>`
 `operator --(int);`

Equality Operator ==

Description Return a true if the `reverse_bidirectional_iterator` `x` is equal to `reverse_bidirectional_iterator` `y`.

Prototype

```
template
< class BidirectionalIterator, class T, class Distance >
bool operator ==
(const reverse_bidirectional_iterator
  <BidirectionalIterator, T, Reference, Distance >& x,
const reverse_bidirectional_iterator
  <BidirectionalIterator, T, Reference, Distance>& y);
```

Template class reverse_iterator

The `reverse_iterator` adaptor takes a random access iterator and produces a new random access iterator for traversal in the opposite direction.

Description A template class for reverse iterators.

Prototype

```
template
    < class RandomAccessIterator,
      class T,
      class Reference = T&,
      class Distance = ptrdiff_t >
class reverse_iterator : public
    random_access_iterator <T, Distance>;
```

The topics in this section are:

- [“Constructor reverse_iterator” on page 296](#)
- [“Public Member Functions reverse_iterator” on page 297](#)

Constructor reverse_iterator

Default Constructor

Prototype `reverse_iterator();`

Overloaded and Copy Constructors

Description This constructor initializes the value of current with `x`.

Prototype

```
explicit reverse_iterator
    (RandomAccessIterator x);
```


Public Member Functions reverse_iterator

reverse_iterator::base

Prototype RandomAccessIterator base();

Dereferencing Operator *

Prototype Reference operator *();

Incrementation Operator ++

Prototype reverse_iterator
 < RandomAccessIterator,
 T,
 Reference,
 Distance >&
operator ++();

Prototype reverse_iterator
 < RandomAccessIterator,
 T,
 Reference,
 Distance >
operator ++(int);

Decrementation Operator --

Prototype reverse_iterator
 < RandomAccessIterator,
 T,
 Reference,
 Distance>&
operator --();

Prototype reverse_iterator<RandomAccessIterator, T,
 Reference, Distance> operator --(int);

Add Operator +

Prototype `reverse_iterator`
 `< RandomAccessIterator,`
 `T,`
 `Reference,`
 `Distance >`
`operator+`
 `(Distance n) const;`

Add & Assign Operator +=

Prototype `reverse_iterator`
 `< RandomAccessIterator,`
 `T,`
 `Reference,`
 `Distance >&`
`operator +=`
 `(Distance n);`

Minus Operator -

Prototype `reverse_iterator`
 `< RandomAccessIterator,`
 `T,`
 `Reference,`
 `Distance >`
`operator -`
 `(Distance n) const;`

Minus & Assign Operator -=

Prototype `reverse_iterator`
 `< RandomAccessIterator,`
 `T,`
 `Reference,`
 `Distance >&`
`operator -=`

(Distance n);

Subset Operator []

Prototype Reference operator[] (Distance n);

Equality Operator ==

Prototype

```
template
< class RandomAccessIterator,
  class T,
  class Reference,
  class Distance >
bool operator ==
(const reverse_iterator
  <RandomAccessIterator, T, Reference, Distance>& x,
const reverse_iterator
  < RandomAccessIterator, T, Reference, Distance>& y);
```

Less Than Operator <

Prototype

```
template
< class RandomAccessIterator,
  class T, class Reference,
  class Distance >
bool operator <
(const reverse_iterator
  < RandomAccessIterator,T,Reference, Distance >& x,
const reverse_iterator
  < RandomAccessIterator,T,Reference, Distance >& y);
```

Minus Operator -

Prototype

```
template
< class RandomAccessIterator,
  class T,
  class Reference,
  class Distance >
Distance operator -
(const reverse_iterator
  < RandomAccessIterator, T, Reference, Distance >& x,
const reverse_iterator
  < RandomAccessIterator, T, Reference, Distance >& y);
```

Add Operator +

Prototype

```
template
< class RandomAccessIterator,
  class T,
  class Reference,
  class Distance >
Reverse_iterator< RandomAccessIterator,T, Reference, Distance >
operator +
(Distance n,
const reverse_iterator
  <RandomAccessIterator,T,Reference,Distance>& x);
```

Template class back_insert_iterator

Insert iterators are provided in the STL to deal with the problem of insertion similar to writing in an array. These iterator are iterator adaptors. There are three types of insert iterator adaptors. They are `back_insert_iterator`, `front_insert_iterator` and `insert_iterator`. In this section, we shall study the interface of these three iterator adaptors.

Description A template class for back insert iterators.

Prototype

```
template
    < class Container >
class back_insert_iterator : public
output_iterator;
```

The topics in this section are:

- [“Constructor back_insert_iterator” on page 301](#)
- [“Public Member Functions back_insert_iterator” on page 301](#)

Constructor back_insert_iterator

Copy Constructor

Prototype

```
explicit back_insert_iterator(Container& x);
```

Public Member Functions back_insert_iterator

Assignment Operator =

Prototype

```
back_insert_iterator
    < Containe r>&
operator=
    (const typename
    Container::value_type& value);
```

Dereferencing Operator *

Prototype

```
back_insert_iterator<Container>& operator*();
```

Incrementation Operator ++

Prototype

```
back_insert_iterator<Container>& operator++();
```

Prototype

```
back_insert_iterator<Container> operator++(int);
```

`back_insert_iterator::back_inserter`

Prototype `template`
 `< class Container >`
`back_insert_iterator`
 `< Container > back_inserter(Container& x);`

Template class `front_insert_iterator`

Description A template class for front insert iterators.

Prototype `template`
 `< class Container >`
`class front_insert_iterator : public`
 `output_iterator;`

The topics in this section are:

- [“Constructor `front_insert_iterator`” on page 302](#)
- [“Public Member Functions `front_insert_iterator`” on page 302](#)

Constructor `front_insert_iterator`

Copy Constructor

Prototype `explicit front_insert_iterator(Container& x);`

Public Member Functions `front_insert_iterator`

Assignment Operator `=`

Prototype `front_insert_iterator<Container>& operator =`
 `(const typename Container::value_type& value);`

Dereferencing Operator `*`

Prototype `front_insert_iterator<Container>& operator*();`

Incrementation Operator ++

Prototype `front_insert_iterator<Container>& operator++();`

Prototype `front_insert_iterator
 < Container >
operator++(int);`

front_insert_iterator::front_inserter

Prototype `template
 < class Container >
front_insert_iterator< Container >
 front_inserter(Container& x);`

Template class insert_iterator

Description A template class for insert iterators

Prototype `template
 < class Container >
class insert_iterator : public output_iterator;`

The topics in this section are:

- [“Constructor insert_iterator” on page 303](#)
- [“Public Member Function insert_iterator” on page 304](#)

Constructor insert_iterator

Copy Constructor

Prototype `insert_iterator
 (Container& x,
 typename Container::iterator i);`

Public Member Function `insert_iterator`

Assignment Operator `=`

Prototype `insert_iterator< Container >& operator =
 (const typename
 Container::value_type& value);`

Dereferencing Operator `*`

Prototype `insert_iterator< Container >& operator*();`

Incrementation Operator `++`

Prototype `insert_iterator< Container >& operator++();`

Prototype `insert_iterator<Container> operator++(int);`

`insert_iterator::inserter`

Prototype `template
 < class Container,
 class Iterator >
insert_iterator< Container > inserter
 (Container& x, Iterator i);`



Algorithms Library

This chapter discusses the algorithms library. These algorithms cover sequences, sorting, and numerics.

Overview of the Algorithms Library

The algorithms library contains 32 distinct algorithms, divided into four main categories:

- [“Non Mutating Sequence Algorithms” on page 307](#)
- [“Mutating Sequence Algorithms” on page 314](#)
- [“Sorting and Related Algorithms” on page 331](#)
- [“Generalized Numeric Algorithms” on page 356](#)

All of the library algorithms are generic, in the sense that they can operate on a variety of data structures. The algorithms are not directly parameterized in terms of data structures. Instead, they are parameterized by iterator types. This allows the algorithms to work with user-defined data structures, as long as these data structures have iterator types satisfying the assumptions of the algorithms.

The remaining topics in this overview are:

- [“In-place and Copying Versions” on page 305](#)
- [“Algorithms with Predicate Parameters” on page 306](#)
- [“Binary Predicates” on page 306](#)

In-place and Copying Versions

Both in-place and copying versions are provided for certain algorithms. The decision whether to include a copying version is based on complexity considerations.

Algorithms Library

Overview of the Algorithms Library

For example, `sort_copy` is not provided, since the cost of sorting is much more significant, and users might as well do `copy` followed by `sort`. On the other hand,

`replace_copy` is provided, since the cost of copying is greater than the cost of replacing a value in a container.

Whenever, a copying version is provided for algorithm, it is called `algorithm_copy`.

Finally, algorithms that take predicates end with the suffix `_if` (which follows the suffix `_copy`, for copying algorithms).

Algorithms with Predicate Parameters

Several algorithms accept function objects as parameters. These function objects are applied to the result of dereferencing the iterators accepted by the algorithm, with the requirement that the resulting value be testable as `true`. A unary `Predicate` class is used in the definition of such algorithms.

In other words, if an algorithm takes a `Predicate pred` as its argument, and `first` as its iterator argument, it should work correctly in the construct

```
if (pred(*first)) {.....}
```

The function object `pred` is assumed not to apply any non-constant function through the dereferenced iterator.

Binary Predicates

A `BinaryPredicate` class is used whenever an algorithm expects a function object that when applied to the result of dereferencing two corresponding iterators or to dereferencing an iterator and a type `T` (where `T` is part of the function signature), returns a value testable as `true`.

In other words, if an algorithm takes
`BinaryPredicate binary_pred`

as its argument and `first1` and `first2` as its iterator arguments, it should work correctly in the construct

```
if (binary_pred(*first1, *first2)) {...}
```

`BinaryPredicate` always takes the first iterator type as its first argument. That is, in those cases when `T value` is part of the function signature, `binary_pred` can be used as follows:

```
if (binary_pred(first, value)) {....}
```

It is expected that `binary_pred` will not apply any non-constant function through the dereferenced iterators.

Non Mutating Sequence Algorithms

Non-mutating sequence algorithms are those that do not directly modify the containers they operate on. The algorithms in this category are:

- [“for_each” on page 307](#)
- [“find_if” on page 308](#)
- [“adjacent_find” on page 309](#)
- [“count” on page 310](#)
- [“count_if” on page 310](#)
- [“mismatch” on page 311](#)
- [“equal” on page 312](#)
- [“search” on page 313](#)

Each of these algorithms, except `for_each`, has two versions: a “normal” version, which uses `operator<` or `operator==` for comparisons, and a “predicate” version, which uses an appropriate function object for comparisons.

for_each

Description	The <code>for_each</code> algorithm applies a specified function to each element of the input container.
--------------------	--

Algorithms Library

Non Mutating Sequence Algorithms

Prototype `template
 < class InputIterator,
 class Function >
Function for_each
 (InputIterator first,
 InputIterator last,
 Function f);`

Remarks The function `f` is applied to the result of dereferencing every iterator in the range `[first, last)`. It is assumed that the function `f` does not apply any non-constant function through the dereferenced iterator. `f` is applied exactly `last-first` times. If `f` returns a result, the result is ignored.

Complexity Time complexity is linear. If `n` is the size of `[first, last)`, then exactly `n` applications of `f` are made. Space complexity is constant.

find

Description The first version of the algorithm traverses the iterators `(first, last]` and returns the first iterator `i` such that `*i == value`. In either case, if such an iterator is not found then the iterator `last` is returned.

Prototype `template
 < class InputIterator,
 class T >
InputIterator find
 (InputIterator first,
 InputIterator last,
 const T& value);`

find_if

Description The second version returns the first iterator `i` such that `pred(*i) == true`. In either case, if such an iterator is not found then the iterator `last` is returned.

Prototype `template`

```
    < class InputIterator,
      class Predicate >
InputIterator find_if
    (InputIterator first,
     InputIterator last,
     Predicate pred);
```

Complexity Time complexity is linear. The number of applications of operator `!=` (or `pred`, for `find_if`) is the size of the range `[first, last)`. Space complexity is constant.

adjacent_find

Description The `adjacent_find` algorithm returns an iterator `i` referring to the first consecutive duplicate element in the range `[first, last)`, or `last` if there is no such element. By consecutive duplicate, it is meant that an element is equal to the element immediately following it in the range.

Prototype

```
template
    < class InputIterator >
InputIterator adjacent_find
    (InputIterator first,
     InputIterator last);
template
    < class InputIterator,
      class BinaryPredicate >
InputIterator adjacent_find
    (InputIterator first,
     InputIterator last,
     BinaryPredicate binary_pred);
```

Remarks Comparisons are done using `operator==` in the first version of the algorithm and a function object `binary_pred` in the second version.

Complexity Time complexity is linear. The number of comparisons done is the size of the range `[first, i)`. Space complexity is constant.

count

Description The count algorithm adds the number of elements in the range `[first, last)` that are equal to `value`, and places the result into the reference argument `n`.

Prototype

```
template
    < class InputIterator,
      class T,
      class Size >
void count(InputIterator first,
          InputIterator last,
          const T& value,
          Size& n);
```

Remarks Count must store the result into a reference argument since it cannot deduce the size type from the built-in iterator types, such as `int*`.

Complexity Time complexity is linear. The number of equality operations performed, or of applications of the predicate `pred`, is the size of the range `[first, last)`. Space complexity is constant.

count_if

Description The `count_if` algorithm adds to `n` the number of iterators in the range `[first, last)` for which the condition `pred(*i) == true` is satisfied.

Prototype

```
template
    < class InputIterator,
      class Predicate,
      class Size >
void count_if
    (InputIterator first,
     InputIterator last,
     Predicate pred,
     Size& n);
```

Complexity Time complexity is linear. The number of equality operations performed, or of applications of the predicate `pred`, is the size of the range `[first, last)`. Space complexity is constant.

mismatch

Description `mismatch` compares corresponding pairs of elements from two ranges, and returns the first mismatched pair.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2 >
pair<InputIterator1, InputIterator2> mismatch
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2);
template
    < class InputIterator1,
      class InputIterator2,
      class BinaryPredicate >
pair<InputIterator1, InputIterator2> mismatch
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     BinaryPredicate binary_pred);
```

Remarks The algorithm finds the first position at which the values in the range `[first1, last1)` disagree with the values in the range starting at `first2`. It returns a pair of iterators `i` and `j` which satisfy the following conditions:

- `i` points into the range `[first, last)`
- `j` points into the range beginning at `first2`
- `i` and `j` are both equidistant from the beginning of their corresponding ranges.
- `*i != *j`, or `binary_pred(i, j) == false`, depending on the version of `mismatch` invoked. In the first version, checks for equality are made with `operator==` and in the

Algorithms Library

Non Mutating Sequence Algorithms

second version they are made with the function object `binary_pred`.

Complexity Time complexity is linear. The number of equality operations or applications of the binary predicate is the size of the range `[first1, i)`.

equal

Description `equal` returns true if the ranges `[first1, last1)` and the range of size `first1-last1` beginning at `first2` contain the same elements in the same order, false otherwise.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2 >
bool equal
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2);
template
    < class InputIterator1,
      class InputIterator2,
      class BinaryPredicate >
bool equal
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     BinaryPredicate binary_pred);
```

Remarks In the first version of `equal`, checks for element equality are made with `operator==`, and in the second version they are made with the function object `pred`.

Complexity Time complexity is linear. The number of equality operations is the size of the range `[first1, i)`, where `i` is the iterator referring to the first element in the range `[first1, last1)` that does not match the corresponding element in the range beginning at `first2`. Space complexity is constant.

search

Description `search` checks whether the second range `[first2, last2)` is contained in the first range `[first1, last1)`. If so, the iterator `i` in `[first1, last1)` that represents the start of the second range in the first is returned. Otherwise, the past-the-end location of the first range, (i.e. `last1`), is returned.

Prototype

```
template
    < class ForwardIterator1,
      class ForwardIterator2 >
void search
    (ForwardIterator1 first1,
     ForwardIterator1 last1,
     ForwardIterator2 first2,
     ForwardIterator2 last2);
template
    < class ForwardIterator1,
      class ForwardIterator2,
      class BinaryPredicate >
void search
    (ForwardIterator1 first1,
     ForwardIterator1 last1,
     ForwardIterator2 first2,
     ForwardIterator2 last2,
     BinaryPredicate binary_pred);
```

Remarks In the first version of the algorithm, checks for element equality are made with `operator==`, while in the second they are made with the function object `binary_pred`.

Complexity Time complexity is quadratic. If `n` is the size of the range `[first1, last1)`, and `m` is the size of the range `[first2, last2)`, then the number of applications of `operator!=` or `binary_pred` is $(n-m)*m$, which is less than or equal to $n*n/4$. If `m > n`, the time taken is 0 (i.e. no match can be found in this case).

The implementation does not use the Knuth-Morris-Pratt algorithm. The KMP algorithm guarantees linear time, but tends to be slower in most practical cases than the naive algorithm with worst case

quadratic behavior. The worst case is extremely unlikely. Space complexity is constant.

Mutating Sequence Algorithms

Mutating sequence algorithms typically modify the containers they operate on. The algorithms in this category are:

- ["copy" on page 315](#)
- ["copy_backward" on page 315](#)
- ["fill" on page 320](#)
- ["fill_n" on page 321](#)
- ["generate" on page 321](#)
- ["generate_n" on page 322](#)
- ["iter_swap" on page 316](#)
- ["partition" on page 329](#)
- ["random_shuffle" on page 329](#)
- ["remove" on page 322](#)
- ["remove_copy" on page 324](#)
- ["remove_copy_if" on page 324](#)
- ["remove_if" on page 323](#)
- ["replace" on page 318](#)
- ["replace_copy" on page 319](#)
- ["replace_copy_if" on page 320](#)
- ["replace_if" on page 319](#)
- ["reverse" on page 327](#)
- ["reverse_copy" on page 327](#)
- ["rotate" on page 327](#)
- ["rotate_copy" on page 328](#)
- ["stable_partition" on page 330](#)
- ["swap" on page 316](#)
- ["swap_ranges" on page 317](#)

- [“transform” on page 317](#)
- [“unique” on page 325](#)
- [“unique_copy” on page 326](#)

copy

Description `copy` copies elements from the sequence `[first, last)` to the sequence of size `last - first` beginning at the iterator `result`, and returns the past-the-end iterator, `result + last - first`. For each non-negative integer $n < (last - first)$, the operation $*(result + n) = *(first + n)$ is performed. The result of `copy` is undefined if `result` is in the range `[first, last)`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator >
void copy
    (InputIterator first,
     InputIterator last,
     OutputIterator result);
```

Complexity Time complexity is linear for both copy algorithms. At most n assignments are performed, where n is the size of the range `[first, last)`. Space complexity is constant.

copy_backward

Description `copy_backward` copies all of the values in the range `[first, last)` to the range of size `last - first` starting at the iterator `result`, and returns the iterator that contains the last element copied (i.e. the beginning of the sequence). For `copy_backward`, the source and destination ranges may overlap if `result >= last`.

Prototype

```
template
    < class BidirectionalIterator1,
      class BidirectionalIterator2 >
void copy_backward
    (InputIterator first,
```

```
InputIterator last,  
OutputIterator result);
```

Complexity Time complexity is linear for both copy algorithms. At most n assignments are performed, where n is the size of the range `[first, last)`. Space complexity is constant.

swap

Description The `swap` function exchanges two elements.

Prototype

```
template  
    < class T >  
void swap  
    (T &a,  
     T &b);
```

Complexity The time required is constant for `swap` and `iter_swap`. For `swap_ranges`, the time complexity is linear. The number of swaps performed is the size of the range `[first, last)`. Space complexity is constant for all the swap algorithms.

iter_swap

Description The function `iter_swap` exchanges values pointed to by two iterators.

Prototype

```
template  
    < class ForwardIterator1,  
        ForwardIterator2 >  
void iter_swap  
    (ForwardIterator1 a,  
     ForwardIterator2 b);
```

Complexity The time required is constant for `swap` and `iter_swap`. For `swap_ranges`, the time complexity is linear. The number of swaps performed is the size of the range `[first, last)`. Space complexity is constant for all the swap algorithms.

swap_ranges

Description The function `swap_ranges` exchanges the elements in the range `[first, last)` with those in the range of size `last - first` beginning at `first2`. `swap_ranges` returns the past-the-end iterator, `first2+last-first`.

Prototype

```
template
    < class ForwardIterator1,
      class ForwardIterator2 >
ForwardIterator swap_ranges
    (ForwardIterator1 first1,
     ForwardIterator1 last1,
     ForwardIterator2 first2);
```

Complexity The time required is constant for `swap` and `iter_swap`. For `swap_ranges`, the time complexity is linear. The number of swaps performed is the size of the range `[first, last)`. Space complexity is constant for all the swap algorithms.

transform

Description The first version of `transform` generates an output sequence of elements by applying a unary function `op` to each element of the input sequence `[first, last)`.

The second version of `transform` accepts the input sequence `[first1, last1)` and the sequence of length `last1 - first1` starting at `first2`, and generates an output by applying a binary operation `binary_op` to each corresponding pair of elements from the input sequences.

Prototype

```
template
    < class InputIterator,
      class OutputIterator,
      class UnaryOperation >
OutputIterator transform
    (InputIterator first,
     InputIterator last,
```

Algorithms Library

Mutating Sequence Algorithms

```
        OutputIterator result,  
        UnaryOperation op);  
template  
    < class InputIterator1,  
      class InputIterator2,  
      class OutputIterator,  
      class BinaryOperation >  
OutputIterator transform  
    (InputIterator1 first1,  
     InputIterator1 last1,  
     InputIterator2 first2,  
     OutputIterator result,  
     BinaryOperation binary_op);
```

Remarks For both versions of `transform`, the resulting sequence is placed starting at the position `result`, and the past-the-end iterator is returned.

Complexity Time complexity is linear. The number of applications of `op` is the size of the range `[first, last)` and the number of applications of `binary_op` is the size of the range `[first1, last1)`. Space complexity is constant.

replace

Description The `replace` algorithm modifies the range `[first, last)` so that all elements equal to `old_value` are replaced by `new_value`, while other values remain unchanged.

Prototype

```
template  
    < class ForwardIterator,  
      class T >  
void replace  
    (ForwardIterator first,  
     ForwardIterator last,  
     const T& old_value,  
     const T& new_value);
```

Complexity Time complexity is linear for all replace algorithms. The number of equality operations performed, or of applications of the predicate `pred`, is the size of the range `[first, last)`. Space complexity is constant.

replace_if

Description `replace_if` modifies the range `[first, last)` so that all elements that satisfy the predicate `pred` are replaced by `new_value`, while other values remain unchanged.

Prototype

```
template
    < class ForwardIterator,
      class Predicate, class T >
void replace_if
    (ForwardIterator first,
     ForwardIterator last,
     Predicate pred,
     const T& new_value);
```

Complexity Time complexity is linear for all replace algorithms. The number of equality operations performed, or of applications of the predicate `pred`, is the size of the range `[first, last)`. Space complexity is constant.

replace_copy

Description `replace_copy` is similar to `replace`, except that the original sequence is not modified. Rather, the altered sequence is placed in the range of size `last - first` beginning at `result`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator,
      class T >
OutputIterator replace_copy
    (InputIterator first,
     InputIterator last,
     OutputIterator result,
```

```
const T& old_value,  
const T& new_value);
```

Complexity Time complexity is linear for all replace algorithms. The number of equality operations performed, or of applications of the predicate `pred`, is the size of the range `[first, last)`. Space complexity is constant.

replace_copy_if

Description `replace_copy_if` is similar to `replace_if`, except that the original sequence is not modified. Rather, the altered sequence is placed in the range of size `last - first` beginning at `result`.

Prototype

```
template  
    < class InputIterator,  
      class OutputIterator,  
      class Predicate,  
      class T >  
OutputIterator replace_copy_if  
    (InputIterator first,  
     InputIterator last,  
     OutputIterator result,  
     Predicate pred,  
     const T& new_value);
```

Complexity Time complexity is linear for all replace algorithms. The number of equality operations performed, or of applications of the predicate `pred`, is the size of the range `[first, last)`. Space complexity is constant.

fill

Description `fill` assigns `value` through all the iterators in the range `[first, last)`.

Prototype

```
template  
    < class ForwardIterator,  
      class T >
```



```
void fill
    (ForwardIterator first,
     ForwardIterator
     last,
     const T& value);
```

Complexity Time complexity is linear. The number of assignments for both versions of the algorithm is the size of the range `[first, last)`. Space complexity is constant.

fill_n

Description `fill_n` assigns `value` through all the iterators in the range `[first, first + n)`.

Prototype

```
template
    < class ForwardIterator,
      class Size,
      class T >
void fill_n
    (ForwardIterator first,
     Size n,
     const T& value);
```

Complexity Time complexity is linear. The number of assignments for both versions of the algorithm is the size of the range `[first, last)`. Space complexity is constant.

generate

Description `generate` fills the range `[first, last)` with the sequence generated by `last - first` successive calls to the function object `gen`.

Prototype

```
template
    < class ForwardIterator,
      class Generator >
void generate
    (ForwardIterator first,
     ForwardIterator last,
```

Generator gen);

Complexity Time complexity is linear. The number of assignments for `generate` is the size of the range `[first, last)`, while for `generate_n` the number of assignments is `n`. Space complexity is constant.

generate_n

Description `generate_n` fills the range of size `n` beginning at `first` with the sequence generated by `n` successive calls to `gen`.

Prototype

```
template
    < class ForwardIterator,
      class Size,
      class Generator >
void generate_n
    (ForwardIterator first,
     Size n,
     Generator gen);
```

Complexity Time complexity is linear. The number of assignments for `generate` is the size of the range `[first, last)`, while for `generate_n` the number of assignments is `n`. Space complexity is constant.

remove

Description The function `remove` removes those elements from the range `[first, last)` that are equal to `value`, and returns the location `i` that is the past-the-end iterator for the resulting range of values that are not equal to `value`.

Prototype

```
template
    < class ForwardIterator,
      class T >
ForwardIterator remove
    (ForwardIterator first,
     ForwardIterator last,
     const T& value);
```

It is important to note that neither `remove` nor `remove_if` alters the size of the original container: the algorithms operate by copying (with assignments) the final generated elements into the range `[first, i)`. No calls are made to the `insert` or `erase` member functions of the containers operated on by the algorithms.

All versions of `remove` are stable, that is, the relative order of the elements that are not removed is the same as their relative order in the original range.

Complexity Time complexity is linear for all versions of `remove`. The number of assignments is the number of elements not removed, at most the size of the range `[first, last)`. Space complexity is constant for all the `remove` algorithms.

`remove_if`

Description The function `remove_if` removes those elements from the range `[first, last)` which satisfy the predicate `pred`, and returns the location `i` that is the past-the-end iterator for the resulting range of values that are not equal to `value`.

Prototype

```
template
    < class ForwardIterator,
      class Predicate >
ForwardIterator remove_if
    (ForwardIterator first,
     ForwardIterator last,
     Predicate pred);
```

Remarks It is important to note that neither `remove` nor `remove_if` alters the size of the original container: the algorithms operate by copying (with assignments) the final generated elements into the range `[first, i)`. No calls are made to the `insert` or `erase` member functions of the containers operated on by the algorithms.

All versions of `remove` are stable, that is, the relative order of the elements that are not removed is the same as their relative order in the original range.

Complexity Time complexity is linear for all versions of `remove`. The number of assignments is the number of elements not removed, at most the size of the range `[first, last)`. Space complexity is constant for all the `remove` algorithms.

remove_copy

Description `remove_copy` is similar to `remove`, except that the final resulting sequences are copied into the range beginning at `result`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator,
      class T >
OutputIterator remove_copy
    (InputIterator first,
     InputIterator last,
     OutputIterator result,
     const T& value);
```

Remarks All versions of `remove` are stable, that is, the relative order of the elements that are not removed is the same as their relative order in the original range.

Complexity Time complexity is linear for all versions of `remove`. The number of assignments is the number of elements not removed, at most the size of the range `[first, last)`. Space complexity is constant for all the `remove` algorithms.

remove_copy_if

Description `remove_copy_if` is similar to `remove_if`, except that the final resulting sequences are copied into the range beginning at `result`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator,
      class Predicate >
OutputIterator remove_copy_if
```

```
(InputIterator first,  
InputIterator last,  
OutputIterator result,  
Predicate pred);
```

Remarks All versions of `remove` are stable, that is, the relative order of the elements that are not removed is the same as their relative order in the original range.

Complexity Time complexity is linear for all versions of `remove`. The number of assignments is the number of elements not removed, at most the size of the range `[first, last)`. Space complexity is constant for all the `remove` algorithms.

unique

Description `unique` eliminates consecutive duplicates from the range `[first, last)`. An element is considered to be a consecutive duplicate if it is equal to an element in the location to its immediate right in the range.

In the first version of `unique`, checks for equality are made using `operator==`, while in the second they are made with the function object `binary_pred`.

Prototype

```
template  
    < class ForwardIterator >  
ForwardIterator unique  
    (ForwardIterator first,  
     ForwardIterator last);
```

Prototype

```
template  
    < class ForwardIterator,  
      class BinaryPredicate >  
ForwardIterator unique  
    (ForwardIterator first,  
     ForwardIterator last,  
     BinaryPredicate binary_pred);
```

Remarks All versions of `unique` return the end of the resulting range.

The `unique` algorithms are typically applied to a sorted range, since in this case all duplicates are consecutive duplicates.

Complexity Time complexity is linear for all versions of `unique`. Exactly `last - first` applications of the corresponding predicates are done. Space complexity is constant for `unique`, and linear for `unique_copy`.

`unique_copy`

Description `unique_copy` is similar to `unique`, except that the resulting sequence is copied into the range starting at `result`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator >
OutputIterator unique_copy
    (InputIterator first,
     InputIterator last,
     OutputIterator result);
template
    < class ForwardIterator,
      class BinaryPredicate >
OutputIterator unique_copy
    (InputIterator first,
     InputIterator last,
     OutputIterator result,
     BinaryPredicate binary_pred);
```

Remarks All versions of `unique` return the end of the resulting range.

The `unique` algorithms are typically applied to a sorted range, since in this case all duplicates are consecutive duplicates.

Complexity Time complexity is linear for all versions of `unique`. Exactly `last - first` applications of the corresponding predicates are done. Space complexity is constant for `unique`, and linear for `unique_copy`.

reverse

Description The reverse algorithm reverses the order of elements in the range `[first, last)`.

Prototype

```
template
    < class BidirectionalIterator >
void reverse
    (BidirectionalIterator first,
     BidirectionalIterator last);
```

Complexity Time complexity is linear. For reverse, exactly $[n/2]$ element exchanges are performed, where n is the size `[first, last)`. For reverse_copy, exactly last-first assignments are done. Space complexity is constant.

reverse_copy

Description The reverse_copy algorithm reverses the sequence `[first, last)` and copies the resulting sequence into the range beginning `result`.

Prototype

```
template
    < class BidirectionalIterator,
      class OutputIterator >
OutputIterator reverse_copy
    (BidirectionalIterator first,
     BidirectionalIterator last,
     OutputIterator result);
```

Complexity Time complexity is linear. For reverse, exactly $[n/2]$ element exchanges are performed, where n is the size `[first, last)`. For reverse_copy, exactly last-first assignments are done. Space complexity is constant.

rotate

Description The rotate algorithm shifts elements in a sequence leftward as follows: for each non-negative integer $i < (\text{last} - \text{first})$, rotate

places the element from the position `first + i` into position `first + (i + (middle - first)) % (last - first)`.

After the `rotate` operation, an element originally at location `i` in the sequence `[first, last)` is finally placed at location `(i+n-m) mod n`, where `m` is the size of the range `[first, middle)`, and `n` is the size of the range `[first, last)`.

Prototype `template`
 `< class ForwardIterator >`
`void rotate`
 `(ForwardIterator first,`
 `ForwardIterator middle,`
 `ForwardIterator last);`

Complexity Time complexity is linear.

For `rotate`, exactly $2 * [n/2] + [m/2] + [(n-m)/2]$ element exchanges are performed, where `m` is the size of the range `[first, middle)` and `n` is the size `[first, last)`. Space complexity is constant.

rotate_copy

Description `rotate_copy` is similar to `rotate`, except that it copies the elements of the resulting sequence into a range of size `last-first` starting at the location `result`.

Prototype `template`
 `< class ForwardIterator,`
 `class OutputIterator >`
`void rotate_copy`
 `(ForwardIterator first,`
 `ForwardIterator middle,`
 `ForwardIterator last,`
 `OutputIterator result);`

Complexity Time complexity is linear.

For `rotate_copy`, exactly n assignment operations are performed, where n is the size `[first, last)`. Space complexity is constant.

random_shuffle

Description `random_shuffle` shuffles the elements in the range `[first, last)` with uniform distribution. `random_shuffle` can take a particular random number generating function object `rand` such that `rand` returns a randomly chosen double in the interval `[0, 1)`.

Prototype

```
template
    < class RandomAccessIterator >
void random_shuffle
    (RandomAccessIterator first,
     RandomAccessIterator last);
```

Prototype

```
template
    < class RandomAccessIterator,
      class RandomNumberGenerator >
void random_shuffle
    (RandomAccessIterator first,
     RandomAccessIterator last,
     RandomNumberGenerator& rand);
```

Complexity Time complexity is linear. The algorithm performs exactly $(last - first) - 1$ swaps. Space complexity is constant.

partition

Description The `partition` algorithm places all elements in the range `[first, last)` that satisfy `pred` before all elements that do not satisfy it.

Prototype

```
template
    < class BidirectionalIterator,
      class Predicate >
void partition
    (BidirectionalIterator first,
     BidirectionalIterator last,
     Predicate pred);
```

Remarks Both algorithms return an iterator `i` such that for any iterator `j` in the range `[first, i)`, `pred(*j) == true`, and for any iterator `k` in the range `[i, last)`, `pred(*k) == false`.

For `partition`, exactly $\lfloor n/2 \rfloor$ element exchanges are performed, where n is the size `[first, last)`. Exactly `last - first` applications of the predicate are performed.

Complexity Time complexity is linear for both versions of the algorithm. Space complexity is constant.

stable_partition

Prototype

```
template
    < class BidirectionalIterator,
      class Predicate >
void stable_partition
    (BidirectionalIterator first,
     BidirectionalIterator last,
     Predicate pred);
```

Description In `stable_partition`, the relative positions of the elements in both groups are preserved. `partition` does not guarantee this.

Remarks Both algorithms return an iterator `i` such that for any iterator `j` in the range `[first, i)`, `pred(*j) == true`, and for any iterator `k` in the range `[i, last)`, `pred(*k) == false`.

If the available memory for a buffer is smaller than the range `[first, last)`, the `stable_partition` function requires $O(n \log n)$ time and performs $n \log n$ swaps, where n is the size of `[first, last)`. If there is enough available memory for the buffer to contain all the elements in the range `[first, last)`, then the `stable_partition` function requires linear time, performing $n + m$ assignment operations and applying the predicate exactly n times, where m is the size of the range `[i, last)` and n is the size of `[first, last)`.

Complexity Time complexity is linear for both versions of the algorithm. For `stable_partition`, the time and space complexity varies with the available memory.

Sorting and Related Algorithms

There are several distinct sets of algorithms related to sorting. Each individual set contains a collection of related algorithms. The sets are:

- [“Sorting” on page 332](#)
- [“Binary Searching” on page 336](#)
- [“Merging” on page 340](#)
- [“Set Operations on Sorted Structures” on page 342](#)
- [“Heap Operations” on page 347](#)
- [“Finding Min and Max” on page 351](#)
- [“Lexicographical Comparison” on page 354](#)
- [“Permutation Generators” on page 355](#)

All of the algorithms have two versions: one that uses `operator<` for comparisons and another that uses a function object of type `Compare`.

`Compare` is used as a function object which accepts two arguments, returns `true` if the first argument is less than the second, and returns `false` otherwise. `Compare comp` is used throughout for algorithms assuming an ordering relation. It is assumed that `comp` will not apply any non-constant function through the dereferenced iterator.

For all algorithms that take `Compare`, there is a version that uses `operator<` instead. That is, `comp(*i, *j) == true` defaults to `*i < *j == true`. For the algorithms to work correctly, `comp` has to induce a total ordering on the values.

A sequence is sorted with respect to a comparator `comp` if for any iterator `i` pointing to the sequence and any non-negative integer `n`

such that `i+n` is a valid iterator pointing to an element of the sequence, `comp(*(i+n), *i) == false`.

In the descriptions of the functions that deal with ordering relationships, we frequently use a notion of equality to describe concepts such as stability. The equality to which we refer is not necessarily an `operator==`, but an equality relation induced by the total ordering. That is, two elements `a` and `b` are considered equal if and only if `!(a < b) && !(b < a)`.

Sorting

Four different sorting algorithms are provided by the library: `sort`, `stable_sort`, `partial_sort` and `partial_sort_copy`.

`sort` uses the quicksort algorithm, which is generally the fastest for a randomly shuffled sequence. It should be used as the default sorting algorithm. However, in the worst case, `sort` might take quadratic time. This worst case occurs if the original input to the algorithm is already sorted.

If worst case behavior is absolutely critical, then `stable_sort` should be used instead of `sort`.

sort

Description `sort` sorts the elements in the range `[first, last)`. It uses a fast quicksort algorithm. If worst case behavior is important `stable_sort` or `partial_sort` should be used.

Prototype

```
template
    < class RandomAccessIterator >
void sort
    (RandomAccessIterator first,
     RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void sort
    (RandomAccessIterator first,
```

```
RandomAccessIterator last,  
Compare comp);
```

Complexity Sort does approximately $N \log N$ (where N is $(\text{last} - \text{first})$) comparisons on the average. Space complexity is constant.

stable_sort

Description `stable_sort` sorts the elements in the range $[\text{first}, \text{last})$, and ensures that the relative order of the equal elements is preserved.

Prototype

```
template  
    < class RandomAccessIterator >  
void stable_sort  
    (RandomAccessIterator first,  
     RandomAccessIterator last);
```

Prototype

```
template  
    < class RandomAccessIterator,  
      class Compare >  
void stable_sort  
    (RandomAccessIterator first,  
     RandomAccessIterator last,  
     Compare comp);
```

Remarks `stable_sort` performs at most $N \log N * \log N$ (where N is $\text{last} - \text{first}$) comparisons. If adequate memory is available, then the number of comparisons is $N \log N$. Space complexity for `stable_sort` is variable, at most $O(N)$.

Complexity Sort does approximately $N \log N$ (where N is $(\text{last} - \text{first})$) comparisons on the average. Space complexity is constant.

partial_sort

Description `partial_sort` sorts only a subsequence of the input range. It places the first $\text{middle} - \text{first}$ sorted elements from the range $[\text{first}, \text{last})$ into the range $[\text{first}, \text{middle})$. The rest of the

elements (i.e. those in the range `[middle, last)`) are placed in an undefined order.

Prototype

```
template
    < class RandomAccessIterator >
void partial_sort
    (RandomAccessIterator first,
     RandomAccessIterator middle,
     RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void partial_sort
    (RandomAccessIterator first,
     RandomAccessIterator middle,
     RandomAccessIterator last,
     Compare comp);
```

Remarks `partial_sort` does approximately $(last - first) * \log(middle - first)$ comparisons. Space complexity is constant.

Complexity Sort does approximately $N \log N$ (where N is $(last - first)$) comparisons on the average. Space complexity is constant.

partial_sort_copy

Description `partial_sort_copy` is similar to `partial_sort`. The algorithm places the first $\min(last - first, result_last - result_first)$ sorted elements from the range `[first, last)` into the sequence beginning at `result_first`.

Prototype

```
template
    < class InputIterator,
      class RandomAccessIterator
> RandomAccessIterator partial_sort_copy
    (InputIterator first, InputIterator last,
     RandomAccessIterator result_first,
     RandomAccessIterator result_last);
template
```

```
    < class InputIterator,
      class RandomAccessIterator,
      class Compare >
RandomAccessIterator partial_sort_copy
    (InputIterator first,
     InputIterator last,
     RandomAccessIterator result_first,
     RandomAccessIterator result_last,
     Compare comp);
```

Remarks `partial_sort_copy` does approximately $(last - first) * \log(\min(last - first, result_last - result_first))$ comparisons. Space complexity is proportional to the length of the sequence copied.

Complexity Sort does approximately $N \log N$ (where N is $(last - first)$) comparisons on the average. Space complexity is constant.

`nth_element`

Description The `nth_element` algorithm is a restricted form of the sort algorithm. It places an element of a sequence in the location where it would be if the sequence were sorted.

Prototype

```
template
    < class RandomAccessIterator >
void nth_element
    (RandomAccessIterator first,
     RandomAccessIterator nth,
     RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void nth_element
    (RandomAccessIterator first,
     RandomAccessIterator nth,
     RandomAccessIterator last,
     Compare comp);
```

Remarks In the first version of the algorithm, element comparisons are done using `operator<`, while in the second version they are done using the function object `comp`.

After a call to `nth_element`, for any iterator `i` in the range `[first, nth)` and any iterator `j` in the range `[nth, last)` it holds that `!(i > j)` or `comp(i, j) == false`. That is, the algorithm partitions the elements of the sequence according to size: elements to the left of the `nth` element are all less than those to its right.

Complexity The algorithm takes $O(N)$ time on the average, where N is the size of the range `[first, last)`. Space complexity is constant.

Binary Searching

All of the algorithms in this section are versions of binary search.

Although binary search is typically efficient (i.e., performs in logarithmic time) only for random access data structures (such as vectors, deques, etc.), the algorithms here have been written so as to also work on non-random access data structures such as lists. For all non-random access data structures, the total time taken is linear in the size of the container, but the number of comparisons is only logarithmic in the size of the container.

`binary_search`

Description The `binary_search` function returns true if `value` is in the range `[first, last)` and false otherwise.

Prototype

```
template
    < class ForwardIterator,
      class T >
bool binary_search
    (ForwardIterator first,
     ForwardIterator last,
     const T& value);
template
    < class ForwardIterator,
      class T,
```



```
class Compare >
bool binary_search
    (ForwardIterator first,
     ForwardIterator last,
     const T& value,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity For random access iterators only, the number of comparisons will be

- at most $\log(N)+1$, for `lower_bound` and `upper_bound`
- at most $\log(N)+2$, for `binary_search`
- at most $2*\log(N)+1$, for `equal_range`

where N is the size of the range `[first, last)`.

For all iterators other than random access, time complexity is linear, since the algorithm has to sequentially traverse through the data structure. Space complexity is constant for all the binary search algorithms.

lower_bound

Description The `lower_bound` functions return an iterator `i` referring to the first position in the sorted sequence in the range `[first, last)` into which `value` may be inserted while maintaining the sorted ordering.

Prototype

```
template
    < class ForwardIterator,
      class T >
ForwardIterator lower_bound
    (ForwardIterator first,
     ForwardIterator last,
     const T& value);
template
```

Algorithms Library

Sorting and Related Algorithms

```
< class ForwardIterator,
class T,
class Compare >
ForwardIterator lower_bound
(ForwardIterator first,
ForwardIterator last,
const T& value,
Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity For random access iterators only, the number of comparisons will be

- at most $\log(N)+1$, for `lower_bound` and `upper_bound`
- at most $\log(N)+2$, for `binary_search`
- at most $2*\log(N)+1$, for `equal_range`

where N is the size of the range `[first, last)`.

For all iterators other than random access, time complexity is linear, since the algorithm has to sequentially traverse through the data structure. Space complexity is constant for all the binary search algorithms.

upper_bound

Description The `upper_bound` functions return an iterator `i` referring to the last position in the sorted sequence in the range `[first, last)` into which `value` may be inserted while maintaining the sorted ordering.

Prototype

```
template
< class ForwardIterator,
class T >
ForwardIterator upper_bound
(ForwardIterator first,
ForwardIterator last,
```

```
        const T& value);  
template  
    < class ForwardIterator,  
      class T,  
      class Compare >  
ForwardIterator upper_bound  
    (ForwardIterator first,  
     ForwardIterator last,  
     const T& value,  
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using operator<, while in the second they are done using the function object comp.

Complexity For random access iterators only, the number of comparisons will be

- at most $\log(N)+1$, for `lower_bound` and `upper_bound`
- at most $\log(N)+2$, for `binary_search`
- at most $2*\log(N)+1$, for `equal_range`

where N is the size of the range `[first, last)`.

For all iterators other than random access, time complexity is linear, since the algorithm has to sequentially traverse through the data structure. Space complexity is constant for all the binary search algorithms.

equal_range

Description The `equal_range` functions return a pair of iterators `i` and `j` referring to the first and last positions in the sorted sequence in the range `[first, last)` into which value may be inserted while maintaining the sorted ordering.

Prototype

```
template  
    < class ForwardIterator, class T >  
pair< ForwardIterator, ForwardIterator >  
equal_range
```

```
        (ForwardIterator first,
         ForwardIterator last,
         const T& value);
template
    < class ForwardIterator, class T >
pair < ForwardIterator, ForwardIterator >
equal_range
    (ForwardIterator first,
     ForwardIterator last,
     const T& value,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity For random access iterators only, the number of comparisons will be

- at most $\log(N)+1$, for `lower_bound` and `upper_bound`
- at most $\log(N)+2$, for `binary_search`
- at most $2*\log(N)+1$, for `equal_range`

where N is the size of the range `[first, last)`.

For all iterators other than random access, time complexity is linear, since the algorithm has to sequentially traverse through the data structure. Space complexity is constant for all the binary search algorithms.

Merging

The merge algorithms join two sorted ranges.

merge

Description `merge` merges two sorted ranges `[first1, last1)` and `[first2, last2)` into the range `[result, result + (last1 - first1) + (last2 - first2))`. The merge is stable, that is, for equal ele-

ments in the two ranges, the elements from the first range always precede the elements from the second. `merge` returns `result + (last1 - first1) + (last2 - first2)`. The result of `merge` is undefined if the resulting range overlaps with either of the original ranges.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator >
OutputIterator merge
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator last2,
     OutputIterator result);
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator,
      class Compare >
OutputIterator merge
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator last2,
     OutputIterator result,
     Compare comp);
```

Complexity For `merge`, at most $(last1 - first1) + (last2 - first2) - 1$ comparisons are performed.

`inplace_merge`

Description `inplace_merge` merges two sorted consecutive ranges `[first, middle)` and `[middle, last)` putting the result of the merge into the range `[first, last)`. The merge is *stable*, that is, for equal elements in the two ranges, the elements from the first range always precede the elements from the second.

Prototype

```
template
    < class BidirectionalIterator >
void inplace_merge
    (BidirectionalIterator first,
     BidirectionalIterator middle,
     BidirectionalIterator last);
template
    < class BidirectionalIterator,
      class Compare >
void inplace_merge
    (BidirectionalIterator first,
     BidirectionalIterator middle,
     BidirectionalIterator last,
     Compare comp);
```

Complexity For `inplace_merge`, at most `last - first` comparisons are performed. If no additional memory is available, the number of assignments can be equal to $N \log N$ where N is equal to `last - first`.

Set Operations on Sorted Structures

The library provides five different types of set operations:

- ["includes" on page 343](#)
- ["set_union" on page 343](#)
- ["set_intersection" on page 344](#)
- ["set_difference" on page 345](#)
- ["set_symmetric_difference" on page 346](#)

The operations work on sorted structures, such as all STL associative containers.

The algorithms even work with multisets containing multiple copies of equal elements. The semantics of the operations have been generalized to multisets in a standard way, by defining union to contain the maximum number of occurrences of every element, intersection to contain the minimum, and so on.

includes

Description includes checks if the second sequence is a subset of the first sequence (both ranges are assumed to be sorted). The algorithm returns true if every element in the range [first2, last2) is contained in the range [first1, last1), and false otherwise.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2 >
bool includes
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2);
template
    < class InputIterator1,
      class InputIterator2,
      class Compare >
bool includes
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     Compare comp);
```

Complexity TAll of the set operations functions require linear time. In all cases, at most $((last1 - first1) + (last2 - first2)) * 2 - 1$ comparisons are performed. Space complexity is constant.

set_union

Description set_union constructs a sorted union of the elements from the two ranges. set_union is stable, that is, if an element is present in both ranges, the one from the first range is copied.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2,
```

```
        class OutputIterator >
OutputIterator set_union
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     OutputIterator result);
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator,
      class Compare >
OutputIterator set_union
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     OutputIterator result,
     Compare comp);
```

Complexity The union, intersection, difference and symmetric difference algorithms all return the end of the constructed range. The result of each of these algorithms is undefined if the resulting range overlaps with either of the original ranges.

All of the set operations functions require linear time. In all cases, at most $((last1 - first1) + (last2 - first2)) * 2 - 1$ comparisons are performed. Space complexity is constant.

set_intersection

Description `set_intersection` constructs a sorted intersection of the elements from the two ranges. `set_intersection` is guaranteed to be stable, that is, if an element is present in both ranges, the one from the first range is copied into the intersection.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2, class OutputIterator >
OutputIterator set_intersection
```



```
        (InputIterator1 first1,
         InputIterator1 last1,
         InputIterator2 first2,
         InputIterator2 last2,
         OutputIterator result);
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator,
      class Compare >
OutputIterator set_intersection
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     OutputIterator result,
     Compare comp);
```

Remarks The union, intersection, difference and symmetric difference algorithms all return the end of the constructed range. The result of each of these algorithms is undefined if the resulting range overlaps with either of the original ranges.

Complexity All of the set operations functions require linear time. In all cases, at most $((last1 - first1) + (last2 - first2)) * 2 - 1$ comparisons are performed. Space complexity is constant.

set_difference

Description `set_difference` constructs a sorted difference of the elements from the two ranges. This difference contains elements that are present in the first set but not in the second.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator >
OutputIterator set_difference
    (InputIterator1 first1,
```

Algorithms Library

Sorting and Related Algorithms

```
        InputIterator1 last1,
        InputIterator2 first2,
        InputIterator2 last2,
        OutputIterator result);
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator,
      class Compare >
OutputIterator set_difference
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     OutputIterator result,
     Compare comp);
```

Remarks The union, intersection, difference and symmetric difference algorithms all return the end of the constructed range. The result of each of these algorithms is undefined if the resulting range overlaps with either of the original ranges.

Complexity All of the set operations functions require linear time. In all cases, at most $((last1 - first1) + (last2 - first2)) * 2 - 1$ comparisons are performed. Space complexity is constant.

set_symmetric_difference

Prototype

```
template
    < class InputIterator1,
      class InputIterator2,
      class OutputIterator >
OutputIterator set_symmetric_difference
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     OutputIterator result);
template
    < class InputIterator1,
```

```
class InputIterator2,  
class OutputIterator,  
class Compare >  
OutputIterator set_symmetric_difference  
(InputIterator1 first1,  
InputIterator1 last1,  
InputIterator2 first2,  
InputIterator2 last2,  
OutputIterator result,  
Compare comp);
```

- Description** `set_symmetric_difference` constructs a sorted symmetric difference of the elements from the two ranges (i.e. a combination of the set of elements that are in the first range but not in the second and vice-versa).
- Remarks** The union, intersection, difference and symmetric difference algorithms all return the end of the constructed range. The result of each of these algorithms is undefined if the resulting range overlaps with either of the original ranges.
- Complexity** All of the set operations functions require linear time. In all cases, at most $((last1 - first1) + (last2 - first2)) * 2 - 1$ comparisons are performed. Space complexity is constant.

Heap Operations

A heap represents a particular organization of a random access data structure (such as a vector or a deque). Given a range `[first, last)`, where `first` and `last` are random access iterators, we say that the elements in the range represent a heap if two key properties are satisfied:

- The value pointed to by the iterator `first` is the largest element in the range
- The value pointed to by the iterator `first` may be removed by `pop_heap`, or a new element added by `push_heap`, in logarithmic time. Both `pop_heap` and `push_heap` return valid heaps.

These properties allow heaps to be used as priority queues.

In addition to `pop_heap` and `push_heap` there are two more heap algorithms: `make_heap` and `sort_heap`.

push_heap

Description `push_heap` assumes the range `[first1, last - 1)` is a valid heap and properly places the value in the location `last - 1` into the resulting heap `[first, last)`.

Prototype

```
template
    < class RandomAccessIterator >
void push_heap
    (RandomAccessIterator first,
     RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void push_heap
    (RandomAccessIterator first,
     RandomAccessIterator last,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity In all of the complexity descriptions below, the number `N` represents the size of the range `[first, last)`.

The `push_heap` and `pop_heap` functions require logarithmic time. The `push_heap` functions require at most $\log N$ time, and the `pop_heap` functions require at most $2 * \log N$ comparisons.

Space complexity is constant for all heap algorithms.

pop_heap

Description `pop_heap` assumes the range `[first, last)` is a valid heap, then swaps the value in the location `first` with the value in the location `last - 1` and makes `[first, last - 1)` into a heap.

Prototype

```
template
    < class RandomAccessIterator >
void pop_heap
    (RandomAccessIterator first,
     RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void pop_heap
    (RandomAccessIterator first,
     RandomAccessIterator last,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity In all of the complexity descriptions below, the number `N` represents the size of the range `[first, last)`.

The `push_heap` and `pop_heap` functions require logarithmic time. The `push_heap` functions require at most $\log N$ time, and the `pop_heap` functions require at most $2 * \log N$ comparisons.

Space complexity is constant for all heap algorithms.

make_heap

Description The `make_heap` functions construct a heap in the range `[first, last)` using the elements in the range `[first, last)`.

Prototype

```
template
    < class RandomAccessIterator >
```

Algorithms Library

Sorting and Related Algorithms

```
void make_heap(
    RandomAccessIterator first,
    RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void make_heap(RandomAccessIterator first,
    RandomAccessIterator last,
    Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity In all of the complexity descriptions below, the number `N` represents the size of the range `[first, last)`.

The `make_heap` functions require linear time and require at most $3 \cdot N$ comparisons.

Space complexity is constant for all heap algorithms.

sort_heap

Description The `sort_heap` functions sort the elements that are stored in the heap represented in the range `[first, last)`.

Prototype

```
template
    < class RandomAccessIterator >
void sort_heap
    (RandomAccessIterator first,
     RandomAccessIterator last);
template
    < class RandomAccessIterator,
      class Compare >
void sort_heap
    (RandomAccessIterator first,
     RandomAccessIterator last,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Complexity In all of the complexity descriptions below, the number *N* represents the size of the range `[first, last)`.

The `sort_heap` functions require $N \log N$ time and $N \log N$ comparisons.

Space complexity is constant for all heap algorithms.

Finding Min and Max

The min and max algorithms identify the larger or smaller of two elements, or of elements in a range.

min

Description The `min` function is passed two elements, and returns the one that is smaller.

Prototype

```
template
    < class T >
T min
    (const T &a,
     const T &b);
template
    < class T,
      class Compare >
T min
    (const T &a,
     const T &b,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using `operator<`, while in the second they are done using the function object `comp`.

Algorithms Library

Sorting and Related Algorithms

Complexity min and max take constant time. Space complexity is constant for all min and max algorithms.

max

Description The max function is passed two elements, and returns the one that is larger.

Prototype

```
template
    < class T >
T max
    (const T &a,
     const T &b);
template
    < class T,
      class Compare >
T max
    (const T &a,
     const T &b,
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using operator<, while in the second they are done using the function object comp.

Complexity min and max take constant time. Space complexity is constant for all min and max algorithms.

min_element

Description The min_element function returns an iterator i referring to the minimum of the elements in the range [first, last).

Prototype

```
template
    < class InputIterator >
InputIterator min_element
    (InputIterator first,
     InputIterator last);
template
```



```
        < class InputIterator,  
        class Compare >  
InputIterator min_element  
    (InputIterator first,  
     InputIterator last,  
     Compare comp);
```

Remarks In the first function of each pair of functions, element comparisons are done using operator<, while in the second they are done using the function object comp.

Complexity Tmin_element takes linear time, with the number of element comparisons being the size of the range [first, last). Space complexity is constant for all min and max algorithms.

max_element

Description The max_element functions returns an iterator i referring to the maximum of the elements in the range [first, last).

Prototype

```
template  
    < class InputIterator >  
InputIterator max_element  
    (InputIterator first,  
     InputIterator last);  
template  
    < class InputIterator,  
    class Compare >  
InputIterator max_element  
    (InputIterator first,  
     InputIterator last,  
     Compare comp);
```

Complexity Tmax_element takes linear time, with the number of element comparisons being the size of the range [first, last). Space complexity is constant for all min and max algorithms.

Lexicographical Comparison

The lexicographical comparison algorithm compares two sequences of elements.

lexicographical_compare

Description The lexicographical comparison of two sequences `[first1, last1)` and `[first2, last2)` is defined as follows: traverse the sequences, comparing corresponding pairs of elements `e1` and `e2`. If `e1 < e2`, stop and return `true`. If `e2 < e1`, stop and return `false`. Otherwise, continue to the next corresponding pair of elements.

If the first sequence is exhausted but the second is not, then return `true`, otherwise return `false`.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2 >
bool lexicographical_compare
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2);

template
    < class InputIterator1,
      class InputIterator2,
      class Compare >
bool lexicographical_compare
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     InputIterator2 last2,
     Compare comp);
```

Remarks Comparisons of `e1` and `e2` are done with operator< in the first version of the algorithm, and with the function object `comp` in the second version.

Complexity Time complexity is linear. The number of comparisons done is at most i , where i is the smallest index at which a disagreement occurs. Space complexity is constant.

Permutation Generators

The library provides two permutation generation algorithms: `next_permutation` and `prev_permutation`. As with all sorting related operations, there are two versions of each algorithm: one that uses `operator<` for comparisons, and one that uses a function object `comp`.

`next_permutation`

Description `next_permutation` takes a sequence defined by the range `[first, last)` and transforms it into the next permutation. The next permutation is found by assuming that the set of all permutations is lexicographically sorted with respect to `operator<` or `comp`. If such a permutation exists, the algorithm returns `true`. Otherwise, it transforms the sequence into the smallest permutation (i.e., the one sorted in an ascending order), and returns `false`.

Prototype

```
template
    < class BidirectionalIterator >
bool next_permutation
    (BidirectionalIterator first,
     BidirectionalIterator last);
template
    < class BidirectionalIterator,
      class Compare >
bool next_permutation
    (BidirectionalIterator first,
     BidirectionalIterator last,
     Compare comp);
```

Complexity Time complexity is linear for both algorithms. The number of comparisons done is at most n where n is half the range `[first, last)`. Space complexity is constant.

prev_permutation

Description `prev_permutation` takes a sequence defined by the range `[first, last)` and transforms it into the previous permutation. The previous permutation is found by assuming that the set of all permutations is lexicographically sorted with respect to `operator<` or `comp`. If such a permutation exists, it returns `true`. Otherwise, it transforms the sequence into the largest permutation, (i.e., the descending sorted one), and returns `false`.

Prototype

```
template
    < class BidirectionalIterator >
bool prev_permutation
    (BidirectionalIterator first,
     BidirectionalIterator last);
template
    < class BidirectionalIterator,
      class Compare >
bool prev_permutation
    (BidirectionalIterator first,
     BidirectionalIterator last,
     Compare comp);
```

Complexity Time complexity is linear for both algorithms. The number of comparisons done is at most n where n is half the range `[first, last)`. Space complexity is constant.

Generalized Numeric Algorithms

The library provides four algorithms for numeric processing:

- [“accumulate” on page 357](#)
- [“inner_product” on page 357](#)
- [“partial_sum” on page 359](#)
- [“adjacent_difference” on page 360](#)

See also [“Generalized Numeric Algorithms” on page 356](#).

accumulate

Description `accumulate` is similar to the APL reduction operator and the Common Lisp `reduce` function, but avoids the difficulty of defining the result of reduction on an empty sequence by always requiring an initial value.

Prototype

```
template
    < class InputIterator, class T >
T accumulate
    (InputIterator first,
     InputIterator last,
     T init);
template
    < class InputIterator,
      class T,
      class BinaryOperation >
T accumulate
    (InputIterator first,
     InputIterator last,
     T init,
     BinaryOperation binary_op);
```

Remarks Accumulation is done by initializing the accumulator `acc` with the initial value `init` and then modifying it with `acc = acc + *i` or `acc = binary_op(acc, *i)` for every iterator `i` in the range `[first, last)` in order. `binary_op` is assumed not to cause any side effects.

Complexity Time complexity is linear. The number of applications of operator+ or `binary_op` done is `n` where `n` is the range `[first, last)`. Space complexity is constant.

inner_product

Description The `inner_product` algorithm computes its result by initializing the accumulator `acc` with initial value `init` and then modifying it as follows:
`acc = acc + (*i1) * (*i2)`

Algorithms Library

Generalized Numeric Algorithms

or
`acc = binary_op1(acc, binary_op2(*i1, *i2))`

for every iterator `i1` in the range
`[first1, last1)`

and `i2` in the range
`[first2, first2 + (last1 - first1))`

in order.

`binary_op1` and `binary_op2` are assumed to cause no side effects.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2,
      class T >
T inner_product
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     T init);
template
    < class InputIterator1,
      class InputIterator2,
      class T,
      class BinaryOperation1,
      class BinaryOperation2 >
T inner_product
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     T init,
     BinaryOperation1 binary_op1,
     BinaryOperation2 binary_op2);
```

Complexity Time complexity is linear. The number of applications of operator+ or `binary_op1`, and the number of applications of operator* or `binary_op2` is `n` where `n` is the size of the range `[first, last)`. Space complexity is constant.

partial_sum

Description The `partial_sum` algorithm computes partial sums of the input sequence and stores the result in the output sequence.

Formally, `partial_sum` assigns to every iterator `i` in the range `[result, result + (last - first))`

a value correspondingly equal to

$$((...(*first + *(first + 1)) + ...) + (*first + (i - result)))$$

or

$$\text{binary_op}(\text{binary_op}(\dots, \text{binary_op}(*first + *(first + 1)) + \dots) + (*first + (i - result))).$$

`binary_op` is expected not to have any side effects.

Prototype

```
template
    < class InputIterator,
      class OutputIterator >
InputIterator partial_sum
    (InputIterator first,
     InputIterator last,
     OutputIterator result);
template
    < class InputIterator,
      class OutputIterator,
      class BinaryOperation >
InputIterator partial_sum
    (InputIterator first,
     InputIterator last,
     OutputIterator result,
     BinaryOperation binary_op);
```

Remarks The `partial_sum` algorithm returns an iterator referring to the past-the-end location of the result sequence.

NOTE: The result may be equal to `first`; i.e., it is possible for the algorithm to work “in-place”, meaning that the algorithm can generate the partial sums and replace the original sequence with them.

Complexity Time complexity is linear. The number of applications of `operator+` or `binary_op` is one less than `n`, where `n` is the size of the range `[first, last)`. Space complexity is constant.

adjacent_difference

Description `adjacent_difference` assigns to every element referred to by iterator `i` in the range `[result + 1, result + (last - first))`

a value correspondingly equal to

$$*(first + (i - result)) - *(first + (i - result) - 1)$$

or

$$binary_op(*(first + (i - result)), *(first + (i - result) - 1)).$$

`binary_op` is expected not to have any side effects.

Prototype

```
template
    < class InputIterator,
      class OutputIterator >
InputIterator adjacent_difference
    (InputIterator first,
     InputIterator last,
     OutputIterator result);
template
    < class InputIterator,
      class OutputIterator,
      class BinaryOperation>
InputIterator adjacent_difference
    (InputIterator first,
     InputIterator last,
```



```
OutputIterator result,  
BinaryOperation binary_op);
```

- Remarks** `result` may be equal to `first`; i.e., the algorithm can work “in-place”.
- Complexity** Time complexity is linear. The number of applications of `operator-` or `binary_op` is one less than `n` where `n` is the range `[first, last)`. Space complexity is constant.



Numerics Library

This chapter is a reference guide to the ANSI/ISO standard Numeric classes which are used to perform the semi-numerical operations.

Overview of the Numerics Library

This library contains the classes for complex number types, numeric arrays, generalized numeric algorithms, and facilities included from the ISO C library.

The sections in this chapter are:

- [“Numeric Type Requirements” on page 363](#)
- [“Numeric Arrays” on page 364](#)
- [“Generalized Numeric Operations” on page 404](#)

Numeric Type Requirements

The `complex` and `valarray` components are parameterized by the type of information they contain and manipulate. A C++ program shall instantiate these components with types that satisfy the following requirements:

- T is not an abstract class, i.e it has no pure virtual member functions;
- T is not a reference type;
- T is not cv-qualified;
- If T is a class, it has a public default constructor;
- If T is a class, it has a public copy constructor with the signature `T::T(const T&);`
- If T is a class, it has a public destructor;

- If `T` is a class, it has a public assignment operator whose signature is either

`T& T::operator=(const T&) or T& T::operator=(T);`

If `T` is a class, its assignment operator, copy and default constructors, and destructor must correspond to each other in the following sense: Initialization of raw storage using the default constructor, followed by assignment, is semantically equivalent to initialization of raw storage using the copy constructor. Destruction of an object, followed by initialization of its raw storage using the copy constructor, is semantically equivalent to assignment to the original object.

In addition, many member and related functions of `valarray<T>` can be successfully instantiated and will exhibit well-defined behavior if and only if `T` satisfies additional requirements specified for each such member or related function.

Numeric Arrays

The header `<valarray>` defines five template classes: `valarray`, `slice_array`, `gslice_array`, `mask_array` and `indirect_array`, two classes: `slice` and `gslice`, and a series of related function signatures for representing and manipulating arrays of values.

Files `#include <valarray.h>`

The array classes are:

- [“Template Class `valarray`” on page 365](#)
- [“Class `slice`” on page 390](#)
- [“Template class `slice_array`” on page 391](#)
- [“Class `gslice`” on page 394](#)
- [“Template Class `gslice_array`” on page 395](#)
- [“Template Class `mask_array`” on page 398](#)
- [“Template Class `indirect_array`” on page 401](#)

Template Class valarray

Description The template class `valarray<T>` is a one-dimensional smart array, with elements numbered sequentially from zero. It is a representation of the mathematical concept of an ordered set of values. The illusion of higher dimensionality may be produced by the familiar idiom of computed indices, together with the powerful subsetting capabilities provided by the generalized subscript operators.

The topics in this section are:

- [“Constructors valarray” on page 365](#)
- [“Element Access valarray” on page 368](#)
- [“Subset Operations valarray” on page 368](#)
- [“Assignment Operators valarray” on page 367](#)
- [“Unary Operators valarray” on page 368](#)
- [“Computed Assignment Type valarray<T>” on page 369](#)
- [“Computed Assignment Type<T>” on page 371](#)
- [“Overloaded Binary Operators valarray” on page 375](#)
- [“Comparison Operators valarray” on page 379](#)
- [“Overloaded Comparison Operators valarray” on page 381](#)
- [“Member Functions valarray” on page 383](#)
- [“Min And Max Functions valarray” on page 385](#)
- [“Transcendentals valarray” on page 386](#)

Constructors valarray

Default Constructor

Description This constructs an object of class `valarray<T>`, which has zero length until it is passed into a library function as a modifiable lvalue or through a non-constant this pointer.

Prototype `valarray();`

Overloaded Constructors

Prototype `valarray (size_t);`

Remarks This constructor sets the array length equal to the value of the argument. The elements of the array are constructed using the default constructor for the instantiating type T.
`valarray (const T&, size_t);`

Remarks This constructor sets the array equal to the value of the second argument and initializes all the elements with the value of the first argument.
`valarray (const T*, size_t);`

Remarks The array created by this constructor has a length equal to the second argument. The values of the elements of the array are initialized with the first n values pointed to by the first argument. It is necessary that the value of the second argument is greater than the number of vales pointed to by the first argument.

Copy Constructor

Description Copy constructor creates a distinct array rather than a alias.

Prototype `valarray (const valarray<T>&);`

Conversion Constructors

Description These are conversion constructors which convert one of the four reference templates to `valarray`.

Prototype `valarray (const slice_array<T>&);`
`valarray (const gslice_array<T>&);`
`valarray (const mask_array<T>&);`
`valarray (const indirect_array<T>&);`

Destructor

Description Destructor for valarray.

Prototype `~valarray ();`

Assignment Operators valarray

Assignment Operator =

Description The assignment operator modifies the length of the `*this` array to be equal to that of the argument array. Each element of `*this` array is then assigned the value of the corresponding element of the argument array. Assignment is the usual way to change the length of an array after initialization. Assignment results in a distinct array rather than an alias.

Prototype `valarray<T>& operator= (const valarray<T>&);`

Overloaded Assignment Operators

Prototype `valarray<T>& operator=
 (const slice_array<T>&);
valarray<T>& operator=
 (const gslice_array<T>&);
valarray<T>& operator=
 (const mask_array<T>&);
valarray<T>& operator=
 (const indirect_array<T>&);`

Remarks These operators allow the results of a generalized subscripting operation to be assigned directly to a valarray.

Element Access valarray

Subscript Operator []

Description For const valarray objects, the subscript operator returns the value of the corresponding element of the array. For non-const valarray objects, a reference to the corresponding element of the array is returned.

Prototype `T operator[] (size_t) const;`
`T& operator[] (size_t);`

Subset Operations valarray

Subscript Operator []

Description Each of these operations returns a subset of the array. The const-qualified versions return this subset as a new valarray. The non-const versions return a class template object which has reference semantics to the original array.

Prototype `valarray<T> operator[](slice) const;`
`slice_array<T> operator[](slice);`
`valarray<T> operator[](const gslice&) const;`
`gslice_array<T> operator[] (const gslice&);`
`valarray<T> operator[]`
`(const valarray<bool>&) const;`
`mask_array<T> operator[](const valarray<bool>&);`
`valarray<T> operator[]`
`(const valarray<size_t>&) const;`
`indirect_array<T> operator[]`
`(const valarray<size_t>&);`

Unary Operators valarray

Description Each of these operators may only be instantiated for a type T to which the indicated operator can be applied and for which the indicated operator returns a value which is of type &T or which may be

unambiguously converted to type T. Each of these operators returns an array whose length is equal to the length of the array. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding element of the array.

Add Operator +

Prototype `valarray<T> operator+() const;`

Minus Operator -

Prototype `valarray<T> operator-() const;`

Complement Operator ~

Prototype `valarray<T> operator~() const;`

Not Operator !

Prototype `valarray<T> operator!() const;`

Computed Assignment Type valarray<T>

Description Each of these operators may only be instantiated for a type T to which the indicated operator can be applied. Each of these operators performs the indicated operation on each of its elements and the corresponding element of the argument array. The array is then returned by reference. If the array and the argument array do not have the same length, the behavior is undefined. The appearance of an array on the left hand side of a computed assignment does not invalidate references or pointers.

Multiply & Assign Operator *=

Prototype `valarray<T>& operator*= (const valarray<T>&);`

Divide and Assign Operator /=

Prototype `valarray<T>& operator/= (const valarray<T>&);`

Remainder & Assign Operator %=

Prototype `valarray<T>& operator%= (const valarray<T>&);`

Add & Assign Operator +=

Prototype `valarray<T>& operator+= (const valarray<T>&);`

Minus and Assign Operator -=

Prototype `valarray<T>& operator-= (const valarray<T>&);`

XOR and Assign Operator ^=

Prototype `valarray<T>& operator^= (const valarray<T>&);`

And & Assign Operator &=

Prototype `valarray<T>& operator&= (const valarray<T>&);`

Or & Assign Operator |=

Prototype `valarray<T>& operator|= (const valarray<T>&);`

Not Equal Operator !=

Prototype `valarray<T>& operator!= (const valarray<T>&);`

Right Shift & Assign Operator >>=

Prototype `valarray<T>& operator>>=(const valarray<T>&);`

Computed Assignment Type<T>

Description Each of these operators may only be instantiated for a type T to which the indicated operator can be applied. Each of these operators applies the indicated operation to each element of the array and the scalar argument. The array is then returned by reference. The appearance of an array on the left hand side of a computed assignment does not invalidate references or pointers to the elements of the array.

Multiply & Assign Operator *=

Prototype `valarray<T>& operator*= (const T&);`

Divide & Assign Operator /=

Prototype `valarray<T>& operator/= (const T&);`

Remainder & Assign Operator %=

Prototype `valarray<T>& operator%= (const T&);`

Add & Assign Operator +=

Prototype `valarray<T>& operator+= (const T&);`

Minus & Assign Operator -=

Prototype `valarray<T>& operator-= (const T&);`

XOR & Assign Operator ^=

Prototype `valarray<T>& operator^= (const T&);`

And & Assign Operator &=

Prototype `valarray<T>& operator&= (const T&);`

Not Equal Operator !=

Prototype `valarray<T>& operator|= (const T&);`

Right Shift & Assign Operator >>=

Prototype `valarray<T>& operator>>=(const T&);`

Non-Member Binary Operators valarray

Description Each of these operators may only be instantiated for a type `T` to which the indicated operator can be applied and for which the indicated operator returns a value which is of type `T` or which can be unambiguously converted to type `T`. Each of these operators returns an array whose length is equal to the lengths of the argument arrays. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding elements of the argument arrays. If the argument arrays do not have the same length, the behavior is undefined.

Multiply Operator *

Prototype

```
template
    < class T >
valarray<T> operator*
    (const valarray<T>&,
     const valarray<T>&);
```

Divide Operator /

Prototype

```
template
    < class T >
valarray<T> operator/
```

```
(const valarray<T>&,
const valarray<T>&);
```

Remainder Operator %

Prototype `template`
 `< class T >`
`valarray<T> operator%`
 `(const valarray<T>&,`
 `const valarray<T>&);`

Add Operator +

Prototype `template`
 `< class T >`
`valarray<T> operator+`
 `(const valarray<T>&,`
 `const valarray<T>&);`

Minus Operator -

Prototype `template`
 `< class T >`
 `valarray<T>`
`operator-`
 `(const valarray<T>&,`
 `const valarray<T>&);`

Bitwise XOR Operator ^

Prototype `template`
 `< class T >`
`valarray<T> operator^`
 `(const valarray<T>&,`
 `const valarray<T>&);`

Bitwise And Operator &

Prototype `template
 < class T >
valarray<T> operator&
 (const valarray<T>&,
 const valarray<T>&);`

Bitwise Or Operator

Prototype `template
 < class T >
valarray<T> operator|
 (const valarray<T>&,
 const valarray<T>&);`

Left Shift Operator <<

Prototype `template
 < class T >
valarray<T> operator<<
 (const valarray<T>&,
 const valarray<T>&);`

Right Shift Operator >>

Prototype `template
 < class T>
valarray<T> operator>>
 (const valarray<T>&,
 const valarray<T>&);`

Logical And Operator &&

Prototype `template
 < class T >
valarray<T> operator&&
 (const valarray<T>&,`

```
const valarray<T>&);
```

Logical Or Operator ||

Prototype

```
template
    < class T >
valarray<T> operator||
    (const valarray<T>&,
     const valarray<T>&);
```

Overloaded Binary Operators valarray

Description Each of these operators may only be instantiated for a type T to which the indicated operator can be applied and for which the indicated operator returns a value which is of type T or which can be unambiguously converted to type T. Each of these operators returns an array whose length is equal to the length of the array argument. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding element of the array argument and the scalar argument.

Multiply Operator *

Prototype

```
template
    < class T >
valarray<T> operator*
    (const valarray<T>&,
     const T&);
template
    < class T >
valarray<T> operator*
    (const T&, const
     valarray<T>&);
```

Divide Operator /

Prototype

```
template
    < class T >
```

```
valarray<T> operator/  
    (const valarray<T>&,   
     const T&);  
template  
    < class T>  
valarray<T> operator/  
    (const T&,   
     const valarray<T>&);
```

Remainder Operator %

Prototype

```
template  
    < class T >  
valarray<T >operator%  
    (const valarray<T>&,   
     const T&);  
template  
    < class T >  
valarray<T> operator%  
    (const T&,   
     const valarray<T>&);
```

Add Operator +

Prototype

```
template  
    < class T >  
valarray<T> operator+  
    (const valarray<T>&,   
     const T&);  
template  
    < class T>  
valarray<T> operator+  
    (const T&,   
     const valarray<T>&);
```

Minus Operator -

Prototype

```
template  
    < class T >
```



```
valarray<T> operator-  
    (const valarray<T>&,  
     const T&);  
template  
    < class T > v  
alarray<T> operator-  
    (const T&,  
     const valarray<T>&);
```

Bitwise XOR Operator ^

Prototype

```
template  
    < class T >  
valarray<T> operator^  
    (const valarray<T>&,  
     const T&);  
template  
    < class T >  
valarray<T> operator^  
    (const T&,  
     const valarray<T>&);
```

Bitwise And Operator &

Prototype

```
template  
    < class T >  
valarray<T> operator&  
    (const valarray<T>&,  
     const T&);  
template  
    < class T >  
valarray<T> operator&  
    (const T&,  
     const valarray<T>&);
```

Bitwise Or Operator |

Prototype

```
template  
    < class T >
```

```
valarray<T> operator|  
    (const valarray<T>&,  
     const T&);  
template  
    < class T >  
valarray<T> operator|  
    (const T&,  
     const valarray<T>&);
```

Left Shift Operator <<

Prototype

```
template  
    < class T >  
valarray<T> operator<<  
    (const valarray<T>&, const T&);  
template  
    < class T>  
valarray<T> operator<<  
    (const T&,  
     const valarray<T>&);
```

Right Shift Operator >>

Prototype

```
template  
    < class T >  
valarray<T> operator>>  
    (const valarray<T>&,  
     const T&);  
template  
    < class T >  
valarray<T> operator>>  
    (const T&, const  
     valarray<T>&);
```

Logical And Operator &&

Prototype

```
template  
    < class T >  
valarray<T> operator&&
```

```
        (const valarray<T>&,
         const T&);
template
    < class T >
valarray<T> operator&&
    (const T&,
     const valarray<T>&);
```

Logical Or Operator ||

Prototype

```
template
    < class T >
valarray<T> operator||
    (const valarray<T>&,
     const T&);
template
    < class T >
valarray<T> operator||
    (const T&,
     const valarray<T>&);
```

Comparison Operators valarray

Description Each of these operators may only be instantiated for a type `T` to which the indicated operator can be applied and for which the indicated operator returns a value which is of type `bool` or which can be unambiguously converted to type `bool`. Each of these operators returns a `bool` array whose length is equal to the length of the array arguments. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding elements of the argument arrays. If the two array arguments do not have the same length, the behavior is undefined.

Equality Operator ==

Prototype

```
template
    < class T >
valarray<bool> operator==
    (const valarray<T>&,
     const valarray<T>&);
```

```
        const valarray<T>&);  
template  
    < class T  
valarray<bool> operator!=  
    (const valarray<T>&,  
     const valarray<T>&);
```

Less Than Operator <

Prototype

```
template  
    < class T >  
valarray<bool> operator<  
    (const valarray<T>&,  
     const valarray<T>&);
```

Greater Than Operator >

Prototype

```
template  
    < class T >  
valarray<bool> operator>  
    (const valarray<T>&,  
     const valarray<T>&);
```

Not Equal Operator !=

Prototype

```
template  
    < class T >  
valarray<bool> operator!=  
    (const valarray<T>&,  
     const valarray<T>&);
```

Greater Than or Equal Operator >=

Prototype

```
template  
    < class T >  
valarray<bool> operator>=  
    (const valarray<T>&,  
     const valarray<T>&);
```

Overloaded Comparison Operators **valarray**

Description Each of these operators may only be instantiated for a type **T** to which the indicated operator can be applied and for which the indicated operator returns a value which is of type **bool** or which can be unambiguously converted to type **bool**. Each of these operators returns a **bool** array whose length is equal to the length of the array argument. Each element of the returned array is initialized with the result of applying the indicated operator to the corresponding element of the array and the scalar argument.

Equality Operator **==**

Prototype

```
template
    < class T >
valarray<bool> operator==
    (const valarray&,
     const T&);
template
    < class T>
valarray<bool> operator==
    (const T&,
     const valarray&);
```

Not Equal Operator **!=**

Prototype

```
template
    < class T >
valarray<bool> operator!=
    (const valarray&,
     const T&);
template
    < class T > valarray<bool> operator!=
    (const T&,
     const valarray&);
```

Less Than Operator <

Prototype

```
template
    < class T >
valarray<bool> operator<
    (const valarray&,
     const T&);
template
    < class T >
valarray<bool> operator<
    (const T&,
     const valarray&);
```

Greater Than Operator >

Prototype

```
template
    < class T >
valarray<bool> operator>
    (const valarray&,
     const T&);
template
    < class T >
valarray<bool> operator>
    (const T&,
     const valarray&);
```

Less Than or Equal Operator <=

Prototype

```
template
    < class T >
valarray<bool> operator<=
    (const valarray&,
     const T&);
template
    < class T >
valarray<bool> operator<=
    (const T&,
     const valarray&);
```

Greater Than or Equal Operator >=

Prototype

```
template
    < class T >
valarray<bool> operator>=
    (const valarray&,
     const T&);
template
    < class T >
valarray<bool> operator>=
    (const T&,
     const valarray&);
```

Member Functions valarray

valarray::length

Description This function returns the number of elements in the array.

Prototype `size_t length() const;`

Pointer Conversion

Description A non-constant array may be converted to a pointer to the instantiating type. A constant array may be converted to a pointer to the instantiating type, qualified by `const`. It is guaranteed that `&a[0] == (T*)a` for any non-constant `valarray<T> a`. The pointer returned for a non-constant array (whether or not it points to a type qualified by `const`) is valid for the same duration as a reference returned by the `size_t` subscript operator. The pointer returned for a constant array is valid for the lifetime of the array.

Prototype

```
operator T*();
operator const T*() const;
```

valarray::sum

Description This function may only be instantiated for a type `T` to which operator`+=` can be applied. This function returns the sum of all the elements of the array. If the array has length 0, the behavior is undefined. If the array has length 1, `sum` returns the value of element 0. Otherwise, the returned value is calculated by applying operator`+=` to a copy of an element of the array and all other elements of the array in an unspecified order.

Prototype `T sum() const;`

valarray::fill

Description This function assigns the value of the argument to all the elements of the array. The length of the array is not changed, nor are any pointers or references to the elements of the array invalidated.

Prototype `void fill (const T&);`

valarray::shift

Prototype `valarray<T> shift(int) const;`

Description This function returns an array whose length is identical to the array, but whose element values are shifted the number of places indicated by the argument. A positive argument value results in a left shift, a negative value in a right shift, and a zero value in no shift.

valarray::cshift

Description This function returns an array whose length is identical to the array, but whose element values are shifted in a circular fashion the number of places indicated by the argument. A positive argument value results in a left shift, a negative value in a right shift, and a zero value in no shift.

Prototype `valarray<T> cshift(int) const;`

valarray::apply

Description These functions return an array whose length is equal to the array. Each element of the returned array is assigned the value returned by applying the argument function to the corresponding element of the array.

Prototype `valarray<T> apply(T func(T)) const;
valarray<T> apply(T func(const T&)) const;`

valarray::free

Description This function sets the length of an array to zero.

Prototype `void free();`

Min And Max Functions valarray

valarray::min

Description This function may only be instantiated for a type T to which operator> and operator< may be applied and for which operator> and operator< return a value which is of type bool or which can be unambiguously converted to type bool. This function returns the minimum (a.min()) value found in the argument array a. The value returned for an array of length 0 is undefined. For an array of length 1, the value of element 0 is returned. For all other array lengths, the determination is made using operator> and operator<, in a manner analogous to the application of operator+= for the sum function.

Prototype `template
 < class T >
T min(const valarray<T>& a);`

valarray::max

Description This function may only be instantiated for a type `T` to which `operator>` and `operator<` may be applied and for which `operator>` and `operator<` return a value which is of type `bool` or which can be unambiguously converted to type `bool`. These functions return the maximum (`a.max()`) value found in the argument array `a`. The value returned for an array of length 0 is undefined. For an array of length 1, the value of element 0 is returned. For all other array lengths, the determination is made using `operator>` and `operator<`, in a manner analogous to the application of `operator+=` for the sum function.

Prototype

```
template
    < class T>
T max(const valarray<T>& a);
```

Transcendentals valarray

Description Each of these functions may only be instantiated for a type `T` to which a unique function with the indicated name can be applied. This function must return a value which is of type `T` or which can be unambiguously converted to type `T`.

valarray::abs

Prototype

```
template
    < class T >
valarray<T> abs(const valarray<T>&);
```

valarray::acos

Prototype

```
template
    < class T>
valarray<T> acos(const valarray<T>&);
```

valarray::asin

Prototype `template
 < class T >
valarray<T> asin(const valarray<T>&);`

valarray::atan

Prototype `template
 < class T >
valarray<T> atan(const valarray<T>&);`

valarray::atan2

Prototype `template
 < class T >
valarray<T> atan2
 (const valarray<T>&,
 const valarray<T>&);`

Prototype `template
 < class T >
valarray<T> atan2
 (const valarray<T>&,
 const T&);`

Prototype `template
 < class T >
valarray<T> atan2
 (const T&,
 const valarray<T>&);`

valarray::cos

Prototype `template
 < class T >
valarray<T> cos (const valarray<T>&);`

valarray::cosh

Prototype `template
 < class T >
valarray<T> cosh(const valarray<T>&);`

valarray::exp

Prototype `template
 < class T >
valarray<T> exp(const valarray<T>&);`

valarray::log

Prototype `template
 < class T >
valarray<T> log(const valarray<T>&);`

valarray::log10

Prototype `template
 < class T >
valarray<T> log10(const valarray<T>&);`

valarray::pow

Prototype `template
 < class T >
valarray<T> pow
 (const valarray<T>&,
 const valarray<T>&);`

Prototype `template
 < class T >
valarray<T> pow
 (const valarray<T>&,
 const T&);`

Prototype `template
 < class T >
valarray<T> pow
 (const T&,
 const valarray<T>&);`

valarray::sin

Prototype `template
 < class T >
valarray<T> sin(const valarray<T>&);`

valarray::sinh

Prototype `template
 < class T >
valarray<T> sinh(const valarray<T>&);`

valarray::sqrt

Prototype `template
 < class T >
valarray<T> sqrt (const valarray<T>&);`

valarray::tan

Prototype `template
 < class T >
valarray<T> tan(const valarray<T>&);`

valarray::tanh

Prototype `template
 < class T >
valarray<T> tanh(const valarray<T>&);`

Class slice

Description The slice class represents a BLAS-like slice from an array. Such a slice is specified by a starting index, a length, and a stride.

Prototype

```
class slice {
    public:
        slice();
        slice(size_t, size_t, size_t);

        size_t start() const;
        size_t length() const;
        size_t stride() const;
};
```

The topics in this section are:

- [“Constructors slice” on page 390](#)
- [“Access Functions slice” on page 391](#)

Constructors slice

Default Constructor

Description The default constructor for slice creates a slice which specifies no elements. A default constructor is provided only to permit the declaration of arrays of slices.

Prototype `slice();`

Overloaded and Copy Constructors

Description The constructor with arguments for a slice takes a start, length, and stride parameter.

Prototype

```
slice(
    size_t start,
    size_t length,
    size_t stride);
```

```
slice(const slice&);
```

Access Functions slice

Description These functions return the start, length, or stride specified by a slice object.

slice::start

Prototype `size_t start() const;`

slice::length

Prototype `size_t length() const;`

slice::stride

Prototype `size_t stride() const;`

Template class slice_array

Description The `slice_array` template is a helper template used by the slice subscript operator `slice_array<T> valarray<T>::operator[] (slice)`; It has reference semantics to a subset of an array specified by a slice object.

The topics in this section are:

- [“Constructors slice_array” on page 392](#)
- [“Assignment Operators slice_array” on page 392](#)
- [“Computed Assignment slice_array” on page 392](#)
- [“Public Member Function slice_array” on page 394](#)—the `fill` function

Constructors slice_array

Default and Copy Constructor

Description The `slice_array` template has no public constructors. These constructors are declared to be private. These constructors need not be defined.

Prototype `slice_array();`

Prototype `slice_array(const slice_array&);`

Assignment Operators slice_array

Assignment Operator =

Description The second of these two assignment operators is declared private and need not be defined. The first has reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which the `slice_array` object refers.

Prototype `void operator= (const valarray<T>&) const;`
`slice_array& operator=(const slice_array&);`

Computed Assignment slice_array

Description These computed assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the `slice_array` object refers.

Multiply & Assign Operator *=

Prototype `void operator*= (const valarray<T>&) const;`

Divide & Assign Operator /=

Prototype `void operator/= (const valarray<T>&) const;`

Remainder & Assign Operator %=

Prototype `void operator%= (const valarray<T>&) const;`

Add & Assign Operator +=

Prototype `void operator+= (const valarray<T>&) const;`

Minus & Assign Operator -=

Prototype `void operator-= (const valarray<T>&) const;`

XOR & Assign Operator ^=

Prototype `void operator^= (const valarray<T>&) const;`

And & Assign Operator &=

Prototype `void operator&= (const valarray<T>&) const;`

Or & Assign Operator |=

Prototype `void operator|= (const valarray<T>&) const;`

Left Shift & Assign Operator <<=

Prototype `void operator<<=(const valarray<T>&) const;`

Right shift & Assign Operator >>=

Prototype `void operator>>=(const valarray<T>&) const;`

Public Member Function slice_array

slice_array::fill

Description This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `slice_array` object refers.

Prototype `void fill(const T&);`

Class gslice

Description This class represents a generalized slice out of an array. A `gslice` is defined by a starting offset (s), a set of lengths (l_j), and a set of strides (d_j). The number of lengths must equal the number of strides. A `gslice` represents a mapping from a set of indices (i_j), equal in number to the number of strides, to a single index k . It is useful for building multidimensional array classes using the `valarray` template, which is one-dimensional. The set of one-dimensional index values specified by a `gslice` are $k = s + \sum i_j d_j$ where the multidimensional indices i_j range in value from 0 to $l_j - 1$. It is possible to have degenerate generalized slices in which an address is repeated. If a degenerate slice is used as the argument to the non-const version of `operator[] (const gslice&)`, the resulting behavior is undefined.

The topics in this section are:

- [“Constructors gslice” on page 394](#)
- [“Access Functions gslice” on page 395](#)

Constructors gslice

Default Constructor

Description The default constructor creates a `gslice` which specifies no elements.

Prototype `gslice ();`

Overloaded Constructors

Description The constructor with arguments builds a `gslice` based on a specification of start, lengths, and strides, as explained in the previous section.

Prototype

```
gslice (size_t start,  
        const valarray<size_t>& lengths,  
        const valarray<size_t>& strides);  
gslice (const gslice&);
```

Access Functions `gslice`

Description These access functions return the representation of the start, lengths, or strides specified for the `gslice`.

`gslice::start`

Prototype `size_t start() const;`

`gslice::length`

Prototype `valarray<size_t> length() const;`

`gslice::stride`

Prototype `valarray<size_t> stride() const;`

Template Class `gslice_array`

Description This template is a helper template used by the slice subscript operator `gslice_array<T> valarray<T>::operator[] (const gslice&);` It has reference semantics to a subset of an array specified by a `gslice` object. Thus, the expression `a[gslice(1, length, stride)] = b` has the effect of assigning the elements of `b` to a generalized slice of the elements in `a`.

The topics in this section are:

- [“Constructors *gslice_array*” on page 396](#)
- [“Assignment *gslice_array*” on page 396](#)
- [“Computed Assignment *gslice_array*” on page 396](#)
- [“Public Member Function *gslice_array*” on page 398](#)—the `fill` function

Constructors *gslice_array*

Default and Copy Constructors

Description The *gslice_array* template has no public constructors. It declares the constructor to be private.

Prototype `gslice_array();`
`gslice_array(const gslice_array&);`

Assignment *gslice_array*

Assignment Operator =

Description The second of these two assignment operators is declared private and need not be defined. The first has reference semantics, assigning the values of the argument array elements to selected elements of the *valarray*<T> object to which the *gslice_array* refers.

Prototype `void operator=(const valarray<T>&) const;`
`gslice_array& operator=(const gslice_array&);`

Computed Assignment *gslice_array*

Description These computed assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the *valarray*<T> object to which the *gslice_array* object refers.

Multiply & Assign Operator *=

Prototype `void operator*= (const valarray<T>&) const;`

Divide & Assign Operator /=

Prototype `void operator/= (const valarray<T>&) const;`

Remainder & Assign Operator %=

Prototype `void operator%= (const valarray<T>&) const;`

Add & Assign Operator +=

Prototype `void operator+= (const valarray<T>&) const;`

Minus & Assign Operator -=

Prototype `void operator-= (const valarray<T>&) const;`

XOR & Assign Operator ^=

Prototype `void operator^= (const valarray<T>&) const;`

And & Assign Operator &=

Prototype `void operator&= (const valarray<T>&) const;`

Or & Assign Operator |=

Prototype `void operator|= (const valarray<T>&) const;`

Left Shift & Assign Operator <<=

Prototype `void operator<<=(const valarray<T>&) const;`

Right Shift & Assign Operator >>=

Prototype `void operator>>=(const valarray<T>&) const;`

Public Member Function gslice_array

gslice_array::fill

Description This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `gslice_array` object refers.

Prototype `void fill(const T&);`

Template Class mask_array

Description This template is a helper template used by the mask subscript operator: `mask_array<T> valarray<T>::operator[](const valarray<bool>&)`. It has reference semantics to a subset of an array specified by a `boolean` mask. Thus, the expression `a[mask] = b;` has the effect of assigning the elements of `b` to the masked elements in `a` (those for which the corresponding element in `mask` is true).

The topics in this section are:

- [“Constructors mask_array” on page 399](#)
- [“Assignment mask_array” on page 399](#)
- [“Computed Assignment mask_array” on page 399](#)
- [“Public Member Function mask_array” on page 401](#)—the `fill` function

Constructors mask_array

Constructors

Description The `mask_array` template has no public constructors. It declares the above constructors to be private. These constructors need not be defined.

Prototype `mask_array();`
`mask_array(const mask_array&);`

Assignment mask_array

Assignment Operator =

Description The second of these two assignment operators is declared private and need not be defined. The first has reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which it refers.

Prototype `void operator= (const valarray<T>&) const;`
`mask_array& operator= (const mask_array&);`

Computed Assignment mask_array

Description These computed assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the mask object refers.

Multiply & Assign Operator *=

Prototype `void operator*= (const valarray<T>&) const;`

Divide & Assign Operator /=

Prototype `void operator/= (const valarray<T>&) const;`

Remainder & Assign Operator %=

Prototype `void operator%= (const valarray<T>&) const;`

Add & Assign Operator +=

Prototype `void operator+= (const valarray<T>&) const;`

Minus & Assign Operator -=

Prototype `void operator-= (const valarray<T>&) const;`

XOR & Assign Operator ^=

Prototype `void operator^= (const valarray<T>&) const;`

And & Assign Operator &=

Prototype `void operator&= (const valarray<T>&) const;`

Or & Assign Operator |=

Prototype `void operator|= (const valarray<T>&) const;`

Left Shift & Assign Operator <<=

Prototype `void operator<<=(const valarray<T>&) const;`

Right Shift & Assign Operator >>=

Prototype `void operator>>=(const valarray<T>&) const;`

Public Member Function mask_array

mask_array::fill

Prototype `void fill(const T&);`

Description This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `mask_array` object refers.

Template Class indirect_array

Description This template is a helper template used by the indirect subscript operator `indirect_array<T> valarray<T>::operator[](const valarray<int>&)`. It has reference semantics to a subset of an array specified by an `indirect_array`. Thus the expression `a[indirect] = b`; has the effect of assigning the elements of `b` to the elements in `a` whose indices appear in `indirect`.

The topics in this section are:

- [“Constructors indirect_array” on page 401](#)
- [“Assignment indirect_array” on page 402](#)
- [“Computed Assignment indirect_array” on page 402](#)
- [“Public Member Function indirect_array” on page 403](#)—the `fill` function

Constructors indirect_array

Default and Copy Constructors

Description The `indirect_array` template has no public constructors. The constructors listed above are private. These constructors need not be defined.

Prototype `indirect_array();`
 `indirect_array(const indirect_array&);`

Assignment indirect_array

Assignment Operator =

Description The second of these two assignment operators is declared private and need not be defined. The first has reference semantics, assigning the values of the argument array elements to selected elements of the `valarray<T>` object to which it refers. If the `indirect_array` specifies an element in the `valarray<T>` object to which it refers more than once, the behavior is undefined.

Prototype

```
void operator=
    (const valarray<T>&) const;
indirect_array& operator=
    (const indirect_array&);
```

Computed Assignment indirect_array

Description These computed assignments have reference semantics, applying the indicated operation to the elements of the argument array and selected elements of the `valarray<T>` object to which the `indirect_array` object refers. If the `indirect_array` specifies an element in the `valarray<T>` object to which it refers more than once, the behavior is undefined.

Multiply & Assign Operator *=

Prototype `void operator*= (const valarray<T>&) const;`

Divide & Assign Operator /=

Prototype `void operator/= (const valarray<T>&) const;`

Remainder & Assign Operator %=

Prototype `void operator%= (const valarray<T>&) const;`

Add & Assign Operator +=

Prototype `void operator+= (const valarray<T>&) const;`

Minus & Assign Operator -=

Prototype `void operator-= (const valarray<T>&) const;`

XOR & Assign Operator ^=

Prototype `void operator^= (const valarray<T>&) const;`

And & Assign Operator &=

Prototype `void operator&= (const valarray<T>&) const;`

Or & Assign Operator |=

Prototype `void operator|= (const valarray<T>&) const;`

Left Shift & Assign Operator <<=

Prototype `void operator<<=(const valarray<T>&) const;`

Right Shift & Assign Operator >>=

Prototype `void operator>>=(const valarray<T>&) const;`

Public Member Function indirect_array

indirect_array::fill

Description This function has reference semantics, assigning the value of its argument to the elements of the `valarray<T>` object to which the `indirect_array` object refers.

Prototype `void fill(const T&);`

Generalized Numeric Operations

The classes are:

- [“Template Class accumulate” on page 404](#)
- [“Template Class inner_product” on page 405](#)
- [“Template Class partial_sum” on page 405](#)
- [“Template Class adjacent_difference” on page 406](#)

See also [“Generalized Numeric Algorithms” on page 356](#).

Template Class accumulate

Description Initializes the accumulator `acc` with the initial value `init` and then modifies it with `acc = acc + *i` or `acc = binary_op(acc, *i)` for every iterator `i` in the range `[first, last)` in order. This function requires that `binary_op` shall not cause side effects.

Prototype

```
template
    < class InputIterator,
      class T >
T accumulate
    (InputIterator first,
     InputIterator last,
     T init);
template
    < class InputIterator,
      class T,
      class BinaryOperation >
T accumulate
    (InputIterator first,
     InputIterator last,
     T init,
     BinaryOperation binary_op);
```

Template Class inner_product

Description Computes its result by initializing the accumulator `acc` with the initial value `init` and then modifying it with `acc = acc + (*i1) * (*i2)` or `acc = binary_op1(acc, binary_op2(*i1, *i2))` for every iterator `i1` in the range `[first, last)` and iterator `i2` in the range `[first2, first2 + (last - first))` in order. This function requires that `binary_op1` and `binary_op2` shall not cause side effects.

Prototype

```
template
    < class InputIterator1,
      class InputIterator2,
      class T >
T inner_product
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2,
     T init);
template
    < class InputIterator1,
      class InputIterator2,
      class T,
      class BinaryOperation1,
      class BinaryOperation2 >
T inner_product
    (InputIterator1 first1,
     InputIterator1 last1,
     InputIterator2 first2, T init,
     BinaryOperation1 binary_op1,
     BinaryOperation2 binary_op2);
```

Template Class partial_sum

Description Assigns to every iterator `i` in the range `[result, result + (last - first))` a value correspondingly equal to `((...(*first + *(first + 1)) + ...) + *(first + (i - result)))` or `binary_op(binary_op(...,`

Numerics Library

Template Class *adjacent_difference*

`binary_op(*first, *(first + 1),...), *(first + (i - result))`). This function returns `result + (last - first)`. The complexity of this function is exactly `(last - first) - 1` applications of `binary_op`. This function requires `binary_op` is expected not to have any side effects. The result may be equal to `first`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator >
OutputIterator partial_sum
    (InputIterator first,
     InputIterator last,
     OutputIterator result);
template
    < class InputIterator,
      class OutputIterator,
      class BinaryOperation >
OutputIterator partial_sum
    (InputIterator first,
     InputIterator last,
     OutputIterator result,
     BinaryOperation binary_op);
```

Template Class *adjacent_difference*

Description Assigns to every element referred to by iterator `i` in the range `[result + 1, result + (last - first))` a value correspondingly equal to `*(first + (i - result)) - *(first + (i - result) - 1)` or `binary_op(*(first + (i - result)), *(first + (i - result) - 1))`. Result gets the value of `*first`. This function requires `binary_op` shall not have any side effects. Result may be equal to `first`. This function returns `result + (last - first)`. The complexity of this function is exactly `(last - first) - 1` applications of `binary_op`.

Prototype

```
template
    < class InputIterator,
      class OutputIterator >
```

```
OutputIterator adjacent_difference
    (InputIterator first,
     InputIterator last,
     OutputIterator result);
template
    < class InputIterator,
      class OutputIterator,
      class BinaryOperation >
OutputIterator adjacent_difference
    (InputIterator first,
     InputIterator last,
     OutputIterator result,
     BinaryOperation binary_op);
```

Numerics Library

Template Class adjacent_difference



26.2 Complex Class

The header `<complex>` defines a template class, and facilities for representing and manipulating complex numbers.

Overview of the Complex Class Library

The header `<complex>` defines classes, operators, and functions for representing and manipulating complex numbers

The topics in this section are:

- [“Header `<complex>`” on page 410](#), shows the complex header class declarations
- [“26.2.3 Complex Specializations” on page 414](#), lists the float, double and long double specializations
- [“Complex Template Class” on page 416](#), is a template class for complex numbers.

`_MSL_CX_LIMITED_RANGE`

This flag effects the `*` and `/` operators of complex.

When defined, the “normal” formulas for multiplication and division are used. They may execute faster on some machines. However, infinities will not be properly calculated, and there is more roundoff error potential.

If the flag is undefined (default), then more complicated algorithms (from the C standard) are used which have better overflow and underflow characteristics and properly propagate infinity. Flipping this switch requires recompilation of the C++ library.

26.2 Complex Class

Header <complex>

NOTE: It is recommend that the `ansi_prefix.xxx.h` is the place to define this flag if you want the simpler and faster multiplication and division algorithms.

Header <complex>

The header <complex> defines classes, operators, and functions for representing and manipulating complex numbers

Listing 12.1 Header <complex> forward declarations

```
namespace std {  
// forward declarations  
template<class T> class complex;  
template<> class complex<float>;  
template<> class complex<double>;  
template<> class complex<long double>;
```

26.2.6 operators:

```
template<class T> complex<T> operator+  
    (const complex<T>&, const complex<T>&);  
template<class T> complex<T> operator+  
    (const complex<T>&, const T&);  
template<class T> complex<T> operator+  
    (const T&, const complex<T>&);  
template<class T> complex<T> operator-  
    (const complex<T>&, const complex<T>&);  
template<class T> complex<T> operator-  
    (const complex<T>&, const T&);  
template<class T> complex<T> operator-  
    (const T&, const complex<T>&);  
template<class T> complex<T> operator*  
    (const complex<T>&, const complex<T>&);  
template<class T> complex<T> operator*  
    (const complex<T>&, const T&);  
template<class T> complex<T> operator*  
    (const T&, const complex<T>&);
```

```
template<class T> complex<T> operator/
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator/
    (const complex<T>&, const T&);
template<class T> complex<T> operator/
    (const T&, const complex<T>&);
template<class T> complex<T> operator+
    (const complex<T>&);
template<class T> complex<T> operator-
    (const complex<T>&);
template<class T> bool operator==
    (const complex<T>&, const complex<T>&);
template<class T> bool operator==
    (const complex<T>&, const T&);
template<class T> bool operator==
    (const T&, const complex<T>&);
template<class T> bool operator!=
    (const complex<T>&, const complex<T>&);
template<class T> bool operator!=
    (const complex<T>&, const T&);
template<class T> bool operator!=
    (const T&, const complex<T>&);
template<class T, class charT, class traits>
basic_istream<charT, traits>& operator>>
    (basic_istream<charT, traits>&, complex<T>&);
template<class T, class charT, class traits>
basic_ostream<charT, traits>& operator<<
    (basic_ostream<charT, traits>&, const complex<T>&);
```

26.2.7 values:

```
template<class T> T real(const complex<T>&);
template<class T> T imag(const complex<T>&);
template<class T> T abs(const complex<T>&);
template<class T> T arg(const complex<T>&);
template<class T> T norm(const complex<T>&);
template<class T> complex<T> conj(const complex<T>&);
template<class T> complex<T> polar(const T&, const T&);
```

26.2 Complex Class

Header `<complex>`

26.2.8 transcendentals:

```
template<class T> complex<T> cos (const complex<T>&);
template<class T> complex<T> cosh (const complex<T>&);
template<class T> complex<T> exp (const complex<T>&);
template<class T> complex<T> log (const complex<T>&);
template<class T> complex<T> log10(const complex<T>&);
template<class T> complex<T> pow(const complex<T>&, int);
template<class T> complex<T> pow(const complex<T>&, const T&);
template<class T> complex<T> pow
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> pow(const T&, const complex<T>&);
template<class T> complex<T> sin (const complex<T>&);
template<class T> complex<T> sinh (const complex<T>&);
template<class T> complex<T> sqrt (const complex<T>&);
template<class T> complex<T> tan (const complex<T>&);
template<class T> complex<T> tanh (const complex<T>&);
}
```

Template Class Complex

```
namespace std {
template<class T>
class complex {
public:
    typedef T value_type;
    complex(const T& re = T(), const T& im = T());
    complex(const complex&);
    template<class X> complex(const complex<X>&);
    T real() const;
    T imag() const;
    complex<T>& operator= (const T&);
    complex<T>& operator+=(const T&);
    complex<T>& operator-=(const T&);
    complex<T>& operator*=(const T&);
    complex<T>& operator/=(const T&);
    complex& operator=(const complex&);
    template<class X> complex<T>& operator= (const complex<X>&);
    template<class X> complex<T>& operator+=(const complex<X>&);
    template<class X> complex<T>& operator-=(const complex<X>&);
};
```

```

template<class X> complex<T>& operator*=(const complex<X>&);
template<class X> complex<T>& operator/=(const complex<X>&);
};
template<class T> complex<T> operator+
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator+
    (const complex<T>&, const T&);
template<class T> complex<T> operator+
    (const T&, const complex<T>&);
template<class T> complex<T> operator-
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator-
    (const complex<T>&, const T&);
template<class T> complex<T> operator-
    (const T&, const complex<T>&);
template<class T> complex<T> operator*
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator*
    (const complex<T>&, const T&);
template<class T> complex<T> operator*
    (const T&, const complex<T>&);
template<class T> complex<T> operator/
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator/
    (const complex<T>&, const T&);
template<class T> complex<T> operator/
    (const T&, const complex<T>&);
template<class T> complex<T> operator+
    (const complex<T>&);
template<class T> complex<T> operator-
    (const complex<T>&);
template<class T> bool operator==
    (const complex<T>&, const complex<T>&);
template<class T> bool operator==
    (const complex<T>&, const T&);
template<class T> bool operator==
    (const T&, const complex<T>&);
template<class T> bool operator!=
    (const complex<T>&, const complex<T>&);
template<class T> bool operator!=

```

26.2 Complex Class

26.2.3 Complex Specializations

```
(const complex<T>&, const T&);
template<class T> bool operator!=
    (const T&, const complex<T>&);
template<class T, class charT, class traits>
basic_istream<charT, traits>& operator>>
    (basic_istream<charT, traits>&, complex<T>&);
template<class T, class charT, class traits>
basic_ostream<charT, traits>& operator<<
    (basic_ostream<charT, traits>&, const complex<T>&);
};
```

26.2.3 Complex Specializations

The standard specialize the template complex class for float, double and long double types.

Listing 12.2 Float specializations

```
template<> class complex<float> {
public:
    typedef float value_type;
    complex(float re = 0.0f, float im = 0.0f);
    explicit complex(const complex<double>&);
    explicit complex(const complex<long double>&);
    float real() const;
    float imag() const;
    complex<float>& operator= (float);
    complex<float>& operator+=(float);
    complex<float>& operator-=(float);
    complex<float>& operator*=(float);
    complex<float>& operator/=(float);
    complex<float>& operator=(const complex<float>&);
    template<class X> complex<float>& operator= (const complex<X>&);
    template<class X> complex<float>& operator+=(const complex<X>&);
    template<class X> complex<float>& operator-=(const complex<X>&);
    template<class X> complex<float>& operator*=(const complex<X>&);
    template<class X> complex<float>& operator/=(const complex<X>&);
};
```

Listing 12.3 Double specializations

```
template<> class complex<double> {
public:
    typedef double value_type;
    complex(double re = 0.0, double im = 0.0);
    complex(const complex<float>&);
    explicit complex(const complex<long double>&);
    double real() const;
    double imag() const;
    complex<double>& operator= (double);
    complex<double>& operator+=(double);
    complex<double>& operator-=(double);
    complex<double>& operator*=(double);
    complex<double>& operator/=(double);
    complex<double>& operator=(const complex<double>&);
    template<class X> complex<double>& operator= (const complex<X>&);
    template<class X> complex<double>& operator+=(const complex<X>&);
    template<class X> complex<double>& operator-=(const complex<X>&);
    template<class X> complex<double>& operator*=(const complex<X>&);
    template<class X> complex<double>& operator/=(const complex<X>&);
};
```

Listing 12.4 Long Double specializations

```
template<> class complex<long double> {
public:
    typedef long double value_type;
    complex(long double re = 0.0L, long double im = 0.0L);
    complex(const complex<float>&);
    complex(const complex<double>&);
    long double real() const;
    long double imag() const;
    complex<long double>& operator=(const complex<long double>&);
    complex<long double>& operator= (long double);
    complex<long double>& operator+=(long double);
    complex<long double>& operator-=(long double);
    complex<long double>& operator*=(long double);
    complex<long double>& operator/=(long double);
    template<class X> complex<long double>& operator=
```

26.2 Complex Class

Complex Template Class

```
(const complex<X>&);
template<class X> complex<long double>& operator+=
    (const complex<X>&);
template<class X> complex<long double>& operator-=
    (const complex<X>&);
template<class X> complex<long double>& operator*=
    (const complex<X>&);
template<class X> complex<long double>& operator/=
    (const complex<X>&);
};
```

Complex Template Class

The template class `complex` contains Cartesian components `real` and `imag` for a complex number.

Remarks The effect of instantiating the template `complex` for any type other than `float`, `double` or `long double` is unspecified.

If the result of a function is not mathematically defined or not in the range of representable values for its type, the behavior is undefined.

The `complex` class consists of:

- [“Constructors and Assignments” on page 416.](#)
- [“Complex Member Functions” on page 417.](#)
- [“Operators” on page 417.](#)

Constructors and Assignments

Constructor, destructor and assignment operators and functions.

Constructors

Description Construct an object of a complex class.

Prototype `complex(const T& re = T(), const T& im = T());`
`complex(const complex&);`


```
template<class X> complex(const complex<X>&);
```

Remarks After construction real equal re and imag equals im.

Assignment Operator

Description An assignment operator for complex classes.

Prototype

```
complex<T>& operator= (const T&);  
complex& operator= (const complex&);  
template<class X> complex<T>& operator=  
    (const complex<X>&);
```

Remarks Assigns a floating point type to the Cartesian complex class.

Complex Member Functions

There are two public member functions

- [“real” on page 417](#)
- [“imag” on page 417](#)

real

Description Retrieves the real component.

Prototype `T real() const;`

imag

Description Retrieves the imag component.

Prototype `T imag() const;`

Operators

Several assignment operators are overloaded for the complex class manipulations.

- [“operator +=” on page 418](#)

26.2 Complex Class

Complex Template Class

- [“operator -=” on page 418](#)
- [“operator *=” on page 419](#)
- [“operator /=” on page 419](#)

operator +=

Description Adds and assigns to a complex class.

Prototype `complex<T>& operator+=(const T&);
template<class X> complex<T>& operator+=
(const complex<X>&);`

Remarks The first operator with a scalar argument adds the scalar value of the right hand side to the real component and stores the result in the object. The imaginary component is left alone.

The second operator with a complex type, adds the complex value of the right hand side to the object and stores the resultant in the object.

Returns The `this` pointer is returned.

operator -=

Description Subtracts and assigns from a complex class.

Prototype `complex<T>& operator-=(const T&);
template<class X> complex<T>& operator-=
(const complex<X>&);`

Remarks The first operator with a scalar argument subtracts the scalar value of the right hand side from the real component and stores the result in the object. The imaginary component is left alone.

The second operator with a complex type, subtracts the complex value of the right hand side from the object and stores the resultant in the object.

Returns The `this` pointer is returned.

operator *=

Description	Multiplies by and assigns to a complex class.
Prototype	<pre>complex<T>& operator*=(const T&); template<class X> complex<T>& operator*= (const complex<X>&);</pre>
Remarks	<p>The first operator with a scalar argument multiplies the scalar value of the right hand side to class object and stores result in the object.</p> <p>The second operator with a complex type, multiplies the complex value of the right hand side to the object and stores the resultant in the object.</p>
Returns	The <code>this</code> pointer is returned.

operator /=

Description	Divides by and assigns to a complex class.
Prototype	<pre>complex<T>& operator/=(const T&); template<class X> complex<T>& operator/= (const complex<X>&);</pre>
Remarks	<p>The first operator with a scalar argument divides the scalar value of the right hand side to class object and stores result in the object.</p> <p>The second operator with a complex type, divides the complex value of the right hand side into the object and stores the resultant in the object.</p>
Returns	The <code>this</code> pointer is returned.

Overloaded Operators and Functions

There are several non member functions and overloaded operators in the complex class library.

["Complex Operators" on page 420](#)

26.2 Complex Class

Complex Template Class

[“Complex Value Operations” on page 423](#)

[“Complex Transcendentals” on page 425](#)

Complex Operators

The overloaded complex operators consists of:

- [“operator +” on page 420](#)
- [“operator -” on page 420](#)
- [“operator /” on page 421](#)
- [“operator !=” on page 422](#)
- [“operator >>” on page 422](#)
- [“operator <<” on page 423](#)

operator +

Description Adds to the complex class.

Prototype

```
template<class T> complex<T> operator+
    const complex<T>&, const complex<T>&);
template<class T> complex<T> operator+
    (const complex<T>&, const T&);
template<class T> complex<T> operator+
    (const T&, const complex<T>&);

template<class T> complex<T> operator+
    (const complex<T>&);
```

Remarks The addition performs an += operation.

Returns The complex class after the addition.

operator -

Description Subtracts from the complex class.

Prototype

```
template<class T> complex<T> operator-
    (const complex<T>&, const complex<T>&);
```

```
template<class T> complex<T> operator-
    (const complex<T>&, const T&);
template<class T> complex<T> operator-
    (const T&, const complex<T>&);

template<class T> complex<T> operator-
    (const complex<T>&);
```

Remarks The subtraction performs a -= operation.

Returns The complex class after the Subtraction.

operator *

Description Multiplies the complex class.

Prototype

```
template<class T> complex<T> operator*
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator*
    (const complex<T>&, const T&);
template<class T> complex<T> operator*
    (const T&, const complex<T>&);
```

Remarks The multiplication performs a *= operation.

Returns The complex class after the multiplication.

operator /

Description Divides from the complex class.

Prototype

```
template<class T> complex<T> operator/
    (const complex<T>&, const complex<T>&);
template<class T> complex<T> operator/
    (const complex<T>&, const T&);
template<class T> complex<T> operator/
    (const T&, const complex<T>&);
```

Remarks The division performs an /= operation.

26.2 Complex Class

Complex Template Class

Returns The complex class after the division.

operator ==

Description A boolean equality comparison.

Prototype

```
template<class T> bool operator==  
    (const complex<T>&, const complex<T>&);  
template<class T> bool operator==  
    (const complex<T>&, const T&);  
template<class T> bool operator==  
    (const T&, const complex<T>&);
```

Remarks Returns true if the real and the imaginary components are equal.

operator !=

Description A boolean non equality comparison.

Prototype

```
template<class T> bool operator!=  
    (const complex<T>&, const complex<T>&);  
template<class T> bool operator!=  
    (const complex<T>&, const T&);  
template<class T> bool operator!=  
    (const T&, const complex<T>&);
```

Remarks Returns true if the real or the imaginary components are not equal.

operator >>

Description Extracts a complex type from a stream.

Prototype

```
template<class T, class charT, class traits>  
basic_istream<charT, traits>& operator>>  
    (basic_istream<charT, traits>&, complex<T>&);
```

Remarks Extracts in the form of u, (u), or (u,v) where u is the real part and v is the imaginary part.

Any failure in extraction will set the failbit and result in undefined behavior.

operator <<

Description Inserts a complex number into a stream.

Prototype `template<class T, class charT, class traits>
basic_ostream<charT, traits>& operator<<
(basic_ostream<charT, traits>&
const complex<T>&);`

Complex Value Operations

The complex value operations consists of:

- [“real” on page 423](#)
- [“imag” on page 423](#)
- [“abs” on page 424](#)
- [“arg” on page 424](#)
- [“norm” on page 424](#)
- [“conj” on page 424](#)
- [“polar” on page 425](#)

real

Description Retrieves the real component of a complex class.

Prototype `template<class T>
T real(const complex<T>&);`

Remarks Returns the real component of the argument.

imag

Description Retrieves the imaginary component of a complex class.

Prototype `template<class T>`

26.2 Complex Class

Complex Template Class

`T imag(const complex<T>&);`

Remarks Returns the imaginary component of the argument.

abs

Description Determines the absolute value of a complex class.

Prototype `template<class T>
T abs(const complex<T>&);`

Remarks Returns the absolute value of the complex class argument.

arg

Description Determines the phase angle.

Prototype `template<class T>
T arg(const complex<T>&);`

Remarks Returns the phase angle of the complex class argument or `atan2(imag(x), real(x))`.

norm

Description Determines the squared magnitude.

Prototype `template<class T>
T norm(const complex<T>&);`

Remarks The squared magnitude of the complex class.

conj

Description Determines the complex conjugate.

Prototype `template<class T>
complex<T> conj(const complex<T>&);`

Remarks Returns the complex conjugate of the complex class argument.

polar

Description	Determines the polar coordinates.
Prototype	<pre>template<class T> complex<T> polar(const T&, const T&);</pre>
Remarks	Returns the complex value corresponding to a complex number whose magnitude is the first argument and whose phase angle is the second argument.

Complex Transcendentals

The complex transcendentals consists of:

- [“cos” on page 425](#)
- [“cosh” on page 426](#)
- [“exp” on page 426](#)
- [“log” on page 426](#)
- [“log10” on page 426](#)
- [“pow” on page 427](#)
- [“sin” on page 427](#)
- [“sinh” on page 427](#)
- [“sqrt” on page 427](#)
- [“tan” on page 428](#)
- [“tanh” on page 428](#)

cos

Description	Determines the cosine.
Prototype	<pre>template<class T> complex<T> cos (const complex<T>&);</pre>
Remarks	Returns the cosine of the complex class argument.

26.2 Complex Class

Complex Template Class

cosh

Description Determines the hyperbolic cosine.

Prototype `template<class T>
complex<T> cosh (const complex<T>&);`

Remarks Returns the cosine of the complex class argument.

exp

Description Determines the exponential.

Prototype `template<class T>
complex<T> exp (const complex<T>&);`

Remarks Returns the base exponential of the complex class argument.

log

Description Determines the natural base logarithm.

Prototype `template<class T>
complex<T> log (const complex<T>&);`

Remarks Returns the natural base logarithm of the complex class argument, in the range of a strip mathematically unbounded along the real axis and in the interval of $[-i\pi, i\pi]$ along the imaginary axis. Where the argument is a negative real number, $\text{imag}(\log(\text{cpx}))$, is π .

log10

Description Determines the logarithm to base ten.

Prototype `template<class T>
complex<T> log10(const complex<T>&);`

Remarks Returns the logarithm base(10) of the argument `cpx` defined as $\log(\text{cpx}) / \log(10)$.

pow

Description Raises the complex class to a set power.

Prototype

```
template<class T>
    complex<T> pow(const complex<T>&, int);
template<class T>
    complex<T> pow(const complex<T>&, const T&);
template<class T> complex<T> pow
    (const complex<T>&, const complex<T>&);
template<class T>
    complex<T> pow(const T&, const complex<T>&);
```

Remarks Returns the complex class raised to the power of second argument defined as the exponent of (the second argument times the log of the first argument).

The value for `pow(0,0)` will return (nan, nan).

sin

Description Determines the sine.

Prototype

```
template<class T>
    complex<T> sin (const complex<T>&);
```

Remarks Returns the sine of the complex class argument.

sinh

Description Determines the hyperbolic sine.

Prototype

```
template<class T>
    complex<T> sinh (const complex<T>&);
```

Remarks Returns the hyperbolic sine of the complex class argument.

sqrt

Description Determines the square root.

26.2 Complex Class

Complex Template Class

Prototype `template<class T>
 complex<T> sqrt (const complex<T>&);`

Remarks Returns the square root of the complex class argument in the range of right half plane. If the argument is a negative real number, the value returned lies on the positive imaginary axis.

tan

Description Determines the tangent.

Prototype `template<class T>
 complex<T> tan (const complex<T>&);`

Remarks Returns the tangent of the complex class argument.

tanh

Description Determines the hyperbolic tangent.

Prototype `template<class T>
 complex<T> tanh (const complex<T>&);`

Remarks Returns the hyperbolic tangent of the complex class argument.



27.1 Input and Output Library

A listing of the set of components that C++ programs may use to perform input/output operations.

Overview of Input and Output Library

The sections in this chapter are:

- [“Input and Output Library Summary” on page 429](#)
- [“27.1 Iostreams requirements” on page 430](#)

Input and Output Library Summary

This library includes the headers.

Table 13.1 **Input/Output Library Summary**

Include	Purpose
<code><iosfwd></code>	Forward declarations
<code><iostream></code>	Standard iostream objects
<code><ios></code>	Iostream base classes
<code><streambuf></code>	Stream buffers
<code><istream></code>	Formatting and manipulators
<code><ostream></code>	
<code><iomanip></code>	
<code><sstream></code>	String streams

27.1 Input and Output Library

27.1 *Iostreams* requirements

Include	Purpose
<code><cstdlib></code>	
<code><fstream></code>	File Streams
<code><cstdio></code>	
<code><wchar></code>	

27.1 *Iostreams* requirements

No requirements library has been defined.

Topics in this section are:

- [“27.1.1 Definitions” on page 430](#)
- [“27.1.2 Type requirements” on page 431](#)
- [“27.1.2.5 Type `SZ_T`” on page 431](#)

27.1.1 Definitions

Additional definitions are:

- `character` - A unit that can represent text
- `character container type` - A class or type used to represent a character.
- `iostream class templates` - A templates that take two arguments: `charT` and `traits`. The argument `charT` is a character container type. The argument `traits` is a structure which defines characteristics and functions of the `charT` type.
- `narrow-oriented iostream classes` - These classes are template instantiation classes. The traditional `iostream` classes are `narrow-oriented iostream classes`.
- `wide-oriented iostream classes` - These classes are template instantiation classes. They are used for the character container class `wchar_t`.
- `repositional streams and arbitrary-positional streams` - A `repositional stream` can seek to only a pre-

viously encountered position. An `arbitrary-positional stream` can integral position within the length of the stream.

27.1.2 Type requirements

Several types are required by the standards, they are consolidated in strings (chapter 21.)

27.1.2.5 Type `SZ_T`

A type that represents one of the signed basic integral types. It is used to represent the number of characters transferred in and input/output operation or for the size of the input/output buffers.

27.1 Input and Output Library

27.1 Iostreams requirements



27.2 Forward Declarations

The header `<iosfwd>` is used for forward declarations of template classes.

Overview of Input and Output Streams Forward Declarations.

The ANSI/ISO standard calls for forward declarations of input and output streams for basic input and output, basic input and basic output. This is for both normal and wide character formats.

Header `<iosfwd>`

```
Prototype namespace std {
    template<class charT> class basic_ios;
    template<class charT> class basic_istream;
    template<class charT> class basic_ostream;

    typedef basic_ios<char> ios;
    typedef basic_ios<wchar_t> wios;

    typedef basic_istream<char> istream;
    typedef basic_istream<wchar_t> wistream;

    typedef basic_ostream<char> ostream;
    typedef basic_ostream<wchar_t> wostream;
}
```

Remarks The template class `basic_ios<charT, traits>` serves as a base class for class `basic_istream` and `basic_ostream`.

27.2 Forward Declarations

Header `<iosfwd>`

The class `ios` is an instantiation of `basic_ios` specialized by the type `char`.

The class `wios` is an instantiation of `basic_ios` specialized by the type `wchar_t`.



27.3 Standard Iostream Objects

The include header `<iostream>` declared input and output stream objects. The declared objects are associated with the standard C streams provided for by the functions in `<stdio>`.

Overview of Standard Input and Output Stream Objects.

The ANSI/ISO standard calls for predetermined objects for standard input, output, logging and error reporting. This is initialized for normal and wide character formats.

Header `<iostream>`

Description Declaration of standard objects

Prototype

```
Header <iostream>
namespace std{
extern istream cin;
extern ostream cout;
extern ostream cerr;
extern ostream clog;

extern wistream wcin;
extern wostream wcout;
extern wostream cerr;
extern wostream wclog;
}
```

Additional topics are:

27.3 Standard Iostream Objects

Header `<iostream>`

- [“27.3.1 Narrow stream objects” on page 436](#)
- [“27.3.2 Wide stream objects” on page 437](#)

27.3.1 Narrow stream objects

Description Narrow stream objects provide unbuffered input and output associated with standard input and output declared in `<cstdio>`.

istream cin

Description An unbuffered input stream.

Prototype `istream cin;`

Remarks The object `cin` controls input from an unbuffered stream buffer associated with `stdin` declared in `<cstdio>`. After `cin` is initialized `cin.tie()` returns `cout`.

Return An `istream` object;

ostream cout

Description An unbuffered output stream.

Prototype `ostream cout;`

Remarks The object `cout` controls output to an unbuffered stream buffer associated with `stdout` declared in `<cstdio>`.

Return An `ostream` object;

ostream cerr

Description Controls output to an unbuffered stream.

Prototype `ostream cerr;`

Remarks The object `cerr` controls output to an unbuffered stream buffer associated with `stderr` declared in `<cstdio>`. After `err` is initialized, `err.flags()` and `unitbuf` is nonzero.

Return An ostream object;

ostream clog

Description Controls output to a stream buffer.

Prototype `ostream clog;`

Remarks The object `clog` controls output to a stream buffer associated with `cerr` declared in `<cstdio>`.

Return An ostream object;

27.3.2 Wide stream objects

Description Narrow stream objects provide unbuffered input and output associated with standard input and output declared in `<cstdio>`.

istream win

Description An unbuffered input stream.

Prototype `wistream win;`

Remarks The object `win` controls input from an unbuffered stream buffer associated with `stdin` declared in `<cstdio>`. After `cin` is initialized `win.tie()` returns `wout`.

Return An wistream object;

ostream wout

Description An unbuffered output stream.

27.3 Standard Iostream Objects

Header `<iostream>`

Prototype `wostream wout;`

Remarks The object `cout` controls output to an unbuffered stream buffer associated with `stdout` declared in `<stdio>`.

Return An `wostream` object;

wostream werr

Description Controls output to an unbuffered stream.

Prototype `wostream werr;`

Remarks The object `werr` controls output to an unbuffered stream buffer associated with `stderr` declared in `<stdio>`. After `werr` is initialized, `werr.flags()` and `unitbuf` is nonzero.

Return An `ostream` object;

wostream wlog

Description Controls output to a stream buffer.

Prototype `wostream wlog;`

Remarks The object `wlog` controls output to a stream buffer associated with `cerr` declared in `<stdio>`.

Return An `ostream` object



27.4 istreams Base Classes

The include header `<ios>` contains the basic class definitions, types, and enumerations necessary for input and output stream reading writing and other manipulations.

Overview of Input and Output Stream Base Classes

The sections in this chapter are:

- [“Header `<ios>`” on page 439](#)
- [“27.4.1 Typedef Declarations” on page 440](#)
- [“27.4.3 Class `ios_base`” on page 441](#)
- [“27.4.4 Template class `basic_ios`” on page 458](#)
- [“27.4.5 `ios_base` manipulators” on page 476](#)

Header `<ios>`

Description The header file `<ios>` provides for implementation of stream objects for standard input and output.

Prototype Header `<ios>`

```
typedef OFF_T streamoff;
typedef SZ_T streamsize;

class ios_base;
template <class charT, class traits =
ios_traits<charT> >
```

27.4 Iostreams Base Classes

27.4.1 Typedef Declarations

```
class basic_ios

typedef basic_ios<char> ios;
typedef basic_ios<wchar_t> wios;

ios_base& boolalpha (ios_base& str)
ios_base& noboolalpha (ios_base& str)

ios_base& showbase (ios_base& str)
ios_base& noshowbase (ios_base& str)

ios_base& showpoint (ios_base& str)
ios_base& noshowpoint (ios_base& str)

ios_base& showpos (ios_base& str)
ios_base& noshowpos (ios_base& str)

ios_base& skipws (ios_base& str)
ios_base& noskipws (ios_base& str)

ios_base& uppercase (ios_base& str)
ios_base& nouppercase (ios_base& str)

ios_base& internal (ios_base& str)
ios_base& left (ios_base& str)
ios_base& right (ios_base& str)

ios_base& dec (ios_base& str)
ios_base& hex (ios_base& str)
ios_base& oct (ios_base& str)

ios_base& fixed (ios_base& str)
ios_base& scientific (ios_base& str)
```

27.4.1 Typedef Declarations

Description The following typedef's are defined in the class `ios_base`.

Definition `typedef OFF_T wstreamoff;`

Definition `typedef POS_T wstreampos;`

Definition `typedef SZ_T streamsize;`

27.4.3 Class **ios_base**

Description A base class for input and output stream mechanisms

The prototype is listed below. Additional topics in this section are:

- [“27.4.3.1 Typedef Declarations” on page 443](#)
- [“27.4.3.1.1 failure” on page 443](#)
- [“27.4.3.1.1.1 failure” on page 444](#)
- [“27.4.3.1.2 Type fmtflags” on page 444](#)
- [“27.4.3.1.3 Type iostate” on page 446](#)
- [“27.4.3.1.4 Type openmode” on page 446](#)
- [“27.4.3.1.5 Type seekdir” on page 447](#)
- [“27.4.3.1.6 Class Init” on page 447](#)
- [“Class Init Constructor” on page 447](#)
- [“27.4.3.2 ios_base fmtflags state functions” on page 448](#)
- [“27.4.3.3 ios_base locale functions” on page 455](#)
- [“27.4.3.4 ios_base storage function” on page 456](#)
- [“27.4.3.5 ios_base Constructor” on page 458](#)

Prototype

```
namespace std{
    class ios_base{
    public: class failure;

        typedef T1 fmtflags;
        static const fmtflags boolalpha;
        static const fmtflags dec;
        static const fmtflags fixed;
        static const fmtflags hex;
        static const fmtflags internal;
```

27.4 istreams Base Classes

27.4.3 Class *ios_base*

```
static const fmtflags left;
static const fmtflags oct;
static const fmtflags right;
static const fmtflags scientific;
static const fmtflags showbase;
static const fmtflags showpoint;
static const fmtflags showpos;
static const fmtflags skipws;
static const fmtflags unitbuf;
static const fmtflags uppercase;
static const fmtflags adjustfield;
static const fmtflags basefield;
static const fmtflags floatfield;

typedef T2 iostate;
static const iostate badbit;
static const iostate eofbit;
static const iostate failbit;
static const iostate goodbit;

typedef T3 openmode;
static const openmode app;
static const openmode ate;
static const openmode binary;
static const openmode in;
static const openmode out;
static const openmode trunc;

typedef T4 seekdir;
static const seekdir beg;
static const seekdir cur;
static const seekdir end;

class Init;
fmtflags flags() const;
fmtflags flags(fmtflags fmtfl);
fmtflags setf(fmtflags fmtfl);
fmtflags setf(fmtflags fmtfl, fmtflags mask);
void unsetf(fmtflags mask);
streamsize precision() const;
```

```

streamsize precision(streamsize prec);
streamsize width() const;
streamsize width(streamsize wide);
locale imbue(const locale& loc);
locale getloc() const;
static int xalloc();
long&  iword(int index);
void*& pword(int index);

~ios_base();

enum event { erase_event, imbue_event, copyfmt_event };
typedef void (*event_callback)(event, ios_base&, int index);
void register_callback(event_call_back fn, int index);
static bool sync_with_stdio(bool sync = true);

protected:
    ios_base();

private:
    // static int index;    exposition only
    // long* iarray;        exposition only
    // void** parray;       exposition only
};
}

```

Remarks The `ios_base` class is a base class and includes many enumerations and mechanisms necessary for input and output operations.

27.4.3.1 Typedef Declarations

No types are specified in the current standards.

27.4.3.1.1 failure

Description Define a base class for types of object thrown as exceptions.

Prototype namespace std {
 class ios_base::failure : public exception {

27.4 Iostreams Base Classes

27.4.3 Class *ios_base*

```
        public:  
            explicit failure(const string&)  
            virtual ~failure();  
            virtual const char* what() const;  
    };  
}
```

27.4.3.1.1 failure

Description Construct a class failure.

Prototype `explicit failure(const string& msg);`

Remarks The function `failure()` construct a class failure initializing with `exception(msg)`.

failure::what

Description To return the exception message.

Prototype `const char *what() const;`

Remarks The function `what()` is use to deliver the `msg.str()`.

Returns Returns the message with which the exception was created.

27.4.3.1.2 Type `fmtflags`

An enumeration used to set various formatting flags for reading and writing of streams.

Table 16.1 Format Flags Enumerations

Flag	Effects when set
<code>boolalpha</code>	insert and extract bool type in alphabetic form
<code>dec</code>	decimal output

Flag	Effects when set
fixed	when set show floating point numbers in normal manner by default that is six decimal places
hex	hexadecimal output
oct	octal output
left	left justified
right	right justified
internal	pad a field between signs or base characters
scientific	show scientific notation for floating point numbers
showbase	show the bases numeric values
showpoint	show the decimal point and trailing zeros
showpos	show the leading plus sign for positive numbers
skipws	skip leading white spaces with input
unitbuf	buffer the output and flush after insertion operation
uppercase	show the scientific notation, x or o in uppercase

Table 16.2 **Format flag field constants**

Constants	Allowable values
adjustfield	left right internal
basefield	dec oct hex
floatfield	scientific fixed

27.4 istreams Base Classes

27.4.3 Class ios_base

Listing 16.1 Example of ios format flags usage

see basic_ios::setf() and basic_ios::unsetf()

27.4.3.1.3 Type iostate

An enumeration that is used to define the various states of a stream.

Table 16.3 Enumeration iostate

Flags	Usage
badbit	iostate improper read / write
failbit	iostate failure
eofbit	end of file bit set note: see variance from AT&T Standards

Listing 16.2 Example of ios iostate flags usage:

See basic_ios::setstate() and basic_ios::rdstate()

27.4.3.1.4 Type openmode

An enumeration that is used to specify various file opening modes.

Table 16.4 Enumeration openmode

Mode	Definition
app	Start the read or write at end of the file
ate	Start the read or write immediately at the end
binary	binary file
in	Start the read at end of the file
out	Start the write at the beginning of the file
trunc	Start the read or write at the beginning of the file

27.4.3.1.5 Type `seekdir`

An enumeration to position a pointer to a specific place in a file stream.

Table 16.5 Enumeration `seekdir`

Enumeration	Position
<code>beg</code>	Beginning of stream
<code>cur</code>	Current position of stream
<code>end</code>	End of stream

Listing 16.3 Example of `ios seekdir` usage:

See: `streambuf::pubseekoff`

27.4.3.1.6 Class `Init`

Description An object that associates `<iostream>` object buffers with standard stream declared in `<cstdio>`.

Prototype

```
namespace std {
class ios_base::Init {
    public:
        Init();
        ~Init();
    private:
        // static int
};
}
```

Class `Init` Constructor

Default Constructor

Description To construct an object of class `Init`;

27.4 Iostreams Base Classes

27.4.3 Class *ios_base*

Prototype `Init();`

Remarks The constructor `Init()` constructs an object of class `Init`. If `init_cnt` is zero the function stores the value one and constructs `cin`, `cout`, `cerr`, `clog`, `win`, `wout`, `werr` and `wlog`. In any case the constructor then adds one to `init_cnt`.

Destructor

Prototype `~Init();`

Remarks The destructor subtracts one from `init_cnt` and if the result is one calls `cout.flush()`, `cerr.flush()` and `clog.flush()`.

27.4.3.2 *ios_base* `fmtflags` state functions

Description To set the state of the *ios_base* format flags.

flags

Description To alter formatting flags using a mask.

Prototype `fmtflags flags() const`
 `fmtflags flags(fmtflags)`

Remarks Use `flags()` when you would like to use a mask of several flags, or would like to save the current format configuration. The return value of `flags()` returns the current `fmtflags`. The overloaded `flags(fmtflags)` alters the format flags but will return the value prior to the flags being changed.

Returns The `fmtflags` type before alterations.

NOTE: See *ios* enumerators for a list of `fmtflags`.

See Also: `setiosflags()` and `resetiosflags()`

Listing 16.4 Example of flags() usage:

```
#include <iostream>

// showf() displays flag settings
void showf();

main()
{
    using namespace std;
    showf(); // show format flags

    cout << "press enter to continue" << endl;
    cin.get();

    cout.setf(ios::right|ios::showpoint|ios::fixed);
    showf();
    return 0;
}

// showf() displays flag settings
void showf()
{
    using namespace std;

    char fflags[][12] = {
        "boolalpha",
        "dec",
        "fixed",
        "hex",
        "internal",
        "left",
        "oct",
        "right",
        "scientific",
        "showbase",
        "showpoint",
        "showpos",
        "skipws",
        "unitbuf",
```

27.4 iostreams Base Classes

27.4.3 Class *ios_base*

```
        "uppercase"
};

long f = cout.flags();    // get flag settings
cout.width(9); // for demonstration
    // check each flag
for(long i=1, j =0; i<=0x4000; i = i<<1, j++)
{
    cout.width(10); // for demonstration
    if(i & f)
        cout << fflags[j] << " is on \n";
    else
        cout << fflags[j] << " is off \n";
}

cout << "\n";
}
```

Result:

```
boolalpha  is off
dec        is on
fixed      is off
hex        is off
internal   is off
left       is off
oct        is off
right      is off
scientific is off
showbase   is off
showpoint  is off
showpos    is off
skipws     is on
unitbuf    is off
uppercase  is off
```

press enter to continue

```
boolalpha is off
    dec is on
    fixed is on
```

```

    hex is off
    internal is off
    left is off
    oct is off
    right is on
    scientific is off
    showbase is off
    showpoint is on
    showpos is off
    skipws is on
    unitbuf is off
    uppercase is off

```

setf

Description Set the stream format flags.

Prototype `fmtflags setf(fmtflags)`
`fmtflags setf(fmtflags, fmtflags)`

Remarks You should use the function `setf()` to set the formatting flags for input/output. It is overloaded. The single argument form of `setf()` sets the flags in the mask. The two argument form of `setf()` clears the flags in the first argument before setting the flags with the second argument.

Returns type `basic_ios::fmtflags`

Listing 16.5 Example of `setf()` usage:

```

#include <iostream>

main()
{
    using namespace std;

    double d = 10.01;

    cout.setf(ios::showpos | ios::showpoint);

```

27.4 Iostreams Base Classes

27.4.3 Class *ios_base*

```
cout << d << endl;
cout.setf(ios::showpoint, ios::showpos | ios::showpoint);
cout << d << endl;

return 0;
}
```

Result:

+10.01

10.01

unsetf

Description To un-set previously set formatting flags.

Prototype void unsetf(fmtflags)

Remarks Use the unsetf () function to reset any format flags to a previous condition. You would normally store the return value of setf () in order to achieve this task.

Returns There is no return.

Listing 16.6 Example of unsetf() usage:

```
#include <iostream>

main()
{
using namespace std;

double d = 10.01;

cout.setf(ios::showpos | ios::showpoint);
cout << d << endl;

cout.unsetf(ios::showpoint);
cout << d << endl;
return 0;
}
```

```
}
```

```
Result:
```

```
+10.01
```

```
+10.01
```

precision

Description Set and return the current format precision.

Prototype `streamsize precision() const`
`streamsize precision(streamsize prec)`

Remarks Use the `precision()` function with floating point numbers to limit the number of digits in the output. You may use `precision()` with scientific or non-scientific floating point numbers. You may use the overloaded `precision()` to retrieve the current precision that is set.

With the flag `ios::floatfield` set the number in `precision` refers to the total number of significant digits generated. If the settings are for either `ios::scientific` or `ios::fixed` then the precision refers to the number of digits after the decimal place.

NOTE: This means that `ios::scientific` will have one more significant digit than `ios::floatfield`, and `ios::fixed` will have a varying number of digits.

Returns The current value set.

See Also `setprecision()`

Listing 16.7 Example of `precision()` usage:

```
#include <iostream>
```

```
extern double pi;
```

27.4 Iostreams Base Classes

27.4.3 Class *ios_base*

```
main()
{
using namespace std;

    double TenPi = 10*pi;

    cout.precision(5);
    cout.setf(0, ios::floatfield);
    cout << "floatfield:\t" << TenPi << endl;
    cout.setf(ios::scientific, ios::floatfield);
    cout << "scientific:\t" << TenPi << endl;
    cout.setf(ios::fixed, ios::floatfield);
    cout << "fixed:\t\t" << TenPi << endl;
    return 0;
}
```

Result:

floatfield: 31.416

scientific: 3.14159e+01

fixed: 31.41593

width

Description	To set the width of the output field.
Prototype	<pre>streamsize width() const streamsize width(streamsize wide)</pre>
Remarks	Use the <code>width()</code> function to set the field size for output. The function is overloaded to return just the current width setting if there is no parameter or to store and then return the previous setting before changing the fields width to the new parameter.
Returns	The previous width setting is returned.

Listing 16.8 Example of width() usage:

```
#include <iostream>

main()
{
    using namespace std;

    int width;

    cout.width(8);
    width = cout.width();
    cout.fill('*');
    cout << "Hi!" << '\n';

    // reset to left justified blank filler
    cout<< "Hi!" << '\n';

    cout.width(width);
    cout<< "Hi!" << endl;

    return 0;
}
```

Result:
Hi!*****
Hi!
Hi!*****

27.4.3.3 *ios_base* locale functions

Description Sets the locale for input output operations.

imbue

Description Stores a value representing the locale.

Prototype `locale imbue(const locale loc);`

27.4 Iostreams Base Classes

27.4.3 Class *ios_base*

Remarks The precondition of the argument `loc` is equal to `getloc()`.

Return The previous value of `getloc()`.

getloc

Description Determined the imbued locale for input output operations.

Prototype `locale getloc() const;`

Return The global C++ locale if no locale has been imbued. Otherwise it returns the locale of the input and output operations.

27.4.3.4 *ios_base* storage function

Description To allocate storage pointers.

xalloc

Description Allocation function.

Prototype `static int xalloc()`

Return `index++`.

yword

Description Allocate an array of `int` and store a pointer.

Remark If `iarray` is a null pointer allocate an array and store a pointer to the first element. The function extends the array as necessary to include `iarray[idx]`. Each new allocated element is initialized to the return value may be invalid.

NOTE: After a subsequent call to `yword()` for the same object the return value may be invalid.

Return `irray[idx]`

pword

Description Allocate an array of pointers.

Prototype `void * &pword(int idx)`

Remarks If parray is a null pointer allocates an array of void pointers. Then extends parray as necessary to include the element parray[idx].

NOTE: After a subsequent call to pword() for the same object the return value may be invalid.

Return `parray[idx].`

register_callback

Description Registers functions when an event occurs.

Prototype `void register_callback
 (event_callback fn,
 int index);`

Remarks Registers the pair (fn, index) such that during calls to imbue(), copyfmt() or ~ios_base() the function fn is called with argument index. Function registered are called when an event occurs, in opposite order of registration. Functions registered while a callback function is active are not called until the next event.

NOTE: Identical pairs are not merged and a function registered twice will be called twice.

27.4 Iostreams Base Classes

27.4.4 Template class *basic_ios*

sync_with_stdio

Description	Synchronizes stream input output with 'C' input and output functions.
Prototype	<code>static bool sync_with_stdio(bool sync = true);</code>
Remarks	Is not supported in the Metrowerks Standard Library.
Returns	Always returns <code>true</code> indicating that the MSLstreams are always synchronized with the C streams.

27.4.3.5 ios_base Constructor

Default Constructor

Description	Construct and destruct an object of class <code>ios_base</code>
Prototype	<code>protected: ios_base();</code>
Remarks	The <code>ios_base</code> constructor is protected so it may only be derived from. If the values of the <code>ios_base</code> members are undermined.

Destructor

Prototype	<code>~ios_base();</code>
Remarks	Calls registered callbacks and destroys an object of class <code>ios_base</code> .

27.4.4 Template class *basic_ios*

Description	A template class for input and output streams. The prototype is listed below. Additional topics in this section are: <ul style="list-style-type: none">• “27.4.4.1 basic_ios Constructor” on page 460• “27.4.4.2 Member Functions” on page 461
--------------------	--

- [“27.4.4.3 basic_ios iostate flags functions” on page 466](#)

Prototype

```

namespace std{
template<class charT,
        class traits = ios_traits<charT> >
class basic_ios : public ios_base {
public:
    typedef charT char_type;
    typedef typename traits::int_type int_type;
    typedef typename traits::pos_type pos_type;
    typedef typename traits::off_type off_type;

    operator bool() const;
    bool operator!() const;
    iostate rdbuf() const;
    void clear(iostate state = goodbit);
    void setstate(iostate state);
    bool good() const;
    bool eof() const;
    bool fail() const;
    bool bad() const;

    explicit basic_ios
        (basic_streambuf<charT, traits>,
         traits *sb);

    virtual ~basic_ios();

    basic_ostream<charT, traits>* tie() const;
    basic_ostream<charT, traits>*
        tie(basic_streambuf<charT, traits>* sb);

    basic_streambuf<charT, traits>* rdbuf() const;
    basic_streambuf<charT, traits>*
        rdbuf(basic_streambuf<charT, traits>* sb);

    basic_ios& copyfmt(const basic_ios& rhs);

    char_type fill()const;
    char_type fill(char_type ch);

```

27.4 Iostreams Base Classes

27.4.4 Template class *basic_ios*

```
        locale imbue(const locale& loc);

protected:
    basic_ios();
    void init(basic_streambuf<charT, traits>* sb);
    };
}
```

Remarks The `basic_ios` template class is a base class and includes many enumerations and mechanisms necessary for input and output operations.

27.4.4.1 `basic_ios` Constructor

Default and Overloaded Constructor

Description Construct an object of class `basic_ios` and assign values.

Prototype

```
public:
    explicit basic_ios
        (basic_streambuf<charT,traits>* sb);
protected:
    basic_ios();
```

Remarks The `basic_ios` constructor creates an object of class `basic_ios` and assigns values to its member functions by calling `init()`.

Destructor

Prototype `virtual ~basic_ios();`

Remarks Destroys an object of type `basic_ios`.

Remarks The conditions of the member functions after `init()` are shown in the following table.

Table 16.6 **Conditions after init()**

Member	Postcondition Value
<code>rdbuf()</code>	<code>sb</code>
<code>tie()</code>	<code>zero</code>
<code>rdstate()</code>	goodbit if stream buffer is not a null pointer otherwise badbit.
<code>exceptions()</code>	goodbit
<code>flags()</code>	<code>skipws dec</code>
<code>width()</code>	<code>zero</code>
<code>precision()</code>	<code>six</code>
<code>fill()</code>	the space character
<code>getloc()</code>	<code>locale::classic()</code>
<code>index</code>	undefined
<code>iarray</code>	a null pointer
<code>parray</code>	a null pointer

27.4.4.2 Member Functions

tie

Description To tie an ostream to the calling stream.

Prototype `basic_ostream<charT, traits>* tie() const;`
`basic_ostream<charT, traits>* tie`
`(basic_ostream<charT, traits>* tiestr);`

Remarks Any stream can have an ostream tied to it to ensure that the ostream is flushed before any operation. The standard input and output objects `cin` and `cout` are tied to ensure that `cout` is flushed before any `cin` operation. The function `tie()` is overloaded the parameterless version returns the current ostream that is tied if any.

27.4 Iostreams Base Classes

27.4.4 Template class *basic_ios*

The `tie()` function with an argument ties the new object to the `ostream` and returns a pointer if any from the first. The postcondition of `tie()` function that takes the argument `tiestr` is that `tiestr` is equal to `tie()`;

Returns A pointer to type `ostream` that is or previously was tied, or zero if there was none.

Listing 16.9 Example of `tie()` usage:

The file MW Reference contains
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

void main()
{
    using namespace std;

    ifstream inOut(inFile, ios::in | ios::out);
    if(!inOut.is_open())
        { cout << "file is not open"; exit(1);}
    ostream Out(inOut.rdbuf());

    if(inOut.tie())
        cout << "The streams are tied\n";
    else cout << "The streams are not tied\n";

    inOut.tie(&Out);
    inOut.rdbuf()->pubseekoff(0, ios::end);

    char str[] = "\nRegistered Trademark";
    Out << str;

    if(inOut.tie())
        cout << "The streams are tied\n";
```

```

else cout << "The streams are not tied\n";

    inOut.close();
}

```

Result:

The streams are not tied

The streams are tied

The file MW Reference now contains

Metrowerks CodeWarrior "Software at Work"

Registered Trademark

rdbuf

Description To retrieve a pointer to the stream buffer.

Prototype `basic_streambuf<charT, traits>* rdbuf() const;`
`basic_streambuf<charT, traits>* rdbuf`
`(basic_streambuf<charT, traits>* sb);`

Remarks To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function `rdbuf()` allows you to retrieve this pointer. The `rdbuf()` function that takes an argument has the postcondition of `sb` is equal to `rdbuf()`.

Returns A pointer to `basic_streambuf` object.

Listing 16.10 Example of `rdbuf()` usage:

```

#include <iostream>

struct address {
    int number;
    char street[40];
} addbook;

main()

```

27.4 istreams Base Classes

27.4.4 Template class *basic_ios*

```
{
using namespace std;

    cout << "Enter your street number: ";
    cin >> addbook.number;

    cin.rdbuf()->pubsync(); // buffer flush

    cout << "Enter your street name: ";
    cin.get(addbook.street, 40);

    cout << "Your address is: "
         << addbook.number << " " << addbook.street;

    return 0;
}
```

Result:

```
Enter your street number: 2201
Enter your street name: Donley Drive
Your address is: 2201 Donley Drive
```

imbue

Description	Stores a value representing the locale.
Prototype	<code>locale imbue(const locale& rhs);</code>
Remarks	The function <code>imbue()</code> calls <code>ios_base::imbue()</code> and <code>rdbuf()->pubimbue()</code> .
Returns	The current locale.

fill

Description	To insert characters into the stream's unused spaces.
Prototype	<code>char_type fill() const</code>


```
char_type fill(char_type)
```

Remarks Use `fill(char_type)` in output to fill blank spaces with a character. The function `fill()` is overloaded to return the current filler without altering it.

Returns The current character being used as a filler.

See Also manipulator `setfill()`

Listing 16.11 Example of `fill()` usage:

```
#include <iostream>

main()
{
    using namespace std;

    char fill;

    cout.width(8);
    cout.fill('*');
    fill = cout.fill();
    cout<< "Hi!" << "\n";
    cout << "The filler is a " << fill << endl;

    return 0;
}
```

```
Result:
Hi!*****
The filler is a *
```

copyfmt

Description Copies a `basic_ios` object.

Prototype `basic_ios& copyfmt(const basic_ios& rhs);`

27.4 Iostreams Base Classes

27.4.4 Template class *basic_ios*

Remarks Assigns members of `*this` object the corresponding objects of the `rhs` argument with certain exceptions. The exceptions are `rdstate()` is unchanged, `exceptions()` is altered last, and the contents of `pword` and `iword` arrays are copied not the pointers themselves.

Returns The `this` pointer.

27.4.4.3 *basic_ios* `iosstate` flags functions

Description To set flags pertaining to the state of the input and output streams.

`operator bool`

Description A `bool` operator.

Prototype `operator bool() const;`

Returns `!fail()`

`operator !`

Description A `bool` not operator.

Prototype `bool operator ! ();`

Return `fail()`.

`rdstate`

Description To retrieve the state of the current formatting flags.

Prototype `iosstate rdstate() const`

Remarks This member function allows you to read and check the current status of the input and output formatting flags. The returned value may be stored for use in the function `ios::setstate()` to reset the flags at a later date.

Returns Type `iosstate` used in `ios::setstate()`

See Also `ios::setstate()`

Listing 16.12 Example of `rdstate()` usage:

The file `MW Reference` contains:
`ABCDEFGHIJKLMNOPQRSTUVWXYZ`

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char * inFile = "MW Reference";

using namespace std;

void status(ifstream &in);

main()
{
    ifstream in(inFile);
    if(!in.is_open())
    {
        cout << "could not open file for input";
        exit(1);
    }

    int count = 0;
    int c;
    while((c = in.get()) != EOF)
    {
        // simulate a bad bit
        if(count++ == 12) in.setstate(ios::badbit);
        status(in);
    }

    status(in);
    in.close();
}
```

27.4 istreams Base Classes

27.4.4 Template class *basic_ios*

```
    return 0;
}

void status(istream &in)
{
    int i = in.rdstate();
    switch (i) {
        case ios::eofbit : cout << "EOF encountered \n";
                           break;
        case ios::failbit : cout << "Non-Fatal I/O Error n";
                           break;
        case ios::goodbit : cout << "GoodBit set \n";
                           break;
        case ios::badbit : cout << "Fatal I/O Error \n";
                           break;
    }
}
```

Result:

```
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
Fatal I/O Error
```

clear

Description Clears iostate field.

Prototype `void clear`
 `(iostate state = goodbit) throw failure;`

Remarks Use `clear()` to reset the failbit, eofbit or a badbit that may have been set inadvertently when you wish to override for continuation of your processing. Postcondition of `clear` is the argument is equal to `rdstate()`.

NOTE: If `rdstate()` and `exceptions()` $\neq 0$ an exception is thrown.

Returns No value is returned.

Listing 16.13 Example of `clear()` usage:

The file MW Reference contains:
ABCDEFGH

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char * inFile = "MW Reference";

using namespace std;

void status(ifstream &in);

main()
{
    ifstream in(inFile);
    if(!in.is_open())
    {
        cout << "could not open file for input";
        exit(1);
    }

    int count = 0;
    int c;
    while((c = in.get()) != EOF) {
        if(count++ == 4)
        {
```

27.4 Iostreams Base Classes

27.4.4 Template class *basic_ios*

```
        // simulate a failed state
        in.setstate(ios::failbit);
        in.clear();
    }
    status(in);
}

status(in);
in.close();
return 0;
}

void status(istream &in)
{
    // note: eof() is not needed in this example
    // if(in.eof()) cout << "EOF encountered \n"
    if(in.fail()) cout << "Non-Fatal I/O Error \n";
    if(in.good()) cout << "GoodBit set \n";
    if(in.bad()) cout << "Fatal I/O Error \n";
}
```

Result:

```
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
GoodBit set
Non-Fatal I/O Error
```

setstate

Description To set the state of the format flags.

Prototype void setstate(iostate state) throw(failure);

Remarks Calls `clear(rdstate() | state)` and may throw an exception.

Returns No Return

Listing 16.14 Example of `setstate()` usage:

See `ios::rdstate()`

good

Description To test for the lack of error bits being set.

Prototype `bool good() const;`

Remarks Use the function `good()` to test for the lack of error bits being set.

Returns

True if `rdstate() == 0`.

Listing 16.15 Example of `good()` usage:

See `basic_ios::bad()`

eof

Description To test for the eofbit setting.

Prototype `bool eof() const`

Remarks Use the `eof()` function to test for an eofbit setting in a stream being processed under some conditions. This end of file bit is not set by stream opening or closing, but only for operations that detect an end of file condition.

Returns True if eofbit is set in `rdstate()`.

27.4 istreams Base Classes

27.4.4 Template class *basic_ios*

Listing 16.16 Example of eof() usage:

MW Reference is simply a one line text document
ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz

```
#include <iostream>
#include <fstream>
#include <cstdlib>

const char* TheText = "MW Reference";

main()
{
    using namespace std;

    ifstream in(TheText);
    if(!in.is_open())
    {
        cout << "Couldn't open file for input";
        exit(1);
    }

    int i = 0;
    char c;
    cout.setf(ios::uppercase);

    //eofbit is not set under normal file opening
    while(!in.eof())
    {
        c = in.get();
        cout << c << " " << hex << int(c) << "\n";

        // simulate an end of file state
        if(++i == 5) in.setstate(ios::eofbit);
    }
    return 0;
}
```

Result:

A 41

B 42

C 43

D 44

E 45

fail

Description To test for stream reading failure from any cause.

Prototype `bool fail() const`

Remarks The member function `fail()` will test for `failbit` and `badbit`.

Returns True if `failbit` or `badbit` is set in `rdstate()`.

Listing 16.17 Example of fail() usage:

MW Reference file for input contains.

float 33.33 double 3.16e+10 Integer 789 character C

```
#include <iostream>
```

```
#include <fstream>
```

```
#include <cstdlib>
```

```
main()
```

```
{
```

```
using namespace std;
```

```
    char inFile[] = "MW Reference";
```

```
    ifstream in(inFile);
```

```
    if(!in.is_open())
```

```
    {cout << "Cannot open input file"; exit(1);}
```

```
    char ch = 0;
```

```
    while(!in.fail())
```

```
    {
```

```
        if(ch)cout.put(ch);
```

```
        in.get(ch);
```

```
    }
```

27.4 istreams Base Classes

27.4.4 Template class *basic_ios*

```
    return 0;
}
```

Result:

float 33.33 double 3.16e+10 integer 789 character C

bad

Description To test for fatal I/O error.

Prototype `bool bad() const`

Remarks Use the member function `bad()` to test if a fatal input or output error occurred which sets the `badbit` flag in the stream.

Returns True if `badbit` is set in `rdstate()`.

See Also `basic_ios::fail()`

Listing 16.18 Example of `bad()` usage:

The File MW Reference contains:

abcdefghijklmnopqrstuvwxyz

```
#include <iostream>
#include <fstream>
#include <cstdlib>
```

```
char * inFile = "MW Reference";
```

```
using namespace std;
```

```
void status(istream &in);
```

```
main()
{
    ifstream in(inFile);
    if(!in.is_open())
```

```
{
    cout << "could not open file for input";
    exit(1);
}

int count = 0;
int c;
while((c = in.get()) != EOF)
{
    // simulate a failed state
    if(count++ == 4) in.setstate(ios::failbit);
    status(in);
}

status(in);
in.close();
return 0;
}

void status(istream &in)
{
    // note: eof() is not needed in this example
    // if(in.eof()) cout << "EOF encountered \n";

    if(in.fail()) cout << "Non-Fatal I/O Error \n";
    if(in.good()) cout << "GoodBit set \n";
    if(in.bad()) cout << "Fatal I/O Error \n";
}
```

Result:

```
GoodBit set
GoodBit set
GoodBit set
GoodBit set
Non-Fatal I/O Error
Non-Fatal I/O Error
```

27.4 Iostreams Base Classes

27.4.5 ios_base manipulators

exceptions

Description	To handle basic_ios exceptions.
Prototype	<pre>iostate exceptions() const; void exceptions(iostate except);</pre>
Remarks	The function <code>exceptions()</code> determines what elements in <code>rdstate()</code> cause exceptions to be thrown. The overloaded <code>exceptions(iostate)</code> calls <code>clear(rdstate())</code> and leaves the argument <code>except</code> equal to <code>exceptions()</code> .
Return	A mask that determines what elements set in <code>rdstate()</code> cause undefined behavior.

27.4.5 ios_base manipulators

Description	To provide an in line input and output formatting mechanism.
--------------------	--

The topics in this section are:

- [“27.4.5.1 fmtflags manipulators” on page 476](#)
- [“27.4.5.2 adjustfield manipulators” on page 478](#)
- [“27.4.5.3 basefield manipulators” on page 478](#)
- [“27.4.5.4 floatfield manipulators” on page 479](#)

27.4.5.1 fmtflags manipulators

Description	To provide an in line input and output numerical formatting mechanism.
--------------------	--

Table 16.7 **Prototype of ios_base manipulators**

Manipulator	Definition
<code>ios_base& boolalpha(ios_base&)</code>	insert and extract bool type in alphabetic format
<code>ios_base& noboolalpha(ios_base&)</code>	unsets insert and extract bool type in alphabetic format
<code>ios_base& showbase(ios_base& b)</code>	set the number base to parameter b
<code>ios_base& noshowbase(ios_base&)</code>	remove show base
<code>ios_base& showpoint(ios_base&)</code>	show decimal point
<code>ios_base& noshowpoint(ios_base&)</code>	do not show decimal point
<code>ios_base& showpos(ios_base&)</code>	show the positive sign
<code>ios_base& noshowpos(ios_base&)</code>	do not show positive sign
<code>ios_base& skipws(ios_base&)</code>	input only skip white spaces
<code>ios_base& noskipws(ios_base&)</code>	input only no skip white spaces
<code>ios_base& uppercase(ios_base&)</code>	show scientific in uppercase
<code>ios_base& nouppercase(ios_base&)</code>	do not show scientific in uppercase

27.4 Iostreams Base Classes

27.4.5 *ios_base* manipulators

	Manipulator	Definition
	<code>ios_base& unitbuf</code> <code>(ios_base::unitbuf)</code>	set the unitbuf flag
	<code>ios_base& nunitbuf</code> <code>(ios_base::unitbuf)</code>	unset the unitbuf flag
Remarks	Manipulators are used in the stream to alter the formatting of the stream.	
Returns	A reference to an object of type <code>ios_base</code> is returned to the stream. (The <code>this</code> pointer.)	

27.4.5.2 **adjustfield** manipulators

Description To provide an in line input and output orientation formatting mechanism.

Table 16.8 Adjustfield manipulators

	Manipulator	Definition
	<code>ios_base& internal(ios_base&)</code>	fill between indicator and value
	<code>ios_base& left(ios_base&)</code>	left justify in a field
	<code>ios_base& right(ios_base&)</code>	right justify in a field
Remarks	Manipulators are used in the stream to alter the formatting of the stream.	
Returns	A reference to an object of type <code>ios_base</code> is returned to the stream. (The <code>this</code> pointer.)	

27.4.5.3 **basefield** manipulators

Description To provide an in line input and output numerical formatting mechanism.

Table 16.9 Basefield manipulators

Manipulator	Definition
<code>ios_base& dec(ios_base&)</code>	format output data as a decimal
<code>ios_base& oct(ios_base&)</code>	format output data as octal
<code>ios_base& hex(ios_base&)</code>	format output data as hexadecimal
Remarks	Manipulators are used in the stream to alter the formatting of the stream.
Returns	A reference to an object of type <code>ios_base</code> is returned to the stream. (The <code>this</code> pointer.)

27.4.5.4 floatfield manipulators

Description To provide an in line input and output numerical formatting mechanism.

Table 16.10 Floatfield manipulators

Manipulator	Definition
<code>ios_base& fixed(ios_base&)</code>	format in fixed point notation
<code>ios_base& scientific(ios_base&)</code>	use scientific notation
Remarks	Manipulators are used in the stream to alter the formatting of the stream.
Returns	A reference to an object of type <code>ios_base</code> is returned to the stream. (The <code>this</code> pointer.)

Listing 16.19 Example of manipulator usage:

```
#include <iostream>
#include <iomanip>

main()
```

27.4 istreams Base Classes

27.4.5 ios_base manipulators

```
{
using namespace std;

    long number = 64;

    cout << "Original Number is "
         << number << "\n\n";
    cout << showbase;
    cout << setw(30) << "Hexadecimal :"
         << hex << setw(10) << right
         << number << '\n';
    cout << setw(30) << "Octal :" << oct
         << setw(10) << left
         << number << '\n';
    cout << setw(30) << "Decimal :" << dec
         << setw(10) << right
         << number << endl;

    return 0;
}
```

Result:

Original Number is 64

Hexadecimal : 0x40

Octal :0100

Decimal : 64

Overloading Manipulators

Description To provide an in line formatting mechanism.

Prototype The basic template for parameterless manipulators,
ostream &manip-name(ostream &stream)
{
 // coding
 return stream;
}

-
- Remarks** Use overloaded manipulators to provide specific and unique formatting methods relative to one class.
- Returns** A reference to ostream. (Usually the `this` pointer.)
- See Also** `<iomanip>` for manipulators with parameters

Listing 16.20 Example of overloaded manipulator usage:

```
#include <iostream>

using namespace std;

ostream &rJus(ostream &stream);

main()
{
    cout << "align right " << rJus << "for column";
    return 0;
}

ostream &rJus(ostream &stream)
{
    stream.width(30);
    stream.setf(ios::right);
    return stream;
}
```

Result:

align right	for column
-------------	------------

27.4 **iostreams** Base Classes

27.4.5 *ios_base* manipulators



27.5 Stream Buffers

The header `<streambuf>` defines types that control input and output to character sequences.

Overview of Stream Buffers

The sections in this chapter are:

- [“Header `<streambuf>`” on page 483](#)
- [“27.5.1 Stream buffer requirements” on page 483](#)
- [“27.5.2 Template class `basic_streambuf<charT, traits>`” on page 484](#)

Header `<streambuf>`

```
Prototype  namespace std {  
            template <class charT, class traits =  
            char_traits<charT> >  
                class basic_streambuf;  
            typedef basic_streambuf<char> streambuf;  
            typedef basic_streambuf<wchar_t> wstreambuf;  
            }
```

27.5.1 Stream buffer requirements

Stream buffers can impose constraints. The constraints include:

- The input sequence can be not readable
- The output sequence can be not writable
- The sequences can be association with other presentations such as external files

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

- The sequences can support operations to or from associated sequences.
- The sequences can impose limitations on how the program can read and write characters to and from a sequence or alter the stream position.

There are three pointers that control the operations performed on a sequence or associated sequences. These are used for read, writes and stream position alteration. If not `null` all pointers point to the same `charT` array object.

- The beginning pointer or lowest element in an array. - (`beg`)
- The next pointer of next element addressed for read or write. - (`next`)
- The end pointer of first element addressed beyond the end of the array. - (`end`)

27.5.2 Template class `basic_streambuf<charT, traits>`

The prototype is listed below. Additional topics in this section are:

- [“27.5.2.1 `basic_streambuf` Constructor” on page 487](#)
- [“27.5.2.2 `basic_streambuf` Public Member Functions” on page 488](#)
- [“27.5.2.2.1 Locales” on page 488](#)
- [“27.5.2.2.2 Buffer Management and Positioning” on page 488](#)
- [“27.5.2.2.3 Get Area” on page 494](#)
- [“27.5.2.2.4 Putback” on page 497](#)
- [“27.5.2.2.5 Put Area” on page 499](#)
- [“27.5.2.3 `basic_streambuf` Protected Member Functions” on page 501](#)
- [“27.5.2.3.1 Get Area Access” on page 501](#)
- [“27.5.2.3.2 Put Area Access” on page 502](#)
- [“27.5.2.4 `basic_streambuf` Virtual Functions” on page 504](#)
- [“27.5.2.4.1 Locales” on page 504](#)

- [“27.5.2.4.2 Buffer Management and Positioning” on page 504](#)
- [“27.5.2.4.3 Get Area” on page 506](#)
- [“27.5.2.4.4 Putback” on page 508](#)
- [“27.5.2.4.5 Put Area” on page 508](#)

Prototype

```
namespace std {
template< class charT, class traits = char_traits<charT> >
class basic_streambuf {
public:

    typedef charT char_type;
    typedef typename traits::int_type int_type;
    typedef typename traits::pos_type pos_type;
    typedef typename traits::off_type off_type;

    virtual ~basic_streambuf();

    locale pubimbue(const locale &loc);
    locale getloc() const;

    basic_streambuf<char_type, traits> * pubsetbuf
        (char_type* s, streamsize n);

    pos_type pubseekoff
        (off_type off,
         ios_base::seekdir way,
         ios_base::openmode which = ios_base::in | ios_base::out);
    pos_type pubseekpos
        (pos_type sp,
         ios_base::openmode which = ios::in | ios::out);

    int pubsync();

    streamsize in_avail();

    int_type snextc();
    int_type sbumpc();
    int_type sgetc();
```

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>

```
streamsize sgetn(char_type *s, streamsize n);

int_type sputback(char_type C);
int_type sungetc();

int_type sputc(char_type c);
int_type sputn(char_type *s, streamsize n);

protected:
    basic_streambuf();

    char_type* eback() const;
    char_type* gptr() const;
    char_type* egptr() const;
    void gbump(int n);
    void setg
        (char_type *gbeg,
         char_type *gnext,
         char_type *gend);

    char_type* pbase() const;
    char_type* pptr() const;
    char_type* epptr() const;

    void pbump(int n);
    void setp(char_type *pbeg, char_type *pend);

    virtual void imbue(const locale &loc);

    virtual basic_streambuf<char_type, traits>* setbuf
        (char_type* s, streamsize n);

    virtual pos_type seekoff
        (off_type off,
         ios_base::seekdir way,
         ios_base::openmode which = ios::in | ios::out);
    virtual pos_type seekpos
        (pos_type sp,
         ios_base::openmode which = ios::in | ios::out);
    virtual int sync();
```

```

virtual int showmanyc();
virtual streamsize xsgetn(char_type *s,
    streamsize n);
virtual int_type underflow();
virtual int_type uflow();

virtual int_type
    pbackfail(int_type c = traits::eof());

virtual streamsize xspn
    (const char_type *s, streamsize n);
virtual int_type overflow
    (int_type c = traits::eof());
};
}

```

Remarks The template class `basic_streambuf` is an abstract class for deriving various stream buffers whose objects control input and output sequences. The type `streambuf` is an instantiation of `char` type. the type `wstreambuf` is an instantiation of `wchar_t` type.

27.5.2.1 `basic_streambuf` Constructor

Default Constructor

Description Construct and destruct an object of type `basic_streambuf`.

Prototype `protected:`
`basic_streambuf();`

Remarks The constructor sets all pointer member objects to null pointers and calls `getloc()` to copy the global locale at the time of construction.

Destructor

Prototype `virtual ~basic_streambuf();`

Remarks Removes the object from memory.

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>

27.5.2.2 *basic_streambuf* Public Member Functions

Description The public member functions allow access to member functions from derived classes.

27.5.2.2.1 Locales

Locales are used for encapsulation and manipulation of information to a particular locale.

basic_streambuf::pubimbue

Description To set the locale.

Prototype `locale pubimbue(const locale &loc);`

Remarks The function `pubimbue` calls `imbue(loc)`.

Return The previous value of `getloc()`.

basic_streambuf::getloc

Description To get the locale.

Prototype `locale getloc() const;`

Return If `pubimbue` has already been called one it returns the last value of `loc` supplied otherwise the current one. If `pubimbue` has been called but has not returned a value it from `imbue`, it then returns the previous value.

27.5.2.2.2 Buffer Management and Positioning

Functions used to manipulate the buffer and the input and output positioning pointers.

basic_streambuf::pubsetbuf

Description	To set an allocation after construction.
Prototype	<code>basic_streambuf<char_type, traits> *pubsetbuf (char_type* s, streamsize n);</code>
Remarks	The first argument is used in an another function by a <code>filebuf</code> derived class. See <code>setbuf()</code> . The second argument is used to set the size of a dynamic allocated buffer.
Return	A pointer to <code>basic_streambuf<char_type, traits></code> via <code>setbuf(s, n)</code> .

Listing 17.1 Example of basic_streambuf::pubsetbuf() usage:

```
#include <iostream>
#include <sstream>

const int size = 100;
char temp[size] = "\0";

main()
{
    using namespace std;

    stringbuf strbuf;
    strbuf.pubsetbuf('\0', size);
    strbuf.sputn("Metrowerks CodeWarrior", 50);
    strbuf.sgetn(temp, 50);
    cout << temp;

    return 0;
}
```

Result:
Metrowerks CodeWarrior

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

`basic_streambuf::pubseekoff`

Description Determines the position of the get pointer.

Prototype `pos_type pubseekoff`
`(off_type off,`
`ios_base::seekdir way, ios_base::openmode`
`which = ios_base::in | ios_base::out);`

Remarks The member function `pubseekoff()` is used to find the difference in bytes of the get pointer from a known position (such as the beginning or end of a stream). The function `pubseekoff()` returns a type `pos_type` which holds all the necessary information.

Return A `pos_type` via `seekoff(off, way, which)`

See Also `pubseekpos()`

Listing 17.2 Example of `basic_streambuf::pubseekoff()` usage:

The MW Reference file contains originally
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <stdlib.h>

char inFile[] = "MW Reference";

void main()
{
    using namespace std;

    ifstream inOut(inFile, ios::in | ios::out);
    if(!inOut.is_open())
        {cout << "Could not open file"; exit(1);}
    ostream Out(inOut.rdbuf());

    char str[] = "\nRegistered Trademark";
```

```

inOut.rdbuf()->pubseekoff(0, ios::end);

Out << str;

inOut.close();
}

```

Result:

The File now reads:

Metrowerks CodeWarrior "Software at Work"

Registered Trademark

basic_streambuf::pubseekpos

Description Determine and move to a desired offset.

Prototype `pos_type pubseekpos`
 `(pos_type sp,`
 `ios_base::openmode which = ios::in | ios::out);`

Remarks The function `pubseekpos()` is use to move to a desired offset using a type `pos_type`, which holds all necessary information.

Return A `pos_type` via `seekpos(sb, which)`

See Also `pubseekoff()`, `seekoff()`, `offset()`

Listing 17.3 Example of `streambuf::pubseekpos()` usage:

The file MW Reference contains:

ABCDEFGHIJKLMNOPQRSTUVWXYZ

```

#include <iostream>
#include <fstream>
#include <cstdlib>

```

```

main()
{

```

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

```
using namespace std;

ifstream in("MW Reference");
if(!in.is_open())
    {cout << "could not open file"; exit(1);}

streampos spEnd, spStart, aCheck;
spEnd = spStart = 5;

aCheck = in.rdbuf()->pubseekpos(spStart, ios::in);
cout << "The offset at the start of the reading"
    << " in bytes is "
    << aCheck.offset() << endl;

char ch;
while(spEnd != spStart+10)
{
    in.get(ch);
    cout << ch;
    spEnd = in.rdbuf()->pubseekoff(0, ios::cur);
}

aCheck = in.rdbuf()->pubseekoff(0, ios::cur);
cout << "\nThe final position's offset"
    << " in bytes now is "
    << aCheck.offset() << endl;

in.close();

return 0;
}
```

Result:

```
The offset for the start of the reading in bytes is 5
FGHIJKLMNO
The final position's offset in bytes now is 15
```

basic_streambuf::pubsync

Description	To synchronize the <code>streambuf</code> object with its input/output.
Prototype	<code>int pubsync();</code>
Remarks	The function <code>pubsync()</code> will attempt to synchronize the <code>streambuf</code> input and output.
Returns	Zero if successful or EOF if not via <code>sync()</code> .

Listing 17.4 Example of `streambuf::pubsync()` usage:

```
#include <iostream>

struct address {
    int number;
    char street[40];
}addbook;

main()
{
    using namespace std;

    cout << "Enter your street number: ";
    cin >> addbook.number;

    cin.rdbuf()->pubsync(); // buffer flush

    cout << "Enter your street name: ";
    cin.get(addbook.street, 40);

    cout << "Your address is: "
         << addbook.number << " " << addbook.street;

    return 0;
}
```

Result:

Enter your street number: 2201

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

Enter your street name: Donley Drive

Your address is: 2201 Donley Drive

27.5.2.2.3 Get Area

Public functions for retrieving input from a buffer.

`basic_streambuf::in_avail`

Description To test for availability of input stream.

Prototype `streamsize in_avail();`

Return If a read is permitted returns size of stream as a type `streamsize`.

`basic_streambuf::snextc`

Description To retrieve the next character in a stream.

Prototype `int_type snextc();`

Remarks The function `snextc()` calls `sbumpc()` to extract the next character in a stream. After the operation, the get pointer references the character following the last character extracted.

Return If `sbumpc` returns `traits::eof` returns that, otherwise returns `sgetc()`.

Listing 17.5 Example of `streambuf::snextc()` usage:

```
#include <iostream>
#include <sstream>

const int size = 100;

main()
{
    using namespace std;
```

```

stringbuf strbuf;
strbuf.pubsetbuf('\0', size);
strbuf.sputn("ABCDE",50);

char ch;
    // look ahead at the next character
ch =strbuf.snextc();
cout << ch;
    // get pointer was not returned after peeking
ch = strbuf.snextc();
cout << ch;

return 0;
}

```

Result:
BC

basic_streambuf::sbumpc

Description	To move the get pointer.
Prototype	<code>int_type sbumpc();</code>
Remarks	The function <code>sbumpc()</code> moves the get pointer one element when called.
Return	The value of the character at the <code>get</code> pointer. It returns <code>uflow()</code> if it fails to move the pointer.
See Also	<code>sgetc()</code>

Listing 17.6 Example of `streambuf::sbumpc()` usage:

```

#include <iostream>
#include <sstream>

const int size = 100;

```

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

```
std::string buf = "Metrowerks CodeWarrior --Software at Work--";

main()
{
    using namespace std;

    stringbuf strbuf(buf);

    int ch;
    for (int i = 0; i < 23; i++)
    {
        ch = strbuf.sgetc();
        strbuf.sbumpc();
        cout.put(ch);
    }
    cout << endl;
    cout << strbuf.str() << endl;
    return 0;
}
```

Result:

```
Metrowerks CodeWarrior
Metrowerks CodeWarrior --Software at Work--
```

`basic_streambuf::sgetc`

- | | |
|--------------------|--|
| Description | To extract a character from the stream. |
| Prototype | <code>int_type sgetc();</code> |
| Remarks | The function <code>sgetc()</code> extracts a single character, without moving the get pointer. |
| Return | A <code>int_type</code> type at the <code>get</code> pointer if available otherwise returns <code>underflow()</code> . |

Listing 17.7 Example of `streambuf::sgetc()` usage:

See `streambuf::sbumpc()`

`basic_streambuf::sgetn`

Description	To extract a series of characters from the stream.
Prototype	<code>streamsize sgetn(char_type *s, streamsize n);</code>
Remarks	The public member function <code>sgetn()</code> is used to extract a series of characters from the stream buffer. After the operation, the <code>get</code> pointer references the character following the last character extracted.
Return	A <code>streamsize</code> type as returned from the function <code>xsgetn(s,n)</code> .

Listing 17.8 Example of `streambuf::sgetn()` usage:

See `pubsetbuf()`

27.5.2.2.4 Putback

Public functions to return a value to a stream.

`basic_streambuf::sputback`

Description	To put a character back into the stream.
Prototype	<code>int_type sputback(char_type c);</code>
Remarks	The function <code>sputbackc()</code> will replace a character extracted from the stream with another character. The results are not assured if the putback is not immediately done or a different character is used.
Return	If successful returns a pointer to the <code>get</code> pointer as an <code>int_type</code> otherwise returns <code>pbackfail(c)</code> .

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>

Listing 17.9 Example of *streambuf::sputbackc()* usage:

```
#include <iostream>
#include <sstream>

std::string buffer = "ABCDEF";

main()
{
    using namespace std;

    stringbuf strbuf(buffer);
    char ch;

    ch = strbuf.sgetc(); // extract first character
    cout << ch; // show it

    //get the next character
    ch = strbuf.snextc();

    // if second char is B replace first char with x
    if(ch == 'B') strbuf.sputbackc('x');

    // read the first character now x
    cout << (char)strbuf.sgetc();

    strbuf.sbumpc(); // increment get pointer
    // read second character
    cout << (char)strbuf.sgetc();

    strbuf.sbumpc(); // increment get pointer
    // read third character
    cout << (char)strbuf.sgetc();

    // show the new stream after alteration
    strbuf.pubseekoff(0, ios::beg);
    cout << endl;

    cout << (char)strbuf.sgetc();
```

```

while( (ch = strbuf.snextc()) != EOF)
    cout << ch;

    return 0;
}

```

Result:

AxBC

xBCDEF

basic_streambuf::sungetc

Description To restore a character extracted.

Prototype `int_type sungetc();`

Remarks The function `sungetc()` restores the previously extracted character. After the operation, the `get` pointer references the last character extracted.

Return If successful returns a pointer to the `get` pointer as an `int_type` otherwise returns `ebackfail(c)`.

Listing 17.10 Example of `streambuf::sungetc()` usage:

See: `streambuf::sputbackc()`

27.5.2.2.5 Put Area

Public functions for inputting characters into a buffer.

basic_streambuf::sputc

Description To insert a character in the stream.

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

Prototype `int_type sputc(char_type c);`

Remarks The function `sputc()` inserts a character into the stream. After the operation, the get pointer references the character following the last character extracted.

Return If successful returns `c` as an `int_type` otherwise returns `overflow(c)`.

Listing 17.11 Example of `streambuf::sputc()` usage:

```
#include <iostream>
#include <sstream>

main()
{
    using namespace std;

    stringbuf strbuf;
    strbuf.sputc('A');

    char ch;
    ch = strbuf.sgetc();
    cout << ch;

    return 0;
}
```

Result:

A

`basic_streambuf::sputn`

Description To insert a series of characters into a stream.

Prototype `int_type sputn(char_type *s, streamsize n);`

- Remarks** The function `sputn()` inserts a series of characters into a stream. After the operation, the `get` pointer references the character following the last character extracted.
- Return** A `streamsize` type returned from a call to `xputn(s,n)`.

27.5.2.3 `basic_streambuf` Protected Member Functions

Protected member functions that are used for stream buffer manipulations by the `basic_streambuf` class and derived classes from it.

27.5.2.3.1 Get Area Access

Member functions for extracting information from a stream.

`basic_streambuf::eback`

- Description** Retrieve the beginning pointer for stream input.
- Prototype** `char_type* eback() const;`
- Return** The beginning pointer.

`basic_streambuf::gptr`

- Description** Retrieve the next pointer for stream input.
- Prototype** `char_type* gptr() const;`
- Return** The next pointer.

`basic_streambuf::egptr`

- Description** Retrieve the end pointer for stream input.
- Prototype** `char_type* egptr() const;`

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>

Return The end pointer.

basic_streambuf::gbump

Description Advances the next pointer for stream input.

Prototype `void gbump(int n);`

Remarks The function `gbump()` advances the input pointer by the value of the `int n` argument.

basic_streambuf::setg

Description To set the beginning, next and end pointers.

Prototype `void setg
 (char_type *gbeg,
 char_type *gnext,
 char_type *gend);`

Remarks After the call to `setg()` the `gbeg` pointer equals `eback()`, the `gnext` pointer equals `gptr()`, and the `gend` pointer equals `egptr()`.

27.5.2.3.2 Put Area Access

Protected member functions for stream output sequences.

basic_streambuf::pbase

Description To retrieve the beginning pointer for stream output.

Prototype `char_type* pbase() const;`

Return The beginning pointer.

basic_streambuf::pptr

Description To retrieve the next pointer for stream output.

Prototype `char_type* pptr() const;`

Return The next pointer.

basic_streambuf::epptr

Description To retrieve the end pointer for stream output.

Prototype `char_type* epptr() const;`

Return The end pointer.

basic_streambuf::pbump

Description To advance the next pointer for stream output.

Prototype `void pbump(int n);`

Remarks The function `pbump()` advances the next pointer by the value of the `int` argument `n`.

basic_streambuf::setp

Description To set the values for the beginning, next and end pointers.

Prototype `void setp
 (char_type* pbeg,
 char_type* pend);`

Remarks After the call to `setp()`, `pbeg` equals `pbase()`, `pbeg` equals `pptr()` and `pend` equals `epptr()`.

27.5 Stream Buffers

27.5.2 Template class `basic_streambuf<charT, traits>`

27.5.2.4 `basic_streambuf` Virtual Functions

Description The virtual functions in `basic_streambuf` class are to be overloaded in any derived class.

27.5.2.4.1 Locales

Description To get and set the stream locale. These functions should be overridden in derived classes.

`basic_streambuf::imbue`

Description To change any translations base on locale.

Prototype `virtual void imbue(const locale &loc);`

Remarks The `imbue()` function allows the derived class to be informed in changes of locale and to cache results of calls to locale functions.

27.5.2.4.2 Buffer Management and Positioning

Virtual functions for positioning and manipulating the stream buffer. These functions should be overridden in derived classes.

`basic_streambuf::setbuf`

Description To set a buffer for stream input and output sequences.

Prototype `virtual basic_streambuf<char_type, traits> *
setbuf
(char_type* s, streamsize n);`

Remarks The function `setbuf()` is overridden in `basic_stringbuf` and `basic_filebuf` classes.

Return The `this` pointer.

basic_streambuf::seekoff

Description To return an offset of the current pointer in an input or output streams.

Prototype `virtual pos_type seekoff
(off_type off,
ios_base::seekdir way,
ios_base::openmode which = ios::in | ios::out);`

Remarks The function `seekoff()` is overridden in `basic_stringbuf` and `basic_filebuf` classes.

Return A `pos_type` value, which is an invalid stream position.

basic_streambuf::seekpos

Description To alter an input or output stream position.

Prototype `virtual pos_type seekpos
(pos_type sp,
ios_base::openmode which = ios::in | ios::out);`

Remarks The function `seekpos()` is overridden in `basic_stringbuf` and `basic_filebuf` classes.

Return A `pos_type` value, which is an invalid stream position.

basic_streambuf::sync

Description To synchronize the controlled sequences in arrays.

Prototype `virtual int sync();`

Remarks If `pbase()` is non null the characters between `pbase()` and `pptr()` are written to the control sequence. The function `setbuf()` is overridden the `basic_filebuf` class.

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>

Return Zero if successful and -1 if failure occurs.

27.5.2.4.3 Get Area

Description Virtual functions for extracting information from an input stream buffer. These functions should be overridden in derived classes.

basic_streambuf::showmanyc

Description Shows how many characters in an input stream

Prototype `virtual int showmanyc();`

Remarks If the function `showmanyc()` returns a positive value then calls to `underflow()` will succeed. If `showmanyc()` returns a negative number any calls to the functions `underflow()` and `uflow()` will fail.

Return Zero for normal behavior and negative or positive one.

basic_streambuf::xsgetn

Description To read a number of characters from an input stream buffer.

Prototype `virtual streamsize xsgetn
(char_type *s, streamsize n);`

Remarks The characters are read by repeated calls to `sbumpc()` until either `n` characters have been assigned or `EOF` is encountered.

Return The number of characters read.

basic_streambuf::underflow

Description To show an underflow condition and not increment the get pointer.

Prototype `virtual int_type underflow();`

Remarks The function `underflow()` is called when a character is not available for `sgetc()`.

There are many constraints for `underflow()`.

- The pending sequence of characters is a concatenation of end pointer minus the get pointer plus some sequence of characters to be read from input.
- The result character if the sequence is not empty the first character in the sequence or the next character in the sequence.
- The backup sequence if the beginning pointer is null, the sequence is empty, otherwise the sequence is the get pointer minus the beginning pointer.

Return The first character of the pending sequence and does not increment the get pointer. If the position is null returns `traits::eof()` to indicate failure.

basic_streambuf::uflow

Description To show a underflow condition for a single character and increment the get pointer.

Prototype `virtual int_type uflow();`

Remarks The function `uflow()` is called when a character is not available for `sbumpc()`.

The constraints are the same as `underflow()`, with the exceptions that the resultant character is transferred from the pending sequence to the back up sequence and the pending sequence may not be empty.

Return Calls `underflow()` and if `traits::eof` is not returned returns the integer value of the get pointer and increments the next pointer for input.

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>

27.5.2.4.4 Putback

Virtual functions for replacing data to a stream. These functions should be overridden in derived classes.

basic_streambuf::pbackfail

Description	To show a failure in a put back operation.
Prototype	<pre>virtual int_type pbackfail (int_type c = traits::eof());</pre>
Remarks	The resulting conditions are the same as the function <code>underflow()</code> .
Return	The function <code>pbackfail()</code> is only called when a put back operation really has failed and returns <code>traits::eof</code> . If success occurs the return is undefined.

27.5.2.4.5 Put Area

Virtual function for inserting data into an output stream buffer. These functions should be overridden in derived classes.

basic_streambuf::xspn

Description	Write a number of characters to an output buffer.
Prototype	<pre>virtual streamsize xspn (const char_type *s, streamsize n);</pre>
Remarks	The function <code>xspn()</code> writes to the output character by using repeated calls to <code>sputc(c)</code> . Write stops when <code>n</code> characters have been written or EOF is encountered.
Return	The number of characters written in a type <code>streamsize</code> .

basic_streambuf::overflow

Description Consumes the pending characters of an output sequence.

Prototype `virtual int_type overflow
(int_type c = traits::eof());`

Remarks The pending sequence is defined as the concatenation of the `put pointer` minus the `beginning pointer` plus either the sequence of characters or an empty sequence, unless the `beginning pointer` is null in which case the pending sequence is an empty sequence.

This function is called by `sputc()` and `sputn()` when the buffer is not large enough to hold the output sequence.

Overriding this function requires that:

- When overridden by a derived class how characters are consumed must be specified.
- After the overflow either the `beginning pointer` must be null or the `beginning` and `put pointer` must both be set to the same non-null value.
- The function may fail if appending characters to an output stream fails or failure to set the previous requirement occurs.

Return The function returns `traits::eof()` for failure or some unspecified result to indicate success.

27.5 Stream Buffers

27.5.2 Template class *basic_streambuf*<charT, traits>



27.6 Formatting And Manipulators

This chapter discusses formatting and manipulators in the input/output library.

Overview of Formatting and Manipulators

There are three headers—`<istream>`, `<ostream>`, and `<iomanip>`—that contain stream formatting and manipulator routines and implementations.

The sections in this chapter are:

- [“Headers” on page 511](#)
- [“27.6.1 Input Streams” on page 513](#)
- [“27.6.2 Output streams” on page 547](#)
- [“27.6.3 Standard manipulators” on page 570](#)

Headers

This section lists the header for `istream`, `ostream`, and `iomanip`.

Header `<istream>`

Prototype

```
#include <ios>
namespace std{
template
    <class charT, class traits = ios_traits<charT> >
class basic_istream;
```

27.6 Formatting And Manipulators

Headers

```
typedef basic_istream<char> istream;
typedef basic_istream<wchar_t> wistream;

template
    <class charT, class traits>
basic_istream<charT, traits> &ws
    (basic_istream<charT,traits> (is);
}
```

Header <ostream>

```
#include <ios>
namespace std{
template
    <class charT, class traits = ios_traits<charT> >
class basic_ostream;

typedef basic_ostream<char> ostream;
typedef basic_ostream<wchar_t> wostream;

template
    <class charT, class traits>
basic_ostream<charT, traits> &endl
    (basic_ostream<charT,traits>& os);

template
    <class charT, class traits>
basic_ostream<charT, traits> &ends
    (basic_ostream<charT,traits>& os);

template
    <class charT, class traits>
basic_ostream<charT, traits> &flush
    (basic_ostream<charT,traits>& os);
}
```

Header <iomanip>

```
#include <ios>
namespace std {
// return types are unspecified
T1 resetiosflags(ios_base::fmtflags mask);
T2 setiosflags (ios_base::fmtflag mask);
T3 setbase(int base);
T4 setfill(int c);
T5 setprecision(int n);
T6 setw(int n);
}
```

27.6.1 Input Streams

The header <istream> controls input from a stream buffer.

The topics in this section are:

- [“27.6.1.1 Template class basic_istream” on page 513](#)
- [“27.6.1.1.1 basic_istream Constructors” on page 516](#)
- [“27.6.1.1.2 Class basic_istream::sentry” on page 517](#)
- [“27.6.1.2 Formatted input functions” on page 519](#)
- [“27.6.1.2.1 Common requirements” on page 519](#)
- [“27.6.1.2.2 Arithmetic Extractors Operator >>” on page 519](#)
- [“27.6.1.2.3 basic_istream extractor operator >>” on page 520](#)
- [“27.6.1.3 Unformatted input functions” on page 525](#)
- [“27.6.1.4 Standard basic_istream manipulators” on page 544](#)
- [“27.6.1.4.1 basic_iostream Constructor” on page 546](#)

27.6.1.1 Template class basic_istream

Description	A class that defines several functions for stream input mechanisms from a controlled stream buffer.
--------------------	---

27.6 Formatting And Manipulators

27.6.1 Input Streams

Prototype

```
namespace std{
template
    <class charT, class traits = ios_traits<charT> >
class basic_istream : virtual public basic_ios<charT, traits> {
public:
    typedef charT
    typedef typename traits::int_type int_type;
    typedef typename traits::pos_type pos_type;
    typedef typename traits::off_type off_type;

    explicit basic_istream
    (basic_streambuf<charT, traits>* sb);

    virtual ~basic_istream();

    class sentry;

    basic_istream<charT, traits>& operator >>
        (basic_istream<charT, traits>& (*pf)
        (basic_istream<charT, traits>&))
    basic_istream<charT, traits>& operator >>
        (basic_ios<charT, traits>& (*pf)
        (basic_ios<charT, traits>&))
    basic_istream<charT, traits>& operator >>
        (char_type *s);
    basic_istream<charT, traits>& operator >>
        (char_type& c);
    basic_istream<charT, traits>& operator >>
        (bool& n);
    basic_istream<charT, traits>& operator >>
        (short& n);
    basic_istream<charT, traits>& operator >>
        (unsigned short& n);
    basic_istream<charT, traits>& operator >>
        (int& n);
    basic_istream<charT, traits>& operator >>
        (unsigned int& n);
    basic_istream<charT, traits>& operator >>
        ( long& n);
```

```
basic_istream<charT, traits>& operator >>
    (unsigned long& n);
basic_istream<charT, traits>& operator >>
    (float& f);
basic_istream<charT, traits>& operator >>
    (double& f);
basic_istream<charT, traits>& operator >>
    (long double & f);
basic_istream<charT, traits>& operator >>
    (void*& p);
basic_istream<charT, traits>& operator >>
    (basic_streambuf<char_type, traits>* sb);

streamsize gcount() const;
int_type get();
basic_istream<charT, traits>& get
    (char_type& c);
basic_istream<charT, traits>& get
    (char_type* s,
     streamsize n,
     char_type delim = traits::newline());
basic_istream<charT, traits>& get
    (basic_streambuf<char_type,
     traits>& sb,
     char_type delim = traits::newline());

basic_istream<charT, traits>& getline
    (char_type* s,
     streamsize n,
     char_type delim = traits::newline());

basic_istream<charT, traits>& ignore
    (streamsize n = 1,
     int_type delim = traits::eof());

int_type peek();

basic_istream<charT, traits>& read
    (char_type* s, streamsize n);
streamsize readsome(charT_type* s, streamsize n);
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
basic_istream<charT, traits>& putback(char_type c);
basic_istream<charT, traits>& unget();

int sync();

pos_type tellg();
basic_istream<charT, traits>& seekg
    (pos_type);
basic_istream<charT, traits>& seekg
    (off_type, ios_base::seekdir);
};
}
```

Remarks The `basic_istream` class is derived from the `basic_ios` class and provides many functions for input operations.

27.6.1.1.1 `basic_istream` Constructors

constructor

Description Creates an `basic_istream` object.

Prototype `explicit basic_istream
(basic_streambuf<charT, traits>* sb);`

Remarks The `basic_istream` constructor is overloaded. It can be created as a base class with no arguments. It may be a simple input class initialized to a previous object's stream buffer.

Destructor

Description Destroy the `basic_istream` object.

Prototype `virtual ~basic_istream()`

Remarks The `basic_istream` destructor removes from memory the `basic_istream` object.

Listing 18.1 Example of basic_istream() usage:

MW Reference file contains

Ask the teacher anything you want to know

```

#include <iostream>
#include <fstream>
#include <cstdlib>

main()
{
    using namespace std;

    ofstream out("MW Reference", ios::out | ios::in);
    if(!out.is_open())
        {cout << "file did not open"; exit(1);}

    istream inOut(out.rdbuf());

    char c;
    while(inOut.get(c)) cout.put(c);

    return 0;
}

```

Result:

Ask the teacher anything you want to know

27.6.1.1.2 Class basic_istream::sentry

Description A class for exception safe prefix and suffix operations.

Prototype

```

namespace std {
template
    <class charT,
    class traits = char_traits<charT> >
class basic_istream<charT, traits>::sentry {
    bool ok_;
public:
    explicit sentry

```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
        (basic_istream<charT,  
        traits>& is,  
        bool noskipws = false);  
    ~sentry();  
    operator bool() {return ok_;}  
};  
}
```

Class `basic_istream::sentry` Constructor

Constructor

Description Prepare for formatted or unformatted input

Prototype `explicit sentry
(basic_istream<charT,
traits>& is,
bool noskipws = false);`

Remarks If after the operation `is.good()` is true `ok_ equals true` otherwise `ok_ equals false`. The constructor may call `set-state(failbit)` which may throw an exception.

Destructor

Prototype `~sentry();`

Remarks The destructor has no effects.

`sentry::Operator bool`

Description To return the value of the data member `ok_`.

Prototype `operator bool();`

Return Operator `bool` returns the value of `ok_`

27.6.1.2 Formatted input functions

Formatted function provide mechanisms for input operations of specific types.

27.6.1.2.1 Common requirements

Each formatted input function begins by calling `ipfx()` and if the scan fails for any reason calls `setstate(failbit)`. The behavior of the scan functions are “as if” it was `fscanf()`.

27.6.1.2.2 Arithmetic Extractors Operator >>

Description Extractors that provide formatted arithmetic input operation.

Prototype

```
basic_istream<charT, traits>& operator >>
    (bool & n);
basic_istream<charT, traits>& operator >>
    (short &n);
```

Remarks: Extracts a short integer value and stores it in `n`.

```
basic_istream<charT, traits>& operator >>
    (unsigned short & n);
basic_istream<charT, traits>& operator >>
    (int & n);
basic_istream<charT, traits>& operator >>
    (unsigned int &n);
basic_istream<charT, traits>& operator >>
    (long & n);
basic_istream<charT, traits>& operator >>
    (unsigned long & n);
basic_istream<charT, traits>& operator >>
    (float & f);
basic_istream<charT, traits>& operator >>
    (double& f);
basic_istream<charT, traits>& operator >>(
    long double& f);
```

Remarks The Arithmetic extractors extract a specific type from the input stream and store it in the address provided

27.6 Formatting And Manipulators

27.6.1 Input Streams

Table 18.1 States and stdio equivalents

state	stdio equivalent
(flags() & basefield) == oct	%o
(flags() & basefield) == hex	%x
(flags() & basefield) != 0	%x
(flags() & basefield) == 0	%i
Otherwise	
signed integral type	%d
unsigned integral type	%u

27.6.1.2.3 basic_istream extractor operator >>

Description

Extracts characters or sequences of characters and converts if necessary to numerical data.

Prototype

```
basic_istream<charT, traits>& operator >>
    basic_istream<charT, traits>& (*pf)
    (basic_istream<charT, traits>&))
```

Remarks

Returns pf(*this).

```
basic_istream<charT, traits>& operator >>
    (basic_ios<charT, traits>& (*pf)
    (basic_ios<charT, traits>&))
```

Remarks

Calls pf(*this) then returns *this.

```
basic_istream<charT, traits>& operator >>
    (char_type *s);
```

Remarks

Extracts a char array and stores it in s if possible otherwise call setstate(failbit). If width() is set greater than zero width()-1 elements are extracted else up to size of s-1 elements are extracted. Scan stops with a whitespace “as if” in fscanf().

```
basic_istream<charT, traits>& operator >>
    (char_type& c);
```

Remarks

Extracts a single character and stores it in c if possible otherwise call setstate(failbit).


```
basic_istream<charT, traits>& operator >>
(void*& p);
```

Remarks Converts a pointer to void and stores it in p.

```
basic_istream<charT, traits>& operator >>
(basic_streambuf<char_type, traits>* sb);
```

Remarks Extracts a `basic_streambuf` type and stores it in sb if possible otherwise call `setstate(failbit)`.

Remarks The various overloaded extractors are used to obtain formatted input dependent upon the type of the argument. Since they return a reference to the calling stream they may be chained in a series of extractions. The overloaded extractors work “as if” like `fscanf()` in standard C and read until a white space character or EOF is encountered.

NOTE: The white space character is not extracted and is not discarded, but simply ignored. Be careful when mixing unformatted input operations with the formatted extractor operators. Such as when using console input.

Returns The this pointer is returned.

See Also `basic_ostream::operator <<`

Listing 18.2 Example of `basic_istream::` extractor usage:

The MW Reference input file contains
float 33.33 double 3.16e+10 Integer 789 character C

```
#include <iostream>
#include <fstream>
#include <cstdlib>
```

```
char ioFile[81] = "MW Reference";
```

```
main()
{
using namespace std;
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
ifstream in(ioFile);
if(!in.is_open())
{cout << "cannot open file for input"; exit(1);}

char type[20];
double d;
int i;
char ch;

in  >> type >> d;
cout << type << " " << d << endl;
in  >> type >> d;
cout << type << " " << d << endl;
in  >> type >> i;
cout << type << " " << i << endl;
in  >> type >> ch;
cout << type << " " << ch << endl;

cout << "\nEnter an integer: ";
cin >> i;
cout << "Enter a word: ";
cin >> type;
cout << "Enter a character \ "
    << "then a space then a double: ";
cin >> ch >> d;

cout << i << " " << type << " "
    << ch << " " << d << endl;

in.close();

return 0;
}
```

Result:

```
float 33.33
double 3.16e+10
Integer 789
character C
```

```
Enter an integer: 123 <enter>
Enter a word: Metrowerks <enter>
Enter a character then a space then a double: a 12.34 <enter>
123 Metrowerks a 12.34
```

Overloading Extractors:

Description	To provide custom formatted data retrieval.
Prototype	<pre>extractor prototype Basic_istream &operator >> (basic_istream &s,const imanip<T>&) { // procedures return s; }</pre>
Remarks	You may overload the extractor operator to tailor the specific needs of a particular class.
Returns	The this pointer is returned.

Listing 18.3 Example of basic_istream overloaded extractor usage:

```
#include <iostream>
#include <iomanip>
#include <cstdlib>
#include <cstring>

class phonebook {
    friend std::ostream &operator<<(std::ostream &stream,
        phonebook o);
    friend std::istream &operator>>(std::istream &stream,
        phonebook &o);

private:
    char name[80];
    int areacode;
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
int exchange;
int num;

public:
void putname() {std::cout << num;}
phonebook() {}; // default constructor
phonebook(char *n, int a, int p, int nm)
    {std::strcpy(name, n); areacode = a;
     exchange = p; num = nm;}
};

main()
{
using namespace std;
    phonebook a;

    cin >> a;
    cout << a;

    return 0;
}

std::ostream &operator<<(std::ostream &stream, phonebook o)
{
using namespace std;

    stream << o.name << " ";
    stream << "(" << o.areacode << ") ";
    stream << o.exchange << "-";
    cout << setfill('0') << setw(4) << o.num << "\n";
    return stream;
}

std::istream &operator>>(std::istream &stream, phonebook &o)
{
using namespace std;

    char buf[5];
    cout << "Enter the name: ";
    stream >> o.name;
```

```
cout << "Enter the area code: ";
stream >> o.areacode;
cout << "Enter exchange: ";
stream >> o.exchange;
cout << "Enter number: ";
stream >> buf;
o.num = atoi(buf);
cout << "\n";
return stream;
}
```

Result:

```
Enter the name: Metrowerks
Enter the area code: 512
Enter exchange: 873
Enter number: 4700
```

```
Metrowerks (512) 873-4700
```

27.6.1.3 Unformatted input functions

The various unformatted input functions all begin by construction an object of type `basic_istream::sentry` and ends by destroying the `sentry` object.

NOTE: Older versions of the library may begin by calling `ipfx()` and end by calling `isfx()` and returning the value specified.

basic_istream::gcount

Description To obtain the number of bytes read.

Prototype `streamsize gcount() const;`

Remarks Use the function `gcount ()` to obtain the number of bytes read by the last unformatted input function called by that object.

27.6 Formatting And Manipulators

27.6.1 Input Streams

Returns An int type count of the bytes read.

Listing 18.4 Example of basic_istream::gcount() usage:

```
#include <iostream>
#include <fstream>

const SIZE = 4;

struct stArray {
    int index;
    double dNum;
};

main()
{
    using namespace std;

    ofstream fOut("test");
    if(!fOut.is_open())
        {cout << "can't open out file"; return 1;}

    stArray arr;
    short i;

    for(i = 1; i < SIZE+1; i++)
    {
        arr.index = i;
        arr.dNum = i *3.14;
        fOut.write((char *) &arr, sizeof(stArray));
    }
    fOut.close();

    stArray aIn[SIZE];

    ifstream fIn("test");
    if(!fIn.is_open())
        {cout << "can't open in file"; return 2;}

    long count =0;
```

```

for(i = 0; i < SIZE; i++)
{
    fIn.read((char *) &aIn[i], sizeof(stArray));

    count+=fIn.gcount();
}

cout << count << " bytes read " << endl;
cout << "The size of the structure is "
    << sizeof(stArray) << endl;
for(i = 0; i < SIZE; i++)
cout << aIn[i].index << " " << aIn[i].dNum
    << endl;

fIn.close();

return 0;
}

```

Result:

```

48 bytes read
The size of the structure is 12
1 3.14
2 6.28
3 9.42
4 12.56

```

basic_istream::get

Description Overloaded functions to retrieve a `char` or a `char` sequence from an input stream.

Prototype `int_type get();`

Remarks Extracts a character if available and returns that value. Else, calls `setstate(failbit)` and returns `eof()`.

`basic_istream<charT, traits>& get(char_type& c);`

Remarks Extracts a character and assigns it to `c` if possible else calls `setstate(failbit)`.

`basic_istream<charT, traits>& get`

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
(char_type* s,  
streamsize n,  
char_type delim = traits::newline());
```

Remarks Extracts characters and stores them in a `char` array at an address pointed to by `s`, until

- A limit (the second argument minus one) or the number of characters to be stored is reached
- A delimiter (the default value is the newline character) is met. In which case, the delimiter is not extracted.
- If `end_of_file` is encountered in which case `setstate(eofbit)` is called.

If no characters are extracted calls `setstate(failbit)`. In any case it stores a `null` character in the next available location of array `s`.

```
basic_istream<charT, traits>& get  
(basic_streambuf<char_type,  
traits>& sb,  
char_type delim = traits::newline());
```

Remarks Extracts a characters and assigns them to the `basic_streambuf` object `sb` if possible else calls `setstate(failbit)`. Extraction stops if...

- an insertion fails
- `end-of-file` is encountered.
- an exception is thrown
- the next the next available character `c == delim` (in which case `c` is not extracted.)

Returns An integer when used with no argument. When used with an argument if a character is extracted the `get()` function returns `The this pointer`. If no character is extracted `setstate(failbit)` is called. In any case a `null char` is appended to the array.

See Also `getline()`

Listing 18.5 Example of `basic_istream::get()` usage:

READ ONE CHARACTER:

MW Reference file for input

float 33.33 double 3.16e+10 Integer 789 character C

```
#include <iostream>
```

```
#include <fstream>
```

```
#include <cstdlib>
```

```
main()
```

```
{
```

```
using namespace std;
```

```
    char inFile[] = "MW Reference";
```

```
    ifstream in(inFile);
```

```
    if(!in.is_open())
```

```
    {cout << "Cannot open input file"; exit(1);}
```

```
    char ch;
```

```
    while(in.get(ch)) cout << ch;
```

```
    return 0;
```

```
}
```

Result:

float 33.33 double 3.16e+10 Integer 789 character C

READ ONE LINE:

```
#include <iostream>
```

```
#include <iostream>
```

```
const int size = 100;
```

```
char buf[size];
```

```
main()
```

```
{
```

```
using namespace std;
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
cout << " Enter your name: ";
cin.get(buf, size);
cout << buf;

return 0;
}
```

Result:

```
Enter your name: Metrowerks CodeWarrior <enter>
Metrowerks CodeWarrior
```

basic_istream::getline

Description To obtain a delimiter terminated character sequence from an input stream.

Prototype `basic_istream<charT, traits>& getline
(char_type* s,
streamsize n,
char_type delim = traits::newline());`

Remarks The unformatted `getline()` function retrieves character input, and stores it in a character array buffer `s` if possible until the following conditions evaluated in this order occur. If no characters are extracted `setstate(failbit)` is called.

- end-of-file occurs in which case `setstate eofbit` is called.
- A delimiter (default value is the newline character) is encountered. In which case the delimiter is read and extracted but not stored.
- A limit (the second argument minus one) is read.
- if `n-1` chars are read that `failbit` gets set.

In any case it stores a null char into the next successive location of the array.

Returns The `this` pointer is returned.

See Also `basic_ostream::flush()`

Listing 18.6 Example of `basic_istream::getline()` usage:

```
#include <iostream>
```

```
const int size = 120;
```

```
main()
```

```
{
```

```
using namespace std;
```

```
    char compiler[size];
```

```
    cout << "Enter your compiler: ";
```

```
    cin.getline(compiler, size);
```

```
    cout << "You use " << compiler;
```

```
    return 0;
```

```
}
```

Result:

Enter your compiler:Metrowerks CodeWarrior <enter>

You use Metrowerks CodeWarrior

```
#include <iostream>
```

```
const int size = 120;
```

```
#define TAB '\t'
```

```
main()
```

```
{
```

```
using namespace std;
```

```
    cout << "What kind of Compiler do you use: ";
```

```
    char compiler[size];
```

```
    cin.getline(compiler, size,TAB);
```

```
    cout << compiler;
```

```
    cout << "\nsecond input not needed\n";
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
cin >> compiler;
cout << compiler;

return 0;
}
```

Result:

```
What kind of Compiler do you use:
Metrowerks CodeWarrior<tab>Why?
Metrowerks CodeWarrior
second input not needed
Why?
```

basic_istream::ignore

Description To extract and discard a number of characters.

Prototype `basic_istream<charT, traits>& ignore
(streamsize n = 1,
int_type delim = traits::eof());`

Remarks The function `ignore()` will extract and discard characters until

- A limit is met (the first argument)
- end-of-file is encountered (in which case `setstate(eofbit)` is called.)
- The next character `c` is equal to the delimiter `delim`, in which case it is extracted except when `c` is equal to `traits::eof()`;

Returns The `this` pointer is returned.

Listing 18.7 Example of `basic_istream::ignore()` usage:

The file `MW Reference` contains:

```
char ch; // to save char
/*This C comment will remain */
while((ch = in.get())!= EOF) cout.put(ch);
// read until failure
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
/* the C++ comments won't */

#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";
char bslash = '/';

main()
{
using namespace std;

    ifstream in(inFile);
    if(!in.is_open())
        {cout << "file not opened"; exit(1);}

    char ch;
    while((ch = in.get()) != EOF)
    {
        if(ch == bslash && in.peek() == bslash)
        {
            in.ignore(100, '\n');
            cout << '\n';
        }
        else
            cout << ch;
    }

    return 0;
}
```

Result:

```
char ch;
    /*This C comment will remain */
while((ch = in.get())!= EOF) cout.put(ch);

/* the C++ comments won't */
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

basic_istream::peek

Description	To view at the next character to be extracted.
Prototype	<code>int_type peek();</code>
Remarks	The function <code>peek()</code> allows you to look ahead at the next character in a stream to be extracted without extracting it.
Returns	If <code>good()</code> is false returns <code>traits::eof()</code> else returns the value of the next character in the stream.

Listing 18.8 Example of basic_istream::peek() usage:

See `basic_istream::ignore()`

basic_istream::read

Description	To obtain a block of binary data from and input stream.
Prototype	<code>basic_istream<charT, traits>& read (char_type* s, streamsize n);</code>
Remarks	<p>The function <code>read()</code> will attempt to extract a block of binary data until the following conditions are met.</p> <ul style="list-style-type: none">• A limit of <code>n</code> number of characters are stored.• <code>end-of-file</code> is encountered on the input (in which case <code>setstate(failbit)</code> is called.
Returns	The <code>this</code> pointer is returned.
See Also	<code>write()</code>

Listing 18.9 Example of basic_istream::read() usage:

```
#include <iostream>
#include <fstream>
#include <iomanip>
```

```
#include <cstdlib>
#include <cstring>

struct stock {
    char name[80];
    double price;
    long trades;
};

char *Exchange = "BBSE";
char *Company = "Big Bucks Inc.";

main()
{
    using namespace std;

    stock Opening, Closing;

    strcpy(Opening.name, Company);
    Opening.price = 180.25;
    Opening.trades = 581300;

    // open file for output
    ofstream Market(Exchange, ios::out | ios::trunc | ios::binary);
    if(!Market.is_open())
        {cout << "can't open file for output"; exit(1);}

    Market.write((char*) &Opening, sizeof(stock));
    Market.close();

    // open file for input
    ifstream Market2(Exchange, ios::in | ios::binary);
    if(!Market2.is_open())
        {cout << "can't open file for input"; exit(2);}

    Market2.read((char*) &Closing, sizeof(stock));

    cout << Closing.name << "\n"
        << "The number of trades was: " << Closing.trades << "\n";
    cout << fixed << setprecision(2)
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
<< "The closing price is: $" << Closing.price << endl;

Market2.close();

return 0;
}
```

Result:

Big Bucks Inc.

The number of trades was: 581300

The closing price is: \$180.25

basic_istream::readsome

Description Extracts characters and stores them in an array.

Prototype `streamsize readsome
(charT_type* s, streamsize n);`

Remarks The function `readsome` extracts and stores characters storing them in the buffer pointed to by `s` until the following conditions are met.

- end-of-file is encountered (in which case `setstate(eofbit)` is called.)
- No characters are extracted.
- A limit of characters is extracted either `n` or the size of the buffer.

Returns The number of characters extracted.

Listing 18.10 Example of `basic_istream::readsome()` usage.

The file MW Reference contains:

Metrowerks CodeWarrior

Software at Work

Registered Trademark

```
#include <iostream>
#include <fstream>
#include <sstream>
#include <cstdlib>

const short SIZE = 81;

main()
{
    using namespace std;

    ifstream in("MW Reference");
    if(!in.is_open())
    {cout << "can't open file for input"; exit(1);}

    char Buffer[SIZE] = "\0";
    ostringstream Paragraph;

    while(in.good() && (in.peek() != EOF))
    {
        in.readsome(Buffer, 5);
        Paragraph << Buffer;
    }

    cout << Paragraph.str();

    in.close();
    return 0;
}
```

Result:

Metrowerks CodeWarrior
Software at Work
Registered Trademark

basic_istream::putback

Description To replace a previously extracted character.

27.6 Formatting And Manipulators

27.6.1 Input Streams

Prototype `basic_istream<charT, traits>& putback
 (char_type c);`

Remarks The function `putback()` allows you to replace the last character extracted by calling `rdbuf()->sungetc()`. If the buffer is empty, or if `sungetc()` returns `eof`, `setstate(failbit)` may be called.

Returns The `this` pointer is returned.

See Also `sungetc()`

Listing 18.11 Example of `basic_istream::putback` usage:

The file `MW Reference` contains.

```
char ch;           // to save char
    /* comment will remain */
while((ch = in.get()) != EOF) cout.put(ch);
// read until failure
```

```
#include <iostream>
#include <fstream>
#include <stdlib.h>
```

```
char inFile[] = "MW Reference";
char bslash = '/';
```

```
main()
{
using namespace std;

    ifstream in(inFile);
    if(!in.is_open())
    {cout << "file not opened"; exit(1);}

    char ch, tmp;
    while((ch = in.get()) != EOF)
    {
        if(ch == bslash)
        {
            in.get(tmp);
```

```

        if(tmp != bslash)
            in.putback(tmp);
        else continue;
    }
    cout << ch;
}

return 0;
}

```

Result:

```

char ch;                // to save char
/* comment will remain */
while((ch = in.get()) != EOF) cout.put(ch);
// read until failure

```

basic_istream::unget

Description To replace a previously extracted character.

Prototype `basic_istream<charT, traits>&unget();`

Remarks Use the function `unget()` to return the previously extracted character. If `rdbuf()` is null or if end-of-file is encountered `setstate(badbit)` is called.

Returns The this pointer is returned.

See Also `putback()`, `ignore()`

Listing 18.12 Example of `basic_istream::unget()` usage:

The file MW Reference contains:

```

char ch;                // to save char
/* comment will remain */
// read until failure
while((ch = in.get()) != EOF) cout.put(ch);

```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";
char bslash = '/';

main()
{
    using namespace std;

    ifstream in(inFile);
    if(!in.is_open())
    {cout << "file not opened"; exit(1);}

    char ch, tmp;
    while((ch = in.get()) != EOF)
    {
        if(ch == bslash)
        {
            in.get(tmp);
            if(tmp != bslash)
                in.unget();
            else continue;
        }
        cout << ch;
    }

    return 0;
}
```

Result:

```
char ch;                to save char
    /* comment will remain */
    read until failure
while((ch = in.get()) != EOF) cout.put(ch);
```

basic_istream::sync

Description	To synchronize input and output
Prototype	<code>int sync();</code>
Remarks	<p>This functions attempts to make the input source consistent with the stream being extracted.</p> <p>If <code>rdbuf()->pubsync()</code> returns <code>-1</code> <code>setstate(badbit)</code> is called and <code>traits::eof</code> is returned.</p>
Returns	If <code>rdbuf()</code> is Null returns <code>-1</code> otherwise returns zero.

Listing 18.13 Example of basic_istream::sync() usage:

The file MW Reference contains:
 This functions attempts to make the input source
 consistent with the stream being extracted.
 --
 Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main()
{
    using namespace std;

    ifstream in(inFile);
    if(!in.is_open())
        {cout << "could not open file"; exit(1);}

    char str[10];
    if(in.sync())// return 0 if successful
        { cout << "cannot sync"; exit(1); }
    while (in.good())
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
{
    in.get(str, 10, EOF);
    cout <<str;
}
return 0;
}
```

Result:

This functions attempts to make the input source consistent with the stream being extracted.

--

Metrowerks CodeWarrior "Software at Work"

basic_istream::tellg

- Description** To determine the offset of the get pointer in a stream
- Prototype** `pos_type tellg();`
- Remarks** The function `tellg` calls `rdbuf()->pubseekoff(0, cur, in)`.
- Returns** The current offset as a `pos_type` if successful else returns `-1`.
- See Also** `basic_streambuf::pubseekoff()`

Listing 18.14 Example of basic_istream::tellg() usage:

See `basic_istream::seekg()`

basic_istream::seekg

- Description** To move to a variable position in a stream.
- Prototype** `basic_istream<charT, traits>& seekg(pos_type);`
`basic_istream<charT, traits>& seekg`
`(off_type, ios_base::seekdir dir);`

Remarks The function `seekg` is overloaded to take a `pos_type` object, or an `off_type` object (defined in `basic_ios` class.) The function is used to set the position of the `get` pointer of a stream to a random location for character extraction.

Returns The `this` pointer is returned.

See Also `basic_streambuf::pubseekoff()` and `pubseekpos()`.

Listing 18.15 Example of `basic_istream::seekg()` usage:

The file `MW Reference` contains:
`ABCDEFGHIJKLMNOPQRSTUVWXYZ`

```
#include <iostream>
#include <fstream>
#include <cstdlib>

main()
{
    using namespace std;

    ifstream in("MW Reference");
    if(!in.is_open())
        {cout << "could not open file"; exit(1);}

    streampos spEnd, spStart, aCheck;
    spEnd = spStart = 5;

    in.seekg(spStart);
    aCheck = in.tellg();
    cout << "The offset at the start of the reading in bytes is "
         << aCheck.offset() << endl;

    char ch;
    while(spEnd != spStart+10)
    {
        in.get(ch);
        cout << ch;
        spEnd = in.tellg();
    }
}
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
}

aCheck = in.tellg();
cout << "\nThe current position's offset in bytes now is "
    << aCheck.offset() << endl;
streamoff gSet = 0;
in.seekg(gSet, ios::beg);

aCheck = in.tellg();
cout << "The final position's offset in bytes now is "
    << aCheck.offset() << endl;

in.close();
return 0;
}
```

Result:

The offset at the start of the reading in bytes is 5

FGHIJKLMNO

The current position's offset in bytes now is 15

The final position's offset in bytes now is 0

27.6.1.4 Standard `basic_istream` manipulators

`basic_ifstream::ws`

Description To provide inline style formatting.

Prototype

```
template
    <class charT, class traits>
basic_istream<charT, traits> &ws
    (basic_istream<charT,traits>& is);
```

Remarks The `ws` manipulator skips whitespace characters in input.

Returns The `this` pointer.

Listing 18.16 Example of basic_istream:: manipulator ws usage:

The file MW Reference (where the number of blanks (and/or tabs) is unknown) contains:

a b c

```
#include <iostream>
#include <fstream>
#include <cstdlib>

main()
{
    char * inFileName = "MW Reference";

    ifstream in(inFileName);
    if (!in.is_open())
    {cout << "Couldn't open for input\n"; exit(1);}

    char ch;
    in.unsetf(ios::skipws);

    cout << "Does not skip whitespace\n|";
    while (1)
    {
        in >> ch; // does not skip white spaces
        if (in.good())
            cout << ch;
        else break;
    }
    cout << "|\n\n";

    //reset file position
    in.clear();
    in.seekg(0, ios::beg);

    cout << "Does skip whitespace\n|";
    while (1)
    {
        in >> ws >> ch; // ignore white spaces

        if (in.good())
```

27.6 Formatting And Manipulators

27.6.1 Input Streams

```
        cout << ch;
    else break;
}
cout << "|" << endl;

    in.close();
    return(0);
}
```

Result:

Does not skip whitespace

| a b c|

Does skip whitespace

|abc|

27.6.1.4.1 basic_iostream Constructor

Constructor

Description Constructs an and destroy object of the class basic_iostream.

Prototype `explicit basic_iostream
 (basic_streambuf<charT, traits>* (sb));`

Remarks Calls `basic_istream(<charT, traits> (sb)` and `basic_ostream(charT, traits>* (sb)`. After it is constructed `rdbuf()` equals `sb` and `gcount()` equals zero.

Destructor

Prototype `virtual ~basic_iostream();`

Remarks Destroys an object of type `basic_iostream`.

27.6.2 Output streams

The include file `<ostream>` includes classes and types that provide output stream mechanisms.

The topics in this section are:

- [“27.6.2.1 Template class `basic_ostream`” on page 547](#)
- [“27.6.2.2 `basic_ostream` Constructor” on page 549](#)
- [“Class `basic_ostream::sentry` Constructor” on page 551](#)
- [“27.6.2.3 Class `basic_ostream::sentry`” on page 550](#)
- [“27.6.2.4 Formatted output functions” on page 552](#)
- [“27.6.2.4.1 Common requirements” on page 552](#)
- [“27.6.2.4.2 Arithmetic Inserter Operator `<<`” on page 552](#)
- [“27.6.2.4.3 `basic_ostream::operator<<`” on page 554](#)
- [“27.6.2.5 Unformatted output functions” on page 558](#)
- [“27.6.2.6 Standard `basic_ostream` manipulators” on page 565](#)

27.6.2.1 Template class `basic_ostream`

A class for stream output mechanisms.

Prototype

```
namespace std{
template
    <class charT, class traits = ios_traits<charT> >
class basic_ostream : virtual public basic_ios<charT, traits>{
public:
    // Types:
    typedef charTchar_type;
    typedef typename traits::int_type int_type;
    typedef typename traits::pos_type pos_type;
    typedef typename traits::off_type off_type;

    explicit basic_ostream (basic_streambuf<char_type, traits>*sb);
    virtual ~basic_ostream();
```

27.6 Formatting And Manipulators

27.6.2 Output streams

```
class sentry;

basic_ostream<charT, traits>& operator<<
    (basic_ostream<charT, traits>&(*pf)
    (basic_ostream<charT, traits>&));
basic_ostream<charT, traits>& operator<<
    (basic_ostream<charT, traits>&(*pf)
    (basic_ios<charT, traits>&));
basic_ostream<charT, traits>& operator<<
    (const char_type *s)
basic_ostream<charT, traits>& operator<<
    (char_type c)
basic_ostream<charT, traits>& operator<<
    (bool n)
basic_ostream<charT, traits>& operator<<
    (short n)
basic_ostream<charT, traits>& operator<<
    (unsigned short n)
basic_ostream<charT, traits>& operator<<
    (int n)
basic_ostream<charT, traits>& operator<<
    (unsigned int n)
basic_ostream<charT, traits>& operator<<
    (long n)
basic_ostream<charT, traits>& operator<<
    (unsigned long n)
basic_ostream<charT, traits>& operator<<
    (float f)
basic_ostream<charT, traits>& operator<<
    (double f)
basic_ostream<charT, traits>& operator<<
    (long double f)
basic_ostream<charT, traits>& operator<<
    (void p)
basic_ostream<charT, traits>& operator<<
    (basic_streambuf<char_type, traits>* sb);)

basic_ostream<charT, traits>& put(char_type c);

basic_ostream<charT, traits>& write
```

```

    (const char_type* s, streamsize n);

    basic_ostream<charT, traits>& flush();

    pos_type tellp();
    basic_ostream<charT, traits>& seekp(pos_type);
    basic_ostream<charT, traits>& seekp
        (off_type, ios_base::seekdir);
};
}

```

Remarks The `basic_ostream` class provides for output stream mechanisms for output stream classes. The `basic_ostream` class may be used as a independent class, as a base class for the `basic_ofstream` class or a user derived classes.

27.6.2.2 basic_ostream Constructor

Description To create and remove from memory `basic_ostream` object for stream output.

Prototype `explicit basic_ostream
(basic_streambuf<char_type, traits>*sb);`

Remarks The `basic_ostream` constructor constructs and initializes the base class object.

Destructor

Prototype `virtual ~basic_ostream();`

Remarks Removes a `basic_ostream` object from memory.

Listing 18.17 Example of `basic_ostream()` usage:

The MW Reference file contains originally
Metrowerks CodeWarrior "Software at Work"

27.6 Formatting And Manipulators

27.6.2 Output streams

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main()
{
    using namespace std;

    ifstream inOut(inFile, ios::in | ios::out);
    if(!inOut.is_open())
        {cout << "Could not open file"; exit(1);}
    ostream Out(inOut.rdbuf());

    char str[] = "\nRegistered Trademark";

    inOut.rdbuf()->pubseekoff(0, ios::end);

    Out << str;

    inOut.close();

    return 0;
}
```

Result:

The File now reads:

Metrowerks CodeWarrior "Software at Work"

Registered Trademark

27.6.2.3 Class `basic_ostream::sentry`

Description A class for exception safe prefix and suffix operations.

Prototype `namespace std {
 template
 < class charT,`

```

        class traits = char_traits<charT> >
class basic_ostream<charT, traits>::sentry
{
    bool ok_;
public:
    explicit sentry
        (basic_ostream<charT,
         traits>& os,
         bool noskipws = false);
    ~sentry();
    operator bool() {return ok_;}
};

```

Class basic_ostream::sentry Constructor

Constructor

Description Prepare for formatted or unformatted output

Prototype `explicit sentry
(basic_ostream<charT, traits>& os);`

Remarks If after the operation `os.good()` is true `ok_ equals true` otherwise `ok_ equals false`. The constructor may call `set-state(failbit)` which may throw an exception.

Destructor

Prototype `~sentry();`

Remarks The destructor under normal circumstances will call `os.flush()`.

sentry::Operator bool

Description To return the value of the data member `ok_`.

Prototype `operator bool();`

27.6 Formatting And Manipulators

27.6.2 Output streams

Return Operator `bool` returns the value of `ok_`

27.6.2.4 Formatted output functions

Description Formatted output functions provide a manner of inserting for output specific data types.

27.6.2.4.1 Common requirements

Remarks The operations begins by calling `opfx()` and ends by calling `osfx()` then returning the value specified for the formatted output.

Some output maybe generated by converting the scalar data type to a NTBS (null terminated bit string) text.

If the function fails for any for any reason the function calls `set-state(failbit)`.

27.6.2.4.2 Arithmetic Inserter Operator <<

Description To provide formatted insertion of types into a stream.

Prototype

```
basic_ostream<charT, traits>& operator<<
    (short n)
basic_ostream<charT, traits>& operator<<
    (unsigned short n)
basic_ostream<charT, traits>& operator<<
    (int n)
basic_ostream<charT, traits>& operator<<
    (unsigned int n)
basic_ostream<charT, traits>& operator<<
    (long n)
basic_ostream<charT, traits>& operator<<
    (unsigned long n)
basic_ostream<charT, traits>& operator<<
    (float f)
basic_ostream<charT, traits>& operator<<
    (double f)
basic_ostream<charT, traits>& operator<<
```


(long double f)

Remarks Converts an arithmetical value. The formatted values are converted "as if" they had the same behavior of the `fprintf()` function

Returns The `this` pointer is returned

Table 18.2 Output states and stdio equivalents.

Output State	stdio equivalent
Integers	
(flags() & basefield) == oct	%o
(flags() & basefield) == hex	%x
(flags() & basefield) != 0	%X
Otherwise	
signed integral type	%d
unsigned integral type	%u
Floating Point Numbers	
(flags() & floatfield) == fixed	%f
(flags() & floatfield) == scientific	%e
(flags() & uppercase) != 0	%E
Otherwise	
(flags() & uppercase) != 0	%g %G
An integral type other than a char type	
(flags() & showpos) != 0	+
(flags() & showbase) != 0	#
A floating point type	
(flags() & showpos) != 0	+
(flags() & showpoint) != 0	#

27.6 Formatting And Manipulators

27.6.2 Output streams

For any conversion if `width()` is non-zero then a field width a conversion specification has the value of `width()`.

For any conversion if `(flags() and fixed) !=0` or if `precision() >0` the conversion specification is the value of `precision()`.

For any conversion padding behaves in the following manner.

Table 18.3 Conversion state and stcio equivalents.

State	Justification	stdio equivalent
<code>(flags() & adjustfield) == left</code>	left	space padding
<code>(flags() & adjustfield) == internal</code>	Internal	zero padding
Otherwise	right	space padding

Remarks The `ostream` insertion operators are overloaded to provide for insertion of most predefined types into an output stream. They return a reference to the `basic_stream` object so they may be used in a chain of statements to input various types to the same stream.

Returns In most cases `*this` is returned unless failure in which case `setstate(failbit)` is called.

27.6.2.4.3 `basic_ostream::operator<<`

Prototype `basic_ostream<charT, traits>& operator<<
 (basic_ostream<charT, traits>&
 (*pf)(basic_ostream<charT, traits>&));`

Remarks Returns `pf(*this)`.
`basic_ostream<charT, traits>& operator<<
 (basic_ostream<charT, traits>&
 (*pf)(basic_ios<charT, traits>&));`

Remarks Calls `pf(*this)` return `*this`.
`basic_ostream<charT, traits>& operator<<
 (const char_type *s)`

```
basic_ostream<charT, traits>& operator<<
    (char_type c)
basic_ostream<charT, traits>& operator<<
    (bool n)
```

Remarks Behaves depending on how the boolalpha flag is set.

```
basic_ostream<charT, traits>& operator<<
    (void p)
```

Remarks Converts the pointer to void p as if the specifier was %p and returns *this.

```
basic_ostream<charT, traits>& operator<<
    (basic_streambuf<char_type, traits>* sb);)
```

Remarks If sb is null calls setstate(failbit) otherwise gets characters from sb and inserts them into *this until:

- end-of-file occurs.
- inserting into the stream fails.
- an exception is thrown.

If the operation fails calls setstate(failbit) or re-throws the exception, otherwise returns *this.

Remarks The formatted output functions insert the values into the appropriate argument type.

Return Most inserters (unless noted otherwise) return the this pointer.

Listing 18.18 Example of basic_ostream inserter usage:

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char oFile[81] = "MW Reference";

main()
{
    using namespace std;
```

27.6 Formatting And Manipulators

27.6.2 Output streams

```
ofstream out(oFile);

out << "float " << 33.33;
out << " double " << 3.16e+10;
out << " Integer " << 789;
out << " character " << 'C' << endl;
out.close();

cout << "float " << 33.33;
cout << "\ndouble " << 3.16e+10;
cout << "\nInteger " << 789;
cout << "\ncharacter " << 'C' << endl;

return 0;
}
```

Result:

Output: to MWReference

float 33.33 double 3.16e+10 Integer 789 character C

Output to console

float 33.33

double 3.16e+10

Integer 789

character C

Overloading Inserters

Description To provide specialized output mechanisms for an object.

Prototype Overloading inserter prototype

```
basic_ostream &operator<<
    (basic_ostream &stream, const omanip<T>&)
{
    // procedures;
    return stream;
}
```

Remarks You may overload the inserter operator to tailor it to the specific needs of a particular class.

Returns The `this` pointer.

Listing 18.19 Example of overloaded inserter usage:

```
#include <iostream>
#include <string.h>
#include <iomanip>

class phonebook {
    friend ostream &operator<<
        (ostream &stream, phonebook o);
protected:
    char *name;
    int areacode;
    int exchange;
    int num;
public:
    phonebook(char *n, int a, int p, int nm) :
        areacode(a),
        exchange(p),
        num(nm),
        name(n) {}
};

main()
{
    using namespace std;

    phonebook a("Sales", 800, 377, 5416);
    phonebook b("Voice", 512, 873, 4700);
    phonebook c("Fax", 512, 873, 4900);

    cout << a << b << c;

    return 0;
}
```

27.6 Formatting And Manipulators

27.6.2 Output streams

```
std::ostream &operator<<(std::ostream &stream, phonebook o)
{
    stream << o.name << " ";
    stream << "(" << o.areacode << ") ";
    stream << o.exchange << "-";
    stream << setfill('0') << setw(4)
        << o.num << "\n";
    return stream;
}
```

Result:

Sales (800) 377-5416

Voice (512) 873-4700

Fax (512) 873-4900

27.6.2.5 Unformatted output functions

Each unformatted output function begins by creating an object of the class sentry. The unformatted output functions are ended by destroying the sentry object and may return a value specified.

basic_ostream::tellp

Description To return the offset of the put pointer in an output stream.

Prototype `pos_type tellp();`

Returns If `fail()` returns `-1` else returns `rdbuf()->pubseekoff(0, cur, out)`.

See Also `basic_istream::tellg()`, `seekp(0)`.

Listing 18.20 Example of `basic_ostream::tellp()` usage.

see `basic_ostream::seekp()`.

basic_ostream::seekp

Description Randomly move to a position in an output stream.

Prototype `basic_ostream<charT, traits>& seekp(pos_type);`

Prototype `basic_ostream<charT, traits>& seekp
(off_type, iosbase::seekdir);`

Remarks The function `seekp` is overloaded to take a single argument of a `pos_type` `pos` that calls `rdbuf()->pubseekpos(pos)`. It is also overloaded to take two arguments an `off_type` `off` and `ios_base::seekdir` type `dir` that calls `rdbuf()->pubseekoff(off, dir)`.

Returns The this pointer.

See Also `basic_istream seekg()`, `tellp()`

Listing 18.21 Example of basic_ostream::seekp() usage.

```
#include <iostream>
#include <sstream>
#include <string>

std::string motto = "Metrowerks CodeWarrior - Software at Work";

main()
{
    using namespace std;

    ostringstream ostr(motto);
    streampos cur_pos, start_pos;

    cout << "The original array was :\n"
         << motto << "\n\n";
    // associate buffer
    stringbuf *strbuf(ostr.rdbuf());

    streamoff str_off = 10;
```

27.6 Formatting And Manipulators

27.6.2 Output streams

```
cur_pos = ostr.tellp();
cout << "The current position is "
      << cur_pos.offset()
      << " from the beginning\n";

ostr.seekp(str_off);

cur_pos = ostr.tellp();
cout << "The current position is "
      << cur_pos.offset()
      << " from the beginning\n";

strbuf->sputc('\0');

cout << "The stringbuf array is\n"
      << strbuf->str() << "\n\n";
cout << "The ostream array is still\n"
      << motto;

return 0;
}
```

Results:

The original array was :
Metrowerks CodeWarrior - Software at Work

The current position is 0 from the beginning
The current position is 10 from the beginning
The stringbuf array is
Metrowerks

The ostream array is still
Metrowerks CodeWarrior - Software at Work

basic_ostream::put

Description To place a single character in the output stream.

Prototype `basic_ostream<charT, traits>& put(char_type c);`

Remarks The unformatted function `put ()` inserts one character in the output stream. If the operation fails calls `setstate(badbit)`.

Returns The `this` pointer.

Listing 18.22 Example of `basic_ostream::put()` usage:

```
#include <iostream>

main()
{
    using namespace std;

    char *str = "Metrowerks CodeWarrior \"Software at Work\"";
    while(*str)
    {
        cout.put(*str++);
    }
    return 0;
}
```

Result:

Metrowerks CodeWarrior "Software at Work"

`basic_ostream::write`

Description To insert a block of binary data into an output stream.

Prototype `basic_ostream<charT, traits>& write
(const char_type* s, streamsize n);`

Remarks The overloaded function `write ()` is used to insert a block of binary data into a stream. This function is can be used to write an object by casting that object as a `unsigned char` pointer. If the operation fails calls `setstate(badbit)`.

Returns A reference to `ostream`. (The `this` pointer.)

See Also `read ()`

27.6 Formatting And Manipulators

27.6.2 Output streams

Listing 18.23 Example of `basic_ostream::write()` usage:

```
#include <iostream>
#include <fstream>
#include <iomanip>
#include <cstdlib>
#include <cstring>

struct stock {
    char name[80];
    double price;
    long trades;
};

char *Exchange = "BBSE";
char *Company = "Big Bucks Inc.";

main()
{
    using namespace std;

    stock Opening, Closing;

    strcpy(Opening.name, Company);
    Opening.price = 180.25;
    Opening.trades = 581300;

    // open file for output
    ofstream Market(Exchange,
        ios::out | ios::trunc | ios::binary);
    if(!Market.is_open())
    {cout << "can't open file for output"; exit(1);}

    Market.write((char*) &Opening, sizeof(stock));
    Market.close();

    // open file for input
    ifstream Market2(Exchange, ios::in | ios::binary);
    if(!Market2.is_open())
    {cout << "can't open file for input"; exit(2);}
```

```

Market2.read((char*) &Closing, sizeof(stock));

cout << Closing.name << "\n"
    << "The number of trades was: "
    << Closing.trades << '\n';
cout << fixed << setprecision(2)
    << "The closing price is: $"
    << Closing.price << endl;

Market2.close();

return 0;
}

```

Result:

Big Bucks Inc.

The number of trades was: 581300

The closing price is: \$180.25

basic_ostream::flush

Description To force the output buffer to release its contents.

Prototype `basic_ostream<charT, traits>& flush();`

Remarks The function `flush()` is an output only function in C++. You may use it for an immediate expulsion of the output buffer. This is useful when you have critical data or you need to ensure that a sequence of events occurs in a particular order. If the operation fails calls `set-state(badbit)`.

Returns The `this` pointer.

Listing 18.24 Example of `basic_ostream::flush()` usage:

```

#include <iostream>
#include <iomanip>
#include <ctime>

```

27.6 Formatting And Manipulators

27.6.2 Output streams

```
class stopwatch {
private:
    double begin, set, end;
public:
    stopwatch();
    ~stopwatch();
    void start();
    void stop();
};

stopwatch::stopwatch()
{
using namespace std;

    begin = (double) clock() / CLOCKS_PER_SEC;
    end    = 0.0;
    start();
    cout << "begin the timer: ";
}

stopwatch::~~stopwatch()
{
using namespace std;

    stop(); // set end
    cout << "\nThe Object lasted: ";
    cout << fixed << setprecision(2)
         << end - begin << " seconds \n";
}

// clock ticks divided by ticks per second
void stopwatch::start()
{
using namespace std;

    set = double(clock())/CLOCKS_PER_SEC;
}

void stopwatch::stop()
```

```
{
using namespace std;

    end = double(clock())/CLOCKS_PER_SEC);
}

void time_delay(unsigned short t);

main()
{
using namespace std;

    stopwatch watch; // create object and initialize
    cout.flush(); // this flushes the buffer
    time_delay(5);
    return 0; // destructor called at return
}
//time delay function
void time_delay(unsigned short t)
{
using namespace std;

    time_t tStart, tEnd;
    time(&tStart);
    while(tStart + t > time(&tEnd)){};
}
```

Result:

Note: comment out the flush and both lines will display simultaneously at the end of the program.

begin the timer: < immediate display then pause >

begin the timer:

The Object lasted: 3.83 seconds

27.6.2.6 Standard basic_ostream manipulators

Description To provide an inline formatting mechanism.

27.6 Formatting And Manipulators

27.6.2 Output streams

basic_ostream::endl

Description To insert a newline and flush the output stream.

Prototype

```
template
    < class charT, class traits >
basic_ostream<charT, traits> & endl
    (basic_ostream<charT,traits>& os);
```

Remarks The manipulator endl takes no external arguments, but is placed in the stream. It inserts a newline character into the stream and flushes the output.

Returns A reference to basic_ostream. (The this pointer.)

See Also ostream:: operators

basic_ostream::ends

Description To insert a NULL character.

Prototype

```
template
    < class charT, class traits >
basic_ostream<charT, traits> &ends
    (basic_ostream<charT,traits>& os);
```

Remarks The manipulator ends, takes no external arguments, but is placed in the stream. It inserts a NULL character into the stream, usually to terminate a string.

Returns A reference to ostream. (The this pointer)

NOTE: The ostringstream provides in-core character streams but must be null terminated by the user. The manipulator ends provides a null terminator.

Listing 18.25 Example of `basic_ostream::ends` usage:

```
#include <iostream>
#include <sstream>

main()
{
    using namespace std;

    ostringstream out; // see note above
    out << "Ask the teacher anything\n";
    out << "OK, what is 2 + 2?\n";
    out << 2 << " plus " << 2 << " equals "
        << 4 << ends;

    cout << out.str();
    return 0;
}
```

Result:

```
Ask the teacher anything
OK, what is 2 + 2?
2 plus 2 equals 4?
```

`basic_ostream::flush`

Description To flush the stream for output.

Prototype `template<class charT, class traits>`
`basic_ostream<charT, traits> &`
`flush(basic_ostream<charT, traits> (os);`

Remarks The manipulator `flush`, takes no external arguments, but is placed in the stream. The manipulator `flush` will attempt to release an output buffer for immediate use without waiting for an external input.

Returns A reference to `ostream`. (The `this` pointer.)

27.6 Formatting And Manipulators

27.6.2 Output streams

See Also `ostream::flush()`

Listing 18.26 Example of `basic_ostream::flush` usage:

```
#include <iostream>
#include <iomanip>
#include <ctime>

class stopwatch {
private:
    double begin, set, end;
public:
    stopwatch();
    ~stopwatch();
    void start();
    void stop();
};

stopwatch::stopwatch()
{
    using namespace std;

    begin = (double) clock() / CLOCKS_PER_SEC;
    end    = 0.0;
    start();
    {
        begin = (double) clock() / CLOCKS_PER_SEC;
        end    = 0.0;
        start();
        cout << "begin time the timer: " << flush;
    }
}

stopwatch::~~stopwatch()
{
    using namespace std;

    stop(); // set end
    cout << "\nThe Object lasted: ";
    cout << fixed << setprecision(2)
```



```
        << end - begin << " seconds \n";
    }

    // clock ticks divided by ticks per second
    void stopwatch::start()
    {
        using namespace std;

        set = double(clock())/CLOCKS_PER_SEC);
    }

    void stopwatch::stop()
    {
        using namespace std;

        end = double(clock())/CLOCKS_PER_SEC);
    }

    void time_delay(unsigned short t);

    main()
    {
        using namespace std;

        stopwatch watch; // create object and initialize
        time_delay(5);
        return 0; // destructor called at return
    }

    //time delay function
    void time_delay(unsigned short t)
    {
        using namespace std;

        time_t tStart, tEnd;
        time(&tStart);
        while(tStart + t > time(&tEnd)){};
    }
```

27.6 Formatting And Manipulators

27.6.3 Standard manipulators

Results:

Note: comment out the flush and both lines display simultaneously at the end of the program.

begin time the timer:

< short pause >

The Object lasted: 3.78 seconds

27.6.3 Standard manipulators

The include file `iomanip` defines a template classes and related functions for input and output manipulation.

Standard Manipulator Instantiations

Description To create a specific use instance of a template by replacing the parameterized elements with pre-defined types.

resetiosflags

Description To unset previously set formatting flags.

Prototypes `smanip resetiosflags(ios_base::fmtflags mask)`

Remarks Use the manipulator `resetiosflags` directly in a stream to reset any format flags to a previous condition. You would normally store the return value of `setf()` in order to achieve this task.

Returns A `smanip` type, that is an implementation defined type.

See Also `ios_base::setf()`, `ios_base::unsetf()`

Listing 18.27 Example of `resetiosflags()` usage:

```
#include <iostream>
#include <iomanip>
```

```
main()
{
    using namespace std;

    double d = 2933.51;
    long flags;
    flags = ios::scientific | ios::showpos | ios::showpoint;

    cout << "Original: " << d << endl;
    cout << "Flags set: " << setiosflags(flags)
        << d << endl;
    cout << "Flags reset to original: "
        << resetiosflags(flags) << d << endl;

    return 0;
}
```

```
Result:
Original:  2933.51
Flags set:  +2.933510e+03
Flags reset to original:  2933.51
```

setiosflags

Description	Set the stream format flags.
Prototypes	<code>smanip setiosflags(ios_base::fmtflags mask)</code>
Remarks	Use the manipulator <code>setiosflags()</code> to set the input and output formatting flags directly in the stream.
Returns	A <code>smanip</code> type, that is an implementation defined type.
See Also	<code>ios_base::setf()</code> , <code>ios_base::unsetf()</code>

Listing 18.28 Example of `setiosflags()` usage:

See `resetiosflags()`

27.6 Formatting And Manipulators

27.6.3 Standard manipulators

:setbase

Description To set the numeric base of an output.

Prototypes `smanip setbase(int)`

Remarks The manipulator `setbase()` directly sets the numeric base of integral output to the stream. The arguments are in the form of 8, 10, 16, or 0. 8 octal, 10 decimal and 16 hexadecimal. Zero represents `ios::basefield`, a combination of all three.

Returns A `smanip` type, that is an implementation defined type.

See Also `ios_base::setf()`

Listing 18.29 Example of <omanip>::setbase usage:

```
#include <iostream>
#include <iomanip>

main()
{
    using namespace std;

    cout << "Hexadecimal "
         << setbase(16) << 196 << '\n';
    cout << "Decimal " << setbase(10) << 196 << '\n';
    cout << "Octal " << setbase(8) << 196 << '\n';

    cout.setf(ios::hex, ios::oct | ios::hex);
    cout << "Reset to Hex " << 196 << '\n';
    cout << "Reset basefield setting "
         << setbase(0) << 196 << endl;

    return 0;
}
```

Result:

Hexadecimal c4

Decimal 196

Octal 304
Reset to Hex c4
Reset basefield setting 196

setfill

Description	To specify the characters to used to insert in unused spaces in the output.
Prototypes	<code>smanip setfill(int c)</code>
Remarks	Use the manipulator <code>setfill()</code> directly in the output to fill blank spaces with character <code>c</code> .
Returns	A <code>smanip</code> type, that is an implementation defined type.
See Also	<code>basic_ios::fill</code>

Listing 18.30 Example of `basic_ios::setfill()` usage:

```
#include <iostream>
#include <iomanip>

main()
{
    using namespace std;

    cout.width(8);
    cout << setfill('*') << "Hi!" << "\n";
    char fill = cout.fill();
    cout << "The filler is a " << fill << endl;

    return 0;
}
```

Result:
Hi!*****
The filler is a *

27.6 Formatting And Manipulators

27.6.3 Standard manipulators

setprecision

Description Set and return the current format precision.

Prototypes `smanip<int> setprecision(int)`

Remarks Use the manipulator `setprecision()` directly in the output stream with floating point numbers to limit the number of digits. You may use `setprecision()` with scientific or non-scientific floating point numbers.

With the flag `ios::floatfield` set the number in `precision` refers to the total number of significant digits generated. If the settings are for either `ios::scientific` or `ios::fixed` then the precision refers to the number of digits after the decimal place.

NOTE: This means that `ios::scientific` will have one more significant digit than `ios::floatfield`, and `ios::fixed` will have a varying number of digits.

Returns A `smanip` type, that is an implementation defined type.

See Also `ios_base::setf()`, `ios_base::precision()`

Listing 18.31 Example of `<omanip>::setprecision()` usage:

```
#include <iostream>
#include <iomanip>

main()
{
    using namespace std;

    cout << "Original: " << 321.123456 << endl;
    cout << "Precision set: " << setprecision(8)
        << 321.123456 << endl;
    return 0;
}
```

Result:
Original: 321.123
Precision set: 321.12346

setw

Description To set the width of the output field.

Prototypes `smanip<int> setw(int)`

Remarks Use the manipulator `setw()` directly in a stream to set the field size for output.

Returns A pointer to `ostream`

See Also `ios_base::width()`

Listing 18.32 Example of `<omanip>::setw()` usage:

```
#include <iostream>
#include <iomanip>

main()
{
    using namespace std;

    cout << setw(8)
         << setfill('*')
         << "Hi!" << endl;
    return 0;
}
```

Result:
Hi!*****

27.6 Formatting And Manipulators

27.6.3 Standard manipulators

Overloaded Manipulator

Description	To store a function pointer and object type for input.
Prototype	<p>Overloaded input manipulator for <code>int</code> type.</p> <pre>istream &imanic_name (istream &stream, type param) { // body of code return stream; }</pre> <p>Overloaded output manipulator for <code>int</code> type.</p> <pre>ostream &omanip_name (ostream &stream, type param) { // body of code return stream; }</pre> <p>For other input/output types</p> <pre>smanip<type> mainip_name(type param) { return smanip<type> (manip_name, param); }</pre>
Remarks	Use an overloaded manipulator to provide special and unique input handling characteristics for your class.
Returns	A pointer to stream object.

Listing 18.33 Example of overloaded manipulator usage:

```
#include <iostream>  
#include <iomanip>  
#include <cstring>  
#include <cstdlib>  
#include <cctype>  
  
char buffer[80];
```


27.6 Formatting And Manipulators

27.6.3 Standard manipulators

```
char *Password = "Metrowerks";

char *StrUpr(char * str);

std::imaneip<char *> verify(char *check);
std::istream &verify_implement(std::istream &stream, char *check);

main()
{
using namespace std;

    cin >> verify(StrUpr(Password));
    cout << "Log in was Completed ! \n";

    return 0;
}

std::imaneip<char *> verify(char *check)
{
    return std::imaneip <char *> (verify_implement, check);
}

std::istream &verify_implement(std::istream &stream, char *check)
{
using namespace std;

    short attempts = 3;

    do {
        cout << "Enter password: ";
        stream >> buffer;

        StrUpr(buffer);
        if (! strcmp(check, buffer)) return stream;
        cout << "\a\a";
        attempts--;
    } while(attempts > 0);

    cout << "All Tries failed \n";
    exit(1);
}
```

27.6 Formatting And Manipulators

27.6.3 Standard manipulators

```
    return stream;
}

char *StrUpr(char * str)
{
    char *p = str;    // dupe string
    while(*p) *p++ = std::toupper(*p);
    return str;
}
```

Result:

Enter password: <codewarrior>

Enter password: <mw>

Enter password: <metrowerks>

Log in was Completed !



27.7 String Based Streams

This chapter discusses string-based streams in the standard C++ library.

Overview of String Based Stream Classes

There are four template classes and 6 various types defined in the header `<sstream>` that are used to associate stream buffers with objects of class `basic_string`.

The sections in this chapter are:

- [“Header `<sstream>`” on page 579](#)
- [“27.7.1 Template class `basic_stringbuf`.” on page 580](#)
- [“27.7.2 Template class `basic_istream`” on page 587](#)
- [“27.7.3 Class `basic_stringstream`” on page 597](#)

Header `<sstream>`

Overview The header `<sstream>` includes classes and typed that associate stream buffers with string objects for input and output manipulations.

Prototype

```
namespace std{
    template
        <class charT, class traits = char_traits<charT> >
        class basic_stringbuf;
    typedef basic_stringbuf<char>stringbuf;
```

27.7 String Based Streams

27.7.1 Template class *basic_stringbuf*.

```
typedef basic_strngbuf<wchar>wstringbuf;

template
    <class charT, class traits = char_traits<charT> >
class basic_istream;
typedef basic_istream<char> istream;
typedef basic_istream<wchar> wistream;

template
    <class charT, class traits = char_traits<charT> >
class basic_ostream;
typedef basic_ostream<char> ostream;
typedef basic_ostream<wchar> wostream;
};
}
```

Remarks The class `basic_string` is discussed in previous chapters.

27.7.1 Template class `basic_stringbuf`.

Overview The template class `basic_stringbuf` is derived from `basic_streambuf` is use to associate both input and output streams with an object of class `basic_string`.

The other topics in this section are:

- [“27.7.1.1 `basic_stringbuf` constructors” on page 581](#)
- [“27.7.1.2 Member functions” on page 583](#)
- [“27.7.1.3 Overridden virtual functions” on page 584](#)

Prototype

```
template
    <class charT, class traits = char_traits<charT> >
class basic_stringbuf: public basic_streambuf<charT, traits> > {
public:

    typedef charT char_type;
    typedef typename traits::int_type int_type;
```

```
typedef typename traits::pos_type pos_type;
typedef typename traits::off_type off_type;

explicit basic_stringbuf
    (ios_base::openmode which = ios_base::in | ios_base::out);
explicit basic_stringbuf
    (const basic_string<char_type> &str,
     ios_base::openmode which = ios_base::in | ios_base::out);

basic_string<char_type> str() const;
void str(const basic_string<char_type>&s);

protected
virtual int_type underflow();
virtual int_type pbackfail
    (int_type c = traits::eof());
virtual int_type overflow
    (int_type c = traits::eof());

virtual pos_type seekoff
    (off_type off,
     ios_base::seekdir way,
     ios_base::openmode which = ios_base::in | ios_base::out);
virtual pos_type seekpos
    (pos_type sp,
     ios_base::openmode which = ios_base::in | ios_base::out);

private:
ios_base::openmode mode; exposition only
};
}
```

Remarks The class `basic_stringbuf` is derived from `basic_streambuf` to associate a stream with a `basic_string` object for in-core memory character manipulations.

27.7.1.1 `basic_stringbuf` constructors

The `basic_stringbuf` has two constructors:

27.7 String Based Streams

27.7.1 Template class *basic_stringbuf*.

- `explicit basic_stringbuf(ios_base::openmode);`
- `explicit basic_stringbuf(const basic_string, ios_base::openmode);`

Constructor

Description To create a string buffer for characters for input/output.

Prototype

```
explicit basic_stringbuf
    (ios_base::openmode which =
     ios_base::in | ios_base::out);
explicit basic_stringbuf
    (const basic_string <char_type> &str,
     ios_base::openmode which =
     ios_base::in | ios_base::out);
```

Remarks The `basic_stringbuf` constructor is used to create an object usually as an intermediate storage object for input and output. The overloaded constructor is used to determine the input or output attributes of the `basic_string` object when it is created.

No array object is allocated.

Listing 19.1 Example of `basic_stringbuf::basic_stringbuf()` usage:

```
#include <iostream>
#include <sstream>

const int size = 100;

main()
{
    using namespace std;

    stringbuf strbuf;
    strbuf.pubsetbuf('\0', size);
    strbuf.sputn("ABCDE",50);

    char ch;
        // look ahead at the next character
```

```
ch =strbuf.snextc();
cout << ch;
    // get pointer was not returned after peeking
ch = strbuf.snextc();
cout << ch;

return 0;
}
```

Result:
BC

27.7.1.2 Member functions

The class `basic_stringbuf` has one member functions:

- `str()`

`basic_stringbuf::str`

Description To return the `basic_string` object stored in the buffer.

Prototype `basic_string<char_type> str() const;`

Remarks The function `str()` freezes the buffer then returns a `basic_string` object.

`void str(const basic_string<char_type>&s);`

Remarks The function `str()` assigns the value of the `basic_string` object to the argument 's' if successful.

Returns If successful a `basic_string` object.

Listing 19.2 Example of `basic_stringbuf::str()` usage:

```
#include <iostream>
#include <sstream>

char CW[] = "Metrowerks CodeWarrior";
char AW[] = " - \"Software at Work\"";
```

27.7 String Based Streams

27.7.1 Template class *basic_stringbuf*.

```
main()
{
    using namespace std;

    string buf;
    stringbuf strbuf(buf, ios::out);

    int size;
    size = strlen(CW);
    strbuf.sputn(CW, size);
    size = strlen(AW);
    strbuf.sputn(AW, size);

    cout << strbuf.str();

    return 0;
}
```

Result

Metrowerks CodeWarrior - "Software at Work"

27.7.1.3 Overridden virtual functions

The base class `basic_streambuf` has several virtual functions that are to be overloaded by derived classes. The are:

- `underflow()`
- `pbackfail()`
- `overflow()`
- `seekoff()`
- `seekpos()`

`basic_stringbuf::underflow`

Description To show an underflow condition and not increment the get pointer.

Prototype `virtual int_type underflow();`

Remarks The function `underflow` overrides the `basic_streambuf` virtual function.

Returns The first character of the pending sequence and does not increment the get pointer. If the position is `null` returns `traits::eof()` to indicate failure.

See Also `basic_streambuf::underflow()`

`basic_stringbuf::pbackfail`

Description To show a failure in a put back operation.

Prototype

```
virtual int_type pbackfail
(int_type c = traits::eof());
```

Remarks The function `pbackfail` overrides the `basic_streambuf` virtual function.

Returns The function `pbackfail()` is only called when a put back operation really has failed and returns `traits::eof`. If success occurs the return is undefined.

See Also `basic_streambuf::pbackfail()`

`basic_stringbuf::overflow`

Description Consumes the pending characters of an output sequence.

Prototype

```
virtual int_type overflow
(int_type c = traits::eof());
```

Remarks The function `overflow` overrides the `basic_streambuf` virtual function.

Returns The function returns `traits::eof()` for failure or some unspecified result to indicate success.

27.7 String Based Streams

27.7.1 Template class *basic_stringbuf*.

See Also `basic_streambuf::overflow()`

`basic_stringbuf::seekoff`

Description To return an offset of the current pointer in an input or output streams.

Prototype

```
virtual pos_type seekoff
    (off_type off,
     ios_base::seekdir way,
     ios_base::openmode which =
     ios_base::in | ios_base::out);
```

Remarks The function `seekoff` overrides the `basic_streambuf` virtual function.

Returns A `pos_type` value, which is an invalid stream position.

See Also `basic_streambuf::seekoff()`

`basic_stringbuf::seekpos`

Description To alter an input or output stream position.

Prototype

```
virtual pos_type seekpos
    (pos_type sp,
     ios_base::openmode which =
     ios_base::in | ios_base::out);
```

Remarks The function `seekoff` overrides the `basic_streambuf` virtual function.

Returns A `pos_type` value, which is an invalid stream position.

See Also `basic_streambuf::seekoff()`

27.7.2 Template class `basic_istream`

Overview The template class `basic_istream` is derived from `basic_istream` and is used to associate input streams with an object of class `basic_string`.

The prototype is listed below. The other topics in this section are:

- [“27.7.2.1 `basic_istream` constructors” on page 588](#)
- [“27.7.2.2 Member functions” on page 589](#)

Prototype

```
namespace std {
    template
        <class charT, class traits = char_traits<charT> >
        class basic_istream : public basic_istream<charT, traits>
    {
    public:
        typedef charT char_type;
        typedef typename traits::int_type int_type;
        typedef typename traits::pos_type pos_type;
        typedef typename traits::off_type off_type;

        explicit basic_istream
            (ios_base::openmode which = ios_base::in);
        explicit basic_istream
            (const basic_string<charT> &str,
             ios_base::openmode which = ios_base::in);

        basic_stringbuf<charT, traits>* rdbuf() const;

        basic_string<charT> str() const;
        void str(const basic_string<charT> &s);

    private:
        basic_stringbuf<charT, traits> sb; exposition only
    };
}
```

27.7 String Based Streams

27.7.2 Template class *basic_istream*

Remarks The class `basic_istream` uses an object of type `basic_stringbuf` to control the associated storage.

See Also `basic_ostringstream`, `basic_string`,
`basic_stringstream`, `basic_filebuf`.

27.7.2.1 `basic_istream` constructors

The class `basic_istream` has two constructors.

- `basic_istream`
 (`ios_base::openmode`)
- `basic_istream`
 (`const basic_string`, `ios_base::openmode`)

Constructor

Description The `basic_istream` constructors create a `basic_stringstream` object and initialize the `basic_streambuf` object.

Prototype `explicit basic_istream`
 (`ios_base::openmode` `which` = `ios_base::in`);
`explicit basic_istream`
 (`const basic_string<charT>` &`str`,
 `ios_base::openmode` `which` = `ios_base::in`);

Remarks The `basic_istream` constructor is overloaded to accept a
an object of class `basic_string` for input.

See Also `basic_ostringstream`, `basic_stringstream`

Listing 19.3 Example of `basic_istream::basic_istream()` usage

```
#include <iostream>
#include <string>
#include <sstream>
```

```
main()
```

```
{
using namespace std;

    string sBuffer = "3 12.3 line";
    int num = 0;
    double flt = 0;
    char szArr[20] = "\\0";

    istream Paragraph(sBuffer, ios::in);
    Paragraph >> num;
    Paragraph >> flt;
    Paragraph >> szArr;

    cout << num << " " << flt << " "
         << szArr << endl;

    return 0;
}
```

Result
3 12.3 line

27.7.2.2 Member functions

The class `basic_istream` has two member functions

- `rdbuf()`
- `str()`

`basic_istream::rdbuf`

Description To retrieve a pointer to the stream buffer.

Prototype `basic_stringbuf<charT, traits>* rdbuf() const;`

Remarks To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function `rdbuf()` allows you to retrieve this pointer.

27.7 String Based Streams

27.7.2 Template class *basic_istream*

Returns A pointer to an object of type `basic_stringbuf` **sb** is returned by the `rdbuf` function.

See Also `basic_ostringstream::rdbuf()` `basic_ios::rdbuf()`
`basic_stringstream::rdbuf()`

Listing 19.4 Example of `basic_istream::rdbuf()` usage.

```
#include <iostream>
#include <sstream>

std::string buf = "Metrowerks CodeWarrior - \"Software at work\"";
char words[50];

main()
{
    using namespace std;

    istringstream ist(buf);
    istream in(ist.rdbuf());
    in.seekg(25);

    in.get(words,50);
    cout << words;

    return 0
}
```

Result
"Software at work"

basic_istream::str

Description To return the `basic_string` object stored in the buffer.

Prototype `basic_string<charT> str() const;`
`void str(const basic_string<charT> &s);`

Remarks	The function <code>str()</code> freezes the buffer then returns a <code>basic_string</code> object.
Returns	If successful a <code>basic_string</code> object.
See Also	<code>basic_streambuf::str()</code> , <code>basic_ostringstream.str()</code> <code>basic_stringstream::str()</code>

Listing 19.5 Example of `basic_istream::str()` usage.

```
#include <iostream>
#include <sstream>

std::string buf = "Metrowerks CodeWarrior - \"Software at Work\"";

main()
{
    using namespace std;

    istringstream istr(buf);
    cout << istr.str();
    return 0;
}
```

Result:
Metrowerks CodeWarrior - "Software at Work"

27.7.2.3 Class `basic_ostringstream`

Overview The template class `basic_ostringstream` is derived from `basic_ostream` is use to associate output streams with an object of class `basic_string`.

The prototype is listed below. The other topics in this section are:

- 27.7.2.4 `basic_ostringstream` constructors
- 27.7.2.5 Member functions

27.7 String Based Streams

27.7.2.3 Class *basic_ostringstream*

Prototype

```
namespace std {
    template
        <class charT, class traits = char_traits<charT> >
        class basic_ostringstream : public basic_ostream<charT, traits>{

        public:
            typedef charT char_type;
            typedef typename traits::int_type int_type;
            typedef typename traits::pos_type pos_type;
            typedef typename traits::off_type off_type;

            explicit basic_ostringstream
                (ios_base::openmode which = ios_base::out);
            explicit basic_ostringstream
                (const basic_string<charT> &str,
                 ios_base::openmode which = ios_base::out);

            basic_stringbuf<charT, traits>* rdbuf() const;

            basic_string<charT> str() const;
            void str(const basic_string<charT> &s);

        private:
            basic_stringbuf<charT, traits> sb; exposition only
        };
}
```

Remarks The class `basic_ostringstream` uses an object of type `basic_stringbuf` to control the associated storage.

See Also `basic_istringstream`, `basic_string`, `basic_stringstream`, `basic_filebuf`.

27.7.2.4 `basic_ostringstream` constructors.

The class `basic_ostringstream` has two constructors

- `basic_ostringstream`
(`ios_base::openmode`)
- `basic_ostringstream`
(`const basic_string`, `ios_base::openmode`)

Constructor

Description The `basic_ostringstream` constructors create a `basic_stringstream` object and initialize the `basic_streambuf` object.

Prototype `explicit basic_ostringstream`
(`ios_base::openmode` `which = ios_base::out`);
`explicit basic_ostringstream`
(`const basic_string<charT> &str`,
`ios_base::openmode` `which = ios_base::out`);

Remarks The `basic_stringstream` constructor is overloaded to accept an object of class `basic_string` for output.

See Also `basic_istringstream`, `basic_stringstream`

Listing 19.6 Example of `basic_ostringstream::basic_ostringstream()` usage

The file MW Reference contains
Metrowerks CodeWarrior - "Software at Work"
Registered Trademark

```
#include <iostream>
#include <fstream>
#include <sstream>
#include <cstdlib>
```

```
main()
{
    using namespace std;
```

```
    ifstream in("MW Reference");
    if(!in.is_open())
        {cout << "can't open file for input"; exit(1);}
```

27.7 String Based Streams

27.7.2.3 Class *basic_ostringstream*

```
ostringstream Paragraph;
char ch = '\\0';

while((ch = in.get()) != EOF)
{
    Paragraph << ch;
}

cout << Paragraph.str();

in.close();
return 0;
}
```

Result:

Metrowerks CodeWarrior - "Software at Work"
Registered Trademark

27.7.2.5 Member functions

The class `basic_ostringstream` has two member functions:

- `rdbuf()`
- `str()`

`basic_ostringstream::rdbuf`

Description	To retrieve a pointer to the stream buffer.
Prototype	<code>basic_stringbuf<charT, traits>* rdbuf() const;</code>
Remarks	To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function <code>rdbuf()</code> allows you to retrieve this pointer.
Returns	A pointer to an object of type <code>basic_stringbuf</code> sb is returned by the <code>rdbuf</code> function.

See Also `basic_ostringstream::rdbuf()` `basic_ios::rdbuf()`
 `basic_stringstream::rdbuf()`

Listing 19.7 example of `basic_ostringstream::rdbuf()` usage

```
#include <iostream>
#include <sstream>
#include <string>

std::string motto = "Metrowerks CodeWarrior - \"Software at
Work\"";

main()
{
    using namespace std;

    ostringstream ostr(motto);
    streampos cur_pos, start_pos;

    cout << "The original array was :\n"
         << motto << "\n\n";
    // associate buffer
    stringbuf *strbuf(ostr.rdbuf());

    streamoff str_off = 10;
    cur_pos = ostr.tellp();
    cout << "The current position is "
         << cur_pos.offset()
         << " from the beginning\n";

    ostr.seekp(str_off);

    cur_pos = ostr.tellp();
    cout << "The current position is "
         << cur_pos.offset()
         << " from the beginning\n";

    strbuf->sputc('\0');

    cout << "The stringbuf array is\n"
```

27.7 String Based Streams

27.7.2.3 Class *basic_ostringstream*

```
<< strbuf->str() << "\n\n";
cout << "The ostringstream array is still\n"
<< motto;

return 0;
}
```

Results:

The original array was :
Metrowerks CodeWarrior - "Software at Work"

The current position is 0 from the beginning
The current position is 10 from the beginning
The stringbuf array is
Metrowerks
Metrowerks CodeWarrior - "Software at Work"

basic_ostringstream::str

Description	To return the <code>basic_string</code> object stored in the buffer.
Prototype	<code>basic_string<charT> str() const;</code> <code>void str(const basic_string<charT> &s);</code>
Remarks	The function <code>str()</code> freezes the buffer then returns a <code>basic_string</code> object.
Returns	If successful a <code>basic_string</code> object.
See Also	<code>basic_streambuf::str()</code> , <code>basic_istringstream.str()</code> <code>basic_stringstream::str()</code>

Listing 19.8 Example of `basic_ostringstream::str()` usage.

```
#include <iostream>
#include <sstream>

main()
```

```
{
using namespace std;

    ostream out;
    out << "Ask the teacher anything\n";
    out << "OK, what is 2 + 2?\n";
    out << 2 << " plus " << 2 << " equals "
        << 4 << ends;

    cout << out.str();
    return 0;
}
```

Result:

```
Ask the teacher anything
OK, what is 2 + 2?
2 plus 2 equals 4?
```

27.7.3 Class `basic_stringstream`

Overview The template class `basic_stringstream` is derived from `basic_istream` is use to associate input and output streams with an object of class `basic_string`.

The prototype is listed below. The other topics in this section are:

- 27.7.3.4 `basic_stringstream` constructors
- 27.7.3.5 Member functions

Prototype

```
namespace std {
    template
        <class charT, class traits = char_traits<charT> >
    class basic_stringstream : public basic_istream<charT, traits>
    {
    public:
        typedef charT char_type;
        typedef typename traits::int_type int_type;
    }
```

27.7 String Based Streams

27.7.3 Class *basic_stringstream*

```
typedef typename traits::pos_type pos_type;
typedef typename traits::off_type off_type;

explicit basic_stringstream
(ios_base::openmode which = ios_base::out | ios_base::out);
explicit basic_stringstream
(const basic_string<charT> &str,
 ios_base::openmode which = ios_base::out | ios_base::out);

basic_stringbuf<charT, traits>* rdbuf() const;

basic_string<charT> str() const;
void str(const basic_string<charT> &s);

private:
basic_stringbuf<charT, traits> sb; exposition only
};
}
```

Remarks The class `basic_stringstream` uses an object of type `basic_stringbuf` to control the associated storage.

See Also `basic_istringstream`, `basic_string`,
`basic_stringstream`, `basic_filebuf`

27.7.3.4 `basic_stringstream` constructors

The class `basic_stringstream` has two constructors:

- `explicit basic_stringstream (ios_base::openmode)`
- `explicit basic_stringstream (const basic_string, ios_base::openmode)`

Constructor

Description The `basic_stringstream` constructors create a `basic_stringstream` object and initialize the `basic_streambuf` object.

Prototype `explicit basic_stringstream
 (ios_base::openmode which =
 ios_base::out | ios_base::out);`
`explicit basic_stringstream
 (const basic_string<charT> &str,
 ios_base::openmode which =
 ios_base::out | ios_base::out);`

Remarks The `basic_stringstream` constructor is overloaded to accept a an object of class `basic_string` for input or output.

See Also `basic_ostringstream`, `basic_istringstream`

Listing 19.9 Example of `basic_stringstream::basic_stringstream()` usage

```
#include <iostream>
#include <sstream>

char buf[50] = "ABCD 22 33.33";
char words[50];

main()
{
    using namespace std;

    stringstream iost;

    char word[20];
    long num;
    double real;

    iost << buf;
    iost >> word;
    iost >> num;
    iost >> real;

    cout << word << " "
         << num << " "
         << real << endl;
```

27.7 String Based Streams

27.7.3 Class *basic_stringstream*

```
    return 0;
}
```

Result

ABCD 22 33.33

27.7.3.5 Member functions

The class `basic_stringstream` has two member functions:

- `rdbuf()`
- `str()`

`basic_stringstream::rdbuf`

Description	To retrieve a pointer to the stream buffer.
Prototype	<code>basic_stringbuf<charT, traits>* rdbuf() const;</code>
Remarks	To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function <code>rdbuf()</code> allows you to retrieve this pointer.
Returns	A pointer to an object of type <code>basic_stringbuf</code> sb is returned by the <code>rdbuf</code> function.
See Also	<code>basic_ostringstream::rdbuf()</code> <code>basic_ios::rdbuf()</code> <code>basic_stringstream::rdbuf()</code>

Listing 19.10 Example of `basic_stringstream::rdbuf()` usage

```
#include <iostream>
#include <iostream>
#include <sstream>

std::string buf = "Metrowerks CodeWarrior - \"Software at Work\"";
char words[50];

main()
```



```
{  
using namespace std;  
  
    stringstream ist(buf, ios::in);  
    istream in(ist.rdbuf());  
    in.seekg(25);  
  
    in.get(words, 50);  
    cout << words;  
  
    return 0;  
}
```

Result
"Software at Work"

`basic_stringstream::str`

- | | |
|--------------------|---|
| Description | To return the <code>basic_string</code> object stored in the buffer. |
| Prototype | <code>basic_string<charT> str() const;</code>
<code>void str(const basic_string<charT> &s);</code> |
| Remarks | The function <code>str()</code> freezes the buffer then returns a <code>basic_string</code> object. |
| Returns | If successful a <code>basic_string</code> object. |
| See Also | <code>basic_streambuf::str()</code> , <code>basic_ostringstream.str()</code>

<code>basic_istringstream::str()</code> |

Listing 19.11 Example of `basic_stringstream::str()` usage

```
#include <iostream>  
#include <sstream>  
  
std::string buf = "Metrowerks CodeWarrior - \"Software at Work\"";  
char words[50];
```

27.7 String Based Streams

27.7.3 Class *basic_stringstream*

```
main()
{
using namespace std;

    stringstream iost(buf, ios::in);

    cout << iost.str();

    return 0;
}
```

Result

Metrowerks CodeWarrior - "Software at Work"



27.8 File Based Streams

Association of stream buffers with files for file reading and writing.

Overview of File Based Streams

The sections in this chapter are:

- [“Header <fstream>” on page 603](#)
- [“27.8.1 File streams” on page 603](#)
- [“27.8.1.1 Template class basic_filebuf” on page 604](#)
- [“27.8.1.5 Template class basic_ifstream” on page 612](#)
- [“27.8.1.8 Template class basic_ofstream” on page 619](#)
- [“27.8.1.11 Template class basic_fstream” on page 626](#)

Header <fstream>

Description The header <fstream> defines template classes and types to assist in reading and writing of files.

27.8.1 File streams

Prototype

```
namespace std{
template
    <class charT,class traits = ios_traits<charT> >
class basic_filebuf;
    typedef basic_filebuf<char> filebuf;
```

27.8 File Based Streams

27.8.1.1 Template class *basic_filebuf*

```
typedef basic_filebuf<wchar_t> wfilebuf;

template
<class charT, class traits = ios_traits<charT> >
class basic_ifstream;
    typedef basic_ifstream<char> ifstream;
    typedef basic_ifstream<wchar_t> wifstream;

template
<class charT, class traits = ios_traits<charT> >
class basic_ofstream;
    typedef basic_ofstream<char> ofstream;
    typedef basic_ofstream<wchar_t> wofstream;
}
```

Remarks A `FILE` refers to the type `FILE` as defined in the Standard C Library and provides an external input or output stream with the underlying type of `char` or `byte`. A `stream` is a sequence of `char` or `bytes`.

27.8.1.1 Template class *basic_filebuf*

Description A class to provide for input and output file stream buffering mechanisms.

The prototype is listed below. Other topics in this section are:

- [“27.8.1.2 *basic_filebuf* Constructors” on page 606](#)
- [“27.8.1.3 Member functions” on page 606](#)
- [“27.8.1.4 Overridden virtual functions” on page 609](#)

Prototype

```
namespace std{
    template
    <class charT, class traits = ios_traits<charT> >
    class basic_filebuf : public basic_streambuf <charT, traits>
    {
    public:
```

```
typedef charT char_type;
typedef typename traits::int_type int_type;
typedef typename traits::pos_type pos_type;
typedef typename traits::off_type off_type;

basic_filebuf();
virtual ~basic_filebuf();

bool is_open() const;
basic_filebuf<charT, traits>* open
    (const char* c, ios_base::openmode mode);
basic_filebuf<charT, traits>* close();

protected:

virtual int showmanyc();

virtual int_type underflow();
virtual int_type pbackfail
    (int_type c = traits::eof());
virtual int_type overflow
    (int_type c = traits::eof());

virtual basic_streambuf<charT traits>* setbuf
    (char_type* s, streamsize n);

virtual pos_type seekoff
    (off_type off,
     ios_base::seekdir way,
     ios_base::in | ios_base::out);
virtual pos_type seekpos
    (pos_type sp,
     ios_base::openmode which,
     ios_base::in | ios_base::out);

virtual int sync();
virtual void imbue(const locale& loc);
```

27.8 File Based Streams

27.8.1.1 Template class *basic_filebuf*

```
};  
}
```

Remarks The `filebuf` class is derived from the `streambuf` class and provides a buffer for file output and or input.

27.8.1.2 `basic_filebuf` Constructors

Default Constructor

Description To construct and initialize a `filebuf` object.

Prototype `basic_filebuf()`

Remarks The constructor opens a `basic_filebuf` object and initializes it with `basic_streambuf<charT, traits>()` and if successful `is_open()` is `false`.

Destructor

Description To remove the `basic_filebuf` object from memory.

Prototype `virtual ~basic_filebuf();`

Listing 20.1 For example of `basic_filebuf::basic_filebuf()` usage:

See `basic_filebuf::open()`.

27.8.1.3 Member functions

`basic_filebuf::is_open`

Description Test to ensure `filebuf` stream is open for reading or writing.

Prototype `bool is_open() const`

Remarks Use the function `is_open()` for a `filebuf` stream to ensure it is open before attempting to do any input or output operation on the stream.

Returns True if stream is available and open.

Listing 20.2 For example of `basic_filebuf::is_open()` usage

See: `basic_filebuf::basic_filebuf`

`basic_filebuf::open`

Description Open a `basic_filebuf` object and associate it with a file.

Prototype `basic_filebuf<charT, traits>* open
(const char* c,
ios_base::openmode mode);`

Remarks You would use the function `open()` to open a `filebuf` object and associate it with a file. You may use `open()` to reopen a buffer and associate it if the object was closed but not destroyed.

WARNING! If an attempt is made to open a file in an inappropriate file opening mode, the file will not open and a test for the object will not give false, therefore use the function `is_open()` to check for file openings.

Table 20.1 Legal `basic_filebuf` file opening modes

Opening Modes	stdio equivalent
Input Only	
<code>ios::in</code>	"r"
<code>ios::binary ios::in</code>	"rb"
Output only	

27.8 File Based Streams

27.8.1.1 Template class `basic_filebuf`

Opening Modes	stdio equivalent
<code>ios::out</code>	<code>"w"</code>
<code>ios::binary ios::out</code>	<code>"wb"</code>
<code>ios::out ios::trunc</code>	<code>"w"</code>
<code>ios::binary ios::out ios::trunc</code>	<code>"wb"</code>
<code>ios::out ios::app</code>	<code>"a"</code>
Input and Output	
<code>ios::in ios::out</code>	<code>"r+"</code>
<code>ios::binary ios::in ios::out</code>	<code>"r+b"</code>
<code>ios::in ios::out ios::trunc</code>	<code>"w+"</code>
<code>ios::binary ios::in ios::out ios::trunc</code>	<code>"w+b"</code>
<code>ios::binary ios::out ios::app</code>	<code>"ab"</code>

Returns If successful the `this` pointer is returned, if `is_open()` equals true then a null pointer is returned.

Listing 20.3 Example of `filebuf::open()` usage:

The file MW Reference before operation contained:
Metrowerks CodeWarrior "Software at Work"

```
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main(){
using namespace std;

    filebuf in;
    in.open(inFile, ios::out | ios::app);
    if(!in.is_open())
        {cout << "could not open file"; exit(1);}
    char str[] = "\n\tregistered trademark";
```



```
in.sputn(str, strlen(str));  
  
in.close();  
return 0;  
}
```

Result:

The file MW Reference now contains:
Metrowerks CodeWarrior "Software at Work"
registered trademark

basic_filebuf::close

Description To close a filebuf stream without destroying it.

Prototype `basic_filebuf<charT, traits>* close();`

Remarks The function `close()` would remove the stream from memory but will not remove the filebuf object. You may re-open a filebuf stream that was closed using the `close()` function.

Returns The `this` pointer with success otherwise a null pointer.

Listing 20.4 For example of `basic_filebuf::close()` usage

See `basic_filebuf::open()`

27.8.1.4 Overridden virtual functions

basic_filebuf::showmanyc

Description Overrides `basic_streambuf::showmanyc()`.

Prototype `virtual int showmanyc();`

Remarks Behaves the same as `basic_sreambuf::showmanyc()`.

27.8 File Based Streams

27.8.1.1 Template class *basic_filebuf*

basic_filebuf::underflow

- Description** Overrides `basic_streambuf::underflow()`;
- Prototype** `virtual int_type underflow();`
- Remarks** Behaves the same as `basic_streambuf::underflow` with the specialization that a sequence of characters is read as if they were read from a file into an internal buffer.

basic_filebuf::pbackfail

- Description** Overrides `basic_streambuf::pbackfail()`.
- Prototype** `virtual int_type pbackfail
(int_type c = traits::eof());`
- Remarks** This function puts back the characters designated by `c` to the input sequence if possible.
- Returns** `traits::eof()` if failure and returns either the character put back or `traits::not_eof(c)` for success.

basic_filebuf::overflow

- Description** Overrides `basic_streambuf::overflow()`
- Prototype** `virtual int_type overflow
(int_type c = traits::eof());`
- Remarks** Behaves the same as `basic_streambuf<charT, traits>::overflow(c)` except the behavior of consuming characters is performed by conversion.
- Returns** `traits::eof()` with failure.

basic_filebuf::seekoff

Description	Overrides <code>basic_streambuf::seekoff()</code>
Prototype	<pre>virtual pos_type seekoff (off_type off, ios_base::seekdir way, ios_base::in ios_base::out);</pre>
Remarks	Sets the offset position of the stream as if using the C standard library function <code>fseek(file, off, whence)</code> .
Returns	Seekoff function returns a newly formed <code>pos_type</code> object which contains all information needed to determine the current position if successful. An invalid stream position if it fails.

basic_filebuf::seekpos

Description	Overrides <code>basic_streambuf::seekpos()</code>
Prototype	<pre>virtual pos_type seekpos (pos_type sp, ios_base::openmode which, ios_base::in ios_base::out);</pre>
Remarks	Description undefined in standard at the time of writing.
Returns	Seekpos function returns a newly formed <code>pos_type</code> object which contains all information needed to determine the current position if successful. An invalid stream position if it fails.

basic_filebuf::setbuf

Description	Overrides <code>basic_streambuf::setbuf()</code>
Prototype	<pre>virtual basic_streambuf<charT traits>* setbuf (char_type* s, streamsize n);</pre>

27.8 File Based Streams

27.8.1.5 Template class *basic_ifstream*

Remarks Description undefined in standard at the time of writing.

basic_filebuf::sync

Description Overrides basic_streambuf::sync

Prototype `virtual int sync();`

Remarks Description undefined in standard at the time of writing.

basic_filebuf::imbue

Description Overrides basic_streambuf::imbue

Prototype `virtual void imbue(const locale& loc);`

Remarks Description undefined in standard at the time of writing.

27.8.1.5 Template class **basic_ifstream**

A class to provide for input file stream mechanisms.

The prototype is listed below. Other topics in this section are:

- [“27.8.1.6 basic_ifstream Constructor” on page 613](#)
- [“27.8.1.7 Member functions” on page 615](#)

Prototype

```
namespace std{
    template
        <class charT, class traits = ios_traits<charT> > {
    class basic_ifstream : public basic_istream<charT, traits>
    {
    public:
        typedef charT char_type;
        typedef typename traits::int_type int_type;
        typedef typename traits::pos_type pos_type;
        typedef typename traits::off_type off_type;
```

```
basic_ifstream();
explicit basic_ifstream
    (const char *s, openmode mode = in);

basic_filebuf<charT, traits>* rdbuf() const;
bool is_open();
void open(const char* s, openmode mode = in);
void close();

private:
basic_filebuf<charT, traits> sb; exposition only
};
}
```

NOTE: If the `basic_ifstream` supports reading from file. It uses a `basic_filebuf` object to control the sequence. That object is represented here as `basic_filebuf sb`.

Remarks The `basic_ifstream` provides mechanisms specifically for input file streams.

27.8.1.6 `basic_ifstream` Constructor

Default Constructor and Overloaded Constructor

Description Create a file stream for input.

Prototype `basic_ifstream();`
`explicit basic_ifstream`
 `(const char *s, openmode mode = in);`

Remarks The constructor creates a stream for file input; it is overloaded to either create and initialize when called or to simply create a class and be opened using the `open()` member function. The default opening mode is `ios::in`. See `basic_filebuf::open()` for valid open mode settings.

27.8 File Based Streams

27.8.1.5 Template class *basic_ifstream*

NOTE: See `basic_ifstream::open` for legal opening modes.

See also `basic_ifstream::open()` for overloaded form usage.

Listing 20.5 Example of `basic_ifstream::basic_ifstream()` constructor usage:

The MW Reference file contains:
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main()
{
    using namespace std;

    ifstream in(inFile, ios::in);
    if(!in.is_open())
        {cout << "can't open input file"; exit(1);}

    char c = '\0';
    while(in.good())
    {
        if(c) cout << c;
        in.get(c);

    }

    in.close();
    return 0;
}
```

Result:
Metrowerks CodeWarrior "Software at Work"

27.8.1.7 Member functions

basic_ifstream::rdbuf

Description	The <code>rdbuf()</code> function retrieves a pointer to a <code>filebuf</code> type buffer.
Prototype	<code>basic_filebuf<charT, traits>* rdbuf() const;</code>
Remarks	In order to manipulate for random access or use an <code>ifstream</code> stream for both input and output you need to manipulate the base buffer. The function <code>rdbuf()</code> returns a pointer to this buffer for manipulation.
Returns	A pointer to type <code>basic_filebuf</code> .

Listing 20.6 Example of `basic_ifstream::rdbuf()` usage:

The MW Reference file contains originally
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main()
{
    using namespace std;

    ifstream inOut(inFile, ios::in | ios::out);
    if(!inOut.is_open())
        {cout << "Could not open file"; exit(1);}

    ostream Out(inOut.rdbuf());

    char str[] = "\n\tRegistered Trademark";

    inOut.rdbuf()->pubseekoff(0, ios::end);
```

27.8 File Based Streams

27.8.1.5 Template class *basic_ifstream*

```
Out << str;

inOut.close();

return 0;
}
```

Result:

The File now reads:

Metrowerks CodeWarrior "Software at Work"
Registered Trademark

basic_ifstream::is_open

Description	Test for open stream.
Prototype	<code>bool is_open() const</code>
Remarks	Use <code>is_open()</code> to test that a stream is indeed open and ready for input from the file.
Returns	True if file is open.

Listing 20.7 For example of `basic_ifstream::is_open()` usage

See `basic_ifstream::basic_ifstream()`

basic_ifstream::open

Description	Open is used to open a file or reopen a file after closing it.
Prototype	<code>void open(const char* s, openmode mode = in);</code>
Remarks	The default open mode is <code>ios::in</code> , but can be one of several modes. (see below) A stream is opened and prepared for input or output as selected.

Returns No return

Table 20.2 17.4.1.1.4 Legal basic_ifstream file opening modes

Opening Modes	stdio equivalent
Input Only	
ios:: in	"r"
ios:: binary ios::in	"rb"
Input and Output	
ios::in ios::out	"r+"
ios::binary ios::in ios::out	"r+b"
ios:: in ios::out ios::trunc	"w+"
ios::binary ios::in ios::out ios::trunc	"w+b"
ios::binary ios:: out ios::app	"ab"

NOTE: If an attempt is made to open a file in an inappropriate file opening mode, the file will not open and a test for the object will not give false, therefore use the function `is_open()` to check for file openings

Listing 20.8 Example of basic_ifstream::open() usage:

The MW Reference file contains:
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main()
{
using namespace std;
```

27.8 File Based Streams

27.8.1.5 Template class *basic_ifstream*

```
ifstream in;
in.open(inFile);
if(!in.is_open())
    {cout << "can't open input file"; exit(1);}

char c = NULL;
while((c = in.get()) != EOF)
{
    cout << c;
}

in.close();
return 0;
}
```

Result:

Metrowerks CodeWarrior "Software at Work"

basic_ifstream::close

Description Closes the file stream.

Prototype void close();

Remarks The close() function closes the stream for operation but does not destroy the ifstream object so it may be re-opened at a later time. If the function fails calls setstate(failbit) which may throw an exception.

Returns: No return.

Listing 20.9 Example of basic_ifstream::close() usage:

See basic_ifstream::basic_ifstream()

27.8.1.8 Template class `basic_ofstream`

Description A class to provide for output file stream mechanisms.

The prototype is listed below. Other topics in this section are:

- [“27.8.1.9 `basic_ofstream` constructor” on page 620](#)
- [“27.8.1.10 Member functions” on page 621](#)

Prototype

```
namespace std{
    template
        <class charT, class traits = ios_traits<charT> >
        class basic_ofstream : public basic_ostream<charT, traits>
        {
        public:
            typedef charT char_type;
            typedef typename traits::int_type int_type;
            typedef typename traits::pos_type pos_type;
            typedef typename traits::off_type off_type;

            basic_ofstream();
            explicit basic_ofstream
                (const char *s, openmode mode = out | trunc);

            basic_filebuf<charT, traits>* rdbuf() const;
            bool is_open();
            void open(const char* s, openmode mode = out);
            void close();

        private:
            basic_filebuf<charT, traits> sb; exposition only
        };
}
```

27.8 File Based Streams

27.8.1.8 Template class *basic_ofstream*

NOTE: The `basic_ofstream` supports writing to file. It uses a `basic_filebuf` object to control the sequence. That object is represented here as `basic_filebuf sb`.

Remarks The `basic_ofstream` class provides for mechanisms specific to output file streams.

27.8.1.9 `basic_ofstream` constructor

Default and Overloaded Constructors

Description To create a file stream object for output.

Prototype

```
basic_ofstream();  
explicit basic_ofstream  
    (const char *s, openmode mode = out | trunc);
```

Remarks The class `basic_ofstream` creates an object for handling file output. It may be opened later using the `ofstream::open()` member function. It may also be associated with a file when the object is declared. The default open mode is `ios::out`.

NOTE: There are only certain valid file opening modes for an `ofstream` object see `basic_ofstream::open()` for a list of valid opening modes.

Listing 20.10 Example of `basic_ofstream::ofstream()` usage:

Before the operation the file MW Reference may or may not exist.

```
#include <iostream>  
#include <fstream>  
#include <cstdlib>
```

```
char outFile[] = "MW Reference";
```

```
main()
{
using namespace std;

    ofstream out(outFile);
    if(!out.is_open())
        {cout << "file not opened"; exit(1);}

    out << "This is an annotated reference that "
        << "contains a description\n"
        << "of the Working ANSI C++ Standard "
        << "Library and other\nfacilities of "
        << "the Metrowerks Standard Library. ";

    out.close();
    return 0;
}
```

Result:

This is an annotated reference that contains a description
of the Working ANSI C++ Standard Library and other
facilities of the Metrowerks Standard Library.

27.8.1.10 Member functions

basic_ofstream::rdbuf

Description	To retrieve a pointer to the stream buffer.
Prototype	<code>basic_filebuf<charT, traits>* rdbuf() const;</code>
Remarks	In order to manipulate a stream for random access or other operations you must use the streams base buffer. The member function <code>rdbuf()</code> is used to return a pointer to this buffer.
Returns	A pointer to filebuf type.

27.8 File Based Streams

27.8.1.8 Template class *basic_ofstream*

Listing 20.11 Example of `basic_ofstream::rdbuf()` usage:

The file MW Reference before the operation contains:
This is an annotated reference that contains a description
of the Working ANSI C++ Standard Library and other
facilities of the Metrowerks Standard Library

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char outFile[] = "MW Reference";

main()
{
    using namespace std;

    ofstream out(outFile, ios::in | ios::out);
    if(!out.is_open())
        {cout << "could not open file for output"; exit(1);}
    istream inOut(out.rdbuf());

    char ch;
    while((ch = inOut.get()) != EOF)
    {
        cout.put(ch);
    }

    out << "\nAnd so it goes...";

    out.close();

    return 0;
}
```

Result:

This is an annotated reference that contains a description
of the Working ANSI C++ Standard Library and other
facilities of the Metrowerks Standard Library.

This is an annotated reference that contains a description

of the Working ANSI C++ Standard Library and other facilities of the Metrowerks Standard Library.
And so it goes...

basic_ofstream::is_open

Description	To test whether the file was opened.
Prototype	<code>bool is_open();</code>
Remarks	The <code>is_open()</code> function is used to check that a file stream was indeed opened and ready for output. You should always test with this function after using the constructor or the <code>open()</code> function to open a stream.
Returns	True if file stream is open and available for output.

Listing 20.12 For example of `basic_ofstream::is_open()` usage

See `basic_ofstream::ofstream()`

basic_ofstream::open

Description	To open or re-open a file stream for output.
Prototype	<code>void open(const char* s, openmode mode = out);</code>
Remarks	The function <code>open()</code> opens a file stream for output. The default mode is <code>ios::out</code> , but may be any valid open mode (see below.) If failure occurs <code>open()</code> calls <code>setstate(failbit)</code> which may throw an exception.
Returns	No return

27.8 File Based Streams

27.8.1.8 Template class *basic_ofstream*

Table 20.3 Legal *basic_ofstream* file opening modes.

Opening Modes	stdio equivalent
Output only	
<code>ios::out</code>	<code>"w"</code>
<code>ios::binary ios::out</code>	<code>"wb"</code>
<code>ios::out ios::trunc</code>	<code>"w"</code>
<code>ios::binary ios::out ios::trunc</code>	<code>"wb"</code>
<code>ios::out ios::app</code>	<code>"a"</code>
Input and Output	
<code>ios::in ios::out</code>	<code>"r+"</code>
<code>ios::binary ios::in ios::out</code>	<code>"r+b"</code>
<code>ios::in ios::out ios::trunc</code>	<code>"w+"</code>
<code>ios::binary ios::in ios::out ios::trunc</code>	<code>"w+b"</code>
<code>ios::binary ios::out ios::app</code>	<code>"ab"</code>

NOTE: If an attempt is made to open a file in an inappropriate file opening mode, the file will not open and a test for the object will not give false, therefore use the function `is_open()` to check for file openings.

Listing 20.13 Example of *basic_ofstream::open()* usage:

Before operation, the file MW Reference contained:
Chapter One

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char outFile[] = "MW Reference";
```



```
main()
{
    using namespace std;

    ofstream out;
    out.open(outFile, ios::out | ios::app);
    if(!out.is_open())
        {cout << "file not opened"; exit(1);}

    out << "\nThis is an annotated reference that "
        << "contains a description\n"
        << "of the Working ANSI C++ Standard "
        << "Library and other\nfacilities of "
        << "the Metrowerks Standard Library.";

    out.close();
    return 0;
}
```

Result:

After the operation MW Reference contained
Chapter One

This is an annotated reference that contains a description
of the Working ANSI C++ Standard Library and other
facilities of the Metrowerks Standard Library.

basic_ofstream::close

Description The member function closes the stream but does not destroy it.

Prototype `void close();`

Remarks Use the function `close()` to close a stream. It may be re-opened at a later time using the member function `open()`. If failure occurs `open()` calls `setstate(failbit)` which may throw an exception.

Returns No return.

27.8 File Based Streams

27.8.1.11 Template class *basic_fstream*

Listing 20.14 For example of `basic_ofstream::close()` usage.

```
basic_ofstream()
```

27.8.1.11 Template class `basic_fstream`

A template class for the association of a file for input and output

The prototype is listed below. The other topic in this section is:

- [“27.8.1.12 `basic_fstream` Constructor” on page 627](#)
- [“27.8.1.13 Member Functions” on page 628](#)

Prototype

```
namespace std {
    template
        <class charT, class traits=ios_traits<charT> >
        class basic_fstream : public basic_iostream<charT, traits>
        {
        public:
            typedef charT char_type;
            typedef typename traits::int_type int_type;
            typedef typename traits::pos_type pos_type;
            typedef typename traits::off_type off_type;

            basic_fstream();
            explicit basic_fstream
                (const char *s,
                 ios_base::openmode = ios_base::in | ios_base::out);

            basic_filebuf<charT, traits>* rdbuf() const;

            bool is_open();
            void open
                (const char* s,
                 ios_base::openmode = ios_base::in | ios_base::out);
            void close();

        private:
```

```
basic_filebuf<charT, traits> sb; exposition only
};
}
```

Remarks The template class `basic_fstream` is used for both reading and writing from files.

NOTE: The `basic_fstream` supports writing to file. It uses a `basic_filebuf` object to control the sequence. That object is represented here as `basic_filebuf sb`.

27.8.1.12 `basic_fstream` Constructor

Default and Overloaded Constructor

Description To construct an object of `basic_ifstream` for input and output operations.

Prototypes

```
basic_fstream();
explicit basic_fstream
    (const char *s,
     ios_base::openmode =
     ios_base::in | ios_base::out);
```

Remarks The `basic_fstream` class is derived from `basic_iostream` and that and a `basic_filebuf` object are initialized at construction.

Listing 20.15 Example of `basic_fstream::basic_fstream()` usage

The MW Reference file contains originally
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>
```

```
char inFile[] = "MW Reference";
```

27.8 File Based Streams

27.8.1.11 Template class *basic_fstream*

```
main()
{
    using namespace std;

    fstream inOut(inFile, ios::in | ios::out);
    if(!inOut.is_open())
        {cout << "Could not open file"; exit(1);}

    char str[] = "\n\tRegistered Trademark";

    char ch;
    while((ch = inOut.get())!= EOF)
    {
        cout << ch;
    }
    inOut.clear();
    inOut << str;
    inOut.close();

    return 0;
}
```

Result:

Metrowerks CodeWarrior "Software at Work"

The File now reads:

Metrowerks CodeWarrior "Software at Work"

Registered Trademark

27.8.1.13 Member Functions

basic_fstream::rdbuf

Description The `rdbuf()` function retrieves a pointer to a `filebuf` type buffer.

Prototype `basic_filebuf<charT, traits>* rdbuf() const;`

Remarks In order to manipulate for random access or use of an `fstream` stream you may need to manipulate the base buffer. The function `rdbuf()` returns a pointer to this buffer for manipulation.

Returns A pointer to type `basic_filebuf`.

Listing 20.16 Example of `basic_fstream::rdbuf()` usage

The MW Reference file contains originally
Metrowerks CodeWarrior "Software at Work"

```
#include <iostream>
#include <fstream>
#include <cstdlib>

char inFile[] = "MW Reference";

main()
{
    using namespace std;

    fstream inOut;
    inOut.open(inFile, ios::in | ios::out);
    if(!inOut.is_open())
        {cout << "Could not open file"; exit(1);}

    char str[] = "\n\tRegistered Trademark";

    inOut.rdbuf()->pubseekoff(0,ios::end);
    inOut << str;
    inOut.close();

    return 0;
}
```

Result:
The File now reads:
Metrowerks CodeWarrior "Software at Work"
Registered Trademark

27.8 File Based Streams

27.8.1.11 Template class *basic_fstream*

basic_fstream::is_open

Description Test to ensure `basic_fstream` file is open and available for reading or writing.

Prototype `bool is_open() const`

Remarks Use the function `is_open()` for a `basic_fstream` file to ensure it is open before attempting to do any input or output operation on a file.

Returns True if a file is available and open.

For an example, see [“Example of basic_fstream::basic_fstream\(\) usage” on page 627](#).

basic_fstream::open

Description To open or re-open a file stream for input or output.

Prototypes `void open
 (const char* s,
 ios_base::openmode =
 ios_base::in | ios_base::out);`

Remarks You would use the function `open()` to open a `basic_fstream` object and associate it with a file. You may use `open()` to reopen a file and associate it if the object was closed but not destroyed.

WARNING! If an attempt is made to open a file in an inappropriate file opening mode, the file will not open and a test for the object will not give false, therefore use the function `is_open()` to check for file openings.

Table 20.4 **Legal file opening modes**

Opening Modes	stdio equivalent
Input Only	
<code>ios::in</code>	"r"
<code>ios::binary ios::in</code>	"rb"
Output only	
<code>ios::out</code>	"w"
<code>ios::binary ios::out</code>	"wb"
<code>ios::out ios::trunc</code>	"w"
<code>ios::binary ios::out ios::trunc</code>	"wb"
<code>ios::out ios::app</code>	"a"
Input and Output	
<code>ios::in ios::out</code>	"r+"
<code>ios::binary ios::in ios::out</code>	"r+b"
<code>ios::in ios::out ios::trunc</code>	"w+"
<code>ios::binary ios::in ios::out ios::trunc</code>	"w+b"
<code>ios::binary ios::out ios::app</code>	"ab"

Returns No return.

For an example, see ["Example of basic_fstream::rdbuf\(\) usage" on page 629](#).

basic_fstream::close

Description The member function closes the stream but does not destroy it.

Prototype `void close();`

27.8 File Based Streams

27.8.1.11 Template class *basic_fstream*

Remarks Use the function `close()` to close a stream. It may be re-opened at a later time using the member function `open()`. If failure occurs `open()` calls `setstate(failbit)` which may throw an exception.

Returns No return.

For an example, see [“Example of `basic_fstream::basic_fstream\(\)` usage” on page 627](#).



C Library files

The header `<cstdio>` contains the C++ implementation of the Standard C Headers.

27.8.2 C Library files

`<cstdio>` Macros

Macros:

BUFSIZ	EOF	FILENAME_MAX
FOPEN_MAX	L_tmpnam	NULL
SEEK_CUR	SEEK_END	SEEK_SET
stderr	stdin	stdout
TMP_MAX	_IOFBF	_IOLBF
_IONBF		

`<cstdio>` Types

Types:

FILE	fpos_t	size_t
------	--------	--------

<stdio> Functions

Functions:

clearerr	fclose	feof
ferror	fflush	fgetc
fgetpos	fgets	fopen
fprintf	fputc	fputs
fread	freopen	fscanf
fseek	fsetpos	ftell
fwrite	getc	getchar
gets	perror	printf
putc	putchar	puts
remove	rename	rewind
scanf	setbuf	setvbuf
sprintf	scanf	tmpnam
ugetc	vprintf	vfprintf
vsprintf	tmpfile	



Annex D Strstream

The header `<strstream>` defines streambuf derived classes that allow for the formatting and storage of character array based buffers, as well as their input and output.

Overview of Strstream Classes

The sections in this chapter are:

- [“Strstreambuf Class” on page 638](#), a base class for strstream classes
 - [“Strstreambuf constructors and Destructors” on page 640](#)
 - [“Strstreambuf Public Member Functions” on page 641](#)
 - [“Protected Virtual Member Functions” on page 644](#)
- [“Istrstream Class” on page 647](#), a strstream class for input
 - [“Constructors and Destructor” on page 648](#)
 - [“Public Member Functions” on page 649](#)
- [“Ostrstream Class” on page 650](#), a strstream class for output
 - [“Constructors and Destructor” on page 651](#)
 - [“Public Member Functions” on page 653](#)
- [“Strstream Class” on page 656](#), a class for input and output
 - [“Constructors and Destructor” on page 657](#)
 - [“Public Member Functions” on page 657](#)

Header `<strstream>`

The include file `strstream` includes three classes, for in memory character array based stream input and output.

Annex D Strstream

Header <strstream>

Listing 22.1 Class declarations for header <strstream>

```
class strstreambuf
{
public:
    explicit strstreambuf(streamsize alsize_arg = 0);
    strstreambuf(void* (*palloc_arg)(size_t),
        void (*pfree_arg)(void*));
    strstreambuf(char* gnext_arg, streamsize n, char* pbeg_arg = 0);
    strstreambuf(const char* gnext_arg, streamsize n);
    strstreambuf(signed char* gnext_arg, streamsize n,
        signed char* pbeg_arg = 0);
    strstreambuf(const signed char* gnext_arg, streamsize n);
    strstreambuf(unsigned char* gnext_arg, streamsize n,
        unsigned char* pbeg_arg = 0);
    strstreambuf(const unsigned char* gnext_arg, streamsize n);
    virtual ~strstreambuf();
    void freeze(bool freezefl = true);
    char* str();
    int pcount() const;
protected:
    virtual int_type overflow (int_type c = EOF);
    virtual int_type pbackfail(int_type c = EOF);
    virtual int_type underflow();
    virtual pos_type seekoff(off_type off, ios_base::seekdir way,
        ios_base::openmode which = ios_base::in | ios_base::out);
    virtual pos_type seekpos(pos_type sp,
        ios_base::openmode which = ios_base::in | ios_base::out);
    virtual streambuf* setbuf(char* s, streamsize n);
private:
    typedef unsigned char strstate;
    static const strstate allocated = 1 << 0;
    static const strstate constant = 1 << 1;
    static const strstate dynamic = 1 << 2;
    static const strstate frozen = 1 << 3;
    static const streamsize default_alsize = 128;
    streamsize alsize_;
    void* (*palloc_)(size_t);
    void (*pfree_)(void*);
};
```

```
    strstate strmode_;

    void init(char* gnext_arg, streamsize n, char* pbeg_arg = 0);
};
```

```
class istrstream : public basic_istream<char>
{
public:
    explicit istrstream(const char* s);
    explicit istrstream(char* s);
    istrstream(const char* s, streamsize n);
    istrstream(char* s, streamsize n);
    virtual ~istrstream();
    strstreambuf* rdbuf() const;
    char* str();
private:
    strstreambuf strbuf_;
};
```

```
class ostrstream : public basic_ostream<char>
{
public:
    ostrstream();
    ostrstream(char* s, int n, ios_base::openmode mode =
ios_base::out);
    virtual ~ostrstream();
    strstreambuf* rdbuf() const;
    void freeze(bool freezefl = true);
    char* str();
    int pcount() const;
private:
    strstreambuf strbuf_;
};
```

```
class strstream : public basic_iostream<char>
{
public:
    // Types
```

Annex D Strstream

Strstreambuf Class

```
typedef char                                     char_type;
typedef typename char_traits<char>::int_type int_type;
typedef typename char_traits<char>::pos_type pos_type;
typedef typename char_traits<char>::off_type off_type;
// constructors/destructor
strstream();
strstream(char* s, int n, ios_base::openmode mode =
ios_base::in|ios_base::out);
virtual ~strstream();
// Members:
strstreambuf* rdbuf() const;
void freeze(bool freezefl = true);
int pcount() const;
char* str();
private:
    strstreambuf strbuf_;
};
```

Strstreambuf Class

The class `strstreambuf` is derived from `streambuf` to associate a stream with an in memory character array.

The `strstreambuf` class includes virtual protected and public member functions

- [“freeze” on page 641](#), freezes the buffer
- [“pcount” on page 642](#), determines the buffer size
- [“str” on page 643](#), returns a string
- [“setbuf” on page 644](#), a virtual function to set the buffer
- [“seekoff” on page 645](#), a virtual function for stream offset
- [“seekpos” on page 645](#), a virtual function for stream position
- [“underflow” on page 645](#), a virtual function for input error
- [“pbackfail” on page 646](#), a virtual function for put back error
- [“overflow” on page 646](#), a virtual function for output error

Listing 22.2 The strstreambuf class declaration.

```
class strstreambuf
: public streambuf
{
public:
    explicit strstreambuf(streamsize alsize_arg = 0);
    strstreambuf(void* (*palloc_arg)(size_t),
        void (*pfree_arg)(void*));
    strstreambuf(char* gnext_arg, streamsize n, char* pbeg_arg = 0);
    strstreambuf(const char* gnext_arg, streamsize n);
    strstreambuf(signed char* gnext_arg, streamsize n,
        signed char* pbeg_arg = 0);
    strstreambuf(const signed char* gnext_arg, streamsize n);
    strstreambuf(unsigned char* gnext_arg, streamsize n,
        unsigned char* pbeg_arg = 0);
    strstreambuf(const unsigned char* gnext_arg, streamsize n);
    virtual ~strstreambuf();
    void freeze(bool freezefl = true);
    char* str();
    int pcount() const;
protected:
    virtual int_type overflow (int_type c = EOF);
    virtual int_type pbackfail(int_type c = EOF);
    virtual int_type underflow();
    virtual pos_type seekoff(off_type off, ios_base::seekdir way,
        ios_base::openmode which = ios_base::in | ios_base::out);
    virtual pos_type seekpos(pos_type sp,
        ios_base::openmode which = ios_base::in | ios_base::out);
    virtual streambuf* setbuf(char* s, streamsize n);
private:
    typedef unsigned char strstate;
    static const strstate allocated = 1 << 0;
    static const strstate constant = 1 << 1;
    static const strstate dynamic = 1 << 2;
    static const strstate frozen = 1 << 3;
    static const streamsize default_alsize = 128;
    streamsize alsize_;
    void* (*palloc_)(size_t);
    void (*pfree_)(void*);
```

Annex D Strstream

Strstreambuf Class

```
    strstate strmode_;

    void init(char* gnext_arg, streamsize n, char* pbeg_arg = 0);
};
```

Remarks The template class `streambuf` is an abstract class for deriving various stream buffers whose objects control input and output sequences.

Strstreambuf constructors and Destructors

Default Constructor and Overloaded Constructors

Description Construct and destruct an object of type `streambuf`.

Dynamic Prototypes `explicit strstreambuf(streamsize alsize_arg = 0);`
`strstreambuf(void* (*palloc_arg)(size_t),`
`void (*pfree_arg)(void*));`

Character Array Prototypes `strstreambuf(char* gnext_arg, streamsize n,`
`char* pbeg_arg = 0);`
`strstreambuf(const char* gnext_arg, streamsize n);`
`strstreambuf(signed char* gnext_arg,`
`streamsize n, signed char* pbeg_arg = 0);`
`strstreambuf(const signed char* gnext_arg,`
`streamsize n);`
`strstreambuf(unsigned char* gnext_arg,`
`streamsize n, unsigned char* pbeg_arg = 0);`
`strstreambuf(const unsigned char* gnext_arg,`
`streamsize n);`

Remarks The constructor sets all pointer member objects to null pointers.

The `strstreambuf` object is used usually for a intermediate storage object for input and output. The overloaded constructor that is used determines the attributes of the array object when it is created. These might be allocated, or dynamic and are stored in a bitmask type. The first two constructors listed allow for dynamic allocation. The

constructors with character array arguments will use that character array for a buffer.

Destructor

Description	To destroy a strstreambuf object.
Prototype	<code>virtual ~strstreambuf();</code>
Remarks	Removes the object from memory.

Strstreambuf Public Member Functions

Description	The public member functions allow access to member functions from derived classes.
--------------------	--

freeze

Description	To freeze the allocation of strstreambuf.
Prototype	<code>void freeze(bool freezefl = true);</code>
Remarks	The function <code>freeze()</code> stops allocation if the strstreambuf object is using dynamic allocation and prevents the destructor from freeing the allocation. The function <code>freeze(0)</code> when used with zero as an argument releases the freeze to allow for destruction.
Return	No return

Listing 22.3 Example of strstreambuf::freeze() usage:

```
#include <iostream>
#include <strstream>
#include <string.h>

const int size = 100;

main()
{
```

Annex D Strstream

Strstreambuf Class

```
        // dynamic allocation minimum allocation 100
strstreambuf strbuf(size);

        // add a string and get size
strbuf.sputn( "Metrowerks ", strlen("Metrowerks "));
cout << "The size of the stream is: "
    << strbuf.pcount() << endl;

        // add a string and get size
strbuf.sputn( "CodeWarrior", strlen("CodeWarrior"));
cout << "The size of the stream is: "
    << strbuf.pcount() << endl;

strbuf.sputc('\0');    // null terminate for output

        // now freeze for no more growth
strbuf.freeze();
        // try to add more
strbuf.sputn( " -- Software at Work --",
            strlen(" -- Software at Work --"));

cout << "The size of the stream is: "
    << strbuf.pcount() << endl;
cout << "The buffer contains:\n"
    << strbuf.str() << endl;
return 0;
}
```

Result:

```
The size of the stream is: 11
The size of the stream is: 22
The size of the stream is: 23
The buffer contains:
Metrowerks CodeWarrior
```

pcount

Description To determine the effective length of the buffer,

Prototype `int pcount() const;`

Remarks The function `pcount()` is used to determine the offset of the next character position from the beginning of the buffer.

Return A null terminated character array.

Listing 22.4 Example of `strstreambuf::pcount()` usage.

See: `strstreambuf::freeze`

str

Description To return the char array stored in the buffer.

Prototype `char* str();`

Remarks The function `str()` freezes the buffer and appends a null character then returns the array. The user is responsible for destruction of any dynamically allocated buffer.

Return A null terminated character array.

Listing 22.5 Example of `strstreambuf::str()` usage

```
#include <iostream>
#include <strstream>

const int size = 100;
char buf[size];
char arr[size] = "Metrowerks CodeWarrior - Software at Work";

main()
{
    ostrstream ostr(buf, size);
    ostr << arr;

    // associate buffer
    strstreambuf *strbuf(ostr.rdbuf());
```

Annex D Strstream

Strstreambuf Class

```
// do some manipulations
strbuf->pubseekoff(10,ios::beg);
strbuf->sputc('\0');
strbuf->pubseekoff(0, ios::beg);

cout << "The original array was\n" << arr << "\n\n";
cout << "The strstreambuf array is\n"
    << strbuf->str() << "\n\n";
cout << "The ostream array is now\n" << buf;

return 0;
}
```

Result:

The original array was
Metrowerks CodeWarrior - Software at Work

The strstreambuf array is
Metrowerks

The ostream array is now
Metrowerks

Protected Virtual Member Functions

Protected member functions that are overridden for stream buffer manipulations by the `strstream` class and derived classes from it.

setbuf

Description To set a buffer for stream input and output sequences.

Prototype `virtual streambuf* setbuf(char* s, streamsize n);`

Remarks The function `setbuf()` is overridden in `strstream` classes.

Return The `this` pointer.

seekoff

Description To return an offset of the current pointer in an input or output streams.

Prototype

```
virtual pos_type seekoff(  
    off_type off,  
    ios_base::seekdir way,  
    ios_base::openmode  
    which = ios_base::in | ios_base::out);
```

Remarks The function `seekoff()` is overridden in `strstream` classes.

Return A `pos_type` value, which is an invalid stream position.

seekpos

Description To alter an input or output stream position.

Prototype

```
virtual pos_type seekpos(  
    pos_type sp,  
    ios_base::openmode  
    which = ios_base::in | ios_base::out);
```

Remarks The function `seekpos()` is overridden in `strstream` classes.

Return A `pos_type` value, which is an invalid stream position.

underflow

Description To show an underflow condition and not increment the get pointer.

Prototype

```
virtual int_type underflow();
```

Remarks The virtual function `underflow()` is called when a character is not available for input.

There are many constraints for `underflow()`.

Annex D Strstream

Strstreambuf Class

- The pending sequence of characters is a concatenation of end pointer minus the get pointer plus some sequence of characters to be read from input.
- The result character if the sequence is not empty the first character in the sequence or the next character in the sequence.
- The backup sequence if the `beginning pointer` is null, the sequence is empty, otherwise the sequence is the `get pointer` minus the `beginning pointer`.

Return The first character of the pending sequence and does not increment the get pointer. If the position is null returns `traits::eof()` to indicate failure.

pbackfail

Description To show a failure in a put back operation.

Prototype `virtual int_type pbackfail(int_type c = EOF);`

Remarks The resulting conditions are the same as the function `underflow()`.

Return The function `pbackfail()` is only called when a put back operation really has failed and returns `traits::eof`. If success occurs the return is undefined.

overflow

Description Consumes the pending characters of an output sequence.

Prototype `virtual int_type overflow (int_type c = EOF);`

Remarks The pending sequence is defined as the concatenation of the `put pointer` minus the `beginning pointer` plus either the sequence of characters or an empty sequence, unless the `beginning pointer` is null in which case the pending sequence is an empty sequence.

This function is called by `sputc()` and `sputn()` when the buffer is not large enough to hold the output sequence.

Overriding this function requires that:

- When overridden by a derived class how characters are consumed must be specified.
- After the overflow either the `beginning pointer` must be null or the `beginning` and `put pointer` must both be set to the same `non-null` value.
- The function may fail if appending characters to an output stream fails or failure to set the previous requirement occurs.

Return The function returns `traits::eof()` for failure or some unspecified result to indicate success.

Istrstream Class

The class `istrstream` is used to create and associate a stream with an array for input.

The `istrstream` class includes the following facilities

- [“Constructors and Destructor” on page 648](#), to create and remove an `istrstream` object
- [“rdbuf” on page 649](#), to access the buffer
- [“str” on page 650](#), returns the buffer

Listing 22.6 The `istrstream` class declaration

```
class istrstream : public basic_istream<char>
{
public:
    explicit istrstream(const char* s);
    explicit istrstream(char* s);
    istrstream(const char* s, streamsize n);
    istrstream(char* s, streamsize n);
    virtual ~istrstream();
    strstreambuf* rdbuf() const;
    char* str();
```

Annex D Strstream

Istrstream Class

```
private:
    strstreambuf strbuf_;
};
```

Constructors and Destructor

The `istrstream` class has an overloaded constructor.

Constructors

Description	Create an array based stream for input
Prototype	<pre>explicit istrstream(const char* s); explicit istrstream(char* s); istrstream(const char* s, streamsize n); istrstream(char* s, streamsize n);</pre>
Remarks	The <code>istrstream</code> constructor is overloaded to accept a dynamic or pre-allocated character based array for input. It is also overloaded to limit the size of the allocation to prevent accidental overflow

Listing 22.7 Example of usage.

```
#include <iostream>
#include <strstream>

char buf[100] = "double 3.21 string array int 321";

main()
{
    char arr[4][20];
    double d;
    long i;

    istrstream istr(buf);
    istr >> arr[0] >> d >> arr[1] >> arr[2] >> arr[3] >> i;

    cout << arr[0] << " is " << d << "\n"
```



```
<< arr[1] << " is " << arr[2] << "\n"
<< arr[3] << " is " << i << endl;

return 0;
}
```

Result:
double is 3.21
string is array
int is 321

Destructor

- Description** To destroy an `istrstream` object.
- Prototype** `virtual ~istrstream();`
- Remarks** The `istrstream` destructor removes the `istrstream` object from memory.

Public Member Functions

There are two public member functions.

rdbuf

- Description** Returns a pointer to the `strstreambuf`
- Prototype** `strstreambuf* rdbuf() const;`
- Remarks** To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the stream's buffer. The function `rdbuf()` allows you to retrieve this pointer.
- Return** A pointer to `strstreambuf`.

Annex D Strstream

Ostrstream Class

Listing 22.8 Example of `istrstream::rdbuf()` usage.

See: `strstreambuf::str()`

str

Description Return a pointer to the stored array.

Prototype `char* str();`

Remarks The function `str()` freezes and terminates the character array stored in the buffer with a null character. It then returns the null terminated character array.

Return A null terminated char array

Listing 22.9 Example of `istrstream::str()` usage.

```
#include <iostream>
#include <strstream>

const int size = 100;
char buf[size] = "Metrowerks CodeWarrior - Software at Work";

main()
{
    istrstream istr(buf, size);
    cout << istr.str();
    return 0;
}
```

Result:
Metrowerks CodeWarrior - Software at Work

Ostrstream Class

The class `strstreambuf` is derived from `streambuf` to associate a stream with an array buffer for output.

The `ostrstream` class includes the following facilities

- [“Constructors and Destructor” on page 651](#)
- [“freeze” on page 653](#)
- [“pcount” on page 654](#)
- [“rdbuf” on page 655](#)
- [“str” on page 655](#)

Listing 22.10 The `ostrstream` class declaration

```
class ostrstream : public basic_ostream<char>
{
public:
    ostrstream();
    ostrstream(char* s, int n, ios_base::openmode mode =
ios_base::out);
    virtual ~ostrstream();
    strstreambuf* rdbuf() const;
    void freeze(bool freezefl = true);
    char* str();
    int pcount() const;
private:
    strstreambuf strbuf_;
};
```

Constructors and Destructor

The `ostrstream` class has an overloaded constructor.

Constructors

Description Creates a stream and associates it with a char array for output.

Prototype `ostrstream();`
 `ostrstream(char* s, int n,`
 `ios_base::openmode mode = ios_base::out);`

Annex D Strstream

Ostrstream Class

Remarks The `ostrstream` array is overloaded for association a pre allocated array or for dynamic allocation.

NOTE: When using an `ostrstream` object the user must supply a null character for termination. When storing a string which is already null terminated that null terminator is stripped off to allow for appending.

Listing 22.11 Example of `ostrstream` usage.

```
#include <iostream>
#include <strstream>

main()
{
    ostrstream out;
    out << "Ask the teacher anything you want to know" << ends;

    istream inOut(out.rdbuf() );

    char c;
    while( inOut.get(c) ) cout.put(c);

    return 0;
}
```

Result:
Ask the teacher anything you want to know

Destructor

Description Destroys an `ostrstream` object.

Prototype `virtual ~ostrstream();`

Remarks A `ostrstream` destructor removes the `ostrstream` object from memory.

Public Member Functions

The `ostream` class has four public member functions.

freeze

Description	Freezes the dynamic allocation or destruction of a buffer.
Prototype	<code>void freeze(bool freezefl = true);</code>
Remarks	To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function <code>rdbuf()</code> allows you to retrieve this pointer.
Return	A pointer to <code>strstreambuf</code> .

Listing 22.12 Example of `ostrstream` `freeze()` usage.

```
#include <iostream>
#include <strstream>

main()
{
    ostrstream out;
    out << "Metowerks " << 1234;
    out << "the size of the array so far is "
        << out.pcount() << " characters \n";

    out << " Software" << '\0';
    out.freeze();    // freezes so no more growth can occur

    out << " at work" << ends;
    out << "the final size of the array  is "
        << out.pcount() << " characters \n";

    cout << out.str() << endl;

    return 0;
}
```

Annex D Strstream

Ostrstream Class

Result:

the size of the array so far is 14 characters
the final size of the array is 24 characters
Metowerks 1234 Software

pcount

Description Determines the number of bytes offset of the current stream position to the beginning of the array.

Prototype `int pcount() const;`

Remarks The function `pcount()` is used to determine the offset of the array. This may not equal to the number of characters inserted due to possible positioning operations.

Return An `int_type`, the length of the array.

Listing 22.13 Example of `ostrstream pcount()` usage.

```
#include <iostream>
#include <strstream>

main()
{
    ostrstream out;
    out << "Metowerks " << 1234 << ends;
    out << "the size of the array so far is "
        << out.pcount() << " characters \n";

    out << " Software at work" << ends;
    out << "the final size of the array is "
        << out.pcount() << " characters \n";

    cout << out.str() << endl;

    return 0;
}
```

Result:
the size of the array so far is 15 characters
the final size of the array is 33 characters
Metoworks 1234

rdbuf

- Description** To retrieve a pointer to the streams buffer.
- Prototype** `strstreambuf* rdbuf() const;`
- Remarks** To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function `rdbuf()` allows you to retrieve this pointer.
- Return** A pointer to `strstreambuf`.

Listing 22.14 Example of ostrstream rdbuf() usage.

See: `streambuf::pubseekoff()`

str

- Description** Returns a pointer to a character array.
- Prototype** `char* str();`
- Remarks** The function `str()` freezes any dynamic allocation.
- Return** A null terminated character array.

Listing 22.15 Example of ostrstream str() usage.

See `ostrstream::freeze()`,

Strstream Class

The class `strstream` is derived from `streambuf` to associate a stream with an array buffer for output

The `strstream` class includes the following facilities

- [“Constructors and Destructor” on page 657](#)
- [“freeze” on page 657](#)
- [“pcount” on page 658](#)
- [“rdbuf” on page 658](#)
- [“str” on page 658](#)

Listing 22.16 The `strstream` class declaration

```
class strstream : public basic_ostream<char>
{
public:
    // Types
    typedef char                               char_type;
    typedef typename char_traits<char>::int_type int_type;
    typedef typename char_traits<char>::pos_type pos_type;
    typedef typename char_traits<char>::off_type off_type;
    // constructors/destructor
    strstream();
    strstream(char* s, int n, ios_base::openmode mode =
ios_base::in|ios_base::out);
    virtual ~strstream();
    // Members:
    strstreambuf* rdbuf() const;
    void freeze(bool freezefl = true);
    int pcount() const;
    char* str();
private:
    strstreambuf strbuf_;
};
```

Strstream Types

The `strstream` class typedefs a `char_type`, `int_type`, `pos_type` and `off_type`, for stream positioning and storage.

Constructors and Destructor

Constructors

Description	Creates a stream and associates it with a char array for input and output.
Prototype	<pre>strstream(); strstream(char* s, int n, ios_base::openmode mode = ios_base::in ios_base::out);</pre>
Remarks	The <code>strstream</code> array is overloaded for association a pre allocated array or for dynamic allocation

Destructor

Description	Destroys a <code>ststream</code> object.
Prototype	<pre>virtual ~strstream();</pre>
Remarks	Removes the <code>strstream</code> object from memory.

Public Member Functions

The class `strstream` has four public member functions.

freeze

Description	Freezes the dynamic allocation or destruction of a buffer.
Prototype	<pre>void freeze(bool freezefl = true);</pre>
Remarks	The function <code>freeze</code> stops dynamic allocation of a buffer.

Annex D Strstream

Strstream Class

pcount

Description	Determines the number of bytes offset of the current stream position to the beginning of the array.
Prototype	<code>int pcount() const;</code>
Remarks	The function <code>pcount()</code> is used to determine the offset of the array. This may not equal to the number of characters inserted due to possible positioning operations.
Return	An <code>int_type</code> , the length of the array.

rdbuf

Description	Retrieves a pointer to the streams buffer
Prototype	<code>strstreambuf* rdbuf() const;</code>
Remarks	To manipulate a stream for random access or synchronization it is necessary to retrieve a pointer to the streams buffer. The function <code>rdbuf()</code> allows you to retrieve this pointer.
Return	A pointer to <code>strstreambuf</code> .

str

Description	Returns a pointer to a character array.
Prototype	<code>char* str();</code>
Remarks	The function <code>str()</code> freezes any dynamic allocation.
Return	A null terminated character array.



Mutex.h

This chapter is a reference guide to the mutex support library.

Overview of Mutex Support Library

The mutex “mutual exclusion” support library provides the mechanism for implementing thread-safe applications. This mechanism consists of software locks that prevent more than one thread having simultaneous access to critical areas of code.

The mutex support library consists of the following classes:

- [“null_mutex” on page 662](#), a class for marking a future mutual exclusion area during program development
- [“mutex” on page 663](#), a class for implementing a basic mutual exclusion area
- [“mutex_block” on page 665](#), a template class for ensuring mutual exclusion for a complete block of code
- [“mutex_arith” on page 666](#), a template class for ensuring mutual exclusion during the evaluation of arithmetic operations with side effects
- [“rw_mutex” on page 670](#), a class for ensuring mutual exclusion during read and write operations
- [“mutex_rec” on page 672](#), a template class for protecting data records against simultaneous access by more than one thread

Header <mutex.h>

Description The header <mutex.h> defines

Mutex.h

Header <mutex.h>

Prototype

```
namespace std{
class null_mutex {
public:
    inline null_mutex ();
    inline ~null_mutex ();
    inline int remove () const;
    inline int acquire (int = 0) const;
    inline int release () const;
};

class mutex {
private:
    mutex_type    _lock;
public:
    inline mutex ();
    inline ~mutex ();
    inline int remove () const;
    inline int acquire (int = 0) const;
    inline int release () const;
    bool try_lock ();
};

template <class MUTEX>
class mutex_block {
public:
    inline mutex_block (const MUTEX& m, int type = 0);
    inline ~mutex_block ();
    inline int remove () const;
    inline int release () const;
    inline int acquire (int type = 0) const;
private:
    const MUTEX&    _lock;
};

template <class TYPE, class MUTEX>
class mutex_arith {
private:
    TYPE    _count;
};
```

```
    MUTEX _lock;
public:
    inline mutex_arith ();
    inline mutex_arith (TYPE i);
    inline TYPE operator++ ();
    inline TYPE operator++ (int);
    inline TYPE operator+= (const TYPE i);
    inline TYPE operator-- ();
    inline TYPE operator-- (int);
    inline TYPE operator-= (const TYPE i);
    inline bool operator== (const TYPE i);
    inline bool operator!= (const TYPE i);
    inline bool operator>= (const TYPE i);
    inline bool operator> (const TYPE i);
    inline bool operator<= (const TYPE i);
    inline bool operator< (const TYPE i);
    inline void operator= (const TYPE i);
    inline operator TYPE ();
};

class rw_mutex {
private:
    mutex_type _lock;
public:
    inline rw_mutex ();
    inline ~rw_mutex ();
    inline int remove () const;
    inline int acquire (int) const;
    inline int release () const;
    bool try_rdlock ();
    bool try_wrlock ();
};

template <class MUTEX = mutex>
class mutex_rec {
public:
    mutex_rec();
    int acquire(int type = 0) const;
    int release() const;
    int remove () const;
```

Mutex.h

null_mutex

```
private:
    thread_id get_tid () const;
    MUTEX                                     lock;
    thread_id                                thr_id;
    mutex_arith<unsigned int,mutex>          nest_count
};
```

null_mutex

Description The null mutex provides a method for defining during program development a code sequence that will need to be protected against simultaneous access by more than one thread. The null mutex provides no actual protection but serves as a marker that can be replaced by actual mutex objects later in the development process.

Prototype

```
class null_mutex {
public:
    inline null_mutex ();
    inline ~null_mutex ();
    inline int remove () const;
    inline int acquire (int = 0) const;
    inline int release () const;
};
```

Constructor and Destructor

Constructor

Description Constructs a null_mutex object.

Prototype inline null_mutex () {

Destructor

Description Removes a null_mutex object.

Prototype inline ~null_mutex () {}

Public Member Functions

remove

Description Explicit null_mutex destruction.

Prototype `inline int remove () const { return 0; }`

acquire

Description Acquire the _lock. (Wait if necessary).

Prototype `inline int acquire (int = 0) const`

Returns Null

release

Description Release the _lock.

Prototype `inline int release () const;`

Returns Null

mutex

Description This provides for the basic mutual exclusion mechanism.

Prototype

```
class mutex {
private:
    mutex_type _lock;
public:
    inline mutex ();
    inline ~mutex ();
    inline int remove () const;
    inline int acquire (int = 0) const;
    inline int release () const;
```

```
        bool try_lock ();  
};
```

Constructor and Destructor

Constructor

Description Initialize the mutex.

Prototype `inline mutex ();`

Destructor

Description Implicit mutex destruction.

Prototype `inline ~mutex ();`

Public Member Functions

remove

Description Explicit mutex destruction.

Prototype `inline int remove () const;`

acquire

Description Acquire the `_lock`. (Wait if necessary).

Prototype `inline int acquire (int = 0) const;`

release

Description Release the `_lock`.

Prototype `inline int release () const;`

try_lock

Description Attempt to lock the mutex, but don't wait.

Prototype `bool try_lock ();`

Return True if successful.

mutex_block

Description This template provides the mutex mechanism for a complete block of code.

Prototype

```
template <class MUTEX>
class mutex_block {
public:
    inline mutex_block (const MUTEX& m, int type =
0);
    inline ~mutex_block ();
    inline int remove () const;
    inline int release () const;
    inline int acquire (int type = 0) const;
private:
    const MUTEX& _lock;
};
```

Constructor and Destructors

Constructor

Description Implicit lock acquisition

Prototype `inline mutex_block (const MUTEX& m, int type = 0);`

Destructor

Description Implicit lock release

Prototype `inline ~mutex_block ();`

Public Member Functions

remove

Description Explicit lock release

Prototype `inline int remove () const`

Return `_lock.remove();`

release

Description Explicit lock release

Prototype `inline int release () const {`

Return `_lock.release ();`

acquire

Description Explicit lock acquisition

Prototype `inline int acquire (int type = 0) const;`

Return `_lock.acquire(type);`

mutex_arith

Description This template provides inline mutual exclusion for arithmetic operations that will protect against multiple thread access during the evaluation of an expression with side effects.

Prototype `template <class TYPE, class MUTEX>
class mutex_arith {
private:`

```
    TYPE    _count;
    MUTEX   _lock;
public:
    inline mutex_arith ();
    inline mutex_arith (TYPE i);
    inline TYPE operator++ ();
    inline TYPE operator++ (int);
    inline TYPE operator+= (const TYPE i);
    inline TYPE operator-- ();
    inline TYPE operator-- (int);
    inline TYPE operator-= (const TYPE i);
    inline bool operator== (const TYPE i);
    inline bool operator!= (const TYPE i);
    inline bool operator>= (const TYPE i);
    inline bool operator> (const TYPE i);
    inline bool operator<= (const TYPE i);
    inline bool operator< (const TYPE i);
    inline void operator= (const TYPE i);
    inline operator TYPE ();
};
```

Constructors

Description Initialize the mutex_arith object.

Prototype inline mutex_arith ()

Remarks Initialize _count to 0

Prototype inline mutex_arith (TYPE i)

Remarks Initialize _count to i.

Public Member Operators

Prefix operator++

Description Increment _count by unit.

Prototype inline TYPE operator++ ();

Postfix operator++

Description Increment `_count` by unit.

Prototype `inline TYPE operator++ (int);`

operator+=

Description Increment `_count` by `i`.

Prototype `inline TYPE operator+= (const TYPE i)`

Prefix operator--

Description Decrement `_count` by unit.

Prototype `inline TYPE operator-- ()`

Postfix operator--

Description Decrement `_count` by unit.

Prototype `inline TYPE operator-- (int)`

operator-=

Description Decrement `_count` by `i`.

Prototype `inline TYPE operator-= (const TYPE i);`

Return `_count -= i;`

operator==

Description Compare `_count` with `i`.

Prototype `inline bool operator== (const TYPE i);`

Return `_count == i;`

Remarks

operator!=

Description Compare `_count` with `i`.

Prototype `inline bool operator!= (const TYPE i)`

Return `_count != i;`

operator>=

Description Check if `_count >= i`.

Prototype `inline bool operator>= (const TYPE i);`

Return `_count >= i;`

operator>

Description Check if `_count > i`.

Prototype `inline bool operator> (const TYPE i);`

Return `_count > i;`

operator<=

Description Check if `_count <= i`.

Prototype `inline bool operator<= (const TYPE i);`

Return `_count <= i;`

operator<

Description Check if `_count < i`.

Prototype `inline bool operator< (const TYPE i);`

Return `_count < i;`

operator=

Description Assign `i` to `count_`

Prototype `inline void operator= (const TYPE i);`

operator TYPE

Description Return `count_`.

Prototype `inline operator TYPE ();`

Return `_count`

rw_mutex

Description This template provides mutual exclusion for input and output operations.

Prototype

```
class rw_mutex {
private:
    mutex_type _lock;
public:
    inline rw_mutex ();
    inline ~rw_mutex ();
    inline int remove () const;
    inline int acquire (int) const;
    inline int release () const;
    bool try_rdlock ();
```

```
        bool try_wrlock ();  
};
```

Constructor and Destructor

Constructor

Description Initialize the readers/writer mutex.

Prototype `inline rw_mutex ();`

Destructor

Description Implicit mutex destruction.

Prototype `inline ~rw_mutex ();`

Public Member Functions

remove

Description Explicit `rw_mutex` destruction.

Prototype `inline int remove () const;`

acquire

Description Acquire the `_lock`. Wait if necessary.

Prototype `inline int acquire (int) const;`

release

Description Release the `_lock`.

Prototype `inline int release () const;`

try_rdlock

Description Attempt to lock the mutex for reading, but don't wait.

Prototype `bool try_rdlock ();`

Return True if successful.

try_wrlock

Description Attempt to lock the mutex for writing, but don't wait.

Prototype `bool try_wrlock ();`

Return True if successful.

mutex_rec

Description This template provides mutual exclusion mechanism for protecting against simultaneous access to a data record.

Prototype

```
template <class MUTEX = mutex>
class mutex_rec {
public:
    mutex_rec();
    int acquire(int type = 0) const;
    int release() const;
    int remove () const;
private:
    thread_id get_tid () const;
    MUTEX lock;
    thread_id thr_id;
    mutex_arith<unsigned int,mutex> nest_count;
};
```


Constructor

Description Creates a mutex_rec class.

Prototype `mutex_rec()`

Public Members Functions

acquire

Description Acquire the _lock. Wait if necessary.

Prototype `int acquire(int type = 0) const`

release

Description Release the _lock.

Prototype `int release() const`

remove

Description Explicit mutex_rec destruction.

Prototype `int remove () const`

Mutex.h

mutex_rec

Index

Symbols

`_MSL_CX_LIMITED_RANGE` 409

A

`abs` 424

algorithms

 categories 305

 generalized numeric 356

 accumulate 356

 in-place and copying versions 305

 mutating sequence 314

 copy 314

 partition 329

 random_shuffle 329

 replace 318

 reverse 327

 rotate 327

 swap 316, 317

 unique 325

 non mutating sequence 307

 count 310

 equal 311

 find 307

 for_each 307

 mismatch 311

 search 313

 numeric processing 356

 sorting 331

 binary_search 336

 nth_element 335

 with predicate parameters 306

Allocator object information 72

`arg` 424

`assign` 96

Assignment Operator

 complex 417

Associative Containers

 Basic Design and Organization 187

 Types and Member Functions 188

`auto_ptr` destructor 91

B

`bad` 474

`basic_filebuf` 604

 close 609

 constructors 606

 destructor 606

 imbue 612

 is_open 606

 open 607

 Open Modes 607

 overflow 610

 pbackfail 610

 seekoff 611

 seekpos 611

 setbuf 611

 showmanyc 609

 sync 612

 underflow 610

`basic_fstream` 626

 close 631

 constructor 627

 is_open 630

 open 630

 Open Modes 631

 rdbuf 628

`basic_ifstream` 612

 close 618

 constructor 613

 is_open 616

 open 616

 Open Modes 617

 rdbuf 615

`basic_ios` 458

 bad 474

 clear 468

 constructors 460

 copyfmt 465

 eof 471

 exceptions 476

 fail 473

 fill 464

 good 471

 imbue 464

 operator! 466

 operator bool 466

 rdbuf 463

Index

- rdstate 466
- setstate 470
- basic_iostream 546
 - constructor 546
 - destructor 546
- basic_istream 513
 - constructors 516
 - destructor 516
 - extractors, arithmetic 519
 - extractors, characters 520
 - gcount 525
 - get 527
 - getline 530
 - ignore 532
 - peek 534
 - putback 537
 - read 534
 - readsome 536
 - seekg 542
 - sentry 517
 - sync 541
 - tellg 542
 - unget 539
 - ws 544
- basic_istreamstream 587
 - constructors 588
 - rdbuf 589
 - str 590
- basic_ofstream 619
 - close 625
 - constructors 620
 - is_open 623
 - open 623
 - Open Modes 624
 - rdbuf 621
- basic_ostream 547
 - constructor 549
 - destructor 549
 - endl 566
 - ends 566
 - flush 563
 - flush,flush 567
 - Inserters, arithmetic 552
 - Inserters, characters 554
 - put 560
 - resetiosflags 570
 - seekp 559
 - sentry 550
 - setbase 572
 - setfill 573
 - setiosflags 571
 - setprecision 574
 - setw 575
 - tellp 558
 - write 561
- basic_ostringstream 591
 - constructors 593
 - rdbuf 594
 - str 596
- basic_streambuf 484
 - constructors 487, 581
 - destructor 487
 - eback 501
 - egptr 501
 - epptr 503
 - gbump 502
 - getloc 488
 - gptr 501
 - imbue 504
 - in_avail 494
 - Locales 488
 - overflow 509, 585
 - pbackfail 508, 585
 - pbase 502
 - pbump 503
 - pptr 503
 - pubseekoff 490
 - pubseekpos 491
 - pubsetbuf 489
 - pubsync 493
 - pubuimbue 488
 - sbumpc 495
 - seekoff 505, 586
 - seekpos 505, 586
 - setbuf 504
 - setg 502
 - setp 503
 - sgetc 496
 - sgetn 497
 - showmanc 506
 - snextc 494
 - sputback 497
 - sputc 499
 - sputn 500

-
- str 583
 - sungetc 499
 - sync 505
 - uflow 507
 - underflow 506, 584
 - xsgetn 506
 - xspn 508
 - basic_string
 - append 117
 - assign 118
 - assignment operator 113
 - at 117
 - begin 114
 - c_str 121
 - capacity 115, 116
 - clear 116
 - compare 125
 - Constructors 112
 - copy 121
 - data 121
 - destructor 113
 - Element Access 116
 - empty 116
 - end 114
 - erase 119
 - extractor 132
 - find 122
 - find_first_not_of 124
 - find_first_of 123
 - find_last_of 123
 - get_allocator 121
 - getline 132
 - insert 118
 - inserter 132
 - Inserters and extractors 132
 - iterator support 114
 - max_size 115
 - Modifiers 117
 - Non-Member Functions and Operators 126
 - Null Terminated Sequence Utilites 133
 - operator 128, 130, 132
 - operator!= 128
 - operator+ 126
 - operator+= 117
 - operator== 127
 - operator> 129
 - operator>= 131
 - operator<< 132
 - rbegin 114
 - rend 115
 - replace 119
 - reserve 116
 - rfind 122
 - size 115
 - String Operations 121
 - substr 125
 - swap 121
 - basic_stringbuf 580
 - basic_stringstream 597
 - constructors 598
 - rdbuf 600
 - str 601
 - boolalpha 477
 - Buffer management 488
- ## C
- C Library files 633
 - cerr 436
 - char_type 97
 - character 96
 - character container type 96
 - Character Trait Definitions 96, 97
 - Character traits definitions 96
 - Class
 - basic_filebuf 604
 - basic_fstream 626
 - basic_ifstream 612
 - basic_ios 458
 - basic_iostream 546
 - basic_istream 513
 - sentry 517
 - basic_istream 587
 - basic_ofstream 619
 - basic_ostream 547
 - sentry 550
 - basic_ostringstream 591
 - basic_streambuf 484
 - basic_stringbuf 580
 - basic_stringstream 597
 - complex 416
 - ios_base 441
 - failure 443
-

Index

- Init 447
- clear 468
- clog 437
- close
 - basic_filebuf 609
 - basic_fstream 631
 - basic_ifstream 618
 - basic_ofstream 625
- compare 96
- Comparison Operations
 - Deque 207
 - List 216
 - Map 247
 - Multimap 258
 - Set 227
 - Vector 198
- complex 416, 420
 - abs 424
 - arg 424
 - conj 424
 - constructor 416
 - cos 425
 - cosh 426
 - exp 426
 - imag 417, 423
 - log 426
 - log10 426
 - norm 424
 - operator 423
 - operator != 422
 - operator * 421
 - operator *= 419
 - operator + 420
 - operator += 418
 - operator / 421
 - operator /= 419
 - operator -= 418
 - operator = 417
 - operator == 422
 - operator >> 422
 - polar 425
 - pow 427
 - real 417, 423
 - sin 427
 - sinh 427
 - sqrt 427

- tan 428
- tanh 428
- Complexity of
 - Deque Insertion 211
 - List Insertion 222
 - Vector Insertion 202
- conj 424
- Constructors 111
 - basic_filebuf 606
 - basic_fstream 627
 - basic_ifstream 613
 - basic_ios 460
 - basic_istream 546
 - basic_istream 516
 - basic_istream 588
 - basic_ofstream 620
 - basic_ostream 549
 - basic_ostream 593
 - basic_streambuf 487, 581
 - basic_stringstream 598
 - failure, ios_base 444
 - ios_base 458
 - istream 648
 - list 215
 - Map 246
 - Multimap 257
 - ostream 651
 - sentry, basic_istream 518
 - sentry, basic_ostream 551
 - stringstream 657
 - stringstream 640
- Container Classes
 - Common Members of 179
- copy 97
- copyfmt 465
- cos 425
- cosh 426
- cout 436
- cstdio
 - Functions 634
 - Macros 633
 - Types 633

D

- dec 479
- Deque

-
- Comparison Operations 207
 - Complexity of Deque Insertion 211
 - Constructors 205
 - Element Access Member Functions 207
 - Insert Member Functions 209
 - Notes on Deque Erase Member Functions 212
 - Related Functions 205
- Destructor
- istream 649
 - ostream 652
 - stringstream 657
- Destructors
- basic_filebuf 606
 - basic_ios 460
 - basic_istream 546
 - basic_istream 516
 - basic_ostream 549
 - basic_streambuf 487
 - deque 205
 - Init, ios_base 448
 - ios_base 458
 - list 215
 - Map 246
 - Multimap 257
 - Multiset 236
 - sentry, basic_istream 518
 - sentry, basic_ostream 551
 - stringstream 641
 - Vector 196
- E**
- eback 501
 - egptr 501
 - endl 566
 - ends 566
 - eof 97, 471
 - eptr 503
 - eq 96
 - eq_int_type 97
 - exceptions
 - basic_ios 476
 - exp 426
 - Extractors
 - basic_istream, arithmetic 519
 - basic_istream, characters 520
- overloading 523
- F**
- fail 473
 - fill 464
 - find 96
 - fixed 479
 - flags 448
 - flush 563
 - fmtflags 444
 - freeze
 - ostream 653
 - stringstream 657
 - stringstream 641
 - fstream 603
 - Function Objects
 - Introduction to Function Objects 80
- G**
- gbump 502
 - gcount 525
 - get 527
 - get_state 97
 - getline 530
 - getloc
 - basic_streambuf 488
 - ios_base 456
 - good 471
 - gptr 501
- H**
- Headers 99
- fstream 603
 - ios 439
 - iosfwd 433
 - istream 435
 - istream 511
 - mutex.h 659
 - streambuf 483
 - stringstream 635
- heap operations 347
 - hex 479
-

Index

- I**
- I/O Library Summary 429
- ignore 532
- imag 423
 - complex 417
- imbue
 - basic_filebuf 612
 - basic_ios 464
 - basic_streambuf 504
 - iosbase 455
- in_avail 494
- Inserters
 - basic_ostream, arithmetic 552
 - basic_ostream, characters 554
 - overloading 556
- int_type 97
- internal 478
- ios 439
- ios_base 441
 - constructors 458
 - failure 443
 - constructor 444
 - what 444
 - flags 448
 - fmtflags 444
 - getloc 456
 - imbue 455
 - Init 447
 - destructor 448
 - iostate 446
 - word 456
 - Open Modes 446
 - precision 453
 - pword 457
 - register_callback 457
 - seekdir 447
 - setf 451
 - sync_with_stdio 458
 - unsetf 452
 - width 454
 - xalloc 456
- iosfwd 433
- iostate 446
- iostream 435
- Iostreams Definitions 430
- Iostreams requirements 430
- is_open
 - basic_filebuf 606
 - basic_fstream 630
 - basic_ifstream 616
 - basic_ofstream 623
- istream 511
- istream win 437
- istrstream 647
 - constructor 648
 - destructor 649
 - rdbuf 649
 - str 650
- word 456
- L**
- left 478
- length 96
- List
 - Comparison Operations 216
 - Erase Member Functions 219
 - Notes on list erase member functions 222
 - Related Functions 215
- Locales
 - basic_streambuf 488
- log 426
- log10 426
- lt 96
- M**
- Manipulator
 - Overloading 576
 - scientific 479
- Manipulators
 - adjustfield 478
 - basefield 478
 - boolalpha 477
 - dec 479
 - endl 566
 - ends 566
 - fixed 479
 - floatfield 479
 - flush 567
 - fmtflags 476
 - hex 479

-
- Instantiations 570
 - internal 478
 - ios_base 476
 - left 478
 - noboolalpha 477
 - noshowbase 477
 - noshowpoint 477
 - noshowpos 477
 - noskipws 477
 - nounitbuf 478
 - nouppercase 477
 - oct 479
 - overloaded 480
 - right 478
 - showbase 477
 - showpoint 477
 - showpos 477
 - skipws 477
 - uppercase 477
 - ws 544
 - Map
 - Comparison Operations 247
 - Constructors 246
 - Destructors 246
 - Element Access Member Functions 248
 - Erase Member Functions 251
 - Insert Member Functions 250
 - Related Functions 246
 - Special Operations 251
 - Memory Model Information 72
 - move 96
 - mtx.h 659
 - Multimap
 - Comparison Operations 258
 - Constructors 257
 - Destructors 257
 - Element Access Member Functions 259
 - Erase Member Functions 261
 - Insert Member Functions 260
 - Related Functions 257
 - Special Operations 262
 - Multiset
 - Comparison Operations 237
 - Element Access Member Functions 238
 - Erase Member Functions 240
 - Insert Member Functions 239
 - Special Operations 241
 - mutex 663
 - acquire 664
 - Constructor 664
 - Destructor 664
 - release 664
 - remove 664
 - try_lock 665
 - mutex_arith 666
 - Constructor 667
 - operator 669, 670
 - operator TYPE 670
 - operator!= 669
 - operator+= 668
 - operator-= 668
 - operator= 670
 - operator== 668
 - operator> 669
 - operator>= 669
 - Postfix operator-- 668
 - Postfix operator++ 668
 - Prefix operator-- 668
 - Prefix operator++ 667
 - mutex_block 665
 - acquire 666
 - Constructor 665
 - Destructor 665
 - release 666
 - remove 666
 - mutex_rec 672
 - acquire 673
 - Constructor 673
 - release 673
 - remove 673
- ## N
- noboolalpha 477
 - norm 424
 - noshowpoint 477
 - noshowpos 477
 - noskipws 477
 - not_eof 97
 - nounitbuf 478
 - nouppercase 477
 - NTCTS 96

Index

null_mutex 662
 acquire 663
 Constructor 662
 Destructor 662
 release 663
 remove 663

O

oct 479
off_type 97
open
 basic_filebuf 607
 basic_fstream 630
 basic_ifstream 616
 basic_ofstream 623
Open Modes
 basic_filebuf 607
 basic_fstream 631
 basic_ifstream 617
 basic_ofstream 624
 ios_base 446
operator 423
operator - 420
 complex 420
Operator !
 basic_ios 466
operator !=
 complex 422
operator *
 complex 421
operator *=
 complex 419
operator +
 complex 420
operator +=
 complex 418
operator /
 complex 421
operator /=
 complex 419
operator -=
 complex 418
operator =
 complex 417
operator ==
 complex 422
operator >>
 complex 422
Operator bool
 basic_ios 466
 sentry, basic_istream 518
 sentry, basic_ostream 551
ostream cerr 436
ostream clog 437
ostream cout 436
ostream wout 437
ostrstream 650
 constructor 651
 destructor 652
 freeze 653
 pcount 654
 rdbuf 655
 str 655
overflow 509, 646
 basic_filebuf 610
 basic_streambuf 585
Overloaded
 manipulators 480
Overloading
 Extractors 523
 Inserters 556
 Manipulator 576

P

pbackfail 508, 646
 basic_filebuf 610
 basic_streambuf 585
pbase 502
pbump 503
pcount
 ostrstream 654
 strstream 658
 strstreambuf 642
peek 534
pointing 262
polar 425
pos_type 98
pow 427
pptr 503
precision 453

predicate parameters 306

predicates

 binary 306

pubimbue 488

pubseekoff 490

pubseekpos 491

pubsetbuf 489

pubsync 493

put 560

putback 537

pword 457

R

rdbuf 463

 basic_fstream 628

 basic_ifstream 615

 basic_istream 589

 basic_ofstream 621

 basic_ostringstream 594

 basic_stringstream 600

 istrstream 649

 ostrstream 655

 strstream 658

rdstate 466

read 534

readsome 536

real 423

 complex 417

register_callback 457

resetiosflags 570

right 478

rw_mutex 670

 acquire 671

 Constructor 671

 Destructor 671

 release 671

 remove 671

 try_rdlock 672

 try_wrlock 672

S

sbumc 495

scientific 479

seekdir 447

seekg 542

seekoff 505

 basic_filebuf 611

 basic_streambuf 586

 strstreambuf 645

seekp 559

seekpos 505

 basic_filebuf 611

 basic_streambuf 586

 strstreambuf 645

sentry 517, 550

 constructor

 basic_istream 518

 basic_ostream 551

 destructor

 basic_istream 518

 basic_ostream 551

 Operator bool

 basic_istream 518

 basic_ostream 551

Set

 Comparison Operations 227

 Constructors 226

 Element Access Member Functions 228

 Erase member Functions 230

 Insert Member Functions 229

 Special Set Operations 231

setbase 572

setbuf 504, 611

 strstreambuf 644

setf 451

setfill 573

setg 502

setiosflags 571

setp 503

setprecision 574

setstate 470

setw 575

sgetc 496

sgetn 497

Shallow Copies 185

showmanc 506

showmanyc

 basic_filebuf 609

Index

showpoint 477
showpos 477
sin 427
sinh 427
skipws 477
sngetc 494
sorting and related algorithms 331
sputback 497
sputc 499
sputn 500
sqrt 427
state_type 98
str
 basic_istream 590
 basic_ostringstream 596
 basic_streambuf 583
 basic_stringstream 601
 istream 650
 ostream 655
 stringstream 658
 stringstream 643
Stream Iterators
 Introduction to Stream Iterators 281
streambuf 483
string 99
stringstream 635, 651
 constructor 640, 657
 destructor 657
 freeze 657
 pcount 658
 rdbuf 658
 str 658
stringstream 638
 freeze 641
 pcount 642
 seekof 645
 seekpos 645
 setbuf 644
 str 643
 stream
 overflow 646
 pbackfail 646
 underflow 645
strstreambuf
 destructor 641

struct char_traits 98
sungetc 499
swap
 basic_string 131
sxputn 508
sync 541
 basic_filebuf 612
 basic_streambuf 505
sync_with_stdio
 ios_base 458

T

tan 428
tanh 428
tellg 542
tellp 558
to_char_type 97
to_int_type 97
traits 96

U

uflow 507
underflow 506
 basic_filebuf 610
 basic_streambuf 584
 stringstream 645
unget 539
unsetf 452
uppercase 477

V

vector
 Comparison Operations 198
 Constructors 196
 Element Access Member Functions 198
 Erase Member Functions 201
 Insert Member Functions 200
 Type Definitions 194

W

werr 438
width 454
win 437

wlog 438
wostream werr 438
wostream wlog 438
wout 437
write 561

ws 544

X

xalloc 456
xsgetn 506

CodeWarrior

MSL C++ Reference

Credits

writing lead: Ron Liechty

other writers: Portions copyright © 1995 by Modena Software Inc.

engineering: Vicki Scott, Howard Hinnant and all other Libraries team members

frontline warriors: MPTP testers



Guide to CodeWarrior Documentation

CodeWarrior documentation is modular, like the underlying tools. There are manuals for the core tools, languages, libraries, and targets. The exact documentation provided with any CodeWarrior product is tailored to the tools included with the product. Your product will not have every manual listed here. However, you will probably have additional manuals (not listed here) for utilities or other software specific to your product.

Core Documentation	
IDE User Guide	How to use the CodeWarrior IDE
Debugger User Guide	How to use the CodeWarrior debugger
CodeWarrior Core Tutorials	Step-by-step introduction to IDE components
Language/Compiler Documentation	
C Compilers Reference	Information on the C/C++ front-end compiler
Pascal Compilers Reference	Information on the Pascal front-end compiler
Error Reference	Comprehensive list of compiler/linker error messages, with many fixes
Pascal Language Reference	The Metrowerks implementation of ANS Pascal
Assembler Guide	Stand-alone assembler syntax
Command-Line Tools Reference	Command-line options for Mac OS and Be compilers
Plugin API Manual	The CodeWarrior plugin compiler/linker API
Library Documentation	
MSL C Reference	Function reference for the Metrowerks ANSI standard C library
MSL C++ Reference	Function reference for the Metrowerks ANSI standard C++ library
Pascal Library Reference	Function reference for the Metrowerks ANS Pascal library
MFC Reference	Reference for the Microsoft Foundation Classes for Win32
Win32 SDK Reference	Microsoft's Reference for the Win32 API
The PowerPlant Book	Introductory guide to the Metrowerks application framework for Mac OS
PowerPlant Advanced Topics	Advanced topics in PowerPlant programming for Mac OS
Targeting Manuals	
Targeting BeOS	How to use CodeWarrior to program for BeOS
Targeting Java VM	How to use CodeWarrior to program for the Java Virtual Machine
Targeting Mac OS	How to use CodeWarrior to program for Mac OS
Targeting MIPS	How to use CodeWarrior to program for MIPS embedded processors
Targeting NEC V810/830	How to use CodeWarrior to program for NEC V810/830 processors
Targeting Net Yaroze	How to use CodeWarrior to program for Net Yaroze game console
Targeting Nucleus	How to use CodeWarrior to program for the Nucleus RTOS
Targeting OS-9	How to use CodeWarrior to program for the OS-9 RTOS
Targeting Palm OS	How to use CodeWarrior to program for PalmPilot
Targeting PlayStation OS	How to use CodeWarrior to program for the PlayStation game console
Targeting PowerPC Embedded Systems	How to use CodeWarrior to program for PPC embedded processors
Targeting VxWorks	How to use CodeWarrior to program for the VxWorks RTOS
Targeting Win32	How to use CodeWarrior to program for Windows